V.V. Novozhilov

The Theory of Thin Shells

THE THEORY OF THIN SHELLS

V.V. NOVOZHILOV

THE THEORY OF THIN SHELLS

TRANSLATED BY

P. G. LOWE

Ove Arup & Partners, London
Formerly University of Sydney

EDITED BY

J. R. M. RADOK

Professor of Applied Mechanics
Polytechnic Institute of Brooklyn

P. NOORDHOFF LTD. — GRONINGEN — THE NETHERLANDS
1959

Copyright 1959 by P. Noordhoff, Ltd. Groningen; The Netherlands.
This book or parts thereof may not be reproduced in any form without written permission of the publishers.
Printed in The Netherlands.

AUTHOR'S PREFACE

TO THE RUSSIAN 1951 EDITION

At the present time, the theory of thin shells (curved plates) is one of the more active branches of the theory of elasticity which is receiving everywhere a great deal of attention.

This is explained by the fact that thin-walled shell constructions combine light weight with high strength, as a result of which they have found wide application in naval, aeronautical and boiler engineering as well as in reinforced concrete roof designs. It must be emphasized that the practical possibilities of the utilization of shells have by no means been exhausted and we are all the time witnesses to the perfection of different types of construction; on the one hand this takes the form of an extension of the range of employment of shells, on the other hand, of a more thorough analysis of their properties (i.e. by improvement of the methods of stress analysis).

Soviet scientists have contributed extensively to the theory of shells and it may be said, without exaggeration, that during the past 15–20 years a large number of valuable and profound ideas in this theory have arisen in our country.

This book is devoted to the analysis of stresses and deformations in shells; this problem is treated here as a linear one, i.e., displacements are assumed to be small in comparison with the thickness of the shell and the strains are not to exceed the limit of proportionality. Linear shell theory is of considerable practical importance, since the assumptions on which it is based are in many problems close to the true conditions.

Non-linear shell theory is of equal practical importance and so is the associated stability theory of shells. However, since they differ essentially from the linear theory as regards their formulation as well as their methods of solution, these theories must be treated individually, and they deserve special monographs.

This book is mainly based on the work of the Russian school in the theory of shells which includes also certain results obtained by the author. It is divided into four chapters the first of which is devoted to the general (moment) theory of thin shells, the second to the membrane (momentless) theory, the third and the fourth to the moment theory of two types of shells which are important in industrial applications, namely, cylindrical shells and shells of revolution.

In order to ease for the reader the burden of understanding the subject and applying it independently to practical problems, the book has been provided with many examples taken from different fields of application. The second chapter dealing with the membrane theory contains especially many of them. The author has there aimed at maximum simplicity and physical clarity (to the prejudice even of mathematical generality and rigour) having in mind that for the engineer the problem of the membrane state of stress of shells is of paramount interest.

ПРЕДИСЛОВИЕ К ПЕРЕВОДУ НА АНГЛИЙСКИЙ ЯЗЫК КНИГИ „ТЕОРИЯ ТОНКИХ ОБОЛОЧЕК"

Эта книга посвящена линейной теории оболочек и освещает данный вопрос с единой точки зрения, суть которой состоит в широком использовании комплексного преобразования. Данный прием (идея которого восходит еще к ученым Цюрихской школы) обобщен здесь на любые задачи линеаризированной теории оболочек.

Мне кажется, что такое изложение имеет ряд преимуществ, поскольку оно делает уравнения более обозримыми, облегчает их преобразование, а иногда и упрощает их интегрирование. Вместе с тем данный путь, разумеется, отнюдь не является единственным. Можно указать хотя бы на прекрасные книги, написанные двумя другими русскими учеными — В. З. Власовым и А. А. Гольденвейзером, посвященные тому же вопросу, но излагающие его в другом духе.

Необходимо далее отметить, что данная книга была написана около десяти лет назад и не учитывает, естественно, те результаты, которые были получены в этот период. Тем не менее она не слишком устарела, поскольку в линейной теории оболочек за это время принципиальных изменений не произошло.

Я должен, в заключение, принести свою искреннюю благодарность профессору Бруклинского политехнического института J. R. M. Radok, взявшему на себя большой труд по редактированию перевода моей книги на английский язык. Надеюсь, что издание этого перевода хотя бы в некоторой мере будет способствовать налаживанию деловых и дружеских отношений между специалистами по теории упругости Советского Союза и других стран.

Ленинград,
30 октября 1958г.

(В. В. Новожилов)

PREFACE TO THE ENGLISH TRANSLATION OF "THE THEORY OF THIN SHELLS"

This book is devoted to the linear theory of shells and it elucidates the inherent problems from a unified point of view which essentially consists of the wide utilization of complex transformations. The underlying method (the idea for which originated from the Zürich school) has been generalized here to include all problems of the linearized theory of shells.

I believe that such a study has a number of advantages, since it makes the equations more accessible, facilitates their transformation and sometimes simplifies their integration. At the same time, this approach is, of course, not at all the only one. I must mention here the fine books, written by two other Russian Scientists – V. Z. Vlasov and A. L. Gol'denweizer which are devoted to the same problem, but each giving his account in a different spirit.

It should also be mentioned that this book has been written almost ten years and that it naturally does not include those results which have been obtained during this period. Nevertheless it has not become obsolète, since during this time no principal changes have occurred in the linear theory of shells.

In conclusion, I must express my sincere gratitude to Professor J. R. M. Radok of the Polytechnic Institute of Brooklyn for taking on himself the sizable task of editing the English translation of my book. I hope that the publication of this translation will in some measure contribute to professional and social interchanges between specialists in the theory of elasticity of the Soviet Union and of other countries.

Leningrad, 30 October 1958 V. V. NOVOZHILOV

TRANSLATOR'S PREFACE

In this translation a sentence by sentence rendering of the original has been aimed at. Any alterations or additions included have been recorded as footnotes. However a number of typographical corrections have been made in the text and figures without special mention. In this connection thanks are due to professor Novozhilov for supplying us with a list of errata. Further the sections in the translation have been numbered consecutively throughout the book rather than chapter by chapter as was used in the Russian original. In addition Auther and Subject Indices have been added.

My personal thanks are due, in particular, to the University of Sydney Authorities for facilities enabling me to complete the work of translation.

London, August 1959 P. G. LOWE

CONTENTS

CHAPTER I

The general theory of thin elastic shells 1

§ 1. Fundamental concepts and assumptions 1

§ 2. Some fundamental results from the theory of surfaces . . 6

§ 3. The law of variation of displacements across the thickness of the shell 14

§ 4. The deformation of a shell and the deformation of its middle surface 19

§ 5. The conditions for the compatibility of strain in the middle surface 27

§ 6. Forces and moments 29

§ 7. The equilibrium of a shell element 33

§ 8. Functions which satisfy the homogeneous statical equations identically 38

§ 9. The strain energy for a shell 42

§ 10. Relations between the forces, moments and the strains of the middle surface 47

§ 11. The boundary conditions for the problem of stresses in a shell 54

§ 12. Formulation of the compatibility conditions in terms of forces and moments 59

§ 13. The two methods of solution of problems in the theory of shells 62

§ 14. Complex transformation of the differential equations in the theory of thin shells when Poisson's ratio is equal to zero 63

§ 15. Other forms of the complex transformation of the equations of the theory of thin shells (for $\mu = 0$) 69

§ 16. Generalization of the concepts of "complex forces" and "complex displacements" to the case of arbitrary Poisson's ratio 75

§ 17. Simplification of the theory of shells by the method of Mushtari-Vlasov 84
§ 18. On types of state of stress in shells 90

CHAPTER II

The membrane theory of shells 93
§ 19. Preliminary remarks. History 93
§ 20. The fundamental equations of the membrane theory . . . 95
§ 21. The boundary conditions 97
§ 22. The conditions for the existence of the membrane state of stress 100
§ 23. The membrane theory of shells of revolution of arbitrary shape 102
§ 24. Method of solution of the differential equations of the membrane theory of shells of revolution 106
§ 25. Symmetrical deformation of shells of revolution 108
§ 26. The membrane theory of domes 111
§ 27. The membrane theory of pressure vessels 117
§ 28. Shells of uniform strength 124
§ 29. "Wind" type loading (The case $k = 1$) 134
§ 30. The membrane theory of shells formed by rotation of curves of second order 138
§ 31. The membrane theory of spherical shells 140
§ 32. The analysis of domes, resting on columns 141
§ 33. Affine transformations in the membrane theory 145
§ 34. The displacements in a shell of revolution under symmetrical deformation 155
§ 35. Deformation of shells of revolution without extension or shearing of the middle surface 157
§ 36. The equations of the membrane theory for cylindrical shells of arbitrary shape 167
§ 37. Determination of the stresses in tubes with arbitrary crosssection, loaded by uniform normal pressure 169
§ 38. The membrane theory of cylindrical vaults 175

CHAPTER III

The analysis of cylindrical shells 182

§ 39. Historical introduction 182

§ 40. The equations of the theory of cylindrical shells in complex form 185

§ 41. The theory of cylindrical shells, reinforced by transverse ribs 189

§ 42. The analysis of cylindrical plates 196

§ 43. The evaluation of the stresses in oval shells, composed of four cylindrical plates 208

§ 44. The simplified theory of long cylindrical plates 219

§ 45. The analysis of cylindrical plates, reinforced by transverse elastic ribs 234

§ 46. The analysis of tubes of arbitrary cross-section with freely supported ends 239

§ 47. The analysis of a cylindrical shell with abruptly changing radius of curvature 246

§ 48. The analysis of tubes for arbitrary end conditions 252

§ 49. On the semi-membrane theory of cylindrical shells 254

CHAPTER IV

Shells of revolution 260

§ 50. Historical remarks 260

§ 51. The differential equations for shells of revolution in "complex forces" and their transformation 263

§ 52. General method for solution of the system (51.17) 267

§ 53. Determination of the displacements 268

§ 54. Symmetrical deformations of shells of revolution 270

§ 55. Asymptotic integration of linear second order differential equations 273

§ 56. Approximate integration of the homogeneous differential equation for symmetrical deformations 282

§ 57. Approximate expressions for the forces, moments and displacements of symmetrically deformed shells of revolution 285

§ 58. Influence coefficients 292

§ 59. The analysis of cylindrical pressure vessels and their end-panels 296

§ 60. Symmetrical deformation of toroidal shells 304

§ 61. Analysis of stress in arched end-panels 316

§ 62. Shells of revolution subject to 'wind' loading 324

§ 63. Design formulae for 'wind' loading 329

§ 64. On the integration of the system (52.3) for shells whose radii of curvature satisfy the relation

$$\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta} = \text{const} \qquad 337$$

§ 65. The analysis of spherical shells for arbitrary loading . . . 346

§ 66. The design of catenoid shells 358

§ 67. Approximate theory of integration for any shells of revolution subject to arbitrary loading 361

REFERENCES 367

AUTHOR INDEX 373

SUBJECT INDEX 375

Chapter I

THE GENERAL THEORY OF THIN ELASTIC SHELLS

§ 1. Fundamental concepts and assumptions

In the theory of elasticity, the term shell is applied to bodies bounded by two curved surfaces, the distance between the surfaces being small in comparison with the other dimensions. The locus of points which lie at equal distances from these two surfaces defines the middle surface of the shell.

Drawing now at any arbitrary point of the middle surface the perpendicular to the middle surface, the length intercepted between the surfaces of the shell determines its thickness which will be designated by δ. The thickness may vary in magnitude; however, in what follows, it will be assumed almost exclusively that the shell has constant thickness, as is mostly the case in practice.

If the shell has no other boundary besides the above two surfaces, it will be called complete. Every complete shell can be divided into parts which will be referred to as incomplete shells. It will be assumed that each edge of an incomplete shell is a plane curve and that the cuts are made perpendicular to the middle surface. The middle surface, thickness and edges completely define the geometry of a shell.

It follows from the above discussion that shells bear the same relation to plates as curved beams to straight beams. Therefore, in the literature, shells are frequently referred to as curved plates. This last expression may prove useful when applied to incomplete shells, but it is of little value when applied to complete shells. Thus, for example, a complete thin-walled sphere may hardly be referred to as a curved plate. In contrast, the name thin-walled sphere for an incomplete shell is also insufficiently suggestive, so that there, at least, the term curved plate could serve some purpose. However, in general, only a remote connection exists between these terms and, for the sake of brevity, it is proposed here to refer to all bodies in the class under discussion as shells.

The theory of shells forms a part of the theory of elasticity concerned with the study of the deformation of elastic bodies under the influence of given loads. For this purpose, it will be assumed that the material

of the shell is isotropic and obeys Hooke's Law and that the displacements at a point are small in comparison with the thickness of the shell. If this last limitation is not imposed, the governing differential equations become non-linear and their solution encounters great difficulties. For a large range of practical problems, however, these limitations do not impose severe restrictions on the usefulness of the theory. It should be noted here that the results obtained below must always be interpreted in the light of these restrictions.

There are two different classes of shells — thick shells and thin shells. A shell will be called thin, if the maximum value of the ratio δ/R (where R is the radius of curvature of the middle surface) can be neglected in comparison with unity. Correspondingly, shells will be called thick whenever such terms cannot be neglected. This division of shells into two classes is not fully defined as long as it is not accompanied by a statement regarding what value of the above ratio can be neglected in comparison with unity. For ordinary technical calculations, it is admissible to have a relative error of 5%, and for thin shells this corresponds to

$$\max\left(\frac{\delta}{R}\right) \leqslant \frac{1}{20}.$$

Hence shells for which this inequality is violated will be regarded as thick shells.

It is clearly suggested by the above discussion that for thin shells some terms in the basic formulae may be neglected, while for thick shells these terms must be retained. Therefore, in correspondence with this subdivision of shells, the theory will be divided into a theory of shells of arbitrary thickness and into a theory of thin shells. Obviously the theory of thin shells will be considerably simpler than that of shells of the other type.

It will be noted here that shells possess many useful properties arising from their elastic nature and that by suitable design they can be made to support large loads even when they are very thin. In this connection, the designer may gain a great deal by considering a plate as a slightly curved shell in the same way was as he may replace a beam by a shallow arch.

This property of shells is readily utilized in constructions which are strong and adaptable to a broad range of applications — such as occur in aircraft, ships and reinforced concrete design — in short, everywhere where light weight is a vitally important factor. For a large number of practical applications, the thicknesses of shells lie in the range

$$\frac{1}{1000} \leqslant \frac{\delta}{R} \leqslant \frac{1}{50},$$

i.e., in the range of thin shells, so that the theory presented in this book is of great practical interest.

As has already been indicated, there is an analogy between plates and shells, suggesting for the latter the alternate term of curved plates. This is the basis for the adoption into a theory of shells of a number of methods from the theory of plates. Therefore a short summary of the historical development of the theory of plates will now be presented.

In the classical theory of plates, there are two fundamental methods for the solution of problems. The first method was proposed by A. Cauchy [39] and S. D. Poisson [50], the second by G. Kirchhoff [46]. The method of Cauchy and Poisson is based on the expansion of the displacements and stresses in the plate in power series of z, i.e., of the distance of a given point from the middle plane of the plate. Retaining the least possible number of terms in these series, one obtains the equations derived by Mlle. Sophie Germain *. By retaining more terms, it is possible to obtain more exact solutions of the problem, these solutions tending to the exact ones as the number of terms becomes infinite. Thus the method of Cauchy and Poisson gives a universal approach to the theory of plates. However, there arose a dispute which developed in two directions:

Firstly, B. de St. Venant [40, page 725] contested the legality of the method, asserting that the corresponding series will, as a rule, diverge. (It should be stated here that the region and nature of the convergence of these series has hitherto remained unclarified.)

Secondly, arguments arose regarding the formulation of the relevant boundary conditions: whether there were to be four or five. The method of Cauchy and Poisson was not able to completely resolve this basic question. (At least, this was the opinion of the scientists of the last century.)

Therefore, the other method which was proposed by Kirchhoff [46] and which introduced physical meaning into the theory of plates has remained in use until to-day. Kirchhoff based his reasoning on several assumptions, analogous to those used in the theory of beams. His assumptions may be reduced to the following statements:

a) The straight fibres of a plate which are perpendicular to the middle surface before deformation remain so after deformation and do not change their length.

b) The normal stresses acting on planes parallel to the middle surface may be neglected in comparison with the other stresses.

The method of Kirchhoff excels over the method of Cauchy-Poisson

* See Todhunter and Pearson 'History of Elasticity.' Vol. I. § 414 p. 209

by its great clarity and physical meaning: It introduced into the basic theory a simplification which had a definite physical interpretation and which was a completely obvious extension of the well proven theory of beams. The introduction of the concepts of internal forces and moments produced a further link between the theory of plates and the theory of beams and eventually it cleared up the problem of the boundary conditions for plates which, as has already been mentioned, remained for a long time a subject for discussion. However, at this stage, it should be pointed out that Kirchhoff's method is insufficient in one respect, namely that it is only approximate and cannot be developed into a more accurate theory. In contrast, the theory of Cauchy-Poisson has the advantage that, once the problem of the convergence of its series has been resolved, it would, in principle, permit the definition of the exact solution.

The two methods in the theory of plates described above can be effectively employed in the development of a theory of shells. A theory of shells, founded on the hypotheses of Kirchhoff, was first presented in the work of G. Aron [37]; however, his development was not strictly correct. These inaccuracies were noticed and corrected by A. E. H. Love in his paper [48] in which he formulated a theory of shells in analogy to the theory of plates of Kirchhoff. A version of the theory of shells, proposed by Love, was given in one of the chapters of his book [49] in a somewhat different form from that in his paper [48].

In spite of its popularity, the development given by Love is not free from inadequacies, in that it is inconsistent with regard to small terms: some are retained and others which are of the same order of magnitude are rejected. These insufficiencies were already noted a long time ago and several authors, using Love's theory, have added certain small terms for the sake of consistency, others have omitted small terms which had been retained. Hence there have originated different versions of the formulae of shell theory which, however, only differ from the prototype — the theory of Love — by terms which are small.

The deficiencies in the formulation given by Love and also the lack of a discussion of the important question, namely, how to write the relations between the forces, moments and the displacements of the middle surface, has for a long time precluded the presentation of the basic theory in a generally acceptable form.

All these deficiencies have been studied in the publications of the Russian School in the theory of shells, led by the late Academician B. G. Galerkin. Although the works of Galerkin [93, 94, 128] relate to thick shells, he was able by his original methods to obtain all

all the formulae of the theory of shells from the equations of the general theory of elasticity. He thus played an important part in the development of a mathematically rigorous theory for thin shells. The equations of the theory of thin shells were for the first time deduced in this way by A. I. Lur'e [15, 17] who, however, was not able to give the necessary criterion for simplifying his formulae. This criterion was given in the papers [30, 28] where the errors introduced by Kirchhoff into the theory of thin shells were elucidated and where it was proved that these errors are of order δ/R in comparison with unity. In this way it was established that the above mentioned assumptions are sufficient for the construction of the theory of thin shells.

Valuable additions to the general theory of shells are given in the works of A. L. Gol'denweizer [6, 5] in which, for the first time, are formulated the conditions for the compatibility of strain. In addition, Gol'denweizer showed there the possibility of identically satisfying the equations of equilibrium by means of four stress functions, his result being analogous to that obtained by Lur'e [17]. In the work [32] which forms the basis of this book the present writer showed that it was possible to represent the equations of the theory of shells in complex form. In this way the equations assumed a more compact form, simplifying their study and, in particular, the understanding of their transformations and of their solution. These transformations are essentially a generalisation of the transformation discovered by E. Meissner [154]. An extension of the work in [32] is given in the article by Kh. M. Mushtari [24].

A statement should still be made about the work of the Russian School devoted to the simplification of the equations of shell theory, applicable to a definite range of problems, for example, the calculation of edge effects and the study of shallow shells. Mention should be made of the works of Kh. M. Mushtari [20, 21], S. Feinberg [36], V. Z. Vlasov [3, 4] and U. N. Rabotnov [34]. Particular attention has in recent times been given to the theory of shallow shells by V. Z. Vlasov [4] and a number of his pupils [80, 81], etc.

A classification of solutions of problems in the theory of shells has been given by Gol'denweizer [8, 9] and Mushtari [25] in whose publications may be found the basis of a general principle for simplifications of the equations of the theory of shells, admissible in various concrete cases.

This summarises the contribution of Russian work to the development of the general theory of shells.

Since only problems of thin shells are to be considered, this book will be based on the two fundamental hypotheses a) and b), given earlier. Adoption of these hypotheses is equivalent to a reduction of the problem

of the deformation of a shell to the study of the deformation of the middle surface in the same way as the introduction of the hypothesis regarding plane sections in the bending of a beam reduces that problem to a study of the bending of the neutral axis.

Thus, the above hypotheses are essentially an extension of the ideas underlying the elementary theory of beams. It would appear that a simpler approach to the study of shells is impossible, if one has in mind a theory which is to apply to all problems; on the basis of the above assumption regarding normals remaining normals and the simplifications with their inherent errors, one is thus justified in calling the theory of this book the technical theory of shells.

§ 2. Some fundamental results from the theory of surfaces

In this chapter, a summary of certain fundamental relations from the theory of surfaces will be given. It will be assumed that the reader has some knowledge of differential geometry and vector analysis.

Every smooth surface may be determined in cartesian coordinates by three equations:

$$\begin{aligned} x &= f_1(\alpha_1, \alpha_2), \\ y &= f_2(\alpha_1, \alpha_2), \\ z &= f_3(\alpha_1, \alpha_2), \end{aligned} \tag{2.1}$$

in which f_1, f_2, f_3 are definite, continuous, single-valued functions of the two variable parameters α_1, α_2.

The ranges of these parameters will be restricted, so that every point of the surface corresponds to one and only one pair of values of α_1, α_2. Then these parameters may be called curvilinear coordinates of the surface under consideration.

Letting the parameter α_2 in (2.1) take successively different constant values and varying α_1, one obtains on the surface a family of curves which will be named the coordinate lines α_1. In a similar manner, giving α_1 different constant values and letting α_2 vary, a second family of curves, the coordinate lines α_2 are found. In view of the above limitations on the range of the variables, only one curve of each of these two families of curves will pass through each point of the surface. Hence, every point of the surface can be considered as the intersection of two coordinate lines α_1 and α_2 (see Fig. 1).

For each surface there exist an infinite number of possible choices for the functions f_1, f_2, f_3 and depending on their choice the form of the coordinate lines on the surface will change. However, not all of these

possible alternatives will be equally convenient. As a rule, the most expedient of these alternatives will be that curvilinear system of coordinates in which the formulae for the surface attain their simplest form. Such a system is that in which the two families of coordinate curves are



Fig. 1.

simultaneously lines of principal curvature of the surface. Such a system will be orthogonal, since the directions of principal curvature on a surface are mutually perpendicular. In what follows, this system of curvilinear coordinates will always be adopted.

The three scalar equations (2.1) correspond to a single vector equation

$$\mathbf{r} = \mathbf{r}(\alpha_1, \alpha_2) \tag{2.2}$$

the projections of which on the axes x, y, z are given by (2.1).

Consider the derivatives of $\mathbf{r}$ with respect to α_1 and α_2

$$\begin{aligned} \mathbf{r}_{\alpha_1} &= \frac{\partial \mathbf{r}}{\partial \alpha_1}, \\ \mathbf{r}_{\alpha_2} &= \frac{\partial \mathbf{r}}{\partial \alpha_2}, \end{aligned} \tag{2.3}$$

where the vectors $\mathbf{r}_{\alpha_1}$, $\mathbf{r}_{\alpha_2}$ will at each point of the surface be tangential to the α_1, α_2 lines respectively. As a result, it is seen that an increase of one of the curvilinear coordinates corresponds to a shift of the vector $\mathbf{r}$ on the surface in the direction corresponding to this coordinate line. Hence the vector

$$d\mathbf{s} = \frac{\partial \mathbf{r}}{\partial \alpha_1} d\alpha_1 + \frac{\partial \mathbf{r}}{\partial \alpha_2} d\alpha_2 \tag{2.4}$$

is equal in magnitude and direction to the segment, joining the points (α_1, α_2) and $(\alpha_1 + d\alpha_1, \alpha_2 + d\alpha_2)$ of the surface.

The square of the length of this segment is given by

$$|d\mathbf{s}|^2 = |\mathbf{r}_{\alpha_1}|^2 d\alpha_1^2 + 2(\mathbf{r}_{\alpha_1}, \mathbf{r}_{\alpha_2}) d\alpha_1 d\alpha_2 + |\mathbf{r}_{\alpha_2}|^2 d\alpha_2^2, \tag{2.5}$$

where the symbol $|\ |^2$ indicates the scalar product of the vector with itself, which is equal to the square of the length of the vector. Similarly, the symbol $(\ ,\ )$ represents the scalar product of two different vectors.

Introduce now the notation

$$\begin{aligned} |\mathbf{r}_{\alpha_1}|^2 = A_1^2 &= \left(\frac{\partial x}{\partial \alpha_1}\right)^2 + \left(\frac{\partial y}{\partial \alpha_1}\right)^2 + \left(\frac{\partial z}{\partial \alpha_1}\right)^2, \\ |\mathbf{r}_{\alpha_2}|^2 = A_2^2 &= \left(\frac{\partial x}{\partial \alpha_2}\right)^2 + \left(\frac{\partial y}{\partial \alpha_2}\right)^2 + \left(\frac{\partial z}{\partial \alpha_2}\right)^2. \end{aligned} \tag{2.6}$$

On the basis of the assumed orthogonality of the curvilinear coordinates, one finds then

$$(\mathbf{r}_{\alpha_1}, \mathbf{r}_{\alpha_2}) = 0. \tag{2.7}$$

Hence the formula (2.5) may be written in the form

$$ds^2 = A_1^2 d\alpha_1^2 + A_2^2 d\alpha_2^2. \tag{2.8}$$

Thus, in the particular cases when only one curvilinear coordinate is varied, one has

$$\begin{aligned} ds_1 &= A_1 d\alpha_1, \\ ds_2 &= A_2 d\alpha_2, \end{aligned} \tag{2.9}$$

where ds_1, ds_2 are the increases of the arc length along the coordinate lines α_1, α_2, corresponding to the increase of the curvilinear coordinates by $d\alpha_1$, $d\alpha_2$ respectively. The quantities A_1, A_2 are called the Lamé parameters.

In future, all vectors which are functions of the points of the surface will be given in terms of their projections on the directions of the tangents to the coordinate lines α_1 and α_2 and on the normal to the surface at the point considered. Since these reference axes change their direction for a passage from one point of the surface to another, it is necessary to investigate the differentiation of these vectors with respect to α_1, α_2.

In view of the fact that every vector, referred to a given system, can be written in the form

$$T = T_{\alpha_1}\mathbf{e}_1 + T_{\alpha_2}\mathbf{e}_2 + T_n\mathbf{e}_n, \tag{2.10}$$

where T_{α_1}, T_{α_2}, T_n are scalars (projections) and $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$ the orthogonal

unit vectors

$$\mathbf{e}_1 = \frac{1}{A_1}\mathbf{r}_{\alpha_1}, \qquad \mathbf{e}_2 = \frac{1}{A_2}\mathbf{r}_{\alpha_2}, \qquad \mathbf{e}_n = [\mathbf{e}_1.\mathbf{e}_2], \tag{2.11}$$

the study of the differentiation rule for vectors reduces to that for the unit vectors (2.11).

In the last formula of (2.11), the symbol [.] denotes the vector product. In future, the system $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$ will be assumed to be right-handed. In addition, it will be assumed that $\mathbf{e}_n$ is directed to the convex side of the surface (or to the side of the centres of negative curvature, if the signs of the radii of curvature are not equal). These conditions do not contradict each other, since the choice of the positive directions for α_1 and α_2 can be arranged according to convenience.

A start will now be made with the study of the rules for the differentiation of the unit vectors $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$. Consider two neighbouring points on the coordinate line α_1 and construct at each of these points the normals $\mathbf{e}_n$ (Fig. 2). These normals intersect at the point O. The corresponding principal radius of curvature of the surface will be denoted by R_1.



Fig. 2.

It is seen from Fig. 2 that the increase of the unit vector $\mathbf{e}_n$ for passage from the point M_1 to the infinitely near point M_2 is to sufficient accuracy parallel to the chord M_1M_2, i.e., in the limit it is parallel to the unit vector $\mathbf{e}_1$. The magnitude of this increase, on the basis of similar triangles, can be seen to be

$$\frac{|\Delta(\mathbf{e}_n)|}{|\mathbf{e}_n|} = \frac{\overline{M_1M_2}}{R_1},$$

where the length $|\mathbf{e}_n| = 1$ and $\overline{M_1M_2} = A_1 d\alpha_1$. Hence one finds

$$\frac{\partial \mathbf{e}_n}{\partial \alpha_1} = \frac{A_1}{R_1}\mathbf{e}_1. \tag{2.12}$$

In a similar manner, one may calculate the derivative of $\mathbf{e}_n$ with

respect to α_2

$$\frac{\partial \mathbf{e}_n}{\partial \alpha_2} = \frac{A_2}{R_2}\mathbf{e}_2, \tag{2.13}$$

where R_2 denotes the second principal radius of curvature of the surface at the point considered.

Note that in deducing the formulae (2.12), (2.13) it had to be assumed that for the passage from the point M_1 to the infinitely near point M_2 the unit vector $\mathbf{e}_n$ changes in such a way that it remains to second order of smallness coplanar and rotates about the corresponding centre of curvature of the surface. This is one of the fundamental properties of lines of principal curvature. If the given unit vector had been shifted along any other line on the surface, it would be impossible to assume that it remains coplanar. The proof of the above stated property of the lines of curvature is known in the theory of surfaces as the 'Theorem of Rodrigues'.

Consider now the evaluation of the derivatives of the unit vectors $\mathbf{e}_1$, $\mathbf{e}_2$. First it will be noted that

$$\frac{\partial \mathbf{r}_{\alpha_1}}{\partial \alpha_2} = \frac{\partial \mathbf{r}_{\alpha_2}}{\partial \alpha_1}, \tag{2.14}$$

since this is equivalent to the identity

$$\frac{\partial^2 \mathbf{r}}{\partial \alpha_2 \partial \alpha_1} = \frac{\partial^2 \mathbf{r}}{\partial \alpha_1 \partial \alpha_2}.$$

Hence

$$\frac{\partial A_1 \mathbf{e}_1}{\partial \alpha_2} = \frac{\partial A_2 \mathbf{e}_2}{\partial \alpha_1}. \tag{2.15}$$

Further, consider the derivative $\dfrac{\partial \mathbf{e}_1}{\partial \alpha_1}$ and study its components along the axes $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$. In the direction $\mathbf{e}_1$, this derivative has obviously no projection, since the length of the vector $\mathbf{e}_1$ is constant and its change is perpendicular to $\mathbf{e}_1$. As regards the projection of $\dfrac{\partial \mathbf{e}_1}{\partial \alpha_1}$ on $\mathbf{e}_2$, it is given by

$$\left(\mathbf{e}_2, \frac{\partial \mathbf{e}_1}{\partial \alpha_1}\right) = \frac{\partial (\mathbf{e}_2, \mathbf{e}_1)}{\partial \alpha_1} - \left(\mathbf{e}_1, \frac{\partial \mathbf{e}_2}{\partial \alpha_1}\right) = -\left(\mathbf{e}_1, \frac{\partial \mathbf{e}_2}{\partial \alpha_1}\right), \tag{2.16}$$

since $(\mathbf{e}_1, \mathbf{e}_2) = 0$ (the lines α_1 and α_2 being orthogonal).

Substituting on the right-hand side of this equality for the derivative $\frac{\partial \mathbf{e}_2}{\partial \alpha_1}$ its value given by (2.15), i.e.,

$$\frac{\partial \mathbf{e}_2}{\partial \alpha_1} = \frac{1}{A_2}\frac{\partial A_1 \mathbf{e}_1}{\partial \alpha_2} - \frac{1}{A_2}\frac{\partial A_2}{\partial \alpha_1}\mathbf{e}_2, \tag{2.17}$$

one finds

$$\left(\mathbf{e}_2, \frac{\partial \mathbf{e}_1}{\partial \alpha_1}\right) = -\frac{1}{A_2}\left(\mathbf{e}_1, \frac{\partial A_1 \mathbf{e}_1}{\partial \alpha_2}\right) + \frac{1}{A_2}\frac{\partial A_2}{\partial \alpha_1}(\mathbf{e}_1, \mathbf{e}_2) =$$

$$= -\frac{A_1}{A_2}\left(\mathbf{e}_1, \frac{\partial \mathbf{e}_1}{\partial \alpha_2}\right) - \frac{1}{A_2}\frac{\partial A_1}{\partial \alpha_2}(\mathbf{e}_1, \mathbf{e}_1). \tag{2.18}$$

However, $(\mathbf{e}_1, \mathbf{e}_1) = 1$ and $\left(\mathbf{e}_1, \frac{\partial \mathbf{e}_1}{\partial \alpha_2}\right) = 0$, as has been indicated above, and therefore, finally,

$$\left(\mathbf{e}_2, \frac{\partial \mathbf{e}_1}{\partial \alpha_1}\right) = -\frac{1}{A_2}\frac{\partial A_1}{\partial \alpha_2}. \tag{2.19}$$

There still remains to evaluate the projection of $\frac{\partial \mathbf{e}_1}{\partial \alpha_1}$ on $\mathbf{e}_n$. This is given by

$$\left(\mathbf{e}_n, \frac{\partial \mathbf{e}_1}{\partial \alpha_1}\right) = \frac{\partial(\mathbf{e}_n, \mathbf{e}_1)}{\partial \alpha_1} - \left(\mathbf{e}_1, \frac{\partial \mathbf{e}_n}{\partial \alpha_1}\right) = -\left(\mathbf{e}_1, \frac{\partial \mathbf{e}_n}{\partial \alpha_1}\right), \tag{2.20}$$

since $(\mathbf{e}_1, \mathbf{e}_n) = 0$.

By use of (2.12), one has

$$-\left(\mathbf{e}_1, \frac{\partial \mathbf{e}_n}{\partial \alpha_1}\right) = -\frac{A_1}{R_1}(\mathbf{e}_1, \mathbf{e}_1) = -\frac{A_1}{R_1}. \tag{2.21}$$

Thus all three components of the derivative $\frac{\partial \mathbf{e}_1}{\partial \alpha_1}$ have been found.

In a similar fashion, one may proceed with the determination of the second derivatives of the same unit vector, i.e., of $\frac{\partial \mathbf{e}_1}{\partial \alpha_2}$. On the basis of considerations similar to those above, its projection on the direction $\mathbf{e}_1$ will be equal to zero. Using (2.15), one obtains

$$\left(\mathbf{e}_2, \frac{\partial \mathbf{e}_1}{\partial \alpha_2}\right) = -\frac{1}{A_1}\frac{\partial A_1}{\partial \alpha_2}(\mathbf{e}_1, \mathbf{e}_2) + \frac{1}{A_1}\left(\mathbf{e}_2, \frac{\partial A_2 \mathbf{e}_2}{\partial \alpha_1}\right) = \frac{1}{A_1}\frac{\partial A_2}{\partial \alpha_1}, \tag{2.22}$$

and finally

$$\left(\mathbf{e}_n, \frac{\partial \mathbf{e}_1}{\partial \alpha_2}\right) = \frac{\partial(\mathbf{e}_n, \mathbf{e}_1)}{\partial \alpha_2} - \left(\mathbf{e}_1, \frac{\partial \mathbf{e}_n}{\partial \alpha_2}\right) = -\left(\mathbf{e}_1, \frac{\partial \mathbf{e}_n}{\partial \alpha_2}\right). \tag{2.23}$$

However, by (2.13),

$$\left(\mathbf{e}_1, \frac{\partial \mathbf{e}_n}{\partial \alpha_2}\right) = -(\mathbf{e}_1, \mathbf{e}_2)\frac{A_2}{R_2} = 0, \tag{2.24}$$

and therefore the derivative $\dfrac{\partial \mathbf{e}_1}{\partial \alpha_2}$ has no projection on the normal.

Similarly, the projections of the derivatives $\dfrac{\partial \mathbf{e}_2}{\partial \alpha_1}$, $\dfrac{\partial \mathbf{e}_2}{\partial \alpha_2}$ can be calculated. The results, however, can be written by analogy with those above. One thus finds

$$\begin{aligned}
\frac{\partial \mathbf{e}_1}{\partial \alpha_1} &= -\frac{1}{A_2}\frac{\partial A_1}{\partial \alpha_2}\mathbf{e}_2 - \frac{A_1}{R_1}\mathbf{e}_n, \\
\frac{\partial \mathbf{e}_1}{\partial \alpha_2} &= +\frac{1}{A_1}\frac{\partial A_2}{\partial \alpha_1}\mathbf{e}_2, \\
\frac{\partial \mathbf{e}_2}{\partial \alpha_2} &= -\frac{1}{A_1}\frac{\partial A_2}{\partial \alpha_1}\mathbf{e}_1 - \frac{A_2}{R_2}\mathbf{e}_n, \\
\frac{\partial \mathbf{e}_2}{\partial \alpha_1} &= \frac{1}{A_2}\frac{\partial A_1}{\partial \alpha_2}\mathbf{e}_1, \\
\frac{\partial \mathbf{e}_n}{\partial \alpha_1} &= \frac{A_1}{R_1}\mathbf{e}_1, \\
\frac{\partial \mathbf{e}_n}{\partial \alpha_2} &= \frac{A_2}{R_2}\mathbf{e}_2.
\end{aligned} \tag{2.25}$$

In what follows, these formulae permit differentiation of vectors with given projections on to the "local" axes of coordinates $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$ (i.e., on axes which depend on the position of the particular point on the surface). These equations lead immediately to important differential relations between the parameters A_1, A_2 and the principal radii of curvature R_1, R_2. These formulae can be obtained from the conditions that the order of differentiation of mixed second derivatives of vectors may be reversed.

For example, it follows from the identity

$$\frac{\partial^2 \mathbf{e}_n}{\partial \alpha_1 \partial \alpha_2} = \frac{\partial^2 \mathbf{e}_n}{\partial \alpha_2 \partial \alpha_1}$$

that

$$\frac{\partial}{\partial\alpha_2}\left(\frac{A_1}{R_1}\mathbf{e}_1\right)=\frac{\partial}{\partial\alpha_1}\left(\frac{A_2}{R_2}\mathbf{e}_2\right)$$

or

$$\frac{\partial}{\partial\alpha_2}\left(\frac{A_1}{R_1}\right)\mathbf{e}_1+\frac{A_1}{R_1}\frac{\partial\mathbf{e}_1}{\partial\alpha_2}=\frac{\partial}{\partial\alpha_1}\left(\frac{A_2}{R_2}\right)\mathbf{e}_2+\frac{A_2}{R_2}\frac{\partial\mathbf{e}_2}{\partial\alpha_1}. \quad (2.26)$$

Replacing $\frac{\partial\mathbf{e}_1}{\partial\alpha_2}$ and $\frac{\partial\mathbf{e}_2}{\partial\alpha_1}$ by their values (2.25) and transferring all terms to the left side, one finds

$$\left[\frac{\partial}{\partial\alpha_2}\left(\frac{A_1}{R_1}\right)-\frac{1}{R_2}\frac{\partial A_1}{\partial\alpha_2}\right]\mathbf{e}_1-$$
$$-\left[\frac{\partial}{\partial\alpha_1}\left(\frac{A_2}{R_2}\right)-\frac{1}{R_1}\frac{\partial A_2}{\partial\alpha_1}\right]\mathbf{e}_2=0. \quad (2.27)$$

Since this vector equation must be satisfied identically, one has thus the two relations

$$\frac{\partial}{\partial\alpha_1}\left(\frac{A_2}{R_2}\right)=\frac{1}{R_1}\frac{\partial A_2}{\partial\alpha_1}, \quad (a)$$
$$\frac{\partial}{\partial\alpha_2}\left(\frac{A_1}{R_1}\right)=\frac{1}{R_2}\frac{\partial A_1}{\partial\alpha_2}, \quad (b) \quad (2.28)$$

which are called in the theory of surfaces the conditions of Codazzi. These conditions have been obtained here for the particular case when the parameters α_1, α_2 are principal coordinates of the surface.

Next consider the other identity

$$\frac{\partial^2\mathbf{e}_1}{\partial\alpha_1\partial\alpha_2}=\frac{\partial^2\mathbf{e}_1}{\partial\alpha_2\partial\alpha_1},$$

which, using (2.25), can be reduced to the form

$$\left[\frac{\partial}{\partial\alpha_1}\left(\frac{1}{A_1}\frac{\partial A_2}{\partial\alpha_1}\right)+\frac{\partial}{\partial\alpha_2}\left(\frac{1}{A_2}\frac{\partial A_1}{\partial\alpha_2}\right)+\frac{A_1A_2}{R_1R_2}\right]\mathbf{e}_2+$$
$$+\left[\frac{\partial}{\partial\alpha_2}\left(\frac{A_1}{R_1}\right)-\frac{1}{R_2}\frac{\partial A_1}{\partial\alpha_2}\right]\mathbf{e}_n=0. \quad (2.29)$$

Again, in order that this vector equation will be satisfied identically, each of the expressions in square brackets must vanish separately. This gives two further differential relations, only the first of which is new,

while the second coincides with one of the relations (2 28) above. Equating the first square brackets above to zero, one obtains

$$\frac{\partial}{\partial\alpha_1}\left(\frac{1}{A_1}\frac{\partial A_2}{\partial\alpha_1}\right)+\frac{\partial}{\partial\alpha_2}\left(\frac{1}{A_2}\frac{\partial A_1}{\partial\alpha_2}\right)=-\frac{A_1A_2}{R_1R_2}. \tag{2.30}$$

In the theory of surfaces this relation is called the condition of Gauss.

There still remains to consider one further identity, namely

$$\frac{\partial^2\mathbf{e}_2}{\partial\alpha_1\partial\alpha_2}=\frac{\partial^2\mathbf{e}_2}{\partial\alpha_2\partial\alpha_1}.$$

It will be left to the reader to verify by a reasoning quite analogous to the above that no new differential relations between A_1, A_2, R_1, R_2 arise from this equality.

It follows from the above that the four functions A_1, A_2, R_1, R_2 of the two parameters α_1, α_2, if they are chosen arbitrarily, will not, in general, define a surface. They may be considered as Lamé parameters and principal radii of curvature of the surface only in the case that they satisfy the conditions of Gauss and Codazzi. If these conditions are satisfied, these parameters determine a definite surface except for its position in space.

The formulae (2.25), (2.28), (2.30) of the theory of surfaces are sufficient for the development of the theory of shells and they will be frequently used in the following pages.

§ 3. The law of variation of displacements across the thickness of the shell

Let the position of a point on the middle surface of the shell be determined by the curvilinear coordinates α_1, α_2 which will be assumed to be the principal coordinates, so that the coordinates of the lines are simultaneously lines of principal curvature of the middle surface. Further, as the result of deformation, let the arbitrary point O on the middle surface undergo the displacement $\mathbf{\Delta}$. This vector will be a function of α_1, α_2, that is, a function of the particular point on the middle surface, and its knowledge is equivalent to determining the deformation of the middle surface. Let the projections of the displacement $\mathbf{\Delta}$ on the directions $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$ at the point O of the middle surface be denoted by u, v, w. In other words, u will be the projection of the displacement of the middle surface on the direction of the tangent to the line α_1, v the projection of this displacement on the direction of the tangent to the line α_2, w the projection on the normal to the middle surface (at the point O).

At the point O erect the normal to the middle surface and consider a second point O_1 in the interior of the shell and located on this normal at a distance z from the middle surface (z will be assumed to be positive, if the segment OO_1 projects on the positive direction of $\mathbf{e}_n$).

The displacement of the point O_1 will be denoted by $\boldsymbol{\Delta}_z$ and its projections on $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$ by $u_{(z)}$, $v_{(z)}$, $w_{(z)}$. The vector $\boldsymbol{\Delta}_{(z)}$ will be a function of α_1, α_2 as well as of the third coordinate z, since the displacement of the point O_1 must depend on that of the point O of the middle surface and on its distance from that point.

On the basis of the assumptions of § 1, the quantities $u_{(z)}$, $v_{(z)}$, $w_{(z)}$ will now be expressed in terms of the displacements of the middle surface u, v, w and z, using the following reasoning.

During the process of deformation, let the point O move into the position O' and the point O_1 into the position O_1' (Fig. 3). It follows from the first of the assumptions of § 1 that the segment $O'O_1'$ will be perpendicular to the deformed middle surface and that its length will be equal to OO_1 — namely z. Hence one has the vector equation



Fig. 3.

$$z\mathbf{e}_n + \boldsymbol{\Delta}_z = z\mathbf{e}_n' + \boldsymbol{\Delta}, \tag{3.1}$$

where $\mathbf{e}_n'$ is the unit vector normal to the deformed middle surface. This equation expresses the fact that the two vector sums on either side are equal to one and the same vector $\mathbf{OO}_1'$ (Fig. 3).

Solving (3.1) for $\boldsymbol{\Delta}_z$, it is found that

$$\boldsymbol{\Delta}_z = \boldsymbol{\Delta} + (\mathbf{e}_n' - \mathbf{e}_n)z, \tag{3.2}$$

where the unit vector $\mathbf{e}_n'$, neglecting terms involving the product of displacements and their derivatives, may be determined from the relation

$$\mathbf{e}_n' = [\mathbf{e}_1'.\mathbf{e}_2']. \tag{3.3}$$

Here $\mathbf{e}_1'$ and $\mathbf{e}_2'$ are the unit vectors tangential to the lines α_1 and α_2 on the deformed middle surface.

Using vector notation, the equation of the deformed middle surface has then the form

$$\mathbf{R} = \mathbf{r} + \boldsymbol{\Delta} = \mathbf{r} + u\mathbf{e}_1 + v\mathbf{e}_2 + w\mathbf{e}_n. \tag{3.4}$$

This formula expresses the fact that the vector $\mathbf{R}$ to the point α_1, α_2 of the deformed middle surface equals the sum of the vector $\mathbf{r}$, describing the middle surface before deformation, and the displacement vector $\boldsymbol{\Delta}$.

The unit vector in the direction α_1 on the strained middle surface will be equal to

$$\mathbf{e}_1' = \frac{1}{A_1'}\frac{\partial \mathbf{R}}{\partial \alpha_1} = \frac{1}{A_1'}\left(\frac{\partial \mathbf{r}}{\partial \alpha_1} + \frac{\partial u\mathbf{e}_1}{\partial \alpha_1} + \frac{\partial v\mathbf{e}_2}{\partial \alpha_1} + \frac{\partial w\mathbf{e}_n}{\partial \alpha_1}\right), \tag{3.5}$$

where A_1' is the length of the vector $\dfrac{\partial \mathbf{R}}{\partial \alpha_1}$, i.e.,

$$A_1' = \sqrt{\left(\frac{\partial \mathbf{R}}{\partial \alpha_1}, \frac{\partial \mathbf{R}}{\partial \alpha_1}\right)}.$$

This vector will now be expanded in the form

$$\frac{\partial \mathbf{R}}{\partial \alpha_1} = A_1\mathbf{e}_1 + u\frac{\partial \mathbf{e}_1}{\partial \alpha_1} + v\frac{\partial \mathbf{e}_2}{\partial \alpha_1} + w\frac{\partial \mathbf{e}_n}{\partial \alpha_1} + \\ + \frac{\partial u}{\partial \alpha_1}\mathbf{e}_1 + \frac{\partial v}{\partial \alpha_1}\mathbf{e}_2 + \frac{\partial w}{\partial \alpha_1}\mathbf{e}_n \tag{3.6}$$

and the derivatives $\dfrac{\partial \mathbf{e}_1}{\partial \alpha_1}$, $\dfrac{\partial \mathbf{e}_2}{\partial \alpha_1}$, $\dfrac{\partial \mathbf{e}_n}{\partial \alpha_1}$ will be replaced by their values in accordance with (2.25). One thus arrives at

$$\frac{\partial \mathbf{R}}{\partial \alpha_1} = A_1\left(1 + \frac{1}{A_1}\frac{\partial u}{\partial \alpha_1} + \frac{1}{A_1A_2}\frac{\partial A_1}{\partial \alpha_2}v + \frac{w}{R_1}\right)\mathbf{e}_1 + \\ + \left(\frac{\partial v}{\partial \alpha_1} - \frac{1}{A_2}\frac{\partial A_1}{\partial \alpha_2}u\right)\mathbf{e}_2 + \left(\frac{\partial w}{\partial \alpha_1} - \frac{A_1}{R_1}u\right)\mathbf{e}_n. \tag{3.7}$$

In the scalar product of this vector with itself (as in all ensuing calculations of this type) all products of displacements and their derivatives will be neglected, since they are of second order of smallness, and only those terms will be retained which are linear in the displacements and their derivatives. This simplification (which is an accepted procedure in the classical theory of elasticity) is as a rule only admissible in those cases in which the displacements of the elastic body are small in comparison with any one of its dimensions. Thus the results of the ensuing theory will apply only in so far as the displacements to which it leads are small in comparison with the thickness of the shell.

In the evaluation of the expression

$$\left(\frac{\partial \mathbf{R}}{\partial \alpha_1}, \frac{\partial \mathbf{R}}{\partial \alpha_1}\right) = \left|\frac{\partial \mathbf{R}}{\partial \alpha_1}\right|^2$$

the scalar products of all terms in (3.7) with each other must be formed. By virtue of the orthogonality of $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$, all the mixed products $(\mathbf{e}_1, \mathbf{e}_2)$, $(\mathbf{e}_1, \mathbf{e}_n)$, $(\mathbf{e}_2, \mathbf{e}_n)$ will vanish. The products $(\mathbf{e}_2, \mathbf{e}_2)$ and $(\mathbf{e}_n, \mathbf{e}_n)$ will be equal to unity, but the coefficients preceding these two terms are second order quantities in as much as they contain only products of the displacements and their derivatives. Therefore, retaining terms of first order, one may write

$$(A_1')^2 = \left|\frac{\partial \mathbf{R}}{\partial \alpha_1}\right|^2 \approx A_1^2\left(1 + \frac{1}{A_1}\frac{\partial u}{\partial \alpha_1} + \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2}v + \frac{w}{R_1}\right)^2. \tag{3.8}$$

Hence

$$A_1' \approx A_1(1 + \varepsilon_1), \tag{3.9}$$

where

$$\varepsilon_1 = \frac{1}{A_1}\frac{\partial u}{\partial \alpha_1} + \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2}v + \frac{w}{R_1}, \tag{3.10}$$

and therefore

$$\mathbf{e}_1' = \frac{1}{A_1'}\frac{\partial \mathbf{R}}{\partial \alpha_1} \approx \mathbf{e}_1 + \left(\frac{1}{A_1}\frac{\partial v}{\partial \alpha_1} - \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2}u\right)\mathbf{e}_2 + \\ + \left(\frac{1}{A_1}\frac{\partial w}{\partial \alpha_1} - \frac{u}{R_1}\right)\mathbf{e}_n. \tag{3.11}$$

This last formula is obtained by dividing (3.7) by (3.9) and neglecting second order terms.

By a similar argument it can be shown that

$$\mathbf{e}_2' = \frac{1}{A_2'}\frac{\partial \mathbf{R}}{\partial \alpha_2} \approx \mathbf{e}_2 + \left(\frac{1}{A_2}\frac{\partial u}{\partial \alpha_2} - \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1}v\right)\mathbf{e}_1 + \\ + \left(\frac{1}{A_2}\frac{\partial w}{\partial \alpha_2} - \frac{v}{R_2}\right)\mathbf{e}_n. \tag{3.12}$$

It is now possible to evaluate the unit vector, normal to the deformed middle surface by use of (3.3), (3.11) and (3.12). It will be recalled that the rules for vector multiplication of unit vectors in an orthogonal

system of coordinates are expressed by the formulae

$$\begin{aligned} [\mathbf{e}_1, \mathbf{e}_2] &= \mathbf{e}_n, \\ [\mathbf{e}_2, \mathbf{e}_n] &= -[\mathbf{e}_n, \mathbf{e}_2] = \mathbf{e}_1, \\ [\mathbf{e}_n, \mathbf{e}_1] &= -[\mathbf{e}_1, \mathbf{e}_n] = \mathbf{e}_2. \end{aligned} \tag{3.13}$$

Introducing (3.11) and (3.12) into (3.3) and neglecting second order terms, one has

$$\begin{aligned} \mathbf{e}_n' = [\mathbf{e}_1', \mathbf{e}_2'] \approx [\mathbf{e}_1, \mathbf{e}_2] + \\ + \left[\mathbf{e}_1, \left(\frac{1}{A_2}\frac{\partial u}{\partial \alpha_2} - \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1} v\right)\mathbf{e}_1 + \left(\frac{1}{A_2}\frac{\partial w}{\partial \alpha_2} - \frac{v}{R_2}\right)\mathbf{e}_n\right] + \\ + \left[\left(\frac{1}{A_1}\frac{\partial v}{\partial \alpha_1} - \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2} u\right)\mathbf{e}_2 + \left(\frac{1}{A_1}\frac{\partial w}{\partial \alpha_1} - \frac{u}{R_1}\right)\mathbf{e}_n, \mathbf{e}_2\right]. \end{aligned} \tag{3.14}$$

However, the vector product of a vector with itself is zero. Hence, by (3.13), one obtains

$$\mathbf{e}_n' = \mathbf{e}_n + \vartheta \mathbf{e}_1 + \psi \mathbf{e}_2, \tag{3.15}$$

where

$$\begin{aligned} \vartheta &= -\frac{1}{A_1}\frac{\partial w}{\partial \alpha_1} + \frac{u}{R_1}, \\ \psi &= -\frac{1}{A_2}\frac{\partial w}{\partial \alpha_2} + \frac{v}{R_2}. \end{aligned} \tag{3.16}$$

The quantities ϑ and ψ have a simple geometrical interpretation. As can be seen by inspection of the expression (3.15), ϑ and ψ are the projections of the vector $\mathbf{e}_n'$, i.e., of the vector normal to the deformed middle surface on the directions $\mathbf{e}_1$ and $\mathbf{e}_2$. Since $\mathbf{e}_n'$ is of unit length and small displacements are assumed, these projections are equal to the angles by which during deformation the normal to the middle surface rotates about the axes $\mathbf{e}_2$ and $\mathbf{e}_1$ respectively. One may likewise say that ϑ and ψ are the angles by which during deformation the tangents to the lines α_1 and α_2 of the middle surface rotate about the axes $\mathbf{e}_2$ and $\mathbf{e}_1$ respectively, since these angles will be equal to the above-mentioned angles of rotation of the normal.

Returning now to (3.2) and replacing in it $\mathbf{e}_n'$ by the expression (3.15), one finds

$$\mathbf{\Delta}_{(z)} = \mathbf{\Delta} + z(\vartheta \mathbf{e}_1 + \psi \mathbf{e}_2). \tag{3.17}$$

Projecting this vector equation on to the directions $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$, one

arrives at

$$\begin{aligned} u_{(z)} &= u + z\vartheta, \\ v_{(z)} &= v + z\psi, \\ w_{(z)} &= w. \end{aligned} \tag{3.18}$$

These last formulae express the components of displacement of an arbitrary point of the shell in terms of the displacement of its corresponding point on the middle surface.

Thus, in accordance with the initial assumptions, the law of variation of the displacements through the thickness of the shell is linear and the normal displacement $w_{(z)}$ is independent of z.

§ 4. The deformation of a shell and the deformation of its middle surface

Consider a point O on the middle surface of a shell before deformation occurs and next to it a point lying on the line α_1 passing through the point O. Before and after deformation the distance between these points will be given by

(a) $$ds_1 = A_1 d\alpha_1, \tag{4.1}$$

and

(b) $$ds_1' = A_1' d\alpha_1 \tag{4.2}$$

respectively, where A_1' is the Lamé parameter for the deformed middle surface. In the preceding section, this parameter has been determined to first order accuracy by the formulae (3.9, 3.10).

The relative increase of a linear element of the middle surface, having direction α_1, is determined by

$$\frac{ds_1' - ds_1}{ds_1}.$$

Using (4.1), (4.2) and (3.9), it is found that this relative increase is given by

$$\varepsilon_1 = \frac{1}{A_1}\frac{\partial u}{\partial \alpha_1} + \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2} v + \frac{w}{R_1}. \tag{4.3}$$

The formula for the corresponding increase in the direction α_2 may now be written by analogy:

$$\varepsilon_2 = \frac{1}{A_2}\frac{\partial v}{\partial \alpha_2} + \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1} u + \frac{w}{R_2}. \tag{4.4}$$

One further quantity characterizing the deformation of the middle surface has still to be determined, namely, the shear strain defined as the cosine of the angle between the lines α_1, α_2 after deformation. It is clear from this definition that the shear strain will be assumed to be positive, if the angle between the lines α_1, α_2 (a right angle prior to deformation) decreases as the result of the deformation. The cosine of the above angle will be equal to the scalar product of the unit vectors $\mathbf{e}_1'$, $\mathbf{e}_2'$

$$\omega = (\mathbf{e}_1', \mathbf{e}_2'). \tag{4.5}$$

Substituting here the values of the vectors as given by (3.11) and (3.12) and taking into consideration that the mixed products of the unit vectors, i.e., $(\mathbf{e}_1, \mathbf{e}_2)$, $(\mathbf{e}_2, \mathbf{e}_n)$, $(\mathbf{e}_1, \mathbf{e}_n)$ are zero, it is found that

$$\omega = \left(\frac{1}{A_1}\frac{\partial v}{\partial \alpha_1} - \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2}u\right)(\mathbf{e}_2, \mathbf{e}_2) + \left(\frac{1}{A_2}\frac{\partial u}{\partial \alpha_2} - \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1}v\right)(\mathbf{e}_1, \mathbf{e}_1) =$$

$$= \frac{A_2}{A_1}\frac{\partial}{\partial \alpha_1}\left(\frac{v}{A_2}\right) + \frac{A_1}{A_2}\frac{\partial}{\partial \alpha_2}\left(\frac{u}{A_1}\right). \tag{4.6}$$

Now let there be drawn inside the shell a surface lying at a distance z from the middle surface (and, in future, to be referred to as a parallel surface) and consider any point on the middle surface and the pair of coordinate lines passing through this point. As the normal to the middle surface passes along these lines, two lines α_1 and α_2 are generated on the parallel surface.

At the point of intersection of these lines consider the triad of unit vectors $\mathbf{e}_1'$, $\mathbf{e}_2'$, $\mathbf{e}_n'$ which are directed along the tangents to the α_1 and α_2 lines and along the normal to the parallel surface respectively. In view of the method of construction of this last surface, $\mathbf{e}_1'$, $\mathbf{e}_2'$ will be parallel to $\mathbf{e}_1$, $\mathbf{e}_2$, and $\mathbf{e}_n'$ parallel to the same straight line as $\mathbf{e}_n$. Hence it is clear that the net of lines α_1, α_2 on the parallel surface is orthogonal and that the normal to the middle surface is at the same time also normal to the parallel surface. Moreover, the lines α_1, α_2 on the parallel surface will themselves be lines of principal curvature, since for infinitely small displacements along either of these lines the unit vector $\mathbf{e}_n'$, coinciding in direction with $\mathbf{e}_n$, will remain coplanar (see § 2).



Fig. 4.

At two adjacent points of the middle surface, lying on the line α_1, construct the unit normal vectors. Fig. 4 shows the cross-section of the middle surface, defined by the directions of the above-mentioned two normal vectors, where the points m_1, m_2 belong to the middle surface and n_1, n_2 are the corresponding points of the parallel surface. In this figure, O_1 is the centre of curvature of the middle surface for the cross-section drawn in the manner stated above.

If the radius of curvature of this cross-section of the middle surface is equal to R_1, then it is clear from Fig. 4 that the corresponding radius of curvature of the parallel surface will be given by

$$R_1^{(z)} = R_1 + z. \tag{4.7}$$

Further, if the length of the arc m_1m_2 of the middle surface is equal to $ds_1 = A_1 d\alpha_1$, then the length of the arc n_1n_2 of the parallel surface will be given by

$$ds_1^{(z)} = A_1\left(1 + \frac{z}{R_1}\right) d\alpha_1;$$

this follows from the similarity of the sectors $m_1m_2O_1$ and $n_1n_2O_1$ of Fig. 4.

It follows from the above discussion that the principal radii of curvature of the parallel surface and its Lamé parameters will be given by

$$\begin{aligned} A_1^{(z)} &= A_1(1 + z/R_1), \qquad R_1^{(z)} = R_1 + z, \\ A_2^{(z)} &= A_2(1 + z/R_2), \qquad R_2^{(z)} = R_2 + z. \end{aligned} \tag{4.8}$$

On the basis of the simplifying assumptions, when the points of the middle surface undergo displacements u, v, w, the corresponding points of the parallel surface receive the displacements $u_{(z)}$, $v_{(z)}$, $w_{(z)}$, determined by (3.18). Further, the radii of curvature and the Lamé parameters of the parallel surface are known. Therefore, the change in length and shear strain of this last surface may now be determined by using the formulae (4.3), (4.4) and (4.6) and replacing in them u, v, w by $u_{(z)}$, $v_{(z)}$, $w_{(z)}$ and A_1, A_2, R_1, R_2 by $A_1^{(z)}$, $A_2^{(z)}$, $R_1^{(z)}$, $R_2^{(z)}$. Performing these substitutions in (4.3) and using (4.8), one finds

$$\varepsilon_1^{(z)} = \frac{1}{A_1(1 + z/R_1)} \frac{\partial u_{(z)}}{\partial \alpha_1} + \\ + \frac{1}{A_1A_2(1 + z/R_1)(1 + z/R_2)} \frac{\partial A_1(1 + z/R_1)}{\partial \alpha_2} v_{(z)} + \frac{w_{(z)}}{R_1 + z}. \tag{4.9}$$

However, by the second of the Codazzi conditions (2.28),

$$\frac{\partial A_1(1+z/R_1)}{\partial\alpha_2}=\frac{\partial A_1}{\partial\alpha_2}+z\frac{\partial}{\partial\alpha_2}\left(\frac{A_1}{R_1}\right)=(1+z/R_2)\frac{\partial A_1}{\partial\alpha_2},$$

as a result of which (4.9) may be rewritten in the form

$$\varepsilon_1^{(z)}=\frac{1}{1+z/R_1}\left(\frac{1}{A_1}\frac{\partial u_{(z)}}{\partial\alpha_1}+\frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}v_{(z)}+\frac{w_{(z)}}{R_1}\right). \tag{4.10}$$

Substituting now the values of $u_{(z)}$, $v_{(z)}$, $w_{(z)}$ from (3.18), one finds

$$\varepsilon_1^{(z)}=\frac{1}{1+z/R_1}(\varepsilon_1+z\kappa_1), \tag{4.11}$$

where

$$\kappa_1=\frac{1}{A_1}\frac{\partial\vartheta}{\partial\alpha_1}+\frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}\psi \tag{4.12}$$

and ε_1 is defined by (4.3). The parameter $\varepsilon_1^{(z)}$ is the change in length of the linear element of the parallel surface in the direction α_1.

In a similar manner, it can be shown that the change in length in the direction α_2 is given by

$$\varepsilon_2^{(z)}=\frac{1}{1+z/R_2}(\varepsilon_2+z\kappa_2), \tag{4.13}$$

where

$$\kappa_2=\frac{1}{A_2}\frac{\partial\psi}{\partial\alpha_2}+\frac{1}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}\vartheta. \tag{4.14}$$

Consider next the formula for the shear strain (4.6) for the purpose of obtaining from it the corresponding shear strain on the parallel surface. From (4.8) and the Codazzi condition (2.28), one finds

$$\omega^{(z)}=\frac{1}{1+z/R_1}\left[\frac{1}{A_1}\frac{\partial v_{(z)}}{\partial\alpha_1}-\frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}u_{(z)}\right]+$$
$$+\frac{1}{1+z/R_2}\left[\frac{1}{A_2}\frac{\partial u_{(z)}}{\partial\alpha_2}-\frac{1}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}v_{(z)}\right], \tag{4.15}$$

or, after substituting for $u_{(z)}$, $v_{(z)}$ from (3.18),

$$\omega^{(z)}=\frac{1}{1+z/R_1}(\omega_1+z\tau_1)+\frac{1}{1+z/R_2}(\omega_2+z\tau_2), \tag{4.16}$$

where

$$\omega_1 = \frac{1}{A_1}\frac{\partial v}{\partial \alpha_1} - \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2} u, \quad \tau_1 = \frac{1}{A_1}\frac{\partial \psi}{\partial \alpha_1} - \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2} \vartheta,$$
$$\omega_2 = \frac{1}{A_2}\frac{\partial u}{\partial \alpha_2} - \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1} v, \quad \tau_2 = \frac{1}{A_2}\frac{\partial \vartheta}{\partial \alpha_2} - \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1} \psi. \tag{4.17}$$

The formula (4.16) contains four separate functions of α_1, α_2, namely ω_1, ω_2, τ_1, τ_2. However, it is possible to reduce it to a form involving only two separate functions of the curvilinear coordinates of the middle surface. In order to show that this is possible, the existence of the identity

$$\tau_1 + \frac{\omega_2}{R_1} = \tau_2 + \frac{\omega_1}{R_2} \tag{4.18}$$

will be noted which is easily verified by substituting in it for τ_1, τ_2, ω_1, ω_2 their expressions in terms of u, v, w and by performing the differentiation by use of the Codazzi conditions.

Introducing now, in addition to $\omega = \omega_1 + \omega_2$, the new notation

$$\tau = \tau_1 + \frac{\omega_2}{R_1} = \tau_2 + \frac{\omega_1}{R_2} \tag{4.19}$$

and reducing the terms of (4.16) to a common denominator, one finds

$$\omega^{(z)} = \frac{1}{(1 + z/R_1)(1 + z/R_2)}\left[\omega + 2z\tau + \frac{z^2}{R_1 R_2}(\tau_1 R_1 + \tau_2 R_2)\right]. \tag{4.20}$$

However, by (4.19),

$$\tau_1 R_1 + \tau_2 R_2 = (R_1 + R_2)\tau - \omega, \tag{4.21}$$

and therefore, finally,

$$\omega^{(z)} = \frac{1}{(1+z/R_1)(1+z/R_2)}\left\{\left(1 - \frac{z^2}{R_1 R_2}\right)\omega + 2\left[1 + \left(\frac{1}{R_1} + \frac{1}{R_2}\right)\frac{z}{2}\right]z\tau\right\}. \tag{4.22}$$

The formulae (4.11), (4.13) and (4.22) determine the change in length and in the shear of a surface lying at a distance z from the middle surface of the shell. With their help the study of the deformations of a shell is reduced to that of the deformation of the middle surface.

The formulae (4.11), (4.13) and (4.22) contain six different functions

of transfer to the middle surface, namely:

$$\varepsilon_1 = \frac{1}{A_1}\frac{\partial u}{\partial \alpha_1} + \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2} v + \frac{w}{R_1},$$

$$\varepsilon_2 = \frac{1}{A_2}\frac{\partial v}{\partial \alpha_2} + \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1} u + \frac{w}{R_2},$$

$$\omega = \frac{A_2}{A_1}\frac{\partial}{\partial \alpha_1}\left(\frac{v}{A_2}\right) + \frac{A_1}{A_2}\frac{\partial}{\partial \alpha_2}\left(\frac{u}{A_1}\right),$$

$$\kappa_1 = -\frac{1}{A_1}\frac{\partial}{\partial \alpha_1}\left(\frac{1}{A_1}\frac{\partial w}{\partial \alpha_1} - \frac{u}{R_1}\right) - \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2}\left(\frac{1}{A_2}\frac{\partial w}{\partial \alpha_2} - \frac{v}{R_2}\right), \tag{4.23}$$

$$\kappa_2 = -\frac{1}{A_2}\frac{\partial}{\partial \alpha_2}\left(\frac{1}{A_2}\frac{\partial w}{\partial \alpha_2} - \frac{v}{R_2}\right) - \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1}\left(\frac{1}{A_1}\frac{\partial w}{\partial \alpha_1} - \frac{u}{R_1}\right),$$

$$\tau = -\frac{1}{A_1 A_2}\left(\frac{\partial^2 w}{\partial \alpha_1 \partial \alpha_2} - \frac{1}{A_1}\frac{\partial A_1}{\partial \alpha_2}\frac{\partial w}{\partial \alpha_1} - \frac{1}{A_2}\frac{\partial A_2}{\partial \alpha_1}\frac{\partial w}{\partial \alpha_2}\right) +$$

$$+ \frac{1}{R_1}\left(\frac{1}{A_2}\frac{\partial u}{\partial \alpha_2} - \frac{1}{A_1 A_2}\frac{\partial A_1}{\partial \alpha_2} u\right) + \frac{1}{R_2}\left(\frac{1}{A_1}\frac{\partial v}{\partial \alpha_1} - \frac{1}{A_1 A_2}\frac{\partial A_2}{\partial \alpha_1} v\right).$$

The geometrical meaning of ε_1, ε_2, ω has been elucidated earlier: they are the relative changes in length and in the shear of the middle surface. In order to interpret the three remaining parameters κ_1, κ_2, τ geometrically, consider a small element of the middle surface bounded by two pairs of adjacent lines α_1, α_2. The knowledge of the changes in length and of the shear at the point $O(\alpha_1, \alpha_2)$ completely characterizes the variation of the dimensions of the given element after deformation.

However, this information is insufficient for the determination of the shape of the element, since, as the result of deformation, the element may undergo bending as well as changes in length and shear and the above-mentioned three parameters do not account for this effect. The bending of the element of the surface may be characterized by changes of its curvatures in the directions α_1, α_2 and by a twist. In this context, twist will be defined as the limit of the ratio of the angle of mutual twist between two opposite sides of the element of the middle surface to the distance between them, as the dimensions of the element tend to zero. It may be proved that this limit is independent of the choice of the pair of opposite sides of the element. However, no proof of this statement will be given here.

For the above definition, the dimension of twist will be $[L]^{-1}$, i.e., the same as that of curvature. Returning now to the expressions (4.11), (4.13), (4.22), it will be shown that the parameters κ_1, κ_2, τ occurring there

characterize the change of curvature and torsion of the middle surface. This may be verified by the following reasoning. Expanding the denominators of the expressions (4.11), (4.13), (4.22) in power series of z and retaining terms of second order in z, one finds

$$\begin{aligned}
\varepsilon_1^{(z)} &= \varepsilon_1 + z(\kappa_1 - \varepsilon_1/R_1) - \frac{z^2}{R_1}(\kappa_1 - \varepsilon_1/R_1),\\
\varepsilon_2^{(z)} &= \varepsilon_2 + z(\kappa_2 - \varepsilon_2/R_2) - \frac{z^2}{R_2}(\kappa_2 - \varepsilon_2/R_2),\\
\omega^{(z)} &= \omega + 2z\left[\tau - \left(\frac{1}{R_1} + \frac{1}{R_2}\right)\frac{\omega}{2}\right] -\\
&\quad - z^2\left(\frac{1}{R_1} + \frac{1}{R_2}\right)\left[\tau - \frac{R_1^2 - R_2^2}{R_1 + R_2}\,\frac{\omega}{R_1 R_2}\right].
\end{aligned} \tag{4.24}$$

If the shell is thin, the third terms in these expressions may be neglected, since without the small factors they are of order z/R. Thus, for a thin shell, the law of variation of strain and of the corresponding stresses through its thickness (and, consequently, the variation as a function of thickness) may be assumed to be linear. At this point it is appropriate to recall the theory of curved beams, where, if the beam is slender, the hypothesis of plane sections leads to a linear law of variation of stress between the extreme fibres of the cross-section, which does not apply to thick beams. This same circumstance is also true for shells.

Neglecting then in (4.24) the terms in z^2, it is found that

$$\begin{aligned}
\varepsilon_1^{(z)} &\approx \varepsilon_1 + z(\kappa_1 - \varepsilon_1/R_1),\\
\varepsilon_2^{(z)} &\approx \varepsilon_2 + z(\kappa_2 - \varepsilon_2/R_2),\\
\omega^{(z)} &\approx \omega + 2z\left[\tau - \left(\frac{1}{R_1} + \frac{1}{R_2}\right)\frac{\omega}{2}\right].
\end{aligned} \tag{4.25}$$

In these formulae, the first terms correspond to strain uniformly distributed through the thickness and the second terms to strain which varies linearly across the thickness, i.e., to a bending strain.

Hence it is clear that the coefficients of z in the first two of the formulae (4.25) must be equal to the changes of curvature of the middle surface in the directions α_1, α_2

$$\begin{aligned}
\frac{1}{R_1'} - \frac{1}{R_1} &= \kappa_1 - \varepsilon_1/R_1,\\
\frac{1}{R_2'} - \frac{1}{R_2} &= \kappa_2 - \varepsilon_2/R_2,
\end{aligned} \tag{4.26}$$

where R_1', R_2' are the radii of curvature of the normal sections of the deformed middle surface. Thus the parameters κ_1 and κ_2 characterize the change of curvature of the middle surface as deformation occurs. Similarly, the parameter τ characterizes the torsion of the middle surface.

However, these parameters cannot be identified as the change of curvature and torsion of the middle surface, since the first two parameters do not allow for the change in curvature due to straining of the middle surface, and the third for the torsion due to the shear strain ω.

Several authors (for example [43, 4] and others) tend to give this circumstance the fundamental interpretation that it indicates the necessity of using in the theory of shells κ_1', κ_2', τ' as characteristic quantities for the distortion of the middle surface rather than κ_1, κ_2, τ, i.e., the actual changes of curvature and torsion. However, this definition leaves the errors inherent in the initial assumptions of the theory of shells unchanged.

In fact, it follows from (4.25) that

$$\Delta\kappa_1 = \kappa_1' - \kappa_1 = -\varepsilon_1/R_1, \quad \Delta\kappa_2 = \kappa_2' - \kappa_2 = -\varepsilon_2/R_2, \qquad \Delta\tau = \tau' - \tau = -(1/R_1 + 1/R_2)\omega/2. \tag{4.27}$$

the following maximum direct and shear strains at the outer layers of the shell arise from additional changes of curvature and torsion:

$$\varepsilon_1' = \pm\frac{\delta}{2R_1}\varepsilon_1, \quad \varepsilon_2' = \pm\frac{\delta}{2R_2}\varepsilon_2, \quad \omega' = \pm\left(\frac{\delta}{R_1} + \frac{\delta}{R_2}\right)\frac{\omega}{2}; \tag{4.28}$$

in comparison with the direct and shear strains at the middle surface at the point under consideration these will be of order δ/R, i.e., of negligibly small order.

Therefore, in the theory of thin shells, one can put

$$\kappa_1' \approx \kappa_1, \quad \kappa_2' \approx \kappa_2, \quad \tau' \approx \tau, \tag{4.29}$$

and the question of the utilisation of one or the other type of parameters may be resolved solely from the point of view of simplicity of the computations.

For all shells, except spherical and in some cases circular cylindrical shells, the parameters κ_1, κ_2, τ are more convenient, and they will therefore be used in this book to characterize the distortion of the middle surface. However, the right will be reserved to use the approximate equalities (4.29) in those particular cases where they lead to a simplification of the calculations.

It will be noted from (4.26) that the parameters κ_1, κ_2 are positive,

if the curvature of the middle surface is increased by deformation. The torsion τ will be positive, if it leads to positive shear strain in a parallel surface lying with respect to the middle surface on the side of the negative centres of curvature.

For the element of the middle surface, shown in Fig. 5, the torsion will be positive, if, as the sides PP_1 and QQ_1 rotate with respect to each other, the point Q descends, since under these circumstances the angle between the lines α_1, α_2 of the element of the parallel surface will decrease.



Fig. 5.

Thus one arrives at the conclusion that the deformation of the middle surface of a shell is completely determined by the six parameters ε_1, ε_2, ω, κ_1, κ_2, τ the first three of which characterize the variations of the dimensions of a small element of the middle surface, while the remaining three characterize its distortion.

Correspondingly, these six parameters, in terms of which the displacements of the middle surface are expressed by (4.23), will be called the deformations of the middle surface. If all these parameters are equal to zero, the surface is not deformed, i.e., either its displacements u, v, w are equal to zero or the surface is displaced as a rigid body.

It should be noted that it is not accidental that the number of parameters, describing the deformation of the middle surface, is equal to six. In the theory of surfaces, it may be proved that, in the general case when a surface is given in non-orthogonal curvilinear coordinates, its dimensions and shape are completely determined by six parameters (the coefficients of the first and second quadratic forms).

Hence, the results obtained above conform completely in as much as the coordinate lines α_1, α_2 on the deformed middle surface cease to be orthogonal.

§ 5. The conditions for the compatibility of strain in the middle surface

It has been shown in § 2 that there exist three differential relations between the Lamé parameters A_1, A_2 and the radii of curvature R_1, R_2 of a surface, given in principal curvilinear coordinates, namely the conditions of Codazzi and of Gauss. These relations are a particular

case of more complicated formulae, involving the six parameters characterizing the surface in the case when the curvilinear coordinates α_1, α_2 are not orthogonal. These relations must, of course, also be satisfied by the deformed middle surface and it follows from this fact that between the six deformation parameters ε_1, ε_2, ω, κ_1, κ_2, τ there must exist three differential relations which must be valid for any values of the displacements u, v, w, i.e., which must be satisfied identically after replacing in them the deformations of the middle surface by their expressions in terms of u, v, w.

For shells of arbitrary form, these relations were first deduced by Gol'denweizer [6] directly from the conditions of Gauss-Codazzi for the deformed middle surface. They will be given here without detailed deduction which requires on the part of the reader a greater knowledge of the theory of surfaces than has been given above. The results are:

$$
\begin{aligned}
&A_2\frac{\partial\kappa_2}{\partial\alpha_1}+\frac{\partial A_2}{\partial\alpha_1}(\kappa_2-\kappa_1)-A_1\frac{\partial\tau}{\partial\alpha_2}-2\frac{\partial A_1}{\partial\alpha_2}\tau+\frac{1}{R_2}\frac{\partial A_1}{\partial\alpha_2}\omega+\\
&\qquad+\frac{1}{R_1}\left[A_1\frac{\partial\omega}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\omega-A_2\frac{\partial\varepsilon_2}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}(\varepsilon_2-\varepsilon_1)\right]=0,\\
&A_1\frac{\partial\kappa_1}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}(\kappa_1-\kappa_2)-A_2\frac{\partial\tau}{\partial\alpha_1}-2\frac{\partial A_2}{\partial\alpha_1}\tau+\frac{1}{R_1}\frac{\partial A_2}{\partial\alpha_1}\omega+\qquad(5.1)\\
&+\frac{1}{R_2}\left[A_2\frac{\partial\omega}{\partial\alpha_1}+\frac{\partial A_2}{\partial\alpha_1}\omega-A_1\frac{\partial\varepsilon_1}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}(\varepsilon_1-\varepsilon_2)\right]=0,\\
&\frac{\kappa_1}{R_2}+\frac{\kappa_2}{R_1}+\frac{1}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[A_2\frac{\partial\varepsilon_2}{\partial\alpha_1}+\frac{\partial A_2}{\partial\alpha_1}(\varepsilon_2-\varepsilon_1)-\frac{A_1}{2}\frac{\partial\omega}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\omega\right]+\right.\\
&\left.\qquad+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[A_1\frac{\partial\varepsilon_1}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}(\varepsilon_1-\varepsilon_2)-\frac{A_2}{2}\frac{\partial\omega}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}\omega\right]\right\}=0.
\end{aligned}
$$

As an exercise, it is recommended that the reader should verify that after substitution for κ_1, κ_2, τ, ε_1, ε_2, ω from (4.23) the three relations are indeed satisfied identically. For this purpose one has, of course, to take into consideration the relations (2.28) and (2.30).

In the theory of shells, the identities (5.1) are completely analogous to the well known conditions of B. de Saint-Venant in the general theory of elasticity and they have the same geometrical meaning. In fact, they assure that the middle surface remains continuous after deformation,

i.e., that it has no gaps. Hence the relations (5.1) are called the compatibility conditions of the middle surface.

§ 6. Forces and moments

As is usual in the study of the theory of elasticity, the investigation of the geometrical properties of the deformations of shells will be followed by that of the corresponding stresses.

Let a space element be separated from a shell by means of four cuts, normal to its middle surface and tangential to the lines α_1, $\alpha_1 + d\alpha_1$, α_2, $\alpha_2 + d\alpha_2$, the height of which will be finite and equal to the thickness of the shell (Fig. 6).

Let

σ_{11}, σ_{22} be the normal stresses, acting on the faces of this element,

σ_{12}, σ_{21} the shear stresses on these faces, acting parallel to the middle surface,

σ_{13}, σ_{23} the shear stresses on these faces, acting normal to the middle surface.

As is usual in the theory of elasticity, stresses acting on faces the outward normals to which coincide with the positive directions of α_1, α_2 will be assumed to be positive whenever they project positively on $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$.



Fig. 6.

As regards the stresses acting on faces for which the external normal is in the opposite direction to α_1 or α_2, they will be assumed to be positive when they project on the negative directions of $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$. In Fig. 6, all stresses shown are positive.

Since the basic assumptions have led to a completely defined law of variation of the deformations through the thickness of the shell, it may now be assumed that the law of variation of the stresses σ_{11}, σ_{22}, σ_{12}, σ_{21} is known.

As in the theory of plates, it is convenient to introduce instead of these stresses, statically equivalent forces and bending moments. Consider that face of the element in Fig. 6 which is perpendicular to the line α_1 (Fig. 7).



Fig. 7.

On the shaded area of this face, there will act the normal stress σ_{11} and the shear stresses σ_{12}, σ_{13}. Let the length of the arc of the middle surface be equal to $ds_2 = A_2 d\alpha_2$, then the length of the shaded region belonging to the parallel surface will be given by

$$ds_2^{(z)} = A_2(1 + z/R_2)\, d\alpha_2.$$

Hence the resultants of the stresses σ_{11}, σ_{12}, σ_{13}, acting on the entire area of the element of the shell will be equal to

$$S_{11} = A_2 d\alpha_2 \int_{-\delta/2}^{+\delta/2} \sigma_{11}(1 + z/R_2)\, dz,$$

$$S_{12} = A_2 d\alpha_2 \int_{-\delta/2}^{+\delta/2} \sigma_{12}(1 + z/R_2)\, dz,$$

$$S_{13} = A_2 d\alpha_2 \int_{-\delta/2}^{+\delta/2} \sigma_{13}(1 + z/R_2)\, dz.$$

These resultants act on the element of the arc of the line α_2 of the middle surface which is equal to $ds_2 = A_2 d\alpha_2$. Hence one finds for the forces per unit length of the given line

$$\begin{aligned} T_1 &= \frac{S_{11}}{A_2 d\alpha_2} = \int_{-\delta/2}^{+\delta/2} \sigma_{11}(1 + z/R_2)\, dz, \\ T_{12} &= \frac{S_{12}}{A_2 d\alpha_2} = \int_{-\delta/2}^{+\delta/2} \sigma_{12}(1 + z/R_2)\, dz, \\ N_1 &= \frac{S_{13}}{A_2 d\alpha_2} = \int_{-\delta/2}^{+\delta/2} \sigma_{13}(1 + z/R_2)\, dz. \end{aligned} \tag{6.1}$$

In an analogous manner, the following quantities may be introduced:

$$\begin{aligned} T_2 &= \int_{-\delta/2}^{+\delta/2} \sigma_{22}(1 + z/R_1)\,dz, \\ T_{21} &= \int_{-\delta/2}^{+\delta/2} \sigma_{21}(1 + z/R_1)\,dz, \\ N_2 &= \int_{-\delta/2}^{+\delta/2} \sigma_{23}(1 + z/R_1)\,dz \end{aligned} \tag{6.2}$$

which are the forces per unit length of the line α_1 of the middle surface. Consider next the moments of the stresses σ_{11}, σ_{12}, acting on one of the faces of the element of the shell about the directions $\mathbf{e}_2$, $\mathbf{e}_1$. This leads to the two new quantities

$$\begin{aligned} M_1 &= \int_{-\delta/2}^{+\delta/2} z(1 + z/R_2)\sigma_{11}\,dz, \\ M_{12} &= \int_{-\delta/2}^{+\delta/2} z(1 + z/R_2)\sigma_{12}\,dz \end{aligned} \tag{6.3}$$

which are the bending and twisting moments per unit length of the line α_2.

Analogously, by considering the second face of the element of the shell which has acting on it stresses σ_{22}, σ_{21}, one arrives at the quantities

$$\begin{aligned} M_2 &= \int_{-\delta/2}^{+\delta/2} z(1 + z/R_1)\sigma_{22}\,dz, \\ M_{21} &= \int_{-\delta/2}^{+\delta/2} z(1 + z/R_1)\sigma_{21}\,dz, \end{aligned} \tag{6.4}$$

the bending and twisting moments per unit length of the line α_1.

In this approximate theory, the six forces T_1, T_{12}, N_1, T_2, T_{21}, N_2 and the four moments M_1, M_{12}, M_2, M_{21} completely characterize the state of stress of the shell, since by the basic assumptions knowledge of these quantities permits calculation of the stresses σ_{11}, σ_{12}, σ_{22} at any point of the shell.

The positive directions of the forces and moments given by the above formulae are shown in Figs. 8 and 9.



Fig. 8.

Replacing the stresses by their equivalent forces and moments, one may in future consider instead of the space element cut from the shell the corresponding element of the middle surface on the sides of which act these forces and moments. Thus, the introduction of the forces and moments achieves the same object as the preceding sections. There, the deformations of an arbitrary layer of the shell were expressed in terms of the deformation of the middle surface. Here, the stresses in the shell are replaced by their resultants, likewise acting in the middle surface.



Fig. 9.

However, it is essential to note that in the previous sections, when investigating the deformations of the layers of the shell parallel to the middle surface, the shear displacements corresponding to the stresses σ_{13}, σ_{23} were neglected, since the assumption regarding normals remaining normals during deformation is obviously equivalent to this simplification. Thus it might be thought that one should neglect N_1, N_2, and consequently assume that the shearing stresses are zero. However, this is not correct, since these forces play an essential role in the equilibrium equations. The hypothesis which requires normals to remain normals is only applied to determine the law of deformation of a fibre of the

shell, parallel to the middle surface. In the study of the equilibrium of forces this condition is not used.

Hence, the first hypothesis of Kirchhoff should, strictly speaking, be formulated somewhat differently from the way in which this was done in § 1, — namely, instead of the point "a" in that section it should be stated that for the determination of the deformations of the fibres of the shell, parallel to the middle surface, one may neglect the shearing displacements corresponding to the stresses σ_{13}, σ_{23} and the strains in the direction perpendicular to the middle surface. This situation is, of course, not at all equivalent to the categorical statement that normals remain normals.

This remark also applies to the customary formulation of the law relating to plane sections in the theory of beams and to that of the basic hypotheses in the theory of plates.

In view of the fact that these classical definitions are used in all textbooks without, to the author's knowledge, ever referring to this misunderstanding, it was considered acceptable to pursue at the beginning of this book just that method of exposition; that is the reason why they have been defined properly only now.

§ 7. The equilibrium of a shell element

The small element shown in Fig. 6 which has been separated from a shell by four cuts perpendicular to the middle surface will now be considered and the conditions for its equilibrium under the influence of all external and internal loads will be determined.

Firstly the external forces will comprise body forces acting on the element and, secondly, surface forces (stresses) acting on the upper and lower boundaries of the element, which are sections of the curved surfaces bounding the shell. The internal forces will be stresses on the side faces of the element.

In the preceding section, all the internal stresses were transferred to the boundaries of the section of the middle surface corresponding to the considered element of the shell and they were replaced by statically equivalent forces and moments. An analogous operation will now be executed for the external forces by replacing them by statically equivalent stresses distributed over the middle surface. The middle surface will thus be loaded by forces as well as moments. However, in practical problems, the latter can be neglected.

In fact, in view of the smallness of the thickness of the shell, it may be assumed that the body forces (weight and inertia forces) are uniformly

distributed throughout the thickness of the shell, so that the moments about the middle surface vanish at least to a term of order δ/R in comparison with unity. As regards the external forces applied to the surfaces bounding the shell, they will in all practical cases act normal to the middle surface (fluid or gas pressure) and hence again the moment transferred to the middle surface will vanish. Thus, for all practical purposes, it may be assumed that, after transfer of the external forces to the middle surface, the latter will only be stressed by distributed forces.

Let the external force, acting on a unit area of the middle surface, be denoted by $\mathbf{q}$ and the components of this vector in the directions $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_n$ by q_1, q_2, q_n.

Now, instead of considering the equilibrium of an element of the shell, one may study the equilibrium of the corresponding element of the middle surface (Fig. 10).

The sides of this element will then be acted upon by the following internal forces and moments:

On the side OC:
the force

$$-\mathbf{T}^{(1)} = -(T_1\mathbf{e}_1 + T_{12}\mathbf{e}_2 + N_1\mathbf{e}_n)A_2 d\alpha_2$$

and the moment

$$-\mathbf{M}^{(1)} = -(M_1\mathbf{e}_2 - M_{12}\mathbf{e}_1)A_2 d\alpha_2;$$

On the side ED:
the force

$$\mathbf{T}^{(1)} + \frac{\partial \mathbf{T}^{(1)}}{\partial \alpha_1} d\alpha_1$$

and the moment

$$\mathbf{M}^{(1)} + \frac{\partial \mathbf{M}^{(1)}}{\partial \alpha_1} d\alpha_1;$$

On the side EO:
the force

$$-\mathbf{T}^{(2)} = -(T_2\mathbf{e}_1 + T_{21}\mathbf{e}_2 + N_2\mathbf{e}_n)A_1 d\alpha_1$$

and the moment

$$-\mathbf{M}^{(2)} = -(M_{21}\mathbf{e}_2 - M_2\mathbf{e}_1)A_1 d\alpha_1;$$

On the side DC:
the force

$$\mathbf{T}^{(2)} + \frac{\partial \mathbf{T}^{(2)}}{\partial \alpha_2} d\alpha_2$$

and the moment

$$\mathbf{M}^{(2)} + \frac{\partial \mathbf{M}^{(2)}}{\partial \alpha_2} d\alpha_2.$$

In addition, the element will be subject to the external surface loading

$$\mathbf{q} A_1 A_2 d\alpha_1 d\alpha_2 = (q_1 \mathbf{e}_1 + q_2 \mathbf{e}_2 + q_n \mathbf{e}_n) A_1 A_2 d\alpha_1 d\alpha_2.$$

In these formulae, and likewise in the following calculations, changes in the dimensions and in the shape of the element of the middle surface arising from its deformation have been neglected, since their inclusion would have been equivalent to the calculation of products of the deriva-



Fig. 10.

tives of the displacement components. It has earlier been agreed to neglect such terms (§ 3). In addition, it should be recalled that the positive directions of the projections of the forces and moments (and likewise of the stresses) are opposite on opposite sides of the element of the middle surface. If this fact is not taken into consideration, the signs in the above formulae are meaningless.

On the basis of this discussion, the condition that the resultant vector of all the forces acting on the element of the middle surface is to vanish can be written in the form

$$-\mathbf{T}^{(1)} + \mathbf{T}^{(1)} + \frac{\partial \mathbf{T}^{(1)}}{\partial \alpha_1} d\alpha_1 - \mathbf{T}^{(2)} + \mathbf{T}^{(2)} + \frac{\partial \mathbf{T}^{(2)}}{\partial \alpha_2} d\alpha_2 + \\ + \mathbf{q} A_1 A_2 d\alpha_1 d\alpha_2 = 0, \tag{7.1}$$

or, after cancellations,

$$\frac{\partial \mathbf{T}^{(1)}}{\partial \alpha_1} d\alpha_1 + \frac{\partial \mathbf{T}^{(2)}}{\partial \alpha_2} d\alpha_2 + \mathbf{q} A_1 A_2 d\alpha_1 d\alpha_2 = 0. \tag{7.2}$$

Replacing here $\mathbf{T}^{(1)}$, $\mathbf{T}^{(2)}$ and $\mathbf{q}$ by their earlier expressions and using the rules (2.25) for differentiation of unit vectors, one finds after dividing by $d\alpha_1 d\alpha_2$

$$\left[\frac{\partial A_2 T_1}{\partial \alpha_1} + \frac{\partial A_1 T_{21}}{\partial \alpha_2} + \frac{\partial A_1}{\partial \alpha_2} T_{12} - \frac{\partial A_2}{\partial \alpha_1} T_2 + \frac{A_1 A_2}{R_1} N_1 + A_1 A_2 q_1\right] \mathbf{e}_1 +$$

$$+ \left[\frac{\partial A_2 T_{12}}{\partial \alpha_1} + \frac{\partial A_1 T_2}{\partial \alpha_2} + \frac{\partial A_2}{\partial \alpha_1} T_{21} - \frac{\partial A_1}{\partial \alpha_2} T_1 + \frac{A_1 A_2}{R_2} N_2 + A_1 A_2 q_2\right] \mathbf{e}_2 +$$

$$+ \left[\frac{\partial A_2 N_1}{\partial \alpha_1} + \frac{\partial A_1 N_2}{\partial \alpha_2} - A_1 A_2 \left(\frac{T_1}{R_1} + \frac{T_2}{R_2}\right) + A_1 A_2 q_n\right] \mathbf{e}_n = 0. \tag{7.3}$$

In order that this vector equation will be satisfied, the terms in the three square brackets must vanish separately, since a vector can only be identically zero if each of its components satisfy this condition.

Hence the following three differential equations are obtained:

$$\begin{aligned}
&\frac{1}{A_1 A_2}\left[\frac{\partial A_2 T_1}{\partial \alpha_1} + \frac{\partial A_1 T_{21}}{\partial \alpha_2} + \frac{\partial A_1}{\partial \alpha_2} T_{12} - \frac{\partial A_2}{\partial \alpha_1} T_2\right] + \frac{N_1}{R_1} + q_1 = 0,\\
&\frac{1}{A_1 A_2}\left[\frac{\partial A_2 T_{12}}{\partial \alpha_1} + \frac{\partial A_1 T_2}{\partial \alpha_2} + \frac{\partial A_2}{\partial \alpha_1} T_{21} - \frac{\partial A_1}{\partial \alpha_2} T_1\right] + \frac{N_2}{R_2} + q_2 = 0,\\
&\frac{1}{A_1 A_2}\left[\frac{\partial A_2 N_1}{\partial \alpha_1} + \frac{\partial A_1 N_2}{\partial \alpha_2}\right] - \frac{T_1}{R_1} - \frac{T_2}{R_2} + q_n = 0.
\end{aligned} \tag{7.4}$$

They express the condition that the resultant vector of all internal and external forces acting on an element of the shell is to vanish.

Next, the conditions for the vanishing of the resultant moment acting on the same element will be determined. On the basis of the earlier results, the geometric sum of all the interior moments acting on the sides of an element of the middle surface will be given by

$$\mathbf{M}^{(1)} + \frac{\partial \mathbf{M}^{(1)}}{\partial \alpha_1} d\alpha_1 - \mathbf{M}^{(1)} + \mathbf{M}^{(2)} + \frac{\partial \mathbf{M}^{(2)}}{\partial \alpha_2} d\alpha_2 - \mathbf{M}^{(2)} =$$

$$= \frac{\partial \mathbf{M}^{(1)}}{\partial \alpha_1} d\alpha_1 + \frac{\partial \mathbf{M}^{(2)}}{\partial \alpha_2} d\alpha_2. \tag{7.5}$$

Substituting here for $\mathbf{M}^{(1)}$ and $\mathbf{M}^{(2)}$ and taking into consideration the differentiation rule for the unit vectors, one finds

$$\frac{\partial \mathbf{M}^{(1)}}{\partial \alpha_1} d\alpha_1 + \frac{\partial \mathbf{M}^{(2)}}{\partial \alpha_2} d\alpha_2 =$$

$$= \left\{ - \left[\frac{\partial A_2 M_{12}}{\partial \alpha_1} + \frac{\partial A_1 M_2}{\partial \alpha_2} + \frac{\partial A_2}{\partial \alpha_1} M_{21} - \frac{\partial A_1}{\partial \alpha_2} M_1 \right] \mathbf{e}_1 + \right.$$

$$+ \left[\frac{\partial A_2 M_1}{\partial \alpha_1} + \frac{\partial A_1 M_{21}}{\partial \alpha_2} + \frac{\partial A_1}{\partial \alpha_2} M_{12} - \frac{\partial A_2}{\partial \alpha_1} M_2 \right] \mathbf{e}_2 +$$

$$\left. + \left[\frac{M_{12}}{R_1} - \frac{M_{21}}{R_2} \right] A_1 A_2 \mathbf{e}_n \right\} d\alpha_1 d\alpha_2. \tag{7.6}$$

Consider now the moment about the point O (Fig. 10) of all the forces, acting on the element of the middle surface. It will be noted that the moment due to the surface loading will have a higher order of smallness than the remaining moments, since it is calculated by multiplying the vector $\mathbf{q}$, firstly, by the area of the element (a second order quantity) and, secondly, by the moment arm (a first order quantity). On the other hand, the remaining moments involve only factors which are of second order of smallness. On this basis, the moment due to the vector $\mathbf{q}$ may be neglected as a third order quantity.

Next, the moment of the forces will be determined. It is easily seen that the components of the forces in the plane of the middle surface give, to a high order accuracy, only moments about the axis $\mathbf{e}_n$, while the components of the forces normal to the middle surface lead only to moments about the axes $\mathbf{e}_1$ and $\mathbf{e}_2$. For this purpose, multiplying the forces by the appropriate moment arms, one may neglect the differential forces, since they are of second order and lead to third order terms.

Taking all this into consideration, one obtains the following expression for the moment of all the forces about the point O [retaining, as in (7.6), only second order terms]:

$$\{N_2 \mathbf{e}_1 - N_1 \mathbf{e}_2 + (T_{12} - T_{21}) \mathbf{e}_n\} A_1 A_2 d\alpha_1 d\alpha_2. \tag{7.7}$$

The vanishing of the resultant moment of all forces acting on the element of the middle surface leads now to the requirement that the sum of the expressions (7.6) and (7.7) must vanish. Thus, after dividing by $d\alpha_1 d\alpha_2$, one arrives at the three differential equations:

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2M_1}{\partial\alpha_1}+\frac{\partial A_1M_{21}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}M_{12}-\frac{\partial A_2}{\partial\alpha_1}M_2\right]-N_1=0,$$

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2M_{12}}{\partial\alpha_1}+\frac{\partial A_1M_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}M_{21}-\frac{\partial A_1}{\partial\alpha_2}M_1\right]-N_2=0, \qquad (7.8)$$

$$T_{12}-T_{21}+\frac{M_{12}}{R_1}-\frac{M_{21}}{R_2}=0.$$

The six equations (7.4) and (7.8) are the conditions for the equilibrium of a small element of the shell.

It will now be shown that the last of these equations, i.e., the equation

$$T_{12}-T_{21}+\frac{M_{12}}{R_1}-\frac{M_{21}}{R_2}=0 \qquad (7.9)$$

is identically satisfied. In fact, replacing in this equation the forces and moments by their expressions from § 6, one finds

$$T_{12}-T_{21}+\frac{M_{12}}{R_1}-\frac{M_{21}}{R_2}=\int_{-\delta/2}^{+\delta/2}(1+z/R_1)(1+z/R_2)(\sigma_{12}-\sigma_{21})\,dz\equiv 0. \qquad (7.10)$$

Thus, independently of the assumptions adopted for the theory of shells, the equality (7.9) will be fulfilled, because it is implied by the symmetry of the stress tensor.

The above six equations of equilibrium involve ten unknowns, i.e., the problem of the theory of shells is 'internally' statically indeterminate (statically indeterminate, even when only an infinitely small element of the shell is being considered). Its solution is therefore impossible unless several of the unknowns entering into the equilibrium equations are related through an elastic law to the deformations.

In conclusion, it should be emphasized that the deduced static equations for shells involve only an approximation, arising from the assumption that the displacements of the shell are to be small in comparison with its thickness. An approximation, based on the initial assumptions, does not enter into these equations, because these assumptions were not used in their deduction.

§ 8. Functions which satisfy the homogeneous statical equations identically

Simultaneously and independently of each other, Lur'e [17] and Gol'denweizer [6] proved that, if the components of the surface loading

on a shell

$$q_1 = q_2 = q_n = 0,$$

i.e., if the shell is only loaded at the edges, then all the ten unknown forces and moments, entering into the system of equations (7.4), (7.8), can be expressed in terms of four arbitrary functions a, b, c, χ of α_1 and α_2 in such a way that the system is identically satisfied. This result is a generalization of a well known idea in the plane theory of elasticity (due to Airy) to shell problems, except that, instead of a single auxiliary function, the present, more complicated problems require four auxiliary functions. The proof of this statement is based on the fact that the equations of equilibrium of the shell element may be transformed into a form which is similar to the conditions of compatibility of the strain of the middle surface.

Introduce the notation [cf. the identity (7.9)]

$$S = T_{12} - \frac{M_{21}}{R_2} = T_{21} - \frac{M_{12}}{R_1}, \quad H = \frac{M_{12} + M_{21}}{2} \tag{8.1}$$

and eliminate from the equations (7.4) the forces N_1, N_2 by substituting for them their values as given by (7.8). Then, taking into consideration the above notation and using for the differentiations the conditions of Codazzi, the equations (7.4) may be written in the form

$$\begin{aligned}
&\frac{\partial A_2 T_1}{\partial \alpha_1} + \frac{\partial A_1 S}{\partial \alpha_2} + \frac{\partial A_1}{\partial \alpha_2} S - \frac{\partial A_2}{\partial \alpha_1} T_2 + \\
&+ \frac{1}{R_1}\left[\frac{\partial A_2 M_1}{\partial \alpha_1} - \frac{\partial A_2}{\partial \alpha_1} M_2 + 2\frac{\partial A_1 H}{\partial \alpha_2} + 2\frac{R_1}{R_2}\frac{\partial A_1}{\partial \alpha_2} H\right] = -A_1 A_2 q_1, \\
&\frac{\partial A_2 S}{\partial \alpha_1} + \frac{\partial A_1 T_2}{\partial \alpha_2} + \frac{\partial A_2}{\partial \alpha_1} S - \frac{\partial A_1}{\partial \alpha_2} T_1 + \\
&+ \frac{1}{R_2}\left[\frac{\partial A_1 M_2}{\partial \alpha_2} - \frac{\partial A_1}{\partial \alpha_2} M_1 + 2\frac{\partial A_2 H}{\partial \alpha_1} + 2\frac{R_2}{R_1}\frac{\partial A_2}{\partial \alpha_1} H\right] = -A_1 A_2 q_2, \\
&\frac{T_1}{R_1} + \frac{T_2}{R_2} - \frac{1}{A_1 A_2}\left\{\frac{\partial}{\partial \alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2 M_1}{\partial \alpha_1} + \frac{\partial A_1 H}{\partial \alpha_2} + \frac{\partial A_1}{\partial \alpha_2} H - \frac{\partial A_2}{\partial \alpha_1} M_2\right] + \right. \\
&\left. + \frac{\partial}{\partial \alpha_2}\frac{1}{A_2}\left[\frac{\partial A_2 H}{\partial \alpha_1} + \frac{\partial A_1 M_2}{\partial \alpha_2} + \frac{\partial A_2}{\partial \alpha_1} H - \frac{\partial A_1}{\partial \alpha_2} M_1\right]\right\} = q_n.
\end{aligned} \tag{8.2}$$

It will now be assumed that the problem is homogeneous, i.e., that

$$q_1 = q_2 = q_n = 0,$$

and the three arbitrary functions a, b, c of the variables α_1, α_2 will be introduced which are to be related to the unknowns in the equations by means of the formulae

$$\begin{aligned} T_1 &= \kappa_2(a, b, c), \\ T_2 &= \kappa_1(a, b, c), \\ S &= -\tau(a, b, c), \\ M_1 &= -\varepsilon_2(a, b, c), \\ M_2 &= -\varepsilon_1(a, b, c), \\ H &= \tfrac{1}{2}\omega(a, b, c), \end{aligned} \tag{8.3}$$

where $\varepsilon_1(a, b, c), \ldots \tau(a, b, c)$ are understood to be the expressions for the strains in the middle surface, defined by (4.23) with u, v, w replaced by a, b, c respectively. By substituting now (8.3) in (8.2), it may be verified that this leads to expressions which are identical with the conditions of compatibility of strain for the middle surface, i.e., with equations (5.1). But these last equations would be identically satisfied by the deformations of the middle surface whatever the displacements u, v and w may be. Hence clearly the equations (8.2) will also be identically satisfied by the expressions (8.3) involving the arbitrary auxiliary functions a, b and c.

Express now the forces T_{12}, T_{21} and the moments M_{12}, M_{21} in terms of these functions. On the basis of (8.1) and (8.3), one may write

$$\begin{aligned} M_{12} + M_{21} &= \omega(a, b, c), \\ T_{12} - \frac{M_{21}}{R_2} &= -\tau(a, b, c), \\ T_{21} - \frac{M_{12}}{R_1} &= -\tau(a, b, c). \end{aligned} \tag{8.4}$$

By the first of these formulae

$$\begin{aligned} M_{12} &= \tfrac{1}{2}\omega(a, b, c) + \Phi, \\ M_{21} &= \tfrac{1}{2}\omega(a, b, c) - \Phi, \end{aligned} \tag{8.5}$$

where Φ is a function which from the point of view of satisfying the static equations has the same arbitrary character as a, b, c.

Substituting now for M_{12}, M_{21} in the last two of the formulae (8.4)

their expressions (8.5), one finds

$$T_{12} = -\tau(a, b, c) + \frac{1}{2R_2}\omega(a, b, c) - \Phi/R_2,$$
$$T_{21} = -\tau(a, b, c) + \frac{1}{2R_1}\omega(a, b, c) + \Phi/R_1. \tag{8.6}$$

There still remains the determination of the normal shearing forces N_1, N_2 in terms of the same four functions. This may be done by substituting from the above formulae in the first two of the equations (7.8). After some manipulations, involving the Gauss-Codazzi relations, one obtains

$$N_1 = \frac{1}{R_2}\vartheta(a, c) - \frac{1}{A_2}\frac{\partial\chi}{\partial\alpha_2},$$
$$N_2 = \frac{1}{R_1}\psi(a, c) + \frac{1}{A_1}\frac{\partial\chi}{\partial\alpha_1}, \tag{8.7}$$

where $\vartheta(a, c)$, $\psi(a, c)$ are the quantities obtained by replacing in (3.16) the displacements u, v, w by a, b, c, while

$$\chi = \Phi - \frac{1}{2A_1A_2}\left[\frac{\partial A_2 a}{\partial\alpha_2} - \frac{\partial A_2 b}{\partial\alpha_1}\right].$$

All the ten forces and moments, characterizing the state of stress of the shell, have now been expressed in terms of the four functions a, b, c, Φ and this has been done in such a manner that by substitution of these expressions into the equations of equilibrium of the element of the shell (8.2) (for $q_1 = q_2 = q_n = 0$) these equations are satisfied identically.

There arises now the question of how the four functions a, b, c, Φ are to be determined. This problem may be resolved in the same way as in the plane theory of elasticity, namely, the stress functions can be found from the conditions of compatibility. For this purpose, the forces and moments must be related to the deformations of the middle surface and this will be done in one of the following sections by use of Hooke's law and the initial assumptions. Then the compatibility equations may be written in terms of the forces and moments and, after substitution of the expressions (8.3), one arrives at three differential equations for the functions a, b, c, Φ.

However, there are four functions and only three equations, so that in order that the problem will be determinate it is necessary to establish one further relation between the unknown functions.

It will become clear later on that on the basis of the initial hypotheses one must have

$$M_{12} = M_{21} = H.$$

Thus the function Φ must be put equal to zero.

Although this method of solution applies only to the particular case when the surface loading on the shell is zero and although by the above method the problem will not be solved directly, nevertheless the results of this section are of great importance for what follows, because the discovered similarity between the equilibrium and compatibility conditions may be used to transform the equations of the general theory of shells. In this way, the order of these differential equations will be halved.

§ 9. The strain energy for a shell

The discussion so far has dealt with the geometry of shells and the equilibrium conditions for its elements, and thus it did not depend on the elastic properties of its material. For this reason, these properties have not been considered so far. However, since the equations of equilibrium obtained in § 7 for an element of the shell are statically indeterminate, the problem cannot be solved until the elastic properties of the shell have been established.

It is known that the elastic nature of a body is completely specified by the expression for its potential energy of deformation. This expression will now be deduced for thin shells made from a material which is homogeneous, isotropic and obeys Hooke's law. For this purpose, a start will be made with the generalized formula of the general theory of elasticity

$$V = \tfrac{1}{2}\int (\sigma_{11}e_{11} + \sigma_{22}e_{22} + \sigma_{33}e_{33} + \sigma_{12}e_{12} + \sigma_{13}e_{13} + \sigma_{23}e_{23})\,dO, \qquad (9.1)$$

where σ_{11}, σ_{22}, σ_{33} are the normal stresses on three mutually perpendicular faces of an element, cut from the elastic body,
e_{11}, e_{22}, e_{33} are the corresponding strains,
σ_{12}, σ_{13}, σ_{23} are the shear stresses on these faces,
e_{12}, e_{13}, e_{23} are the corresponding shear deformations,
dO is the volume of the element,

and the integration in (9.1) extends over the entire volume of the body under consideration.

This formula will be applied to an element separated from a shell by four neighbouring cuts perpendicular to the lines α_1, α_2 of the middle

surface and by two cuts parallel to the middle surface (Fig. 6), the volume of which will be equal to the product of its three sides (since they are perpendicular to each other)

$$dO = A_1A_2(1 + z/R_1)(1 + z/R_2)\,d\alpha_1 d\alpha_2 dz. \tag{9.2}$$

The hypotheses of Kirchhoff are equivalent to neglecting the stress σ_{33} in comparison with the remaining stresses and the strains e_{13}, e_{23} in comparison with the remaining strains (§ 1). Hence it follows from these hypotheses that one may write

$$V = \tfrac{1}{2}\int\int\int (\sigma_{11}e_{11}+\sigma_{22}e_{22}+\sigma_{12}e_{12})A_1A_2(1+z/R_1)(1+z/R_2)\,d\alpha_1 d\alpha_2 dz, \tag{9.3}$$

where the first integral extends through the thickness of the shell (i.e., from $z = -\delta/2$ to $z = +\delta/2$) and the remaining integrals are taken over its entire middle surface.

By Hooke's law, one has for homogeneous and isotropic bodies

$$\begin{aligned}
\sigma_{11} &= \frac{E}{1+\mu}\left(e_{11} + \frac{\mu}{1-2\mu}e\right),\\
\sigma_{22} &= \frac{E}{1+\mu}\left(e_{22} + \frac{\mu}{1-2\mu}e\right),\\
\sigma_{33} &= \frac{E}{1+\mu}\left(e_{33} + \frac{\mu}{1-2\mu}e\right),\\
\sigma_{12} &= \frac{E}{2(1+\mu)}e_{12},
\end{aligned} \tag{9.4}$$

where

E is Young's modulus,

μ is Poisson's ratio,

$e = e_{11} + e_{22} + e_{33}$.

Neglecting in (9.4) the stress σ_{33} in comparison with the remaining stresses, one finds

$$\frac{1+\mu}{E}\sigma_{33} = e_{33} + \frac{\mu e}{1-2\mu} = \frac{1}{1-2\mu}[(1-\mu)e_{33} + \mu(e_{11}+e_{22})] = 0,$$

and hence

$$e_{33} = -\frac{\mu}{1-\mu}(e_{11} + e_{22}). \tag{9.5}$$

Introducing this value for the strain e_{33} into the first two of the formulae (9.4), one obtains

$$\sigma_{11} = \frac{E}{1-\mu^2}(e_{11} + \mu e_{22}),$$
$$\sigma_{22} = \frac{E}{1-\mu^2}(e_{22} + \mu e_{11}), \tag{9.6}$$

or, since in this case e_{11}, e_{22}, e_{33} are identical with the strains $\varepsilon_1^{(z)}$, $\varepsilon_2^{(z)}$, $\omega^{(z)}$ considered in § 1, one may write

$$\sigma_{11} = \frac{E}{1-\mu^2}[\varepsilon_1^{(z)} + \mu\varepsilon_2^{(z)}],$$
$$\sigma_{22} = \frac{E}{1-\mu^2}[\varepsilon_2^{(z)} + \mu\varepsilon_1^{(z)}], \tag{9.7}$$
$$\sigma_{12} = \frac{E}{2(1+\mu)}\omega^{(z)},$$

where $\varepsilon_1^{(z)}$, $\varepsilon_2^{(z)}$, $\omega^{(z)}$ are given in terms of the deformations of the middle surface ε_1, ε_2, ω, κ_1, κ_2, τ and the coordinate z by the formulae (4.11), (4.13), (4.22).

After substituting these expressions in (9.7) and then from (9.7) into (9.3), the integration with respect to z can be carried out. In order to simplify the result, the integrand in (9.3) will now be expanded in a series of powers of z, retaining terms of up to and including the second order. The corresponding expressions for the strains $\varepsilon_1^{(z)}$, $\varepsilon_2^{(z)}$, $\omega^{(z)}$, to the same order of accuracy, have already been obtained earlier in the formula (4.25). Introducing (4.25) into (9.7) and into (9.3) (replacing there e_{11}, e_{22}, e_{33}) and rejecting powers of z higher than the second, one finds

$$V = \frac{E}{2(1-\mu^2)}\int\int\left\{\int_{-\delta/2}^{+\delta/2}(Q_0 + Q_1 z + Q_2 z^2)\,dz\right\} A_1 A_2\, d\alpha_1\, d\alpha_2, \tag{9.8}$$

where

$$Q_0 = (\varepsilon_1 + \varepsilon_2)^2 - 2(1-\mu)\left(\varepsilon_1\varepsilon_2 - \frac{\omega^2}{4}\right),$$
$$Q_2 = (\kappa_1 + \kappa_2)^2 - 2(1-\mu)(\kappa_1\kappa_2 - \tau^2) -$$
$$- 2\left(\frac{1}{R_1} - \frac{1}{R_2}\right)(\varepsilon_1\kappa_1 - \varepsilon_2\kappa_2) - (1-\mu)\left(\frac{1}{R_1} + \frac{1}{R_2}\right)\omega\tau + \tag{9.9}$$
$$+ \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\left(\frac{\varepsilon_1^2}{R_1} - \frac{\varepsilon_2^2}{R_2}\right) + \frac{1-\mu}{2}\left(\frac{1}{R_1^2} - \frac{1}{R_1 R_2} + \frac{1}{R_2^2}\right)\omega^2.$$

The value of Q_1 will be of no interest, since

$$\int_{-\delta/2}^{+\delta/2} Q_1 z\, ds = Q_1 \int_{-\delta/2}^{+\delta/2} z\, dz = 0.$$

After carrying out the integration with respect to z in (9.8), one finds

$$V = \frac{E\delta}{2(1-\mu^2)} \iint \left[(\varepsilon_1+\varepsilon_2)^2 - 2(1-\mu)\left(\varepsilon_1\varepsilon_2 - \frac{\omega^2}{4}\right)\right] A_1 A_2\, d\alpha_1\, d\alpha_2 +$$

$$+ \frac{E\delta^3}{24(1-\mu^2)} \iint \Big\{ (\kappa_1+\kappa_2)^2 - 2(1-\mu)(\kappa_1\kappa_2 - \tau^2) -$$

$$- 2\left(\frac{1}{R_1} - \frac{1}{R_2}\right)(\varepsilon_1\kappa_1 - \varepsilon_2\kappa_2) -$$

$$- (1-\mu)\left(\frac{1}{R_1} + \frac{1}{R_2}\right)\omega\tau + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\left(\frac{\varepsilon_1^2}{R_1} - \frac{\varepsilon_2^2}{R_2}\right) +$$

$$+ \frac{1-\mu}{2}\left(\frac{1}{R_1^2} - \frac{1}{R_1 R_2} + \frac{1}{R_2^2}\right)\omega^2 \Big\} A_1 A_2\, d\alpha_1\, d\alpha_2, \quad (9.10)$$

where the integration extends only over the middle surface of the shell.

Since in this theory of shells there is an admissible error of order δ/R in comparison with unity, replacement of (9.1) by (9.3) introduces into the potential energy an error of the stated order. Hence, in (9.10), terms of this order may not be rejected and it must be discovered which terms are to be retained or rejected. This process will be more difficult, since (9.10) contains the quantities ε_1, ε_2, ω and κ_1, κ_2, τ, where each group has different dimensions (namely — the first group contains dimensionless quantities, while those in the second group have the dimension $[L]^{-1}$).

Introduce therefore instead of κ_1, κ_2, τ the parameters

$$\varepsilon_1' = \frac{\delta}{2}\kappa_1, \quad \varepsilon_2' = \frac{\delta}{2}\kappa_2, \quad \omega' = \tau\delta,$$

which have simple physical interpretations; namely, ε_1', ε_2' are the strains in the extreme fibres of the shell, caused by the bending κ_1, κ_2, and ω' is the shear strain in the outer layer of the shell, arising from the twist τ.

These last interpretations follow from (4.11), (4.13) and (4.22) after neglecting there the ratios z/R_1, z/R_2 in comparison with unity and letting $z = \frac{\delta}{2}$.

The quantities ε_1', ε_2', ω' are now dimensionally similar to ε_1, ε_2, ω. Introducing these quantities into (9.10) instead of κ_1, κ_2, τ, this formula may be reduced to the form

$$V = \frac{E\delta}{2(1-\mu^2)}\iint\Big\{(\varepsilon_1+\varepsilon_2)^2 - 2(1-\mu)\left(\varepsilon_1\varepsilon_2 - \frac{\omega^2}{4}\right) + \\ + \frac{1}{3}\left[(\varepsilon_1'+\varepsilon_2')^2 - 2(1-\mu)\left(\varepsilon_1'\varepsilon_2' - \frac{\omega'^2}{4}\right)\right] - \\ - \frac{1}{3}\left(\frac{\delta}{R_1}-\frac{\delta}{R_2}\right)(\varepsilon_1\varepsilon_1' - \varepsilon_2\varepsilon_2') - \frac{1-\mu}{12}\left(\frac{\delta}{R_1}+\frac{\delta}{R_2}\right)\omega\omega' + \\ + \frac{1}{12}\left(\frac{\delta}{R_1}-\frac{\delta}{R_2}\right)\left(\frac{\delta}{R_1}\varepsilon^2 - \frac{\delta}{R_2}\varepsilon_2^2\right) + \\ + \frac{1-\mu}{24}\left(\frac{\delta^2}{R_1^2} - \frac{\delta^2}{R_1R_2} + \frac{\delta^2}{R_2^2}\right)\omega^2\Big\}A_1A_2\,d\alpha_1\,d\alpha_2. \qquad (9.11)$$

The integrand above is now a quadratic form in the six dimensionless parameters ε_1, ε_2, ω, ε_1', ε_2', ω'. Comparing its three groups of terms

$$\text{(I)} \quad (\varepsilon_1+\varepsilon_2)^2 - 2(1-\mu)\left(\varepsilon_1\varepsilon_2 - \frac{\omega^2}{4}\right) + \\ + \frac{1}{3}\left[(\varepsilon_1'+\varepsilon_2')^2 - 2(1-\mu)\left(\varepsilon_1'\varepsilon_2' - \frac{\omega'^2}{4}\right)\right],$$

$$\text{(II)} \quad -\frac{1}{3}\left(\frac{\delta}{R_1}-\frac{\delta}{R_2}\right)(\varepsilon_1\varepsilon_1' - \varepsilon_2\varepsilon_2') - \frac{1-\mu}{12}\left(\frac{\delta}{R_1}+\frac{\delta}{R_2}\right)\omega\omega',$$

$$\text{(III)} \quad \frac{1}{12}\left(\frac{\delta}{R_1}-\frac{\delta}{R_2}\right)\left(\frac{\delta}{R_1}\varepsilon_1^2 - \frac{\delta}{R_2}\varepsilon_2^2\right) + \frac{1-\mu}{24}\left(\frac{\delta^2}{R_1^2} - \frac{\delta^2}{R_1R_2} + \frac{\delta^2}{R_2^2}\right)\omega^2,$$

it is seen that for arbitrary values of the parameters ε_1', ε_2', ω', ε_1, ε_2, ω the sum of the terms of the second group, if compared to that of the terms of the first group, will be a quantity of order not greater than δ/R, while the sum of the terms of the third group, compared with that of the first group, will be of order δ^2/R^2. This fact is readily established by making all possible assumptions concerning the relative magnitudes of the parameters ε_1, ε_2, ω, ε_1', ε_2', ω (the least favourable of which will be the case when all quantities are of equal order). Hence it follows that, having agreed on the basic assumptions for the theory, one must, in order to be mathematically consistent, neglect the terms (II) and (III) in comparison with the term (I).

Thus the potential energy of deformation in the theory of thin shells must be written in the form

$$V = \frac{E\delta}{2(1-\mu^2)}\iint\left[(\varepsilon_1+\varepsilon_2)^2 - 2(1-\mu)\left(\varepsilon_1\varepsilon_2 - \frac{\omega^2}{4}\right)\right]A_1A_2\,d\alpha_1\,d\alpha_2 +$$

$$+ \frac{E\delta^3}{24(1-\mu^2)}\iint[(\kappa_1+\kappa_2)^2 - 2(1-\mu)(\kappa_1\kappa_2-\tau^2)]A_1A_2\,d\alpha_1\,d\alpha_2, \quad (9.12)$$

where the double integrals extend over the entire middle surface. In this formula, the first term represents the potential energy of extension and shear, the second that of bending and torsion.

Formula (9.12) is quite analogous to the expression for the potential energy of plates. It contains the deformations of the middle surface which are expressed in terms of the three displacement components u, v, w by (4.23).

§ 10. Relations between the forces, moments and the strains of the middle surface

Consider now the expression for the variational change of the potential energy of deformation which, as is known from the theory of elasticity, is of the form

$$\delta(V) = \iiint[\sigma_{11}\delta(e_{11}) + \sigma_{22}\delta(e_{22}) + \sigma_{33}\delta(e_{33}) + \sigma_{12}\delta(e_{12}) +$$

$$+ \sigma_{13}\delta(e_{13}) + \sigma_{23}\delta(e_{23})]\,dO, \quad (10.1)$$

where $\delta(\ldots)$ is the symbol for the variational increment.

Using the basic assumptions, this formula may be written for the case of thin shells in the form

$$\delta(V) = \iiint[\sigma_{11}\delta(e_{11}) + \sigma_{22}\delta(e_{22}) + \sigma_{12}\delta(e_{12})](1+z/R_1)$$

$$\times (1+z/R_2)A_1A_2\,d\alpha_1\,d\alpha_2\,dz, \quad (10.2)$$

where integration extends over the entire volume of the shell.

Introducing here

$$\delta(e_{11}) = \delta(\varepsilon_1^{(z)}) = \frac{1}{1+z/R_1}[\delta(\varepsilon_1) + z\delta(\kappa_1)],$$

$$\delta(e_{22}) = \delta(\varepsilon_2^{(z)}) = \frac{1}{1+z/R_2}[\delta(\varepsilon_2) + z\delta(\kappa_2)], \quad (10.3)$$

$$\delta(e_{12}) = \delta(\omega^{(z)}) = \frac{1}{1+z/R_1}[\delta(\omega_1) + z\delta(\tau_1)] + \frac{1}{1+z/R_2}[\delta(\omega_2) + z\delta(\tau_2)]$$

and using (6.1), (6.2), (6.3), (6.4), one finds

$$\delta(V) = \iint [T_1\delta(\varepsilon_1) + T_2\delta(\varepsilon_2) + T_{12}\delta(\omega_1) + T_{21}\delta(\omega_2) + \\ + M_1\delta(\kappa_1) + M_2\delta(\kappa_2) + M_{12}\delta(\tau_1) + M_{21}\delta(\tau_2)]A_1A_2\,d\alpha_1\,d\alpha_2, \quad (10.4)$$

where the integration ranges over the middle surface of the shell.

But, by (4.9),

$$\delta(\tau_1) = \delta(\tau) - \frac{1}{R_1}\delta(\omega_2),$$

$$\delta(\tau_2) = \delta(\tau) - \frac{1}{R_2}\delta(\omega_1), \quad (10.5)$$

$$\delta(\omega) = \delta(\omega_1) + \delta(\omega_2).$$

Hence (10.4) may be reduced to the form

$$\delta(V) = \iint [T_1\delta(\varepsilon_1) + T_2\delta(\varepsilon_2) + S\delta(\omega) + M_1\delta(\kappa_1) + M_2\delta(\kappa_2) + \\ + 2H\delta(\tau)]A_1A_2\,d\alpha_1\,d\alpha_2, \quad (10.6)$$

where, as in § 8,

$$S = T_{12} - \frac{M_{21}}{R_2} = T_{21} - \frac{M_{12}}{R_1}, \quad (10.7)$$

$$H = \tfrac{1}{2}(M_{12} + M_{21}).$$

On the basis of (9.12) and (10.6), relations between the quantities T_1, T_2, S, M_1, M_2, H and the deformations of the middle surface may be readily established. For this purpose, one has to determine the variational increase of the potential energy starting from (9.12) and then to compare the coefficients for variational changes of the deformations in this expression with the corresponding coefficients in (10.6).

In this manner, the following relations are obtained:

$$T_1 = \frac{E\delta}{1-\mu^2}(\varepsilon_1 + \mu\varepsilon_2), \qquad T_2 = \frac{E\delta}{1-\mu^2}(\varepsilon_2 + \mu\varepsilon_1),$$

$$M_1 = \frac{E\delta^3}{12(1-\mu^2)}(\kappa_1 + \mu\kappa_2), \quad M_2 = \frac{E\delta^3}{12(1-\mu^2)}(\kappa_2 + \mu\kappa_1), \quad (10.8)$$

$$S = \frac{E\delta}{2(1+\mu)}\omega, \qquad H = \frac{E\delta^3}{12(1+\mu)}\tau.$$

The last two of the formulae (10.8), written out in full, represent the

three equations (8.1)

$$T_{12} - \frac{M_{21}}{R_2} = \frac{E\delta}{2(1+\mu)}\omega,$$
$$T_{21} - \frac{M_{12}}{R_1} = \frac{E\delta}{2(1+\mu)}\omega, \tag{10.9}$$
$$M_{12} + M_{21} = \frac{E\delta^3}{6(1+\mu)}\tau,$$

which by their very nature are insufficient to express each of the quantities T_{12}, T_{21}, M_{12}, M_{21} uniquely in terms of ω and τ.

One finds from these equations

$$T_{12} = \frac{E\delta}{2(1+\mu)}\left(\omega + \frac{\delta^2}{6R_2}\tau\right) - \Phi/R_2,$$
$$T_{21} = \frac{E\delta}{2(1+\mu)}\left(\omega + \frac{\delta^2}{6R_1}\tau\right) + \Phi/R_1, \tag{10.10}$$
$$M_{12} = \frac{E\delta^3}{12(1+\mu)}\tau + \Phi, \quad M_{21} = \frac{E\delta^3}{12(1+\mu)}\tau - \Phi,$$

where from the point of view of the preceding reasoning the function Φ may be chosen to suit convenience. It is curious that this indeterminateness (as has been noted recently) has no importance for the further study of the theory of shells. It has turned out that, in general, it is not necessary to find in the theory of shells the forces T_{12}, T_{21} and the moments M_{12}, M_{21} separately, since these forces and moments only enter into the equilibrium equations (after elimination of N_1, N_2) and into the boundary conditions in the combinations denoted above by S and H. For the equilibrium equations, this feature was established in § 8, while for the boundary conditions, this fact will be established in the next section.

Thus, for the solution of problems of the theory of shells (independently of whether they will be solved in terms of forces and moments or in terms of displacements), it is not necessary to express T_{12}, T_{21}, M_{12}, M_{21} in terms of the deformations of the middle surface, but only the corresponding quantities S and H. The values of T_{12}, T_{21}, M_{12}, M_{21} are required separately only for the determination of the normal shearing forces N_1, N_2. However, the evaluation of these latter forces is not usually of much practical interest, since in thin shells the shear stresses σ_{13}, σ_{23} corresponding to given forces are always very small (in comparison with the remaining stresses), a fact on which, in essence, the hypotheses of Kirchhoff are based. The little importance attached to these stresses is evident from the fact that no reference to the literature can be given

where the question of determining the maximum values of the stresses σ_{13}, σ_{23} for given values of the normal shearing forces N_1, N_2 is discussed.

If for some reason it is desired to evaluate the quantities T_{12}, T_{21}, M_{12}, M_{21} separately, one may proceed to the determination of the function Φ in (10.10), for example, in the following manner:
it is found from (6.3) and (6.4) that

$$M_{12} - M_{21} = 2\Phi = \left(\frac{1}{R_2} - \frac{1}{R_1}\right) \int_{-\delta/2}^{+\delta/2} z^2 \sigma_{12}\, dz; \tag{10.11}$$

substituting here for σ_{12} from the last of the formulae (9.7) and for $\omega^{(z)}$ from (4.22), one has

$$2\Phi = \frac{E}{2(1+\mu)}\left(\frac{1}{R_2} - \frac{1}{R_1}\right) \int_{-\delta/2}^{+\delta/2} \frac{z^2}{(1 + z/R_1)(1 + z/R_2)} \left\{\left(1 - \frac{z^2}{R_1 R_2}\right)\omega + \right.$$
$$\left. + 2\left[1 + \frac{1}{2}\left(\frac{1}{R_1} + \frac{1}{R_2}\right) z\right] z\tau \right\} dz; \tag{10.12}$$

neglecting now in this last expression (under the integral sign) quantities of order δ/R_1, δ/R_2 in comparison with unity, i.e., letting

$$1 + z/R_1 \approx 1 + z/R_2 \approx 1 - \frac{z^2}{R_1 R_2} \approx 1 + \frac{1}{2}\left(\frac{1}{R_1} + \frac{1}{R_2}\right) z \approx 1,$$

one obtains for Φ the approximate expression

$$\Phi \approx \left(\frac{1}{R_2} - \frac{1}{R_1}\right) \frac{E\delta^3}{48(1+\mu)}\, \omega. \tag{10.13}$$

Introducing this expression into (10.10), one arrives after some analysis at the conclusion that the effect of the introduction of Φ is always insignificant, since it is beyond the limit of the error of the initial assumptions of the theory of thin shells. Using this result, one may set $\Phi = 0$ in (10.10), identifying in this way M_{12} and M_{21} with H.

The above development exhausts the question regarding the relations between the forces, moments and the deformations of the middle surface in the theory of thin shells. These are given by (10.8), obtained from the expressions for the potential energy (9.12), simplified in accordance with the accuracy of the initial assumptions of the theory of thin shells.

The attentive reader will no doubt note that there exists another and simpler way of arriving at the relations between the forces, moments and deformations than that which was used above. In fact, using (6.1),

(6.2), (6.3), (6.4), (9.7), (4.11), (4.13), (4.22), one may write

$$T_1 = \frac{E}{1-\mu^2}\int_{-\delta/2}^{+\delta/2}\left\{\frac{1+z/R_2}{1+z/R_1}(\varepsilon_1 + z\kappa_1) + \mu(\varepsilon_2 + z\kappa_2)\right\}dz,$$

$$T_2 = \frac{E}{1-\mu^2}\int_{-\delta/2}^{+\delta/2}\left\{\frac{1+z/R_1}{1+z/R_2}(\varepsilon_2 + z\kappa_2) + \mu(\varepsilon_1 + z\kappa_1)\right\}dz,$$

$$T_{12} = \frac{E}{2(1+\mu)}\int_{-\delta/2}^{+\delta/2}\left\{\left(1-\frac{z^2}{R_1R_2}\right)\omega - \right.$$
$$\left. + 2\left[1 + \frac{1}{2}\left(\frac{1}{R_1}+\frac{1}{R_2}\right)z\right]z\tau\right\}\frac{dz}{1+z/R_1},$$

$$T_{21} = \frac{E}{2(1+\mu)}\int_{-\delta/2}^{+\delta/2}\left\{\left(1-\frac{z^2}{R_1R_2}\right)\omega + \right.$$
$$\left. + 2\left[1 + \frac{1}{2}\left(\frac{1}{R_1}+\frac{1}{R_2}\right)z\right]z\tau\right\}\frac{dz}{1+z/R_2}, \quad (10.14)$$

$$M_1 = \frac{E}{1-\mu^2}\int_{-\delta/2}^{+\delta/2}\left\{\frac{1+z/R_2}{1+z/R_1}(\varepsilon_1 + z\kappa_1) + \mu(\varepsilon_2 + z\kappa_2)\right\}z\,dz,$$

$$M_2 = \frac{E}{1-\mu^2}\int_{-\delta/2}^{+\delta/2}\left\{\frac{1+z/R_1}{1+z/R_2}(\varepsilon_2 + z\kappa_2) + \mu(\varepsilon_1 + z\kappa_1)\right\}z\,dz,$$

$$M_{12} = \frac{E}{2(1+\mu)}\int_{-\delta/2}^{+\delta/2}\left\{\left(1-\frac{z^2}{R_1R_2}\right)\omega + \right.$$
$$\left. + 2\left[1 + \frac{1}{2}\left(\frac{1}{R_1}+\frac{1}{R_2}\right)z\right]z\tau\right\}\frac{z\,dz}{1+z/R_1},$$

$$M_{21} = \frac{E}{2(1+\mu)}\int_{-\delta/2}^{+\delta/2}\left\{\left(1-\frac{z^2}{R_1R_2}\right)\omega + \right.$$
$$\left. + 2\left[1 + \frac{1}{2}\left(\frac{1}{R_1}+\frac{1}{R_2}\right)z\right]z\tau\right\}\frac{z\,dz}{1+z/R_2}.$$

All the integrals in (10.14) can be evaluated. However, if no simplifications

are made, one obtains very cumbersome expressions involving a number of small terms the magnitude of which is such that they lie beyond the limits of accuracy of the initial assumptions of the theory of shells.

Taking into consideration the accuracy of these assumptions, one has to omit in (10.14) quantities of order δ/R compared with unity. Hence, at a first glance, one must put there

$$1 + z/R_1 \approx 1 + z/R_2 \approx 1, \tag{10.15}$$

since

$$-\delta/2 \leqslant z \leqslant \delta/2.$$

As a result of this simplification, the following relations between the forces, moments and the deformations of the middle surface are obtained:

$$\begin{gathered} T_1 = \frac{E\delta}{1-\mu^2}(\varepsilon_1 + \mu\varepsilon_2), \quad T_2 = \frac{E\delta}{1-\mu^2}(\varepsilon_2 + \mu\varepsilon_1), \\ T_{12} = T_{21} = \frac{E\delta}{2(1+\mu)}\omega, \\ M_1 = \frac{E\delta^3}{12(1-\mu^2)}(\kappa_1 + \mu\kappa_2), \quad M_2 = \frac{E\delta^3}{12(1-\mu^2)}(\kappa_2 + \mu\kappa_1), \\ M_{12} = M_{21} = \frac{E\delta^3}{12(1+\mu)}\tau. \end{gathered} \tag{10.16}$$

These are very similar to the formulae (10.10) in that they differ from them only by the absence of terms in the expressions for T_{12} and T_{21}. The formulae (10.16) are used more often in the theory of shells. Love recommended them as first approximations, but he made the mistake of stating that these expressions correspond to the definition of the potential energy of shells by the expression (9.12), (cf. Love [49] p. 557). The merit of the formulae (10.16) lies in their simplicity and their complete analogy with the corresponding formulae of the theory of plates.

However, the adoption of these formulae introduces several contradictions into the theory of shells. For example, substituting these expressions into the equilibrium equations for an element of the shell, one obtains differential equations in the displacement components for which it is impossible to select stress functions. In other words, a shell, the elastic properties of which are expressed by (10.16), is such that not all deformations of the elastic body are expressible as potential energy of deformation. A further consequence of this discrepancy is that the reciprocal theorem does not hold. Further, substituting (10.16) into the

six equilibrium equations (7.9) for an element of the shell, it may be verified that they are not identically satisfied. Meanwhile, as has already been shown in § 7, the fact that these equations are satisfied identically secures the symmetry of the stress tensor from which follows that (10.16) contradict these fundamental properties of the stresses. These contradictions, introduced into the theory of shells by the formulae (10.16), were first pointed out by V. Z. Vlasov. The author of this book does not agree with the excessive exaggeration of the harmful role played by these contradictions in the theory of shells, since no examples are known where they would introduce mathematical inaccuracies exceeding those due to the initial assumptions underlying the theory of thin shells. However, at the same time, he cannot, of course, deny that the presence of such contradictions is a defect of a theory which admits them. All these contradictions may be removed, if the laws relating the forces, moments and deformations of the middle surface are selected in the form (10.8), (10.10) rather than in the form (10.16), as it will be recommended here.

It should be pointed out that until quite recently differences in opinion have existed regarding the best way of writing the relations between the forces, moments and deformations, and a considerable number of variations of these formulae have been proposed which were the result of neglecting (sometimes in a quite arbitrary manner) one or the other term in (10.14). Only one of these variations will be mentioned here which is more logical and was proposed by Lur'e [17].

Since Lur'e did not have at his disposal a criterion for discarding small terms, he proceeded, in order to avoid errors, by expanding the integrands in (10.14) in power series of z, omitting all terms of order larger than z^2. As a result he obtained the expressions

$$
\begin{aligned}
T_1 &= \frac{E\delta}{1-\mu^2}\left[\varepsilon_1 + \mu\varepsilon_2 - \frac{\delta^2}{12}\left(\frac{1}{R_1} - \frac{1}{R_2}\right)(\kappa_1 - \varepsilon_1/R_1)\right],\\
T_2 &= \frac{E\delta}{1-\mu^2}\left[\varepsilon_2 + \mu\varepsilon_1 + \frac{\delta^2}{12}\left(\frac{1}{R_1} - \frac{1}{R_2}\right)(\kappa_2 - \varepsilon_2/R_2)\right],\\
T_{12} &= \frac{E\delta}{2(1+\mu)}\left[\omega - \frac{\delta^2}{12}\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\left(\tau - \frac{\omega}{R_1}\right)\right], \qquad (10.17)\\
T_{21} &= \frac{E\delta}{2(1+\mu)}\left[\omega + \frac{\delta^2}{12}\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\left(\tau - \frac{\omega}{R_2}\right),\right.\\
M_1 &= \frac{E\delta^3}{12(1-\mu^2)}\left[\kappa_1 + \mu\kappa_2 - \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\varepsilon_1\right],
\end{aligned}
$$

$$M_2 = \frac{E\delta^3}{12(1-\mu^2)}\left[\kappa_2 + \mu\kappa_1 + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\varepsilon_2\right],$$
$$M_{12} = \frac{E\delta^3}{12(1+\mu)}\left(\tau - \frac{\omega}{2R_1}\right), \quad M_{21} = \frac{E\delta^3}{12(1+\mu)}\left(\tau - \frac{\omega}{2R_2}\right). \tag{10.17}$$

Comparing these formulae with (10.10) and (10.16), it is seen that they are considerably more cumbersome and it is clear from the above discussion that these additional terms introduce into the theory corrections which do not exceed the accuracy of the initial assumptions. Hence the formulae (10.17) have come to be regarded as inconsistent and, for shells of arbitrary form, they introduce into the equations quite unnecessary complications. However, for the particular case of spherical shells, the equations are essentially simplified thanks to the presence of the factor $(1/R_1 - 1/R_2)$ and it turns out that for such shells, which are of great practical importance, simpler equations are obtained by use of (10.17) than by (10.10). Therefore, when considering spherical shells, it will be expedient to employ the formulae (10.17).

In conclusion, it will be noted that the formulae (10.10) were first obtained in 1944 by the author of this book [32] and, almost simultaneously, by L. I. Balabukh. Balabukh sought the simplest form of relation between the forces, moments and deformations of the middle surface which would satisfy the reciprocal law and the six equilibrium equations of an element of a shell and arrived at his result by trial.

The present author sought that form of the same relation which, apart from being simplest, would simultaneously ensure solution of any problem of the theory of shells to an accuracy, not exceeding that of the initial assumptions of the given theory. It turned out that the results of these two different approaches coincided.

§ 11. The boundary conditions for the problem of stresses in a shell

The solutions of the differential equations (8.2), (10.8) naturally do not yet determine completely the state of stress in a shell as long as they are not subject to boundary conditions, i.e., until a certain number of relations between the forces, moments, displacements or functions of these quantities at the supporting edge or edges of the shell are specified.

It will now be shown how many boundary conditions must be imposed in any given case; in addition, the accepted formulation of these boundary conditions will be presented.

Consider first the case when the shell has no boundary, i.e., when it

is completely closed or complete. It is evident that in this case the concept of the boundary condition loses its meaning. However, it does not follow from this that any solution satisfying (8.2), (10.8) and (4.23) is in this case a solution of the stress problem of the shell. The coordinate lines α_1, α_2 on the middle surface of a complete shell will themselves be closed curves. Letting $\alpha_2 = \text{const.}$ and allowing α_1 to vary (or vice versa), one will periodically return to the same point of the middle surface. Since the displacements of this point will be completely determined quantities, one must impose (in this case) on the solutions of the system (8.2), (10.8) the conditions that the solutions are to be periodic functions of α_1 and α_2 (with such a period that the above mentioned single-valuedness of the displacements will be insured). Thus, in the case of complete shells, the boundary conditions are replaced by the conditions of periodicity.

It may at times happen that a shell is complete with respect to the one coordinate and incomplete with regard to the other, as is, for example, the case for cylindrical tubes. In this case, a condition of periodicity will apply only for one of the coordinates.

Proceeding now to shells with boundaries, consideration will be limited to the simplest case where the boundaries coincide with lines of principal curvature of the middle surface, since this case is encountered most frequently in practice. The formulations of the boundary conditions for the general case may be found, for example, in the book by Love [49].

Thus, let one of the coordinate lines, for example, the line $\alpha_2 = \alpha_2^0 = \text{const.}$ be the boundary of a shell which, as has been stated in § 1, will be assumed to be generated by the motion of the normal to the middle surface along this line.

In the present theory, the stresses acting on the boundary will be integrated over the thickness and replaced by three forces per unit length (in this case T_{21}, T_2 and N_2) and by two moments per unit length (here M_2 and M_{21}). Hence one would think that the number of boundary conditions, completely determining the solution, must be equal to five (the number of quantities, determining the state of stress).

However, the problem of the stresses in a plate (as in a shell, since the analogous reasoning may also be applied in this case) is not completely defined by five, but only by four boundary conditions. In fact, the twisting moment on the boundary of the shell can be replaced by corresponding, distributed, tangential and transverse forces. This statement will now be proved.

For this purpose, consider a segment of the boundary of the middle surface near some point m_1 (Fig. 11 which shows the plane, containing the tangent to the edge at the point m_1 and the normal to the middle

surface at this point). The boundary curve will now be approximated by a polygon, formed by a number of very small segments of equal length. The length of each segment, with high order accuracy, may be set equal to the length of the arc spanning it

$$m_1m_2 = mm_1 \approx ds_1.$$

Next, place half way between the points m, m_1 and m_1, m_2 the points n_1 and n_2. Then it is evident that

$$n_1n_2 \approx ds_1.$$

The value of the twisting moment at the point n_1 will be M_{21}, while at the point n_2 it will be given by

$$M_{21} + \frac{\partial M_{21}}{\partial s_1} ds_1.$$

Further, replace the twisting moment acting over the boundary mm_1 by two forces, equal in magnitude and opposite in direction,



Fig. 11.

which are placed at the ends of the arc mm_1. For this purpose, the force placed at the point m_1 will be directed along the normal to the middle surface at the point n_1 (i.e., parallel to On_1 in Fig. 11) and the force at the point m in the opposite direction. In a similar manner, the twisting moment in the adjacent section m_1m_2 will be replaced by two forces, parallel to the normal at the point n_2, etc.

Then, at each of the corners of the above polygon, there will apply two forces. One will be directed along the normal at the point n_1 and it will be

equal to the twisting moment, belonging to the arc ds_1 and divided by that moment arm. The second will be directed along the normal at the point n_2 a distance ds_1 from n_1 (and pointing in the opposite direction to the first force). Its magnitude will be

$$M_{21} + \frac{\partial M_{21}}{ds_1} ds_1.$$

Projecting both these forces, acting at the point m_1, on the direction of the normal to the middle surface (the direction of N_2) and on the direction of the tangent to the middle surface (the direction of T_{21}), one obtains:

a) in the first case

$$\frac{\partial M_{21}}{ds_1} ds_1 + M_{21} - M_{21} = \frac{\partial M_{21}}{ds_1} ds_1;$$

b) in the second case

$$\left(2M_{21} + \frac{\partial M_{21}}{\partial s_1} ds_1\right) \varphi,$$

where 2φ is the angle between the normals to the middle surface at the points n_1 and n_2, i.e.,

$$2\varphi = \frac{ds_1}{R_1}.$$

Substituting this value for φ into the expression b) and retaining only first order quantities, one finds

$$\frac{M_{21}}{R_1} ds_1.$$

Thus, along the edge of the shell, the twisting moment can be replaced by distributed normal shear forces

$$\frac{\partial M_{21}}{\partial s_1}$$

and distributed tangential forces

$$\frac{M_{21}}{R_1}.$$

By replacing the twisting moments by statically equivalent forces, one admits a certain redistribution of the stresses over the thickness

of the shell along its edges. By the principle of St. Venant, the effect of this approximation cannot be significant; it can only be noticeable within the immediate neighbourhood of the edges (at distances of the order of the thickness of the shell).

It follows from the above that, in the given case when the boundary is a line $\alpha_2 = \alpha_2^0 = \text{constant}$, the four quantities

$$T_2,\ T_{21} + \frac{M_{21}}{R_1},\ N_2 + \frac{1}{A_1}\frac{\partial M_{21}}{\partial \alpha_1},\ M_2$$

completely determine the state of stress at the edge of the shell; therefore, the number of boundary conditions at each of its edges must be equal to four, and not five.

Notice further that, by (8.1) and the second of the equations (7.8),

$$T_{21} + \frac{M_{21}}{R_1} = T_{21} - \frac{M_{12}}{R_1} + \frac{1}{R_1}(M_{21} + M_{12}) = S + 2\frac{H}{R_1}, \tag{11.1}$$

$$N_2 + \frac{1}{A_1}\frac{\partial M_{21}}{\partial \alpha_1} = \frac{1}{A_1 A_2}\left(2\frac{\partial A_2 H}{\partial \alpha_1} + \frac{\partial A_1 M_2}{\partial \alpha_2} - \frac{\partial A_1}{\partial \alpha_2} M_1\right). \tag{11.2}$$

Hence it is clear that the forces T_{12}, T_{21} and the moments M_{12}, M_{21} do not enter separately into the boundary conditions, but only in the combinations denoted earlier by S and H.

Using the above results, it is not difficult to deduce by analogy the boundary conditions for the case when the edge of the shell is a line

$$\alpha_1 = \alpha_1^0 = \text{const.}$$

Of course, it is not always the case that the boundary conditions will be expressed just in terms of the four quantities above. The former may also be given indirectly, for example, by prescribing displacements or angles of rotation at the edge. This leads to a number of possible variations of the boundary conditions:

a) Free edge

$$T_2 = 0,\ T_{21} + \frac{M_{21}}{R_1} = 0,\ N_2 + \frac{1}{A_1}\frac{\partial M_{21}}{\partial \alpha_1} = 0,\ M_2 = 0;$$

b) Hinged edge with fixed support

$$M_2 = 0,\ u = 0,\ v = 0,\ w = 0;$$

c) Hinged edge with support free to move in the normal direction

$$M_2 = 0,\ N_2 + \frac{1}{A_1}\frac{\partial M_{21}}{\partial \alpha_1} = 0,\ u = 0,\ v = 0;$$

d) Clamped edge

$$u = 0,\ v = 0,\ w = 0,\ \psi = -\frac{1}{A_2}\frac{\partial w}{\partial \alpha_2} + \frac{v}{R_2} = 0$$

(where the last of these equalities expresses the fact that the angle of rotation of the edge of the shell is equal to zero — formula (3.16)).

The above alternatives of the boundary conditions do not exhaust all possibilities. Depending on the character of the supports on which the shell rests, its boundary conditions may assume a great variety of forms. Although the number of boundary conditions for plates as well as for shells equals four, the problem of the stresses in a plate [1] breaks up into two independent problems (the plane problem and the problem of bending) and therefore the boundary conditions likewise comprise two independent groups. Therefore, the bending of plates is determined by two conditions at each of their boundaries. For shells, excluding the simplest problems, one is obliged, as a rule, to deal with all four boundary conditions. Hence, the boundary conditions in the theory of shells are more diversified than in the theory of beams and plates. In particular, the concepts of "support" and "clamping" are quite determined in the theory of beams and plates, while in the theory of shells there is no such degree of definiteness, since a shell, completely unmovable with regard to one displacement, may be free or freely supported with regard to the other displacement.

§ 12. Formulation of the compatibility conditions in terms of forces and moments

On the basis of the formulae (10.8), the strain of the middle surface is expressed in terms of the forces and moments by the following relations:

$$\varepsilon_1 = \frac{1}{E\delta}(T_1 - \mu T_2),\ \varepsilon_2 = \frac{1}{E\delta}(T_2 - \mu T_1),$$

$$\omega = \frac{2(1+\mu)}{E\delta}S = \frac{2(1+\mu)}{E\delta}\left(T_{12} - \frac{H}{R_2}\right) = \frac{2(1+\mu)}{E\delta}\left(T_{21} - \frac{H}{R_1}\right),$$

$$\kappa_1 = \frac{12}{E\delta^3}(M_1 - \mu M_2),\ \kappa_2 = \frac{12}{E\delta^3}(M_2 - \mu M_1), \tag{12.1}$$

$$\tau = \frac{12(1+\mu)}{E\delta^3}H.$$

[1] Having in mind the linear theory of plates.

Substituting these expressions into the conditions for the compatibility of strain in the middle surface, i.e., in (5.1), one finds

$$\frac{\partial A_2(M_2-\mu M_1)}{\partial\alpha_1}-(1+\mu)\left(\frac{\partial A_1 H}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}H\right)-\frac{\partial A_2}{\partial\alpha_1}(M_1-\mu M_2)-$$
$$-\frac{\delta^2}{12R_1}\left[\frac{\partial A_2(T_2-\mu T_1)}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}(T_1-\mu T_2)-2(1+\mu)\frac{\partial A_1 S}{\partial\alpha_2}-\right.$$
$$\left.-2(1+\mu)\frac{R_1}{R_2}\frac{\partial A_1}{\partial\alpha_2}S\right]=0,$$

$$\frac{\partial A_1(M_1-\mu M_2)}{\partial\alpha_2}-(1+\mu)\left(\frac{\partial A_2 H}{\partial\alpha_1}+\frac{\partial A_2}{\partial\alpha_1}H\right)-\frac{\partial A_1}{\partial\alpha_2}(M_2-\mu M_1)-$$
$$-\frac{\delta^2}{12R_2}\left[\frac{\partial A_1(T_1-\mu T_2)}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}(T_2-\mu T_1)-2(1+\mu)\frac{\partial A_2 S}{\partial\alpha_1}-\right.$$
$$\left.-2(1+\mu)\frac{R_2}{R_1}\frac{\partial A_2}{\partial\alpha_1}S\right]=0, \tag{12.2}$$

$$\frac{M_2-\mu M_1}{R_1}+\frac{M_1-\mu M_2}{R_2}+\frac{\delta^2}{12}\frac{1}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2(T_2-\mu T_1)}{\partial\alpha_1}-\right.\right.$$
$$\left.-(1+\mu)\left(\frac{\partial A_1 S}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}S\right)-\frac{\partial A_2}{\partial\alpha_1}(T_1-\mu T_2)\right]+$$
$$+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[\frac{\partial A_1(T_1-\mu T_2)}{\partial\alpha_2}-(1+\mu)\left(\frac{\partial A_2 S}{\partial\alpha_1}+\frac{\partial A_2}{\partial\alpha_1}S\right)-\right.$$
$$\left.\left.-\frac{\partial A_1}{\partial\alpha_2}(T_2-\mu T_1)\right]\right\}=0.$$

These three differential relations are the compatibility conditions in terms of the forces and moments. Their name is based on the following considerations. It will be assumed that the forces and moments are known. Substituting their values in (12.1) and replacing in these formulae the strains of the middle surface by their expressions in terms of the displacement components (using 4.23), six partial differential equations for the determination of the three displacements u, v, w will be obtained. It is evident that the given system may turn out to be inconsistent, i.e., it may be found that there do not exist functions u, v, w, satisfying all the six equations.

The necessary and sufficient conditions for such functions to exist are that the forces and moments must satisfy (12.2). Thus the differential

relations between the forces and moments (12.2) guarantee the compatibility of the formulae (12.1), which can be regarded as a system of differential equations for the determination of the displacements.

It will be recalled that in the general theory of elasticity the conditions of St. Venant which, when written in terms of stresses are the so-called Beltrami-Michell equations, likewise ensure the possibility of integrating the formulae connecting the displacements and the stresses. Hence the formulae (12.2) are the analogue to the equations of Beltrami-Michell in the theory of shells. In view of the existence of such an analogue, there will be no need to prove the above statements.

It should still be mentioned that the compatibility conditions of the middle surface (12.2), after transformations employing the equilibrium equations for shells, can be reduced to the form

$$(1+\mu)N_1 = \frac{1}{A_1}\frac{\partial M}{\partial \alpha_1} - \frac{\delta^2}{12m_1}\left\{\frac{1}{R_1A_1}\frac{\partial T}{\partial \alpha_1} - \frac{(1+\mu)}{A_2}\left(\frac{1}{R_1}\frac{\partial S}{\partial \alpha_2} + \frac{2S}{R_2A_1}\frac{\partial A_1}{\partial \alpha_2}\right) + \right.$$
$$\left. + \frac{1}{R_1}\left[\frac{1}{R_1A_1}\frac{\partial M}{\partial \alpha_1} + \frac{1+\mu}{A_2}\left(\frac{1}{R_1}\frac{\partial H}{\partial \alpha_2} + \frac{2H}{R_2A_1}\frac{\partial A_1}{\partial \alpha_2}\right)\right] + \frac{1+\mu}{R_1}q_1\right\},$$

$$(1+\mu)N_2 = \frac{1}{A_2}\frac{\partial M}{\partial \alpha_2} - \frac{\delta^2}{12m_2}\left\{\frac{1}{R_2A_2}\frac{\partial T}{\partial \alpha_2} - \frac{1+\mu}{A_1}\left(\frac{1}{R_2}\frac{\partial S}{\partial \alpha_1} + \frac{2S}{R_1A_2}\frac{\partial A_2}{\partial \alpha_1}\right) + \right.$$
$$\left. + \frac{1}{R_2}\left[\frac{1}{R_2A_2}\frac{\partial M}{\partial \alpha_2} + \frac{1+\mu}{A_1}\left(\frac{1}{R_2}\frac{\partial H}{\partial \alpha_1} + \frac{2H}{R_1A_2}\frac{\partial A_2}{\partial \alpha_1}\right)\right] + \frac{1+\mu}{R_2}q_2\right\}, \quad (12.3)$$

$$\frac{M_1-\mu M_2}{R_2} + \frac{M_2-\mu M_1}{R_1} + \frac{\delta^2}{12}\left\{\Delta(T) + \frac{1+\mu}{A_1A_2}\left[\frac{\partial}{\partial \alpha_1}\left(\frac{A_2}{R_1}N_1\right) + \frac{\partial}{\partial \alpha_2}\left(\frac{A_1}{R_2}N_2\right)\right] + \right.$$
$$+ \frac{1+\mu}{A_1A_2}\left[\frac{\partial}{\partial \alpha_1}\left(\frac{1}{R_1}\frac{\partial H}{\partial \alpha_2} + \frac{2H}{R_2A_1}\frac{\partial A_1}{\partial \alpha_2}\right) + \frac{\partial}{\partial \alpha_2}\left(\frac{1}{R_2}\frac{\partial H}{\partial \alpha_1} + \frac{2H}{R_1A_2}\frac{\partial A_2}{\partial \alpha_1}\right)\right] +$$
$$\left. + \frac{1+\mu}{A_1A_2}\left[\frac{\partial}{\partial \alpha_1}(A_2q_1) + \frac{\partial}{\partial \alpha_2}(A_1q_2)\right]\right\} = 0,$$

where

$$T = T_1 + T_2, \qquad M = M_1 + M_2, \quad (12.4)$$

$$m_1 = 1 + \frac{\delta^2}{12R_1^2}, \quad m_2 = 1 + \frac{\delta^2}{12R_2^2}, \quad (12.5)$$

and the symbol $\Delta(\ldots)$ denotes the Laplace operator in the curvilinear

coordinates α_1, α_2, i.e.,

$$\Delta(\ldots) = \frac{1}{A_1 A_2}\left\{\frac{\partial}{\partial\alpha_1}\left[\frac{A_2}{A_1}\frac{\partial(\ldots)}{\partial\alpha_1}\right] + \frac{\partial}{\partial\alpha_2}\left[\frac{A_1}{A_2}\frac{\partial(\ldots)}{\partial\alpha_2}\right]\right\}. \quad (12.6)$$

§ 13. The two methods of solution of problems in the theory of shells

In the general theory of elasticity, there exist two methods for solving problems. The first involves replacement in the equilibrium equations of the element of the elastic body of the stresses by their expressions in terms of the displacements. In this way, one obtains for the displacements in a homogeneous, isotropic body a system of three equations, the so-called "equations of Lamé". The second method replaces in the compatibility conditions of St. Venant the strains by their expressions in terms of the stresses. In this way, one obtains the six equations of Beltrami-Michell which, in conjunction with the equilibrium equations, permit the solution of the problem directly in terms of the stresses.

In a similar manner, problems in the theory of shells may be solved by two methods — in terms of the displacements of the middle surface or in terms of the forces and moments. The first method replaces in the equilibrium equations (8.2) the forces and moments by their expressions in terms of the strains of the middle surface. If for this purpose the forces and moments are determined by use of (10.8), one obtains for the displacements of the middle surface a system of three partial differential equations. This system will be of eighth order. Here and in the future discussion, the statement that a system of partial differential equations is of eighth (or, in general, of n-th) order will be understood to mean that the system is equivalent to some single eighth (or n-th) order partial differential equation.

The second method consists in supplementing the equilibrium equations (8.2) by the compatibility relations in terms of the forces and moments which, if use is made of (10.8), will have the form (12.2) or (12.3). Then one obtains for the determination of the unknowns T_1, T_2, S, M_1, M_2, H a system of six partial differential equations (which again are of eighth order).

Because of the hypothesis that the displacements are to be small in comparison with the thickness of the shell, all the equations will be linear in both cases, a fact which, of course, greatly simplifies their study. However, not withstanding this simplification, the problems associated with shell calculations remain very difficult, in view of the complexity and high order of the governing equations. Even for the simplest circular

cylindrical shells for which the calculations reduce to the study of a system of equations with constant coefficients, the computations remain involved and by far not all problems of practical interest for such shells have been solved. This statement applies to an even greater extent to other shells for which the computations require the study of differential equations with variable coefficients. In view of this situation, instruction in shell theory has lately been directed towards the search for possibilities of simplifying the problems. Several such possibilities will be considered later on.

§ 14. Complex transformation of the differential equations in the theory of thin shells when Poisson's ratio is equal to zero

Poisson's ratio will now be assumed to be equal to zero and for this particular case the equilibrium equations (8.2) will be written in such a way that they alternate with the continuity equations (12.2). Then, the following system of six equations in six unknowns is obtained:

$$\text{(I)}\quad \frac{\partial A_2T_1}{\partial\alpha_1}+\frac{\partial A_1S}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}S-\frac{\partial A_2}{\partial\alpha_1}T_2+\frac{1}{R_1}\left[\frac{\partial A_2M_1}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}M_2+\right.$$
$$\left.+2\frac{\partial A_1H}{\partial\alpha_2}+2\frac{R_1}{R_2}\frac{\partial A_1}{\partial\alpha_2}H\right]=-A_1A_2q_1,$$

$$\text{(II)}\quad \frac{\partial A_2M_2}{\partial\alpha_1}-\frac{\partial A_1H}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}H-\frac{\partial A_2}{\partial\alpha_1}M_1-\frac{\delta^2}{12R_1}\left[\frac{\partial A_2T_2}{\partial\alpha_1}-\right.$$
$$\left.-\frac{\partial A_2}{\partial\alpha_1}T_1-2\frac{\partial A_1S}{\partial\alpha_2}-2\frac{R_1}{R_2}\frac{\partial A_1}{\partial\alpha_2}S\right]=0,$$

$$\text{(III)}\quad \frac{\partial A_2S}{\partial\alpha_1}+\frac{\partial A_1T_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}S-\frac{\partial A_1}{\partial\alpha_2}T_1+\frac{1}{R_2}\left[\frac{\partial A_1M_2}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}M_1+\right.$$
$$\left.+2\frac{\partial A_2H}{\partial\alpha_1}+2\frac{R_2}{R_1}\frac{\partial A_2}{\partial\alpha_1}H\right]=-A_1A_2q_2, \qquad (14.1)$$

$$\text{(IV)}\quad -\frac{\partial A_2H}{\partial\alpha_1}+\frac{\partial A_1M_1}{\partial\alpha_2}-\frac{\partial A_2}{\partial\alpha_1}H-\frac{\partial A_1}{\partial\alpha_2}M_2-\frac{\delta^2}{12R_2}\left[\frac{\partial A_1T_1}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}T_2-\right.$$
$$\left.-2\frac{\partial A_2S}{\partial\alpha_1}-2\frac{R_2}{R_1}\frac{\partial A_2}{\partial\alpha_1}S\right]=0,$$

$$\text{(V)}\quad \frac{T_1}{R_1}+\frac{T_2}{R_2}-\frac{1}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2M_1}{\partial\alpha_1}+\frac{\partial A_1H}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}H-\frac{\partial A_2}{\partial\alpha_1}M_2\right]+\right.$$
$$\left.+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[\frac{\partial A_2H}{\partial\alpha_1}+\frac{\partial A_1M_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}H-\frac{\partial A_1}{\partial\alpha_2}M_1\right]\right\}=q_n,$$

$$\text{(VI)}\quad \frac{M_2}{R_1}+\frac{M_1}{R_2}+\frac{\delta^2}{12}\frac{1}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2T_2}{\partial\alpha_1}-\frac{\partial A_1S}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}S-\frac{\partial A_2}{\partial\alpha_1}T_1\right]+\right.$$

$$\left.+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[\frac{\partial A_1T_1}{\partial\alpha_2}-\frac{\partial A_2S}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}S-\frac{\partial A_1}{\partial\alpha_2}T_2\right]\right\}=0. \quad (14.1)$$

A study of this system shows that the equations possess the property of symmetry; in fact, the unknowns T_1, T_2, S, M_1, M_2, H enter into equations (I), (III), (IV) in the same way as M_2, M_1, $-H$, $-T_2$, $-T_1$, $-S$ enter into equations (II), (IV), (VI) (overlooking the constant multiplier $\delta^2/12$). This property of symmetry of the continuity equations and the equilibrium equations has already been exploited earlier, namely in § 8, when finding functions which identically satisfy the homogeneous equations of equilibrium of an element of the shell. In this way, the solution of the system (14.1) could be reduced to the solution of a system of altogether three equations of half the order of the system (14.1).

Introduce the three complex auxiliary functions

$$\tilde{T}_1=T_1-\frac{i}{c_0}M_2,$$

$$\tilde{T}_2=T_2-\frac{i}{c_0}M_1, \quad (14.2)$$

$$\tilde{S}=S+\frac{i}{c_0}H,$$

where

$$c_0=\frac{\delta}{\sqrt{12}}.$$

Further, express T_1, T_2, S in terms of M_1, M_2, H, $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$ and substitute these expressions in (14.1). As a result, one finds

$$\text{(I)}\quad \frac{i}{c_0}\left[\frac{\partial A_2M_2}{\partial\alpha_1}-\frac{\partial A_1H}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}H-\frac{\partial A_2}{\partial\alpha_1}M_1\right]+\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+$$

$$+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2+\frac{1}{R_1}\left[\frac{\partial A_2M_1}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}M_2+2\frac{\partial A_1H}{\partial\alpha_2}+\right.$$

$$\left.+2\frac{R_1}{R_2}\frac{\partial A_1}{\partial\alpha_2}H\right]=-A_1A_2q_1, \quad (14.3)$$

$$\text{(II)}\quad -\frac{c_0^2}{R_1}\left[\frac{\partial A_2\tilde{T}_2}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_1-2\frac{\partial A_1\tilde{S}}{\partial\alpha_2}-2\frac{R_1}{R_2}\frac{\partial A_1}{\partial\alpha_2}\tilde{S}\right]+\frac{\partial A_2M_2}{\partial\alpha_1}-$$

$$-\frac{\partial A_1H}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}H-\frac{\partial A_2}{\partial\alpha_1}M_1-i\frac{c_0}{R_1}\left[\frac{\partial A_2M_1}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}M_2+\right.$$

$$\left.+2\frac{\partial A_1H}{\partial\alpha_2}+2\frac{R_1}{R_2}\frac{\partial A_1}{\partial\alpha_2}H\right]=0,$$

$$\text{(III)}\quad \frac{i}{c_0}\left[\frac{\partial A_1M_1}{\partial\alpha_2}-\frac{\partial A_2H}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}H-\frac{\partial A_1}{\partial\alpha_2}M_2\right]+\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+$$

$$+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1+\frac{1}{R_2}\left[\frac{\partial A_1M_2}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}M_1+2\frac{\partial A_2H}{\partial\alpha_1}+\right.$$

$$\left.+2\frac{R_2}{R_1}\frac{\partial A_2}{\partial\alpha_1}H\right]=-A_1A_2q_2,$$

$$\text{(IV)}\quad -\frac{c_0^2}{R_2}\left[\frac{\partial A_1\tilde{T}_1}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_2-2\frac{\partial A_2\tilde{S}}{\partial\alpha_1}-2\frac{R_2}{R_1}\frac{\partial A_2}{\partial\alpha_1}\tilde{S}\right]+\frac{\partial A_1M_1}{\partial\alpha_2}-$$

$$-\frac{\partial A_2H}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}H-\frac{\partial A_1}{\partial\alpha_2}M_2-i\frac{c_0}{R_2}\left[\frac{\partial A_1M_2}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}M_1+\right.$$

$$\left.+2\frac{\partial A_2H}{\partial\alpha_1}+2\frac{R_2}{R_1}\frac{\partial A_2}{\partial\alpha_1}H\right]=0, \tag{14.3}$$

$$\text{(V)}\quad \frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}+\frac{i}{c_0}\left(\frac{M_2}{R_1}+\frac{M_1}{R_2}\right)-\frac{1}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\times\right.$$

$$\times\left[\frac{\partial A_2M_1}{\partial\alpha_1}+\frac{\partial A_1H}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}H-\frac{\partial A_2}{\partial\alpha_1}M_2\right]+$$

$$\left.+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[\frac{\partial A_2H}{\partial\alpha_1}+\frac{\partial A_1M_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}H-\frac{\partial A_1}{\partial\alpha_2}M_1\right]\right\}=q_n,$$

$$\text{(VI)}\quad \frac{M_2}{R_1}+\frac{M_1}{R_2}+\frac{c_0^2}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2\tilde{T}_2}{\partial\alpha_1}-\frac{\partial A_1\tilde{S}}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_1\right]+\right.$$

$$+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[-\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_1}{\partial\alpha_2}-\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_2\right]\Big\}+$$

$$+i\frac{c_0}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2M_1}{\partial\alpha_1}+\frac{\partial A_1H}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}H-\frac{\partial A_2}{\partial\alpha_1}M_2\right]+\right.$$

$$\left.+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[\frac{\partial A_2H}{\partial\alpha_1}+\frac{\partial A_1M_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}H-\frac{\partial A_1}{\partial\alpha_2}M_1\right]\right\}=0.$$

Now multiply equations (II), (IV), (VI) by $\frac{i}{c_0}$ and subtract them from equations (I), (III), (V) respectively. This operation eliminates the terms containing moments and one arrives at the following system of three partial differential equations in three unknowns — the auxiliary functions $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$:

$$\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2+$$

$$+i\frac{c_0}{R_1}\left[\frac{\partial A_2\tilde{T}_2}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_1-2\frac{\partial A_1\tilde{S}}{\partial\alpha_2}-2\frac{R_1}{R_2}\frac{\partial A_1}{\partial\alpha_2}\tilde{S}\right]=-A_1A_2q_1,$$

$$\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1+ \tag{14.4}$$

$$+i\frac{c_0}{R_2}\left[\frac{\partial A_1\tilde{T}_1}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_2-2\frac{\partial A_2\tilde{S}}{\partial\alpha_1}-2\frac{R_2}{R_1}\frac{\partial A_2}{\partial\alpha_1}\tilde{S}\right]=-A_1A_2q_2,$$

$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-i\frac{c_0}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2\tilde{T}_2}{\partial\alpha_1}-\frac{\partial A_1\tilde{S}}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_1\right]+\right.$$

$$\left.+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[\frac{\partial A_1\tilde{T}_1}{\partial\alpha_2}-\frac{\partial A_2\tilde{S}}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_2\right]\right\}=q_n.$$

The solution of this system will be equivalent to the solution of the system (14.1), since, once the auxiliary functions $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$ have been found, the quantities T_1, T_2, S, M_1, M_2, H may be determined from (14.2) by separation of the real and imaginary parts.

The system (14.4) includes the equilibrium equations of the shell element and the equations of compatibility for the strains of the middle surface. It is of fourth order, i.e., half the order of the system (14.1), and it contains half the number of unknowns and equations. In view of this fact, this reduction of the system (14.1) to the system (14.4) must be considered an essential simplification of the problem.

It will be expedient to modify somewhat the equations (14.4). Taking into consideration the identities

$$\frac{\partial A_2\tilde{T}_2}{\partial\alpha_1}-\frac{\partial A_1\tilde{S}}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_1=$$

$$=A_2\frac{\partial\tilde{T}}{\partial\alpha_1}-\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}-\frac{\partial A_1\tilde{S}}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\tilde{S}+\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2, \tag{14.5}$$

$$\frac{\partial A_1\tilde{T}_1}{\partial\alpha_2}-\frac{\partial A_2\tilde{S}}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_2=$$

$$=A_1\frac{\partial\tilde{T}}{\partial\alpha_2}-\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}-\frac{\partial A_2\tilde{S}}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}\tilde{S}+\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1, \quad (14.5)$$

the first two of the equations (14.4) may be reduced to the form

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2\right]+$$

$$+i\frac{c_0}{1-i\dfrac{c_0}{R_1}}\left[\frac{1}{R_1A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}-\frac{1}{R_1A_2}\frac{\partial\tilde{S}}{\partial\alpha_2}-\frac{2\tilde{S}}{R_2}\frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}\right]=-\frac{q_1}{1-i\dfrac{c_0}{R_1}}, \quad (14.6)$$

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1\right]+$$

$$+i\frac{c_0}{1-i\dfrac{c_0}{R_2}}\left[\frac{1}{R_2A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}-\frac{1}{R_2A_1}\frac{\partial\tilde{S}}{\partial\alpha_1}-\frac{2\tilde{S}}{R_1}\frac{1}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}\right]=-\frac{q_2}{1-i\dfrac{c_0}{R_2}}, \quad (14.7)$$

where $\tilde{T}=\tilde{T}_1+\tilde{T}_2$.

By use of the same identities, the third of the equations (14.4) can be written in the form

$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-ic_0\Delta(\tilde{T})+i\frac{c_0}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2\right]+\right.$$

$$\left.+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1\right]\right\}=q_n, \quad (14.8)$$

where, as before,

$$\Delta(\ldots)=\frac{1}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\left[\frac{A_2}{A_1}\frac{\partial(\ \ )}{\partial\alpha_1}\right]+\frac{\partial}{\partial\alpha_2}\left[\frac{A_1}{A_2}\frac{\partial(\ \ )}{\partial\alpha_2}\right]\right\}. \quad (14.9)$$

Further, substituting for the expressions in the square brackets in (14.8) their values from (14.6) and (14.7), one finds

$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-ic_0\Delta(\tilde{T})+\frac{c_0^2}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{1-ic_0/R_1}\left[\frac{1}{R_1}\frac{A_2}{A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}-\frac{1}{R_1}\frac{\partial\tilde{S}}{\partial\alpha_2}-\right.\right.$$

$$\left.\left.-\frac{2\tilde{S}}{R_2}\frac{1}{A_1}\frac{\partial A_1}{\partial\alpha_2}\right]+\frac{\partial}{\partial\alpha_2}\frac{1}{1-ic_0/R_2}\left[\frac{1}{R_2}\frac{A_1}{A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}-\frac{1}{R_2}\frac{\partial\tilde{S}}{\partial\alpha_1}-\frac{2\tilde{S}}{R_1}\frac{1}{A_2}\frac{\partial A_2}{\partial\alpha_1}\right]\right\}=$$

$$=q_n+i\frac{c_0}{A_1A_2}\left[\frac{\partial}{\partial\alpha_1}\left(\frac{A_2q_1}{1-ic_0/R_1}\right)+\frac{\partial}{\partial\alpha_2}\left(\frac{A_1q_2}{1-ic_0/R_2}\right)\right]. \quad (14.10)$$

Hence the system (14.4) may now be written in the following final form:

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2\right]+$$

$$+i\frac{c_0}{1-i\frac{c_0}{R_1}}\left[\frac{1}{R_1A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}-\frac{1}{R_1A_2}\frac{\partial\tilde{S}}{\partial\alpha_2}-\frac{2\tilde{S}}{R_2}\frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}\right]=-\tilde{q}_1(\alpha_1,\alpha_2),$$

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1\right]+$$

$$+i\frac{c_0}{1-i\frac{c_0}{R_2}}\left[\frac{1}{R_2A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}-\frac{1}{R_2A_1}\frac{\partial\tilde{S}}{\partial\alpha_1}-\frac{2\tilde{S}}{R_1}\frac{1}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}\right]=-\tilde{q}_2(\alpha_1,\alpha_2),$$

$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-ic_0\Delta(\tilde{T})+ \tag{14.11}$$

$$+\frac{c_0^2}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{1-i\frac{c_0}{R_1}}\left[\frac{1}{R_1}\frac{A_2}{A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}-\frac{1}{R_1}\frac{\partial\tilde{S}}{\partial\alpha_2}-\frac{2\tilde{S}}{R_2}\frac{1}{A_1}\frac{\partial A_1}{\partial\alpha_2}\right]+\right.$$

$$\left.+\frac{\partial}{\partial\alpha_2}\frac{1}{1-i\frac{c_0}{R_2}}\left[\frac{1}{R_2}\frac{A_1}{A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}-\frac{1}{R_2}\frac{\partial\tilde{S}}{\partial\alpha_1}-\frac{2\tilde{S}}{R_1}\frac{1}{A_2}\frac{\partial A_2}{\partial\alpha_1}\right]\right\}=\tilde{q}_n(\alpha_1,\alpha_2),$$

where

$$\tilde{q}_1(\alpha_1,\alpha_2)=\frac{1}{1-i\frac{c_0}{R_1}}q_1,$$

$$\tilde{q}_2(\alpha_1,\alpha_2)=\frac{1}{1-i\frac{c_0}{R_2}}q_2, \tag{14.12}$$

$$\tilde{q}_n(\alpha_1,\alpha_2)=q_n+i\frac{c_0}{A_1A_2}\left[\frac{\partial}{\partial\alpha_1}\left(\frac{A_2q_1}{1-i\frac{c_0}{R_1}}\right)+\frac{\partial}{\partial\alpha_2}\left(\frac{A_1q_2}{1-i\frac{c_0}{R_2}}\right)\right].$$

The auxiliary functions $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$ will in future be called complex stress resultants or stresses. The name is justified by the fact that knowledge of these functions immediately determines all forces and moments.

§ 15. Other forms of the complex transformation of the equations of the theory of thin shells (for $\mu = 0$)

Continuing with the particular case when Poisson's ratio is equal to zero, introduce into the consideration three further complex auxiliary functions, denoted by $\tilde{u}$, $\tilde{v}$, $\tilde{w}$ and related to the complex stresses by the six differential relations

$$\begin{aligned}
\tilde{\varepsilon}_1 &= \frac{1}{E\delta}\tilde{T}_1, \\
\tilde{\varepsilon}_2 &= \frac{1}{E\delta}\tilde{T}_2, \\
\tilde{\omega} &= \frac{2}{E\delta}\tilde{S},
\end{aligned} \tag{15.1}$$

$$\begin{aligned}
\tilde{\kappa}_1 &= \frac{i}{c_0}\frac{1}{E\delta}(\tilde{T}_2 - T_2^*), \\
\tilde{\kappa}_2 &= \frac{i}{c_0}\frac{1}{E\delta}(\tilde{T}_1 - T_1^*), \\
\tilde{\tau} &= -\frac{i}{c_0}\frac{1}{E\delta}(\tilde{S} - \tilde{S}^*).
\end{aligned} \tag{15.2}$$

In these relations, the quantities $\tilde{\varepsilon}_1$, $\tilde{\varepsilon}_2$, $\tilde{\omega}$, $\tilde{\kappa}_1$, $\tilde{\kappa}_2$, $\tilde{\tau}$ will be understood to be the expressions obtained from the formulae (4.23) after replacing in them the displacements u, v, w by $\tilde{u}$, $\tilde{v}$, $\tilde{w}$ respectively. As regards the quantities T_1^*, T_2^*, S^*, they are certain functions which must be chosen in such a manner that the two systems (15.1) and (15.2) will be compatible. It is now obvious from what has been said in § 12 that, for compatibility of the systems (15.1), (15.2), the functions on their right hand sides must satisfy three differential relations, obtained by substituting $\tilde{\varepsilon}_1$, $\tilde{\varepsilon}_2$, $\tilde{w}$, $\tilde{\kappa}_1$, $\tilde{\kappa}_2$, $\tilde{\tau}$ into the identities (5.1). In this way one obtains

$$\begin{aligned}
&\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1} + \frac{\partial A_1\tilde{S}}{\partial\alpha_2} + \frac{\partial A_1}{\partial\alpha_2}\tilde{S} - \frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2 + \\
&\quad + i\frac{c_0}{R_1}\left[\frac{\partial A_2\tilde{T}_2}{\partial\alpha_1} - \frac{\partial A_2}{\partial\alpha_1}\tilde{T}_1 - 2\frac{\partial A_1\tilde{S}}{\partial\alpha_2} - 2\frac{R_1}{R_2}\frac{\partial A_1}{\partial\alpha_2}\tilde{S}\right] = \\
&\quad = \frac{\partial A_2 T_1^*}{\partial\alpha_1} + \frac{\partial A_1 S^*}{\partial\alpha_2} + \frac{\partial A_1}{\partial\alpha_2}S^* - \frac{\partial A_2}{\partial\alpha_1}T_2^*,
\end{aligned}$$

$$\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1+$$

$$+i\frac{c_0}{R_2}\left[\frac{\partial A_1\tilde{T}_1}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_2-2\frac{\partial A_2\tilde{S}}{\partial\alpha_1}-2\frac{R_2}{R_1}\frac{\partial A_2}{\partial\alpha_1}\tilde{S}\right]=$$

$$=\frac{\partial A_2S^*}{\partial\alpha_1}+\frac{\partial A_1T_2^*}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}S^*-\frac{\partial A_1}{\partial\alpha_2}T_1^*, \qquad (15.3)$$

$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-i\frac{c_0}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{A_1}\left[\frac{\partial A_2\tilde{T}_2}{\partial\alpha_1}-\frac{\partial A_1\tilde{S}}{\partial\alpha_2}-\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_1\right]+\right.$$

$$\left.+\frac{\partial}{\partial\alpha_2}\frac{1}{A_2}\left[\frac{\partial A_1\tilde{T}_1}{\partial\alpha_2}-\frac{\partial A_2\tilde{S}}{\partial\alpha_1}-\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_2\right]\right\}=\frac{T_1^*}{R_1}+\frac{T_2^*}{R_2}.$$

But the complex stresses $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$ satisfy the differential equations (14.4), the left hand sides of which are identical with the left hand sides of the relations (15.3). Hence it follows that the right hand sides of the equations (14.4) must be equal to the right hand sides of the relations (15.3) so that one may write

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2T_1^*}{\partial\alpha_1}+\frac{\partial A_1S^*}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}S^*-\frac{\partial A_2}{\partial\alpha_1}T_2^*\right]+q_1=0,$$

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2S^*}{\partial\alpha_1}+\frac{\partial A_1T_2^*}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}S^*-\frac{\partial A_1}{\partial\alpha_2}T_1^*\right]+q_2=0, \qquad (15.4)$$

$$\frac{T_1^*}{R_1}+\frac{T_2^*}{R_2}=q_n.$$

In other words, in order that the systems (15.1), (15.2) will be compatible, the functions T_1^*, T_2^*, S^* must satisfy the differential equations (15.4). For this purpose, it is sufficient if T_1^*, T_2^*, S^* are not the general solution of the system (15.4), but any of its particular solutions, because in this case compatibility of the systems (15.1), (15.2) will be insured. The differential equations (15.4) are called the equations of the membrane theory of shells. They can be obtained from (14.4) by putting $c_0 = 0$ (i.e., by assuming that the shell is infinitely thin) or from the equilibrium equations of an element of the shell by letting $M_1 = M_2 = H = 0$. A detailed study of the system (15.4) will be given in the following chapter, where it will be shown that these equation can be solved for many shells. For all such shells T_1^*, T_2^*, S^* may be determined.

Revert now to the system of six equations (15.1), (15.2) and eliminate the complex stresses. As a result, one obtains the three equations

$$\tilde{\varepsilon}_1 + ic_0\tilde{\kappa}_2 = \frac{1}{E\delta} T_1^*,$$

$$\tilde{\varepsilon}_2 + ic_0\tilde{\kappa}_1 = \frac{1}{E\delta} T_2^*, \tag{15.5}$$

$$\frac{\tilde{\omega}}{2} - ic_0\tilde{\tau} = \frac{1}{E\delta} S^*,$$

which, after substitution for $\tilde{\varepsilon}_1$, $\tilde{\varepsilon}_2$, $\tilde{\omega}$, $\tilde{\kappa}_1$, $\tilde{\kappa}_2$, $\tilde{\tau}$ in terms of $\tilde{u}$, $\tilde{v}$, $\tilde{\omega}$, become a system of partial differential equations for these last three auxiliary functions ($\tilde{u}$, $\tilde{v}$, $\tilde{w}$).

This system, similar to the system (14.11), will be of fourth order, i.e., of half the order of the differential equations which characterize the theory of shells in real variables. At the same time, its solution will be equivalent to the solution of the real variable equations of the theory of shells, because, after finding $\tilde{u}$, $\tilde{v}$, $\tilde{w}$, all the complex forces may be determined by use of (15.1), and this immediately permits one to write down expressions for all the forces and moments.

Thus (so far only for the particular case $\mu = 0$) the calculation of shells has been reduced to the solution of a system of differential equations of fourth order for which two versions have been obtained, namely the equations (14.11) and (15.5). At this stage, the question might be asked in what manner the general solution of a system of fourth order can be equivalent to the general solution of a system of eighth order.

The number of arbitrary quantities in the solution in the second case will be twice the number of arbitrary quantities in the solution in the first case, and consequently it might be thought that the arbitrary boundary conditions for the second equations cannot be satisfied, starting from the first equations. However, it should not be forgotten that the solutions of the fourth order system will be complex, and, consequently, they will contain arbitrary quantities which are complex. But an arbitrary complex quantity comprises two real quantities, so that the general solutions of the systems (14.11) and (15.5) contain eight real arbitrary functions, i.e., the same number which must enter into the general solution of the equations of the theory of shells. Thus it has been verified that the solutions of the systems (14.11) and (15.5) are equivalent to the solution of the original system (14.1) and no contradiction has been found.

There remains to interpret the auxiliary functions $\tilde{u}$, $\tilde{v}$, $\tilde{w}$. Let

$$\begin{aligned} \tilde{u} &= u' + iu'', \\ \tilde{v} &= v' + iv'', \\ \tilde{w} &= w' + iw'', \end{aligned} \tag{15.6}$$

so that u', u''; v', v''; w', w'' are the real and imaginary parts of $\tilde{u}$, $\tilde{v}$, $\tilde{w}$. Substituting (15.6) and the expressions for the complex stresses (14.2) into the formulae (15.1) and (15.2), one finds

$$\begin{aligned} E\delta(\varepsilon_1' + i\varepsilon_1'') &= T_1 - \frac{i}{c_0} M_2, \\ E\delta(\varepsilon_2' + i\varepsilon_2'') &= T_2 - \frac{i}{c_0} M_1, \\ \frac{E\delta}{2}(\omega' + i\omega'') &= S + \frac{i}{c_0} H, \\ c_0 E\delta(\kappa_1' + i\kappa_1'') &= \frac{M_1}{c_0} + i(T_2 - T_2^*), \\ c_0 E\delta(\kappa_2' + i\kappa_2'') &= \frac{M_2}{c_0} + i(T_1 - T_1^*), \\ c_0 E\delta(\tau' + i\tau'') &= \frac{H}{c_0} - i(S - S^*). \end{aligned} \tag{15.7}$$

In these equations, ε_1', ε_2', ..., τ' are the values of the strains after replacing u, v, w by u', v', w' respectively; similarly, ε_1'', ε_2'', ..., τ'' are the values of the strains corresponding to u'', v'', w''. The equations (15.7) lead to two independent differential systems, one of which contains only u', v', w', the other only u'', v'', w''. In fact,

$$\begin{aligned} E\delta\varepsilon_1' &= T_1, & E\delta\varepsilon_2' &= T_2, \\ E\delta\frac{\omega'}{2} &= S \\ \frac{E\delta^3}{12}\kappa_1' &= M_1, & \frac{E\delta^3}{12}\kappa_2' &= M_2, \\ \frac{E\delta^3}{12}\tau' &= H. \end{aligned} \tag{15.8}$$

$$\frac{E\delta^2}{\sqrt{12}}\varepsilon_1'' = -M_2, \qquad \frac{E\delta^2}{\sqrt{12}}\varepsilon_2'' = -M_1,$$
$$\frac{E\delta^2}{2\sqrt{12}}\omega'' = H, \qquad \frac{E\delta^2}{\sqrt{12}}\kappa_1'' = T_2 - T_2^*, \tag{15.9}$$
$$\frac{E\delta^2}{\sqrt{12}}\tau'' = -S + S^*, \qquad \frac{E\delta^2}{\sqrt{12}}\kappa_2'' = T_1 - T_1^*.$$

Compare now the formulae (15.8) with (12.1), letting in the last formulae $\mu = 0$. Then it is possible to write

$$\begin{aligned}
&\varepsilon_1(u - u',\ v - v',\ w - w') = 0,\\
&\varepsilon_2(u - u',\ v - v',\ w - w') = 0,\\
&\omega\,(u - u',\ v - v',\ w - w') = 0,\\
&\kappa_1(u - u',\ v - v',\ w - w') = 0,\\
&\kappa_2(u - u',\ v - v',\ w - w') = 0,\\
&\tau\ (u - u',\ v - v',\ w - w') = 0.
\end{aligned} \tag{15.10}$$

It follows from these equalities that the differences $u - u'$, $v - v'$, $w - w'$ correspond to zero strains of the middle surface, i.e., that these differences can only be rigid body displacements of the middle surface. Thus, apart from such displacements, one must have $u' = u$, $v' = v$, $w' = w$. In other words, the real parts of the auxiliary functions $\tilde{u}$, $\tilde{v}$, $\tilde{w}$ are equal to the displacements of the middle surface.

Several complicating features arise in the interpretation of the imaginary parts. Consideration will be restricted to the homogeneous problem, i.e., to the case where $q_1 = q_2 = q_n = 0$ and the shell is deformed by edge loading only. For this purpose, one may take as particular solutions of the system (15.4)

$$T_1^* = T_2^* = S^* = 0. \tag{15.11}$$

Then, comparing (15.9) with (8.3), one obtains

$$\begin{aligned}
&\frac{E\delta^2}{\sqrt{12}}\varepsilon_1(u'', v'', w'') = \varepsilon_1(a, b, c),\\
&\frac{E\delta^2}{\sqrt{12}}\varepsilon_2(u'', v'', w'') = \varepsilon_2(a, b, c),\\
&\ldots \qquad\qquad\qquad\qquad (15.12)\\
&\qquad\qquad \ldots\ldots\ldots\\
&\ldots\ldots\ldots\ldots\ldots\\
&\frac{E\delta^2}{\sqrt{12}}\tau(u'', v'', w'') = \tau(a, b, c).
\end{aligned}$$

Hence

$$u'' = \frac{\sqrt{12}}{E\delta^2}\, a,\quad v'' = \frac{\sqrt{12}}{E\delta^2}\, b,\quad w'' = \frac{\sqrt{12}}{E\delta^2}\, c, \tag{15.13}$$

where a, b, c are the Lur'e-Gol'denweizer functions (§ 8).

It is more difficult to give an interpretation of the quantities u'', v'', w'' for the general case of the non-homogeneous problem, and this is actually unnecessary. Indeed, having found the functions $\tilde{u}$, $\tilde{v}$, $\tilde{w}$ by means of the solutions of the system (15.5), they can be used at once to determine the displacements of the middle surface which are equal to the real parts of these auxiliary functions $\tilde{u}$, $\tilde{v}$, $\tilde{w}$. Further, this knowledge of the displacements of the middle surface is sufficient for the complete solution of the problem, since formulae are available which express any quantities characterizing the stresses or strains of a shell in terms of the displacements of the middle surface.

The fact that the determination of the auxiliary functions $\tilde{u}$, $\tilde{v}$, $\tilde{w}$ is directly equivalent to finding the displacements u, v, w justifies these functions being called "complex displacements".

For the homogeneous problem, when one may put $T_1^* = T_2^* = S^* = 0$, the equations (15.5) for the complex displacements become homogeneous and may be written in the form

$$\begin{aligned} &\tilde{\varepsilon}_1 + ic_0\tilde{\kappa}_2 = 0,\\ &\tilde{\varepsilon}_2 + ic_0\tilde{\kappa}_1 = 0,\\ &\frac{\tilde{\omega}}{2} - ic_0\tilde{\tau} = 0. \end{aligned} \tag{15.14}$$

In fact, it was in this form that they were first obtained in the paper [32]. Somewhat later the author succeeded in giving the generalization to the non-homogeneous problem [33].

In conclusion, it will be noted that, as is clear from the above discussion, one may take for T_1^*, T_2^*, S^* not only the particular but also the general solutions of the membrane equations (15.4). Then arbitrary functions will enter into the right hand sides of the equations of the system (15.5) which, from the point of view of the generality of the solutions, are optional. However, in certain cases their introduction will be convenient, since they permit simplification of the study of the system (15.5). This fact should be remembered.

§ 16. Generalization of the concepts of "complex forces" and "complex displacements" to the case of arbitrary Poisson's ratio

The method which has been studied in the preceding two sections and which led to a halving of the order of the differential equations of the theory of shells has only been deduced for the particular case when Poisson's ratio is zero.

In this case, there was no need to neglect any terms in the equilibrium equations of the element of the shell or in the compatibility equations for its middle surface, so that the above theory conforms completely to these two groups of equations. The only point at which errors enter into this theory is represented by the relations between stress and moment resultants and the strains of the middle surface, i.e., by the formulae (10.8). However, since during the deduction of these last relations it has been shown that they involved errors not exceeding those inherent in the initial assumptions of the theory of thin shells, it may be stated that this is also true for the errors in the complex equations (14.11) and (15.5).

Since the complex transformation of the equations of the theory of shells simplifies the solution of problems, it will be desirable to generalize this method to the case of arbitrary Poisson's ratio. Although it is impossible to retain the same accuracy as in the above development, nevertheless, after neglecting some small terms in the original equations, the required results can be attained at the price of additional errors which, for the majority of problems, are not large.

A beginning will be made with the discussion of the possible simplifications in the system (14.11). From this point of view, one may first of all put

$$1 - ic_0/R_1 \approx 1 - ic_0/R_2 \approx 1, \tag{16.1}$$

since this leads to a probable error of order δ/R in comparison with unity.

Then the system (14.11) can be written in the following way:

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2\right]+$$
$$+i\frac{c_0}{R_1}\left(\frac{1}{A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}-\underline{\frac{1}{A_2}\frac{\partial\tilde{S}}{\partial\alpha_2}-2\frac{R_1}{R_2}\frac{\tilde{S}}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}}\right)=-q_1,$$
$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1\right]+$$
$$+i\frac{c_0}{R_2}\left[\frac{1}{A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}-\underline{\frac{1}{A_1}\frac{\partial\tilde{S}}{\partial\alpha_1}-2\frac{R_2}{R_1}\frac{\tilde{S}}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}}\right]=-q_2, \tag{16.2}$$

$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-ic_0\Delta(\tilde{T})+$$

$$+\frac{c_0^2}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\left(\underline{\frac{1}{R_1}\frac{A_2}{A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}-\frac{1}{R_1}\frac{\partial\tilde{S}}{\partial\alpha_2}-\frac{2\tilde{S}}{R_2}\frac{1}{A_1}\frac{\partial A_1}{\partial\alpha_2}}\right)+\right.$$

$$\left.+\frac{\partial}{\partial\alpha_2}\left(\underline{\frac{1}{R_2}\frac{A_1}{A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}-\frac{1}{R_2}\frac{\partial\tilde{S}}{\partial\alpha_1}-\frac{2\tilde{S}}{R_1}\frac{1}{A_2}\frac{\partial A_2}{\partial\alpha_1}}\right)\right\}=\tilde{q}_n\approx$$

$$\approx q_n+i\frac{c_0}{A_1A_2}\left(\frac{\partial A_2q_1}{\partial\alpha_1}+\frac{\partial A_1q_2}{\partial\alpha_2}\right). \tag{16.2}$$

Further, it will be noted that the underlined terms in the first two equations occur in the same equations without the factor $i\frac{c_0}{R}$, the modulus of which is small. As regards the underlined terms in the third equation, they involve the factor $\frac{c_0^2}{A_1A_2}$. On this basis, all the underlined terms in (16.2) can be neglected and one arrives at the equations

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2\right]+i\frac{c_0}{R_1}\frac{1}{A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}+q_1=0,$$

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1\right]+i\frac{c_0}{R_2}\frac{1}{A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}+q_2=0, \tag{16.3}$$

$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-ic_0\Delta(\tilde{T})=\tilde{q}_n.$$

It is clear from the character of these simplifications that the error incurred by replacing the system of equations (14.11) by the system (16.3) will, as a rule, be a quantity of the order δ/R in comparison with unity. Those special cases for which the above statement is violated will be indicated below.

Further, consider the form in which the initial shell equations (for $\mu=0$) must be written, so that they will correspond to the complex equations (16.3). After some manipulations it may be verified that in order to achieve this object one must put in the equilibrium equations for an element of the shell (7.4) and (7.8)

$$T_{12}\approx T_{21}\approx S. \tag{16.4}$$

In addition, one must neglect in the conditions of compatibility (12.3)

a number of terms by giving these relations the following simplified form:

$$(1+\mu)N_1 = \frac{1}{A_1}\frac{\partial M}{\partial \alpha_1} - \frac{\delta^2}{12}\underline{\frac{1}{R_1 A_1}\frac{\partial T}{\partial \alpha_1}},$$

$$(1+\mu)N_2 = \frac{1}{A_2}\frac{\partial M}{\partial \alpha_2} - \frac{\delta^2}{12}\underline{\frac{1}{R_2 A_2}\frac{\partial T}{\partial \alpha_2}}, \tag{16.5}$$

$$\frac{M_1-\mu M_2}{R_2} + \frac{M_2-\mu M_1}{R_1} + \frac{\delta^2}{12}\Delta(T) = -\frac{\delta^2}{12}\frac{(1+\mu)}{A_1 A_2}\left[\frac{\partial A_2 q_1}{\partial \alpha_1} + \frac{\partial A_1 q_2}{\partial \alpha_2}\right].$$

The terms underlined in these formulae are likewise of negligible magnitude, as has been indicated first in the papers [28] and [31]. Thus, for a wide range of problems of the theory of shells, the first two of the conditions of compatibility of the middle surface can be written in the following simple manner:

$$(1+\mu)N_1 \approx \frac{1}{A_1}\frac{\partial M}{\partial \alpha_1},$$

$$(1+\mu)N_2 \approx \frac{1}{A_2}\frac{\partial M}{\partial \alpha_2}. \tag{16.6}$$

Eliminate from the first three equilibrium equations (7.4), in conformity with (16.4), the normal shearing forces by use of (16.6) and from the remaining equations (7.8) the shearing forces by use of (16.5). In this way, one obtains

$$\text{(I)}\quad \frac{1}{A_1 A_2}\left[\frac{\partial A_2 T_1}{\partial \alpha_1} + \frac{\partial A_1 S}{\partial \alpha_2} + \frac{\partial A_1}{\partial \alpha_2}S - \frac{\partial A_2}{\partial \alpha_1}T_2\right] + \frac{1}{1+\mu}\frac{1}{R_1 A_1}\frac{\partial M}{\partial \alpha_1} + q_1 = 0.$$

$$\text{(II)}\quad \frac{1}{A_1 A_2}\left[-\frac{\partial A_2(M_2-\mu M_1)}{\partial \alpha_1} + (1+\mu)\left(\frac{\partial A_1 H}{\partial \alpha_2} + \frac{\partial A_1}{\partial \alpha_2}H\right) + \right.$$

$$\left. + \frac{\partial A_2}{\partial \alpha_1}(M_1 - \mu M_2)\right] + \frac{\delta^2}{12 R_1 A_1}\frac{\partial T}{\partial \alpha_1} = 0, \tag{16.7}$$

$$\text{(III)}\quad \frac{1}{A_1 A_2}\left[\frac{\partial A_2 S}{\partial \alpha_1} + \frac{\partial A_1 T_2}{\partial \alpha_2} + \frac{\partial A_2}{\partial \alpha_1}S - \frac{\partial A_1}{\partial \alpha_2}T_1\right] + \frac{1}{1+\mu}\frac{1}{R_2 A_2}\frac{\partial M}{\partial \alpha_2} + q_2 = 0,$$

$$\text{(IV)}\quad \frac{1}{A_1 A_2}\left[-\frac{\partial A_1(M_1-\mu M_2)}{\partial \alpha_2} + (1+\mu)\left(\frac{\partial A_2 H}{\partial \alpha_1} + \frac{\partial A_2}{\partial \alpha_1}H\right) + \right.$$

$$\left. + \frac{\partial A_1}{\partial \alpha_2}(M_2 - \mu M_1)\right] + \frac{\delta^2}{12 R_2 A_2}\frac{\partial T}{\partial \alpha_2} = 0,$$

$$\text{(V)}\quad \frac{T_1}{R_1} + \frac{T_2}{R_2} - \frac{1}{1+\mu}\Delta(M) - q_n = 0,$$

$$\text{(VI)}\quad \frac{M_2-\mu M_1}{R_1}+\frac{M_1-\mu M_2}{R_2}+\frac{\delta^2}{12}\Delta(T)=-$$

$$-\frac{\delta^2}{12}\frac{1+\mu}{A_1A_2}\left[\frac{\partial}{\partial\alpha_2}(A_2q_1)+\frac{\partial}{\partial\alpha_1}(A_1q_2)\right]. \qquad (16.7)$$

Letting in these equations $\mu = 0$, introducing the complex stresses $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$ defined in (14.2) and performing the computations in the same manner as in § 14, one arrives at the system of differential equations (16.3).

Thus it is seen that the equations for the complex stresses, simplified to the form (16.3), are equivalent to writing the initial equations in the approximate form (16.7). However, as regards this last system of equations, the complex transformation may be applied without neglecting Poisson's ratio.

In fact, introduce now the auxiliary functions

$$\tilde{T}_1 = T_1 - \frac{i}{c}\frac{M_2-\mu M_1}{1-\mu^2},$$

$$\tilde{T}_2 = T_2 - \frac{i}{c}\frac{M_1-\mu M_2}{1-\mu^2}, \qquad (16.8)$$

$$\tilde{S} = S + \frac{i}{c}\frac{H}{1-\mu},$$

where

$$c = \frac{\delta}{\sqrt{12(1-\mu^2)}},$$

which are the generalizations of the complex stresses to the case $\mu \neq 0$. Replace in (16.7) the stresses T_1, T_2, S by their expressions in terms of M_1, M_2, H, $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$ as indicated by (16.8). In this way one arrives at a system of equations from which one may eliminate the unknowns M_1, M_2, H in the same manner as was done in § 14. This process leads to the following system of partial differential equations for the complex stresses:

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2\right]+i\frac{c}{R_1A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}+q_1=0,$$

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1\right]+i\frac{c}{R_2A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}+q_2=0,$$

$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-ic\Delta(T)=\tilde{q}_n, \qquad (16.10)$$

where

$$\tilde{q}_n = q_n + i\,\frac{(1+\mu)c}{A_1A_2}\left[\frac{\partial A_2 q_1}{\partial \alpha_1} + \frac{\partial A_1 q_2}{o\alpha_2}\right] \approx q_n.$$

This system is the generalization of the differential equations (14.11) to the case when Poisson's ratio is not zero. If this system had been deduced from the simplified equations (16.7), one would have obtained simpler equations than those of the system (14.11), the deduction of which did not require omission of terms either from the equilibrium equations or from the compatibility conditions.

Next, the concept of complex displacements will be generalized to the case $\mu \neq 0$ by defining them as the auxiliary functions $\tilde{u}$, $\tilde{v}$, $\tilde{w}$, related to the complex stresses by means of the six equations

$$\begin{aligned}
\tilde{\varepsilon}_1 &= \frac{1}{E\delta}(\tilde{T}_1 - \mu\tilde{T}_2),\\
\tilde{\varepsilon}_2 &= \frac{1}{E\delta}(\tilde{T}_2 - \mu\tilde{T}_1),\\
\tilde{\omega} &= \frac{2(1+\mu)}{E\delta}\tilde{S};
\end{aligned} \tag{16.11}$$

$$\begin{aligned}
\tilde{\kappa}_1 &= \frac{i}{c}\,\frac{1}{E\delta}(\tilde{T}_2 - T_2^*),\\
\tilde{\kappa}_2 &= \frac{i}{c}\,\frac{1}{E\delta}(\tilde{T}_1 - T_1^*),\\
\tilde{\tau} &= -\frac{i}{c}\,\frac{1}{E\delta}(\tilde{S} - S^*).
\end{aligned} \tag{16.12}$$

As before, the quantities $\tilde{\varepsilon}_1, \tilde{\varepsilon}_2, \ldots, \tilde{\tau}$ are the values of the strains of the middle surface after replacing u, v, w by $\tilde{u}$, $\tilde{v}$, $\tilde{w}$ respectively and T_1^*, T_2^*, S^* are particular (or the general) solutions of the equations of the membrane theory, that is, of the system (15.4).

Substituting $\tilde{\varepsilon}_1, \tilde{\varepsilon}_2, \ldots, \tilde{\tau}$ in (5.1) and proceeding in a manner analogous to that in §§ 14, 15, one obtains the following three differential equations for the quantities $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$ which will be the conditions of compatibility for the formulae (16.11) and (16.12), considered as differential equations

for $\tilde{u}$, $\tilde{v}$, $\tilde{w}$:

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{T}_1}{\partial\alpha_1}+\frac{\partial A_1\tilde{S}}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}\tilde{S}-\frac{\partial A_2}{\partial\alpha_1}\tilde{T}_2\right]+$$
$$+i\frac{c}{1-i(1+\mu)c/R_1}\left[\frac{1}{R_1A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}-(1+\mu)\left(\frac{1}{R_1A_2}\frac{\partial\tilde{S}}{\partial\alpha_2}+\right.\right.$$
$$\left.\left.+\frac{2\tilde{S}}{R_2}\frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}\right)\right]=\frac{q_1}{1-i(1+\mu)c/R_1};$$
$$\frac{1}{A_1A_2}\left[\frac{\partial A_2\tilde{S}}{\partial\alpha_1}+\frac{\partial A_1\tilde{T}_2}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}\tilde{S}-\frac{\partial A_1}{\partial\alpha_2}\tilde{T}_1\right]+$$
$$+i\frac{c}{1-i(1+\mu)c/R_2}\left[\frac{1}{R_2A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}-(1+\mu)\left(\frac{1}{R_2A_1}\frac{\partial\tilde{S}}{\partial\alpha_1}+\right.\right.$$
$$\left.\left.+\frac{2\tilde{S}}{R_1}\frac{1}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}\right)\right]=\frac{q_2}{1-i(1+\mu)c/R_2}, \tag{16.13}$$
$$\frac{\tilde{T}_1}{R_1}+\frac{\tilde{T}_2}{R_2}-ic\Delta(\tilde{T})+$$
$$+\frac{(1+\mu)c^2}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\frac{1}{1-i(1+\mu)c/R_1}\left[\frac{1}{R_1}\frac{A_2}{A_1}\frac{\partial\tilde{T}}{\partial\alpha_1}-\right.\right.$$
$$-(1+\mu)\left(\frac{1}{R_1}\frac{\partial\tilde{S}}{\partial\alpha_2}+\frac{2\tilde{S}}{R_2}\frac{1}{A_1}\frac{\partial A_1}{\partial\alpha_2}\right)\Big]+$$
$$+\frac{\partial}{\partial\alpha_2}\frac{1}{1-i(1+\mu)c/R_2}\left[\frac{1}{R_2}\frac{A_1}{A_2}\frac{\partial\tilde{T}}{\partial\alpha_2}-\right.$$
$$\left.\left.-(1+\mu)\left(\frac{1}{R_2}\frac{\partial\tilde{S}}{\partial\alpha_1}+\frac{2\tilde{S}}{R_1}\frac{1}{A_2}\frac{\partial A_2}{\partial\alpha_1}\right)\right]\right\}=q_n+$$
$$+i\frac{(1+\mu)c}{A_1A_2}\left[\frac{\partial}{\partial\alpha_1}\left(\frac{A_2q_1}{1-i(1+\mu)c/R_1}\right)+\frac{\partial}{\partial\alpha_2}\left(\frac{A_1q_2}{1-i(1+\mu)c/R_2}\right)\right].$$

But the above complex stresses $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$ were solutions of the system of differential equations (16.10) which differs from (16.13) and, therefore, the equations (16.11) and (16.12) remain incompatible.

However, comparing (16.10) with (16.13), it is seen that these two systems differ by terms which, as has been established above, are in the majority of problems of order δ/R [cf. the reasoning for the transition from the system (14.4) to the system (16.3)].

Hence it is concluded that the compatibility of the equations (16.11), (16.12) will be violated only by terms of corresponding order which may not be taken into consideration, so that these are to be eliminated during the computations as their identity is established. Thus, the equations (16.11) and (16.12) will be assumed to be compatible in the above stated approximate sense.

Eliminating from these equations the complex stresses, one obtains the following system of differential equations for $\tilde{u}$, $\tilde{v}$, and $\tilde{w}$:

$$\begin{aligned}
\frac{\tilde{\varepsilon}_1 + \mu\tilde{\varepsilon}_2}{1-\mu^2} + ic\tilde{\kappa}_2 &= \frac{1}{E\delta} T_1^*, \\
\frac{\tilde{\varepsilon}_2 + \mu\tilde{\varepsilon}_1}{1-\mu^2} + ic\tilde{\kappa}_1 &= \frac{1}{E\delta} T_2^*, \\
\frac{\tilde{\omega}}{2(1+\mu)} - ic\tilde{\tau} &= \frac{1}{E\delta} S^*,
\end{aligned} \tag{16.14}$$

which is therefore the generalization of the system (15.5) for the case when $\mu \neq 0$. Thus, the concepts of complex stresses as well as of complex displacements have now been extended to arbitrary values of Poisson's ratio; however, this has been done at the cost of the omission of certain terms in the equilibrium equations for an element of the shell and in the compatibility conditions of the middle surface, a step which was unnecessary when considering the particular case $\mu = 0$.

The mathematical consequence of this omission is that the solutions of the systems of equations (16.10) and (16.14) will not be identical. However, in the majority of problems this disagreement will be insignificant, the errors not exceeding those inherent in the initial hypotheses underlying the theory of shells.

For a confident utilization of the results of this section it is important to know in what cases the errors in the equations (16.10) and (16.14) may be essential. Because of lack of space, it is not possible to give here a complete study of this question and the reader will be referred to the papers [32, 139]. However, the conclusions will be stated here which may be drawn on the basis of these publications.

In fact, it turns out that for solutions of homogeneous problems, i.e., in cases when the components of the surface loading are equal to zero, the errors of the equations (16.10) and (16.14) apparently never exceed those due to the basic assumptions of the theory of shells, so that they are of order δ/R compared with unity.

In the general non-homogeneous problem, however, the accuracy of the equations (16.10) and (16.14) is found to depend on the character

of the surface loading. Namely, if the loading is smooth so that the derivatives of its components with respect to the curvilinear coordinates α_1, α_2 are of smaller order than q_1, q_2, q_n, then the errors in the equations (16.10) and (16.14) will not exceed those inherent in the original assumptions. However, if this condition is not fulfilled, the errors may be much more significant.

The fact is that the simplifications on which the systems (16.10) and (16.14) have been based lead (for the stated transformations of the systems) to the appearance of terms of the form

$$\frac{\delta}{R}\frac{\partial^k q}{\partial \alpha^k},$$

where the order of differentiation "k" may be found to be higher than the order of differentiation in the basic terms without factors δ/R which involve the components of the surface loading.

For smooth load distributions, terms of this form will be quantities of order δ/R, whereas for loadings which are not smooth their magnitudes may increase to any degree. Hence it follows that for the transformations of the systems (16.10) and (16.14) one must reject terms which depend on the surface loading and are multiplied by factors of order δ/R, since the above theory, based on the omission of such terms, will not be correct. By adhering to this principle, apparently one may obtain solutions which, by the help of the equations (16.10) and (16.14), are even correct for loadings which are not smooth. It should be noted that most types of surface loadings encountered in practice will actually be smooth. Examples are uniform normal pressure, hydrostatic pressure and wind or snow loadings on domes. For all these types of loading, the equations of this section will give solutions of the problems with errors not exceeding those inherent in the original assumptions underlying the theory of thin shells.

In conclusion, it should be pointed out that the above theory may not be referred to as 'The Complex Theory of Shells' in the full sense of the word, since no complex independent variables have been introduced. Correspondingly, the boundary conditions have not been given in complex form so that, in order to subject the solutions to these conditions, one must first separate the complex stresses and displacements into real and imaginary parts. From this point of view, the above transformations exhibit an incompleteness which can hardly be removed. Nevertheless, in the majority of cases the employment of the complex form of the equations of the theory of shells will be convenient.

Firstly, these equations are much more concise (and correspondingly

more lucid) than the equations of the theory of shells in their ordinary (real) form, a fact which makes it easy to investigate possible transformations and simplifications [cf. § 40, 51, 54, 62, 64].

Secondly, for the solution of problems by simple Fourier series (one of the basic practical methods of the theory of shells) when the solution of systems of partial differential equations is reduced to the integration of a number of systems of ordinary differential equations, the halving of the order of the differential equations resulting from the complex transformation is a real advantage. (See chapters III and IV).

Thirdly, for the solution of problems by double Fourier series (when the question of satisfying the boundary conditions does not arise, since this method permits only the study of one single form of the boundary conditions), all the manipulations may be executed in complex form until the last step is reached, i.e., until the evaluation of the displacements and stresses (see § 46).

Fourthly, a type of problem may be formulated for the solution of which the boundary conditions may be formulated directly in terms of the complex auxiliary functions. In particular, such problems are those dealing with two shells of equal thickness, joined together in, such a manner that on their common boundaries the tangents to the lines of curvature remain continuous, only the curvatures suffering discontinuities (cf. § 61). This example may be generalized to certain cases of shells which are joined at an angle.

Thus, the method of complex transformations essentially increases the possibilities at the disposal of the student in command of this method to justify its study in this book as a basic method of approach. Gol'denweizer in his review [11] of an earlier edition of this book notes "that in applying the complex representation, the author complicates his problem in order to give a treatment accessible to the engineer". This reproach is hardly just, since the knowledge of the theory of a complex variable, required for the understanding and the practical applications of the method under consideration, is limited to the algebra of complex numbers which is part of all undergraduate programs at universities and technical colleges.

In addition, it should be remembered that the first successful practical applications of the theory of shells began essentially in 1913 with the discovery of the complex transformation of the equations for the symmetrical deformation of shells of revolution. The appearance of this transformation (which is a particular case of the above general transformation) largely secured the possibility for the development of engineering methods for the calculation of certain shells. (See Chapter IV). Thus, the

assertion that the appearence in the calculations of complex auxiliary functions seems to be in contrast to the practical objectives of the theory of shells, besides everything else, contradicts the facts of the history of the development of this discipline. The other question, namely that the proposed complex method exhibits certain peculiar features and that it requires a certain amount of time and training to master it, will be studied irrespective of all this by practical engineers or such qualified theoreticians as Gol'denweizer.

§ 17. Simplification of the theory of shells by the method of Mushtari-Vlasov

As has already been mentioned, the first attempt at the construction of a theory of shells on the basis of the hypothesis that normals remain normals was made by Aron (§ 1) who, by the way, disregarded for this purpose terms depending on the tangential displacements u and v in the formulae for change of curvature and twist.

In the paper [48], Love corrected a series of Aron's inaccuracies and also gave the formulae for κ_1, κ_2, τ used earlier. However, afterwards it was discovered that Aron's approximation (essentially his simplified equations) is in many cases completely justified. A deliberate and well-founded application of this method was given in the lectures of Kh. M. Mushtari [20, 21] who applied it to a number of problems of the stability of shells.

Mushtari established that the neglect of the displacements u and v in the formulae for change of curvature and twist is justified in those cases where the stresses arising from the moments are of comparable order with those due to the in the plane stress resultants (or smaller). For this purpose, the stresses due to the moments forces (and likewise the displacements of the middle surface) will be functions which increase on every differentiation even though it is with respect to one curvilinear coordinate. In the use of the above mentioned simplified formulae for κ_1, κ_2, τ. This last circumstance makes it possible to neglect a number of other terms in the equations of the theory of shells. In particular, the normal shearing forces in the first two of the equilibrium equations (7.4) can be neglected and, in addition, one may put

$$T_{21} = T_{12} = S.$$

The equations of the theory of shells which use this system of simplifications will now be derived.

Rejecting the displacements u and v, in the formulae for the parameters of the changes of curvature and twist one finds

$$\begin{aligned}
\kappa_1 &= -\frac{1}{A_1}\frac{\partial}{\partial\alpha_1}\left(\frac{1}{A_1}\frac{\partial w}{\partial\alpha_1}\right) - \frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}\frac{1}{A_2}\frac{\partial w}{\partial\alpha_2},\\
\kappa_2 &= -\frac{1}{A_2}\frac{\partial}{\partial\alpha_2}\left(\frac{1}{A_2}\frac{\partial w}{\partial\alpha_2}\right) - \frac{1}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}\frac{1}{A_1}\frac{\partial w}{\partial\alpha_1},\\
\tau &= -\frac{1}{A_1A_2}\left(\frac{\partial^2 w}{\partial\alpha_1\partial\alpha_2} - \frac{1}{A_1}\frac{\partial A_1}{\partial\alpha_2}\frac{\partial w}{\partial\alpha_1} - \frac{1}{A_2}\frac{\partial A_2}{\partial\alpha_1}\frac{\partial w}{\partial\alpha_2}\right).
\end{aligned} \tag{17.1}$$

These formulae will now be introduced into the equations (7.8) which will first be rewritten in the form

$$\begin{aligned}
N_1 &= \frac{1}{1+\mu}\frac{1}{A_1}\frac{\partial M}{\partial\alpha_1} + \frac{1}{1+\mu}\left\{\frac{\mu}{A_1}\frac{\partial M_1}{\partial\alpha_1} - \frac{1}{A_1}\frac{\partial M_2}{\partial\alpha_1} + \right.\\
&\qquad \left. + \frac{1+\mu}{A_1A_2}\left[\frac{\partial A_2}{\partial\alpha_1}(M_1 - M_2) + \frac{\partial A_1 H}{\partial\alpha_2} + \frac{\partial A_1}{\partial\alpha_2}H\right]\right\},\\
N_2 &= \frac{1}{1+\mu}\frac{1}{A_2}\frac{\partial M}{\partial\alpha_2} + \frac{1}{1+\mu}\left\{\frac{\mu}{A_2}\frac{\partial M_2}{\partial\alpha_2} - \frac{1}{A_2}\frac{\partial M_1}{\partial\alpha_2} + \right.\\
&\qquad \left. + \frac{1+\mu}{A_1A_2}\left[\frac{\partial A_1}{\partial\alpha_2}(M_2 - M_1) + \frac{\partial A_2 H}{\partial\alpha_1} + \frac{\partial A_2}{\partial\alpha_1}H\right]\right\}.
\end{aligned} \tag{17.2}$$

Substituting here the expressions for the moments in terms of the changes in curvature and using (10.8), one finds

$$\begin{aligned}
N_1 &= \frac{E\delta^3}{12(1-\mu^2)}\left\{\frac{1}{A_1}\frac{\partial(\kappa_1+\kappa_2)}{\partial\alpha_1} - \right.\\
&\qquad \left. - \frac{1-\mu}{A_1A_2}\left[\frac{\partial A_2\kappa_2}{\partial\alpha_1} - \frac{\partial A_2}{\partial\alpha_1}\kappa_1 - \frac{\partial A_1\tau}{\partial\alpha_2} - \frac{\partial A_1}{\partial\alpha_2}\tau\right]\right\},\\
N_2 &= \frac{E\delta^3}{12(1-\mu^2)}\left\{\frac{1}{A_2}\frac{\partial(\kappa_1+\kappa_2)}{\partial\alpha_2} - \right.\\
&\qquad \left. - \frac{1-\mu}{A_1A_2}\left[\frac{\partial A_1\kappa_1}{\partial\alpha_2} - \frac{\partial A_1}{\partial\alpha_2}\kappa_2 - \frac{\partial A_2\tau}{\partial\alpha_1} - \frac{\partial A_2}{\partial\alpha_1}\tau\right]\right\},
\end{aligned} \tag{17.3}$$

where, on the basis of (17.1),

$$\kappa_1 + \kappa_2 = -\Delta(w) \tag{17.4}$$

with $\Delta(\ldots)$ the Laplace operator (12.6).

The expressions in (17.3) which are contained in square brackets can be simplified using the first two of the identities (5.1).

Remembering that for $u = v = 0$, $\varepsilon_1 = \frac{w}{R_1}$, $\varepsilon_2 = \frac{w}{R_2}$, $\omega = 0$, one finds in this way

$$\begin{aligned}
&\frac{\partial A_2\kappa_2}{\partial\alpha_1} - \frac{\partial A_2}{\partial\alpha_1}\kappa_1 - \frac{\partial A_1\tau}{\partial\alpha_2} - \frac{\partial A_1}{\partial\alpha_2}\tau = \frac{1}{R_1}\left(\frac{\partial A_2\varepsilon_2}{\partial\alpha_1} - \frac{\partial A_2}{\partial\alpha_1}\varepsilon_1\right) = \frac{A_2}{R_1R_2}\frac{\partial w}{\partial\alpha_1},\\
&\frac{\partial A_1\kappa_1}{\partial\alpha_2} - \frac{\partial A_1}{\partial\alpha_2}\kappa_2 - \frac{\partial A_2\tau}{\partial\alpha_1} - \frac{\partial A_2}{\partial\alpha_1}\tau = \frac{1}{R_2}\left(\frac{\partial A_1\varepsilon_1}{\partial\alpha_2} - \frac{\partial A_1}{\partial\alpha_2}\varepsilon_2\right) = \frac{A_1}{R_1R_2}\frac{\partial w}{\partial\alpha_2}.
\end{aligned} \tag{17.5}$$

Hence the formulae (17.3) can be written

$$\begin{aligned}
N_1 &= -\frac{E\delta^3}{12(1-\mu^2)}\frac{1}{A_1}\left[\frac{\partial\Delta(w)}{\partial\alpha_1} + \underline{\frac{1-\mu}{R_1R_2}\frac{\partial w}{\partial\alpha_1}}\right],\\
N_2 &= -\frac{E\delta^3}{12(1-\mu^2)}\frac{1}{A_2}\left[\frac{\partial\Delta(w)}{\partial\alpha_2} + \underline{\frac{1-\mu}{R_1R_2}\frac{\partial w}{\partial\alpha_2}}\right].
\end{aligned}$$

Since it has been assumed that for differentiation w essentially increases, the underlined terms in the above formulae must be rejected. Hence

$$\begin{aligned}
N_1 &\approx -\frac{E\delta^3}{12(1-\mu^2)}\frac{1}{A_1}\frac{\partial\Delta(w)}{\partial\alpha_1},\\
N_2 &\approx -\frac{E\delta^3}{12(1-\mu^2)}\frac{1}{A_2}\frac{\partial\Delta(w)}{\partial\alpha_2}.
\end{aligned} \tag{17.6}$$

Further, neglecting as indicated above the normal shearing forces in the first two equations (7.4) and replacing in the third equation these forces by their expressions (17.6), one obtains

$$\begin{aligned}
&\frac{1}{A_1A_2}\left[\frac{\partial A_2T_1}{\partial\alpha_1} + \frac{\partial A_1S}{\partial\alpha_2} + \frac{\partial A_1}{\partial\alpha_2}S - \frac{\partial A_2}{\partial\alpha_1}T_2\right] + q_1 = 0,\\
&\frac{1}{A_1A_2}\left[\frac{\partial A_2S}{\partial\alpha_1} + \frac{\partial A_1T_2}{\partial\alpha_2} + \frac{\partial A_2}{\partial\alpha_1}S - \frac{\partial A_1}{\partial\alpha_2}T_1\right] + q_2 = 0,\\
&\frac{E\delta^3}{12(1-\mu^2)}\Delta[\Delta(w)] + \frac{T_1}{R_1} + \frac{T_2}{R_2} = q_n.
\end{aligned} \tag{17.7}$$

The equations are now in the form employed by Mushtari.

A further transformation of the equations (17.7) was studied by S. Feinberg [36] and Vlasov [3, 4]. Here the development due to Vlasov will be given.

This author introduced into the consideration an auxiliary function Φ which he related to the forces by means of the formulae

$$T_1 = -\frac{1}{A_2}\frac{\partial}{\partial\alpha_2}\left(\frac{1}{A_2}\frac{\partial\Phi}{\partial\alpha_2}\right) - \frac{1}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}\frac{1}{A_1}\frac{\partial\Phi}{\partial\alpha_1},$$

$$T_2 = -\frac{1}{A_1}\frac{\partial}{\partial\alpha_1}\left(\frac{1}{A_1}\frac{\partial\Phi}{\partial\alpha_1}\right) - \frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}\frac{1}{A_2}\frac{\partial\Phi}{\partial\alpha_2}, \qquad (17.8)$$

$$S = \frac{1}{A_1A_2}\left(\frac{\partial^2\Phi}{\partial\alpha_1\partial\alpha_2} - \frac{1}{A_1}\frac{\partial A_1}{\partial\alpha_2}\frac{\partial\Phi}{\partial\alpha_1} - \frac{1}{A_2}\frac{\partial A_2}{\partial\alpha_1}\frac{\partial\Phi}{\partial\alpha_2}\right),$$

which are analogous to the formulae (17.1).

Substitution of (17.8) into the first two equations of the system (17.7) gives

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2T_1}{\partial\alpha_1} + \frac{\partial A_1S}{\partial\alpha_2} + \frac{\partial A_1}{\partial\alpha_2}S - \frac{\partial A_2}{\partial\alpha_1}T_2\right] = \frac{1}{R_1R_2}\frac{1}{A_1}\frac{\partial\Phi}{\partial\alpha_1},$$

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2S}{\partial\alpha_1} + \frac{\partial A_1T_2}{\partial\alpha_2} + \frac{\partial A_2}{\partial\alpha_1}S - \frac{\partial A_1}{\partial\alpha_2}T_1\right] = \frac{1}{R_1R_2}\frac{1}{A_2}\frac{\partial\Phi}{\partial\alpha_2}. \qquad (17.9)$$

Taking now the rapid variation of the function Φ into consideration, it can be said that the expressions (17.8) satisfy the first two of the equations (17.7) (for $q_1 = q_2 = 0$) exactly, apart from small errors, since after substitution of (17.8) into the equations (17.7) all terms containing second and third order derivatives of Φ cancel; there remain only first order derivatives which can be neglected in comparison with higher order derivatives. Assuming that the first two of the equations (17.7) are approximately satisfied, (17.8) will now be substituted into the third equation of this system. In this way one obtains the following differential relation between w and Φ

$$\frac{E\delta^3}{12(1-\mu^2)}\Delta\Delta(w) - D(\Phi) = q_n, \qquad (17.10)$$

where $D(\ldots)$ is the differential operator

$$D(\ldots) = \frac{1}{A_1A_2}\left\{\frac{\partial}{\partial\alpha_1}\left[\frac{1}{R_2}\frac{A_2}{A_1}\frac{\partial(\ldots)}{\partial\alpha_1}\right] + \frac{\partial}{\partial\alpha_2}\left[\frac{1}{R_1}\frac{A_1}{A_2}\frac{\partial(\ldots)}{\partial\alpha_2}\right]\right\}. \qquad (17.11)$$

A second relation between the same functions was obtained by Vlasov from the third condition of compatibility (5.1) by introducing in it, instead of κ_1, κ_2, τ, their expressions in terms of w and instead of ε_1,

ε_2, ω their expressions in terms of Φ, using the formulae (17.8) and

$$\varepsilon_1 = \frac{1}{E\delta}(T_1 - \mu T_2),\quad \varepsilon_2 = \frac{1}{E\delta}(T_2 - \mu T_1),\quad \omega = \frac{2(1+\mu)}{E\delta}S. \tag{17.12}$$

Without giving all the details of these manipulations, since they are entirely analogous to those involved in the deduction of (17.5), the final result will be given in the form

$$E\delta D(w) + \Delta[\Delta(\Phi)] + \underline{+ \frac{1+\mu}{A_1A_2}\left[\frac{\partial}{\partial\alpha_1}\left(\frac{1}{R_1R_2}\frac{A_2}{A_1}\frac{\partial\Phi}{\partial\alpha_1}\right) + \frac{\partial}{\partial\alpha_2}\left(\frac{1}{R_1R_2}\frac{A_1}{A_2}\frac{\partial\Phi}{\partial\alpha_2}\right)\right]} = 0, \tag{17.13}$$

where the underlined terms can be neglected by taking into consideration the increase in value of Φ on differentiation. Combining this equation with (17.10) above, one has for w and Φ the pair of partial differential equations

$$\begin{aligned} \frac{1}{E\delta}\Delta\Delta(\Phi) + D(w) &= 0, \\ \frac{E\delta^3}{12(1-\mu^2)}\Delta\Delta(w) - D(\Phi) &= q_n. \end{aligned} \tag{17.14}$$

Above all, the system (17.14) can be successfully employed for those problems in which the bending stresses in the shell are comparable in magnitude with stresses due to in-plane forces, since in these problems the solutions of the system (17.14) can be expressed in terms of rapidly changing functions, i.e., in terms of functions with the same property which was assumed for the deduction of the equations under consideration. (Here, and in the further discussion, the term *rapidly changing function* will refer to a function, the ratio of which to its derivative is small everywhere in comparison with unity except in the neighbourhood of points where the derivative vanishes). Such states of stress in shells will be encountered often (§ 18) and, in future, they will be called stress conditions of the mixed type.

Further, the system (17.14) can also be employed for the investigation of shallow shells, i.e., for shells which geometrically differ little from plates. The possibility of applying the equations (17.14) to this class of shell is based on the fact that all the terms which were rejected in the deduction of these equations contained the parameters of the curvature of the middle surface as factors. The statement of Gol'denweiser [11] that the equations (17.14) are also applicable to shells of zero Gaussian

curvature of any degree (the Gaussian curvature of a surface being the product $\frac{1}{R_1R_2}$) is wrong, as is easily verified, starting from these equations, by studying the problem of bending of infinitely long tubes subject to transverse loading, constant along the length of the tube. If the cross-section of the tube is assumed to be circular, the differential equation describing this problem must be identical to the known equation for the bending of a flat curved beam. However, this last equation is not obtained from (17.14). This is obviously explained by the fact that during the derivation of (17.14) there have been neglected not only terms which have the Gaussian curvature of the middle surface as a factor, but also terms multiplied by the principal curvatures $1/R_1$ and $1/R_2$ separately (cf. the terms rejected in the formulae for κ_1, κ_2, τ).

The equations (17.14) are readily obtained from the equations (16.10) in which certain terms must be omitted. In fact, in (16.10) one must let

$$q_1 = q_2 = 0,$$

then, in the first two of these equations neglect the imaginary terms, i.e.,

$$i\frac{c}{R_1}\frac{1}{A_1}\frac{\partial \tilde{T}}{\partial \alpha_1} \text{ and } i\frac{c}{R_2}\frac{1}{A_2}\frac{\partial \tilde{T}}{\partial \alpha_2},$$

and introduce the auxiliary complex function $\tilde{\Psi}$ related to the complex stresses by means of the equalities

$$\begin{aligned}
\tilde{T}_1 &= -\frac{1}{A_2}\frac{\partial}{\partial \alpha_2}\left(\frac{1}{A_2}\frac{\partial \tilde{\Psi}}{\partial \alpha_2}\right) - \frac{1}{A_1A_2}\frac{\partial A_2}{\partial \alpha_1}\frac{1}{A_1}\frac{\partial \tilde{\Psi}}{\partial \alpha_1}, \\
\tilde{T}_2 &= -\frac{1}{A_1}\frac{\partial}{\partial \alpha_1}\left(\frac{1}{A_1}\frac{\partial \tilde{\Psi}}{\partial \alpha_1}\right) - \frac{1}{A_1A_2}\frac{\partial A_1}{\partial \alpha_2}\frac{1}{A_2}\frac{\partial \tilde{\Psi}}{\partial \alpha_2}, \qquad (17.15) \\
\tilde{S} &= \frac{1}{A_1A_2}\left(\frac{\partial^2 \tilde{\Psi}}{\partial \alpha_1 \partial \alpha_2} - \frac{1}{A_1}\frac{\partial A_1}{\partial \alpha_2}\frac{\partial \tilde{\Psi}}{\partial \alpha_1} - \frac{1}{A_2}\frac{\partial A_2}{\partial \alpha_1}\frac{\partial \tilde{\Psi}}{\partial \alpha_2}\right).
\end{aligned}$$

Under these conditions, if $\tilde{\Psi}$ is a rapidly varying function (even if only of one of the curvilinear coordinates α_1, α_2) or if the shell has sufficient slope, it may be assumed that the expressions (17.15) satisfy the first two of the equations (16.10) approximately in the above stated simplified manner. The third of the equations (16.10) then becomes the following equation with the auxiliary function $\tilde{\Psi}$ as single variable,

$$-D(\tilde{\Psi}) + ic\Delta\Delta(\tilde{\Psi}) = q_n, \qquad (17.16)$$

where $D(\ldots)$ is the operator (17.11).

In this equation letting

$$\tilde{\Psi} = \Phi - i \frac{E\delta^2}{\sqrt{12(1-\mu^2)}} w \tag{17.17}$$

and separating real and imaginary parts, one arrives at the system of equations (17.14). Substituting now (17.17) into (17.15) and again separating real and imaginary parts, one obtains the formulae (17.8) and (17.1).

In conclusion, it should be noted that, although the equations (17.14) in their general form (for shells of arbitrary shape) were only deduced in 1944 [3], they were used much earlier for the particular case of circular cylindrical shells [113, 27].

§ 18. On types of state of stress in shells

Generally speaking, the bending stresses in shells must be assumed to be quantities of the same order as the stresses due to in-plane forces ('chain' or membrane stresses in the terminology of ship-design). This state of stress in a shell has already been termed in the preceding section state of stress of the 'mixed' type.

However, side by side with the above, one should have in mind two important particular cases, namely

(1), when the bending stresses are negligible in comparison with the membrane stresses;

(2), when the membrane stresses are negligible in comparison with the bending stresses.

The first case will be called the "momentless" or membrane state of stress; the second, the pure bending state of stress in shells.

It should be emphasized that both these terms are not completely precise, since the membrane condition will admit the existence of small bending stresses, and in the pure bending condition small membrane stresses.

There are strong reasons for studying the above two particular cases separately. The fact is that, in view of their small thickness, shells adapt themselves badly to bending, so that relatively small bending moments generate considerable stresses and deflections. Therefore the pure bending type of stress condition is to be avoided and is technically disadvantageous for shells. One should always aim at avoiding this condition by a suitable choice of the shape of the shell and of the support of its edges, which sometimes may require the introduction of additional supports. It is necessary to know about this state of stress in order to avoid it. In contrast, in the membrane state of stress (for which

the shell is loaded uniformly across its thickness) the transmission of the external forces from the edges is achieved in a more rational manner and is technically most expedient and it should always be aimed at in the design of shells, again employing a suitable choice for the shape of the shell and the arrangement of its supports. Hence there arises the practical advantage of studying this type of state of stress.

In certain cases, the ideal membrane state of stress of shells may be realized in practice to a high degree of accuracy (for example, in the design of domes). However, in the majority of cases, the membrane state of stress turns out to be unpractical and then one will be forced to admit regions in a shell where a stress condition of the mixed type occurs. Under these conditions, depending on the success in confining the bending stresses within the bounds of variation of the membrane stresses, such a solution of the problem will be technically acceptable. It should be noted that often the mixed state of stress may be restricted to the edge regions of the shell as, for example, in the design of reservoirs and their bottoms where the membrane condition will be preserved through the remainder of the shell. Hence, there has originated the term 'edge-effect' by which is understood the rapid decay of the stresses of the mixed type with the distance from the edge region of the shell.

In different shells, the edge-effect manifests itself in different ways. Thus, for symmetrical deformations of shells of revolution, it has a particularly pronounced character. In cylindrical plates (vaults), the stresses arising at the straight edges decay much more slowly with the distance from the edges and they obviously extend practically throughout the entire shell. In view of this the application of the term 'edge-effect' has not the same physical justification as in the preceding case. Further, not only the edges may be sources of stresses of the mixed type, but also any curve on the middle surface across which there occurs an abrupt change of the curvature of the shell or its thickness. The behaviour of those stresses and the methods for their study will not differ at all from those for the edge-effects.

In view of the above discussion, the expression 'stress condition of the mixed type' is preferred to the expression 'edge effect', but, at the same time, it may be decided to use this latter term in cases where it will be physically appropriate.

As a consequence of the above classification of the stress conditions in shells, methods will be developed for the simplification of the differential equations of the theory of shells and approximate methods for their integration.

The reader has already been acquainted in the preceding section with

one of those methods developed for the study of states of stress of the mixed type. Other methods will be found in the following chapters.

It should be noted that in what follows problems will be rarely solved without resort to one or other simplification of the differential equations of the theory of shells or of their integrals, depending upon the nature of the stress condition under consideration.

CHAPTER II

THE MEMBRANE THEORY OF SHELLS

§ 19. Preliminary remarks. History

Historically, the general theory of shells studied in the first chapter was preceded by the so called membrane theory which is considerably simpler and, at the same time, gives in certain cases a completely correct notion of the shell mechanism. In the study of the equilibrium of the shell element, this theory neglects all moments.

It follows from the relations

$$M_1 = \frac{E\delta^3}{12(1-\mu^2)}(\kappa_1 + \mu\kappa_2), \qquad M_2 = \frac{E\delta^3}{12(1-\mu^2)}(\kappa_2 + \mu\kappa_1),$$
$$H = \frac{E\delta^3}{12(1+\mu)}\tau, \tag{19.1}$$

that the neglecting of the moments will be well justified either when the shell has very small bending stiffness or when the changes of curvature and twist of the middle surface are very small.

In the first case, one is concerned with the equilibrium of absolutely flexible shells (membranes); in the second case, with the momentless state of stress of shells which have finite bending stiffness. Although both these problems are described by one and the same theory, nevertheless a distinction must be made between them since they exhibit special features. Thus, an absolutely flexible shell (for example, made from cloth) is not able to sustain compression forces, since any compression, however small, will cause loss of stability of its shape, i.e., the formation of wrinkles. Therefore, the calculations for such a shell will only correspond to a real situation in the case where tensile forces are obtained at all sections. For example, this condition is the basic requirement which must be satisfied by the body of a flexible (or semi-rigid) airship in order to ensure its longitudinal stability.

On the other hand, shells with finite bending stiffness, in contrast to absolutely flexible shells, may sustain in the momentless state of stress compressive as well as tensile forces. They will loose stability only when

the compressive forces exceed a certain critical value. For absolutely flexible shells, since they do not possess resistance to bending, only the momentless state of stress is possible; for shells with finite stiffness such a state of stress is only one of the possible stress conditions and for its existence a number of supplementary conditions must be fulfilled which refer to the shape of the shell, the type of the external loads and the support of its edges.

It is not out of place here to compare the properties of shells with those of curved beams. As is well known, an arch of arbitrary form functions, as a rule, not only as a compression member, but also in bending. However, it is possible to specify its shape and the manner of its loading in such a way that it does not experience bending, so that, in agreement with the above terminology, it is in a momentless state of stress. Thus, for example, for a parabolic arch bending will not be induced by a vertical load uniformly distributed over its chord, while for a catenary arch this is true, if it is loaded by its own weight. The ability of arches to support certain transverse loads without bending is the reason for their technical advantage over straight beams.

Shells possess an analogous advantage over plates with, however, the essential difference that, while an arch of a given form will support only one completely determined load without bending, a shell of given shape has, as a rule, the same property for a wide range of loads which satisfy only very general requirements, provided its edges are suitably supported. In fact, this property of shells to react, under certain conditions, without or with insignificant bending is the reason for the extended practical application which they have found lately in different fields of industry. It should be emphasized as an important point in connection with the above that the concept of the momentless state of stress is not at all necessarily linked to infinitely large flexibility of shells (or, what is the same thing, to their infinitely small thickness). Even a thick shell, under suitable conditions, may exhibit momentless behaviour (in the sense that its bending stresses will be of order δ/R compared with the direct stresses).

The conditions for the existence of the momentless state of stress will be elucidated in the following section. However, these conditions may not always be fulfilled in a design and then a mixed stress field will be superimposed on the momentless state of stress (as has already been stated at the end of the last chapter, the pure bending condition has no advantage and should be avoided). Thus, the momentless stress condition occupies a place of honor in the design of shells and it is an ideal (sometimes, unfortunately, unobtainable) at which the designer should aim.

Brief mention will now be made of the stages of the development of the momentless or membrane theory. Its origin goes back to the work of G. Lamé and B. P. E. Clapeyron [70] who considered the symmetrical loading of shells of revolution. The general form of the equations of the membrane theory were established by E. Beltrami [65] and L. Lecornu [72].

The greatest successes of the momentless theory are connected with work of Russian origin. Among the contributions to the general momentless theory, the paper by V. V. Sokolovskii [64] should be noted since he reduced the equations of the problem to cannonical form and revealed a number of their characteristic properties.

The study of Iu. N. Rabotnov [61] is likewise of basic importance for the general membrane theory. In this paper, the problem of the momentless theory was linked to the problem of bending of a surface. The determination of the forces and displacements in a momentless shell was thus reduced to the solution of two independent partial differential equations.

The differential equations of the membrane theory are easily integrated for shells of zero Gaussian curvature (in particular, for cylindrical shells). It is likewise not difficult to obtain solutions for the practically important cases of symmetrical and wind type loadings on shells of revolution. Shells of revolution, loaded in an arbitrary manner, were investigated by V. Z. Vlasov [53, 4], Sokolovskii [63] and other authors. The momentless theory of shells (the middle surface being a second order surface) has been worked out by Vlasov [54, 55] who applied to this problem the theory of functions of a complex variable.

§ 20. The fundamental equations of the membrane theory

The equations of the membrane theory can be obtained directly from the equations of the general theory. For this purpose, it will be assumed that, although in principle the shell may be resistant to bending, in view of the smallness of the changes of curvature and twist, the moment terms in the equations of equilibrium for the shell element are unimportant. Rejecting these terms in the equations (7.8), one will have

$$\begin{aligned} T_{12} &= T_{21} = S^*, \\ N_1 &= N_2 = 0. \end{aligned} \tag{20.1}$$

Thus, the neglect of the moments leads to the neglect of the normal shearing forces.

Introducing these results into the equations (7.4), one arrives at the

system of differential equations

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2T_1^*}{\partial\alpha_1}+\frac{\partial A_1S^*}{\partial\alpha_2}+\frac{\partial A_1}{\partial\alpha_2}S^*-\frac{\partial A_2}{\partial\alpha_1}T_2^*\right]+q_1=0,$$

$$\frac{1}{A_1A_2}\left[\frac{\partial A_2S^*}{\partial\alpha_1}+\frac{\partial A_1T_2^*}{\partial\alpha_2}+\frac{\partial A_2}{\partial\alpha_1}S^*-\frac{\partial A_1}{\partial\alpha_2}T_1^*\right]+q_2=0, \quad (20.2)$$

$$\frac{T_1^*}{R_1}+\frac{T_2^*}{R_2}=q_n,$$

which, in conjunction with (20.1), are the conditions of equilibrium for the shell element in the momentless or membrane state of stress.

Here and in what follows, the stress resultants corresponding to the membrane stress condition will be distinguished by means of an asterisk.

In the system (20.2), the number of unknowns is equal to the number of equations, so that the problem of the theory of shells in the above stated formulation is statically determinate (in relation to the equilibrium of an infinitely small element of the shell, but not always in relation to the equilibrium of the shell as a whole). The reader is reminded that an analogous example is the problem of the bending of a beam in its technical formulation, where likewise the number of unknowns in the equilibrium equations corresponds to the number of equations and where nevertheless the determination of the reactions at the supports requires sometimes first the determination of the displacements. It will be assumed that the system (20.2) may be solved (the question of the boundary conditions which must be supplied for this purpose will be overlooked for the time being). Then, for the determination of the displacements in a shell which is in a membrane state of stress, one may write down the following system of three partial differential equations

$$\varepsilon_1^*=\frac{1}{A_1}\frac{\partial u}{\partial\alpha_1}+\frac{1}{A_1A_2}\frac{\partial A_1}{\partial\alpha_2}v+\frac{w}{R_1}=\frac{1}{E\delta}(T_1^*-\mu T_2^*),$$

$$\varepsilon_2^*=\frac{1}{A_2}\frac{\partial v}{\partial\alpha_2}+\frac{1}{A_1A_2}\frac{\partial A_2}{\partial\alpha_1}u+\frac{w}{R_2}=\frac{1}{E\delta}(T_2^*-\mu T_1^*), \quad (20.3)$$

$$\omega^*=\frac{A_2}{A_1}\frac{\partial}{\partial\alpha_1}\left(\frac{v}{A_2}\right)+\frac{A_1}{A_2}\frac{\partial}{\partial\alpha_2}\left(\frac{u}{R_1}\right)=\frac{2(1+\mu)}{E\delta}S^*,$$

the right hand sides of which are known functions of α_1 and α_2. The general solutions of this system can be presented in the form

$$\begin{aligned} u &= u^* + u^{**}, \\ v &= v^* + v^{**}, \\ w &= w^* + w^{**}, \end{aligned} \quad (20.4)$$

where u^*, v^*, w^* are understood to be any particular integrals of the system (20.3) and u^{**}, v^{**}, w^{**} are the general solutions of the homogeneous system of equations

$$\begin{aligned}
&\frac{1}{A_1}\frac{\partial u^{**}}{\partial \alpha_1}+\frac{1}{A_1A_2}\frac{\partial A_1}{\partial \alpha_2}v^{**}+\frac{w^{**}}{R_1}=0,\\
&\frac{1}{A_2}\frac{\partial v^{**}}{\partial \alpha_2}+\frac{1}{A_1A_2}\frac{\partial A_2}{\partial \alpha_1}u^{**}+\frac{w^{**}}{R_2}=0,\\
&\frac{A_2}{A_1}\frac{\partial}{\partial \alpha_1}\left(\frac{v^{**}}{A_2}\right)+\frac{A_1}{A_2}\frac{\partial}{\partial \alpha_2}\left(\frac{u^{**}}{A_1}\right)=0.
\end{aligned} \tag{20.5}$$

It is now seen that the displacements u^{**}, v^{**}, w^{**} give zero values for the direct and shear strains of the middle surface. Hence it is clear that the corresponding displacements may only be either displacements due to pure bending of the shell or displacements of the shell as a rigid body.

Thus, in general, the solutions of the equations of the membrane theory present pure bending displacements on an equal basis with displacements of the shell as a rigid body. Physically, this means that a freely flexible shell admits the appearance of such displacements without offering any resistance.

For the statement of the problems of the membrane theory, the pure bending displacements must either be eliminated completely or, at least, bounded in a proper manner. This remark applies not only to freely flexible shells (the shape of which otherwise will be undetermined), but also to shells with bending stiffness which are in such a state of stress that the bending stresses may be neglected in comparison with the membrane stresses. Actually, for such shells, the presence of essentially large bending displacements will be incompatible with the hypothesis of small bending stresses.

The principal possibility of the indeterminacy of the magnitudes of the displacements in the membrane theory and the consequent necessity for imposing bounds on the displacements, which is one of the conditions for the existence of the membrane state of stress, has an effect on the formulation of the boundary conditions in the membrane theory, as will become clear in the next section.

§ 21. The boundary conditions

The system of differential equations (20.2) for determining the stresses in the membrane theory is of the second order. Accordingly, also the system (20.3) for the displacements is of second order. However, the

forces entering into the right hand sides of the equations of the last system are themselves solutions of a second order system.

Hence, the displacements in the membrane theory satisfy a fourth order system of equations which can be obtained by substituting into the equations (20.2) for the forces T_1^*, T_2^*, S^* their expressions in terms of the strains. However, this will not be done, because it is always more convenient to obtain the solutions in two successive steps — determination of the stresses from the system (20.2) and of the displacements from the system (20.3). Thus, in the membrane theory, the differential equations for the displacements have half the order of those in the general (moment) theory of shells; therefore the number of edge conditions which must be satisfied in the first theory will be half the number of edge conditions in the second theory.

In fact, in the membrane theory, only two boundary conditions may be specified on each edge of the shell.

For the sake of definiteness, consider the case when the edge of the shell is the line $\alpha_1 = \text{constant}$. In the general theory of shells, there must be given on this edge the quantities

$$T_1,\ T_{12} + \frac{M_{12}}{R_2},\ N_1 + \frac{1}{A_2}\frac{\partial M_{12}}{\partial \alpha_2},\ M_1,$$

(when the boundary conditions have been formulated in terms of the stresses). In the membrane theory, one has

$$N_1 = N_2 = M_1 = M_2 = M_{12} = M_{21} = 0$$

at all points of the middle surface, and hence also on the boundary of the shell.

Therefore the edges of a shell in the membrane state of stress must be free from external edge loading in the form of normal shearing stresses and bending moments. Membranes can only support tangential edge loadings, as a result of which only the forces T_1 and $S = T_{12}$ may act on the edge under consideration. Hence the boundary conditions must be formulated in terms of these quantities.

Consider further the case where the boundary conditions are given in terms of the displacements. Then, in order to make the solutions of the equations of the general theory of shells unique, one must specify (on the boundary $\alpha_1 = \text{constant}$) the quantities

$$u,\ v,\ w,\ \vartheta = -\frac{1}{A_1}\frac{\partial w}{\partial \alpha_1} + \frac{u}{R_1}.$$

In the membrane theory, it is impossible to specify the edge displacement w and the angle of twist ϑ, since this would immediately affect the values of the corresponding generalized forces N_1 and M_1. For example, letting $w = \vartheta = 0$ on the edge of the shell (i.e., "clamping" the edge in relation to radial displacement and angle of rotation), it is, of course, impossible to assume that on the same edge $N_1 = 0$, $M_1 = 0$, since the last directly contradicts the first condition. It follows from this that on the edge of the membrane one may only specify the tangential displacement components of the middle surface, i.e., u and v. Therefore, the boundary conditions of the membrane theory, if they are to be given in terms of displacements, must be formulated in terms of these quantities. Further, it must be taken into consideration that the differential equations of the membrane theory in terms of forces and displacements are of different order, i.e., of second and fourth order respectively. As a consequence of this, the edge conditions for membranes may not be given in terms of forces only, but half of these conditions must be given in terms of the displacements. This necessity for giving half the edge conditions in terms of the displacements has the following physical meaning: as has been shown in the previous section, a shell without bending stiffness is not a rigid body, but a mechanism which is free to admit displacements corresponding to pure bending. As a rule, displacements corresponding to an appropriate support of the edges may be eliminated, i.e., the shell can be converted into a rigid system. For this purpose, use must be made of the "compulsory" boundary conditions referred to above.

The remaining edge conditions can be given either in terms of forces or displacements. In the case when all these remaining boundary conditions are given in terms of forces, the problem of the membrane theory will be statically determinate (the stresses in the shell may be found independently of the displacements). However, if one of these boundary conditions is given in terms of displacements, the problem of the membrane theory is statically indeterminate.

In one particular case, all the boundary conditions for the membrane can be formulated in terms of the displacements. The rigid clamping of the edges of such a shell corresponds to the conditions

$$u = v = 0$$

which must be satisfied on every edge.

§ 22. The conditions for the existence of the membrane state of stress

It has been established in the previous section that one of the sources of contradiction in the membrane theory stems from the fact that the solutions of this last theory may not be subjected to the general boundary conditions of § 11.

The membrane may not be loaded along its edges by transverse forces or moments. The angles of twist and the normal displacements at its edges may not be constrained. Finally, it is necessary to give on its edges boundary conditions (in terms of displacements) which will ensure appropriate bounds on the values of the pure bending displacements (which sometimes may prove to be impossible, cf. § 37). Violation of any of these requirements is equivalent to disturbing the membrane state of stress to a greater or lesser degree. However, while these requirements are necessary, they are not sufficient; in addition to these conditions, there are supplementary requirements without which the membrane state of stress may not exist.

Another source of contradiction in the membrane theory is the fact that its equations determine the forces in the shell without dependence on the compatibility relations for the middle surface [equations (5.1)]. This also leads to violations of a greater or smaller magnitude. If the form of the shell and its surface loading are smooth, so that the derivatives of R_1, R_2, δ, q_1, q_2, q_n with respect to α_1 and α_2 are continuous, then it is sufficient for the purpose of satisfying the compatibility conditions to assume the presence of small bending moments and normal shear forces which are such that they may be neglected in the equilibrium equations of the shell element. This will be different if the curvature of the shell, its thickness or its loading exhibit at some sections sudden variations. Under these circumstances the displacements in the membrane theory will behave in the same manner, thus essentially violating the continuity of the middle surface. For this purpose, in order to satisfy the conditions of continuity, one must assume the presence of large normal shear stresses and moments in the regions of the stated sections which is equivalent to a rejection of the use of the membrane theory (in these particular regions of the shell). It may be expected that this conclusion remains in force in those cases where the radii of curvature, the thickness or the loading on the shell, while not being discontinuous, change sufficiently abruptly at certain sections.

In particular, it follows from this that a membrane may not be loaded by concentrated forces, perpendicular to its middle surface. The state

of stress in a shell loaded by such forces will involve moments (at least in the neighbourhoods of the points of application of these forces).

Summarizing the above results, it should again be emphasized that the existence of the membrane state of stress is connected with the necessity of satisfying a number of conditions relating to the shape of the shell, the character of the load applied and the attachment of its edges. Since these conditions are sufficiently numerous one would think that the membrane theory must deviate a great deal in particular cases (from the general shell theory). Nevertheless, the membrane theory is of great practical importance. Above all, its value is determined by the technical advantage of the membrane state of stress (from the point of view of the uniformity of the utilization of the material of the shell).

In view of this, the planning of a design consisting of shells should always give a great deal of consideration to the fulfillment of the requirements of the membrane theory. However, in this direction the possibilities are limited by a number of circumstances — in particular, by constructional and technological considerations. Thus, for example, (from the point of view of satisfying the requirements of the membrane theory) the most advantageous shapes for reservoirs subject to large external or internal pressures are closed surfaces of sufficiently smooth form (sphere, ellipsoid with small eccentricity). However, it would seem unlikely that one could design a fire tube steam-boiler in one of the above stated shapes, since they are from all other points of view (except from the consideration of strength) unsuitable for this type of structure.

As another example, it may be said that (from the point of view of satisfying the requirements of the membrane theory) the most convenient method of production of metallic shells is casting, since in this way the designer has at his disposal many possibilities of joining shells with all accompanying details. Casting likewise permits variation of the thickness of the shell according to any law, increasing it where large stresses are expected and decreasing it where the stresses are smaller. However, the casting of very thin structures which have large dimensions is very difficult and in certain cases presents an insoluble technological problem. In view of this situation, casting is relatively rarely used for manufacturing shells. Quite often use is made of manufacturing processes such as pressing, forging and rolling, although these methods offer fewer possibilities than casting with regard to the choice of the form and the smoothness of the transitions between the components of the shell.

However, all this does not alter the fact that the struggle with bending stresses is one of the most important problems facing the designer of shells. If he does not succeed in eliminating these stresses completely,

he must aim at localizing them and limiting their magnitude. He must also be in a position to correctly evaluate the forces in those regions of the shell where bending occurs. Thus, the solution given by the membrane theory must in many cases be supplemented by a solution of the equations of the bending theory in those parts of the shell where bending proves to be important. Such a combination of the bending and membrane theories is one of the important ideas on the basis of which the majority of the problems of shell theory are being solved at the present time.

Hence, practical interest will even attach to a study based on the membrane theory of such problems for which not all the requirements of that theory can be satisfied (for example, the analysis of pressure vessel heads, of thin cylindrical roofs, of shells subject to concentrated forces, etc.).

In conclusion, it should be noted that the role played by the membrane theory in the general theory of shells may be compared with that of the theory of the velocity potential of an ideal fluid in hydrodynamics. Potential flow is not realized exactly in practice, but, starting from this concept, there have been deduced many important practical results of hydrodynamics. The combination of the theories of ideal and viscous fluids (by use of the concept of the boundary layer) has some similarity (as a method of approach) with the above combination of the membrane and bending theories.

§ 23. The membrane theory of shells of revolution of arbitrary shape

Consider a shell the middle surface of which is a surface of revolution. For such a shell the lines of principal curvature are its meridians and parallel circles (the lines of intersection of the surface with the meridian planes and the planes perpendicular to the axis). Accordingly, one may take as the principal curvilinear co-ordinates of the middle surface the angle θ (between the normal to the middle surface and the axis of the shell) and the angle φ determining the position of a point on the corresponding parallel circle (Fig. 12).

Let R_1 be the radius of curvature of the meridian. The second radius of curvature R_2 will always be the length of the intercept of the normal to the middle surface between this surface and the axis of the shell, since, considering two adjacent points on the same parallel circle, the normals from these points intersect on the axis of the shell.

The element of arc of a meridian will be given by

$$ds_1 = R_1 d\theta,$$

whence follows

$$A_1 = R_1. \tag{23.1}$$

Correspondingly, the element of arc of a parallel circle is given by

$$ds_2 = R_2 \sin\theta\, d\varphi,$$

and therefore

$$A_2 = R_2 \sin\theta. \tag{23.2}$$

Thus, the middle surface of a shell of revolution is completely determined by knowledge of its two principal radii of curvature R_1, R_2 which



Fig. 12.



$EB = R_2$; $DB = R_2 \sin\theta$

$AC - DB = \Delta(R_2 \sin\theta)$

$(AC - DB) : \cos\theta = AB$; $AB = R_1 \Delta\theta$

$$\frac{\Delta(R_2 \sin\theta)}{\Delta\theta} = R_1 \cos\theta$$

Fig. 13.

will obviously be functions of only one of the curvilinear coordinates, namely θ.

The first two of the relations of Gauss-Codazzi (§ 2) are in this case satisfied identically, while the third gives

$$\frac{dR_2 \sin\theta}{d\theta} = R_1 \cos\theta. \tag{23.3}$$

The necessity for the existence of this differential relationship between the radii of curvature of shells of revolution is clear from the simple calculations reproduced underneath Fig. 13.

Substituting in the general differential equations of the membrane theory (20.2) for A_1, A_2 their values from (23.1) and (23.2) and taking

into consideration the differential relation (23.3), one will have

$$\frac{1}{R_1}\frac{\partial T_1^*}{\partial\theta}+\frac{\operatorname{cotan}\theta}{R_2}(T_1^*-T_2^*)+\frac{1}{R_2\sin\theta}\frac{\partial S^*}{\partial\varphi}+q_1=0,$$

$$\frac{1}{R_1}\frac{\partial S^*}{\partial\theta}+2\frac{\operatorname{cotan}\theta}{R_2}S^*+\frac{1}{R_2\sin\theta}\frac{\partial T_2^*}{\partial\varphi}+q_2=0, \tag{23.4}$$

$$\frac{T_1^*}{R_1}+\frac{T_2^*}{R_2}=q_n,$$

where the q_1, q_2 and q_n are the projections of the surface loading on the tangent to the meridian, on the tangent to the parallel circle and on the normal to the middle surface (Fig. 12).

Solving the third of the above equations for T_2^* and substituting the value so found into the remaining two equations, one finds

$$\frac{1}{R_1}\frac{\partial T_1^*}{\partial\theta}+\left(\frac{1}{R_1}+\frac{1}{R_2}\right)\operatorname{cotan}\theta T_1^*+\frac{1}{R_2\sin\theta}\frac{\partial S^*}{\partial\varphi}=q_n\operatorname{cotan}\theta-q_1,$$

$$\frac{1}{R_1}\frac{\partial S^*}{\partial\theta}+2\frac{\operatorname{cotan}\theta}{R_2}S^*-\frac{1}{R_1\sin\theta}\frac{\partial T_1^*}{\partial\varphi}=-q_2-\frac{1}{\sin\theta}\frac{\partial q_n}{\partial\varphi}. \tag{23.5}$$

Introducing instead of T_1^* and S^* the new unknowns

$$U^*=T_1^*R_2\sin^2\theta,$$
$$V^*=S^*R_2^2\sin^2\theta, \tag{23.6}$$

and taking into consideration (23.3) for purposes of differentiation, the system (23.5) reduces to the form

$$\frac{R_2^2\sin\theta}{R_1}\frac{\partial U^*}{\partial\theta}+\frac{\partial V^*}{\partial\varphi}=(q_n\cos\theta-q_1\sin\theta)R_2^3\sin^2\theta,$$

$$\frac{\partial V^*}{\partial\theta}-\frac{R_2}{\sin\theta}\frac{\partial U^*}{\partial\varphi}=-\left(q_2\sin\theta+\frac{\partial q_n}{\partial\varphi}\right)R_1R_2^2\sin\theta. \tag{23.7}$$

Further, eliminating the unknown V^*, one arrives at the following partial differential equation of second order in the single unknown U^*:

$$\frac{1}{R_1R_2\sin\theta}\frac{\partial}{\partial\theta}\left[\frac{R_2^2\sin\theta}{R_1}\frac{\partial U^*}{\partial\theta}\right]+\frac{1}{R_1\sin^2\theta}\frac{\partial^2U^*}{\partial\varphi^2}=F(\theta,\varphi), \tag{23.8}$$

where

$$F(\theta,\varphi)=\frac{1}{R_1R_2\sin\theta}\frac{\partial}{\partial\theta}[(q_n\cos\theta-q_1\sin\theta)R_2^3\sin^2\theta]+$$
$$+R_2\left(\frac{\partial^2q_n}{\partial\varphi^2}+\frac{\partial q_2}{\partial\varphi}\sin\theta\right). \tag{23.9}$$

Thus, the determination of the stresses in a shell of revolution by means of the membrane theory is reduced to the solution of the differential equation (23.8).

It will now be shown that the determination of the displacements leads in this case to the study of an analogous equation. For shells of revolution, the system (20.3) may be written

$$R_1\varepsilon_1 = \frac{\partial u}{\partial \theta} + w = \frac{R_1}{E\delta}(T_1^* - \mu T_2^*),$$

$$R_2\varepsilon_2 = \frac{1}{\sin\theta}\frac{\partial v}{\partial \varphi} + u\operatorname{cotan}\theta + w = \frac{R_2}{E\delta}(T_2^* - \mu T_1^*), \tag{23.10}$$

$$R_2\omega = \frac{R_2}{R_1}\frac{\partial v}{\partial \theta} - v\operatorname{cotan}\theta + \frac{1}{\sin\theta}\frac{\partial u}{\partial \varphi} = \frac{2R_2(1+\mu)}{E\delta}S^*.$$

Eliminating from these equations w and taking into consideration the third of the equations (23.4), one has

$$\frac{\partial u}{\partial \theta} - u\operatorname{cotan}\theta - \frac{1}{\sin\theta}\frac{\partial v}{\partial \varphi} = \frac{R_1^2+R_2^2+2\mu R_1R_2}{R_1}\frac{T_1^*}{E\delta} - \frac{R_2(R_2+\mu R_1)}{E\delta}q_n,$$

$$\frac{R_2}{R_1}\frac{\partial v}{\partial \theta} - v\operatorname{cotan}\theta + \frac{1}{\sin\theta}\frac{\partial u}{\partial \varphi} = \frac{2(1+\mu)}{E\delta}R_2S^*. \tag{23.11}$$

Introduce now instead of u and v the new variables

$$\xi = \frac{u}{\sin\theta}, \qquad \zeta = \frac{v}{R_2\sin\theta}. \tag{23.12}$$

Then the system (23.11) reduces to the form

$$\frac{\partial \xi}{\partial \theta} - \frac{R_2}{\sin\theta}\frac{\partial \zeta}{\partial \varphi} = \frac{R_1^2+R_2^2+2\mu R_1R_2}{R_1\sin\theta}\frac{T_1^*}{E\delta} - \frac{R_2(R_2+\mu R_1)}{E\delta\sin\theta}q_n,$$

$$\frac{R_2^2\sin\theta}{R_1}\frac{\partial \zeta}{\partial \theta} + \frac{\partial \xi}{\partial \varphi} = \frac{2(1+\mu)R_2}{E\delta}S^*. \tag{23.13}$$

Finally, eliminating ξ, one finds

$$\frac{1}{R_1R_2\sin\theta}\frac{\partial}{\partial \theta}\left[\frac{R_2^2\sin\theta}{R_1}\frac{\partial \zeta}{\partial \theta}\right] + \frac{1}{R_1\sin^2\theta}\frac{\partial^2\zeta}{\partial \varphi^2} = f(\theta, \varphi), \tag{23.14}$$

where

$$f(\theta, \varphi) = \frac{1}{R_1 R_2 \sin\theta}\left\{2(1+\mu)\frac{\partial R_2 S^*}{\partial\theta} - \frac{R_1^2+R_2^2+2\mu R_1 R_2}{R_1 \sin\theta}\frac{\partial T_1^*}{\partial\varphi} + \right.$$
$$\left. + \frac{R_2(R_2+\mu R_1)}{\sin\theta}\frac{\partial q_n}{\partial\varphi}\right\}\frac{1}{E\delta}. \quad (23.15)$$

Denoting now by $B(\ldots)$ the differential operator

$$B(\ldots) = \frac{1}{R_1 R_2 \sin\theta}\frac{\partial}{\partial\theta}\left[\frac{R_2^2 \sin\theta}{R_1}\frac{\partial(\ldots)}{\partial\theta}\right] + \frac{1}{R_1 \sin^2\theta}\frac{\partial^2(\ldots)}{\partial\varphi^2}, \quad (23.16)$$

the equations (23.8) and (23.14) can be written in the form

$$\begin{aligned} B(U^*) &= F(\theta, \varphi), \\ B(\zeta) &= f(\theta, \varphi). \end{aligned} \quad (23.17)$$

Thus, the determination of the stresses as well as of the displacements in the membrane theory of shells of revolution leads to the study of essentially one and the same differential equation, so that, having solved the first part of the problem, it is always possible to solve its second part.

§ 24. Method of solution of the differential equations of the membrane theory of shells of revolution

Consider a shell of revolution bounded by one or two parallel circles (Fig. 14). In this case, the components of the surface loading as well as those of the edge loading will be periodic functions of the angle φ (with period 2π) as a result of the closed character of the shell with respect to the stated curvilinear coordinate. Hence, the components of the arbitrary surface loading can be represented in the form of the series



Fig. 14.

$$q_1 = \sum_{k=0}^{\infty}(q_{1,k}\cos k\varphi + q'_{1,k}\sin k\varphi),$$
$$q_2 = \sum_{k=0}^{\infty}(q'_{2,k}\cos k\varphi + q_{2,k}\sin k\varphi), \quad (24.1)$$
$$q_n = \sum_{k=0}^{\infty}(q_{n,k}\cos k\varphi + q'_{n,k}\sin k\varphi),$$

the coefficients of which (being functions only of the angle θ) are determined in any particular case by the known formulae of the theory of Fourier Series. Therefore, in order to analyze shells of revolution loaded in an arbitrary manner, it is sufficient to consider

loadings of the form

$$\begin{aligned} q_1 &= q_{1,k} \cos k\varphi, \\ q_2 &= q_{2,k} \sin k\varphi, \\ q_n &= q_{n,k} \cos k\varphi, \end{aligned} \tag{24.2}$$

since knowing the solution for this particular case, one may always by use of the series (24.1) obtain the solution for any other distributed loading.

Substitute (24.2) into (23.9) and seek the solution of the differential equation (23.8) in the form

$$U^* = U_k^* \cos k\varphi, \tag{24.3}$$

where U_k^* is a function of θ only. Then, dividing the equation (23.8) by the trigonometric term $\cos k\varphi$, one obtains for the determination of U_k^* the ordinary, second order differential equation

$$\frac{1}{R_1 R_2 \sin\theta} \frac{d}{d\theta}\left[\frac{R_2^2 \sin\theta}{R_1} \frac{dU_k^*}{d\theta}\right] - \frac{k_2}{R_1 \sin^2\theta} U_k^* = F_k(\theta), \tag{24.4}$$

where

$$F_k(\theta) = \frac{1}{R_1 R_2 \sin\theta} \frac{d}{d\theta}[(q_{n,k}\cos\theta - q_{1,k}\sin\theta) R_2^3 \sin^2\theta] - \\ - k(kq_{n,k} - q_{2,k}\sin\theta) R_2. \tag{24.5}$$

Integrating this equation and then using the formulae (23.6), (23.7) and (23.4), one arrives at the following expressions for the stresses:

$$T_1^* = T_{1,k}^* \cos k\varphi, \quad T_2^* = T_{2,k}^* \cos k\varphi, \quad S^* = S_k^* \sin k\varphi, \tag{24.6}$$

in which $T_{1,k}^*$, $T_{2,k}^*$, S_k^* are known functions of θ [including two constants of integration, entering into the general solution of the equation (24.4)]. Substituting these expressions and also those for q_n as given by (24.2) into (23.15), one obtains the function $f(\theta, \varphi)$ in the form

$$f(\theta, \varphi) = f_k(\theta) \sin k\varphi, \tag{24.7}$$

where

$$f_k(\theta) = \frac{1}{E\delta} \frac{1}{R_1 R_2 \sin\theta}\left\{2(1+\mu)\frac{dR_2 S_k^*}{d\theta} + \right. \\ \left. + k\frac{R_1^2 + R_2^2 + 2\mu R_1 R_2}{R_1 \sin\theta} T_{1,k}^* - k\frac{R_2(R_2 + \mu R_1)}{\sin\theta} q_{n,k}\right\}. \tag{24.8}$$

Introducing (24.7) on the right hand side of the second of the equations (23.17), its solution will be sought in the form

$$\zeta = \zeta_k(\theta) \sin k\varphi. \tag{24.9}$$

Then the following second order, ordinary differential equation is obtained for the determination of $\zeta_k(\theta)$:

$$\frac{1}{R_1 R_2 \sin\theta} \frac{d}{d\theta}\left[\frac{R_2^2 \sin\theta}{R_1} \frac{d\zeta_k}{d\theta}\right] - \frac{k^2}{R_1 \sin^2\theta}\zeta_k = f_k(\theta). \tag{24.10}$$

This last equation is identical with the equation (24.4) from which it differs only by the free term on the right hand side.

After finding $\zeta_k(\theta)$ and then using the formulae (23.12) and (23.10), it is possible to obtain the following expressions for the displacements:

$$u = u_k(\theta) \cos k\varphi, \quad v = v_k(\theta) \sin k\varphi, \quad w = w_k(\theta) \cos k\varphi, \tag{24.11}$$

in which u_k, v_k, w_k are known functions of θ, including four constants of integration: two coming from the general solution of the equation (24.4) entering into the right hand side of the equation (24.10), two from the integration of the equation (24.10).

Hence, in order that the solution will be unique, there must be given on each of the two parallel circles bounding the shell two boundary conditions. Out of the total number (four) of conditions, at least two conditions must be given in terms of displacements, in order to eliminate the possibility of pure bending of the shell, and also its displacement as a rigid body. The remaining two conditions may be given in terms of stresses or displacements.

As will become clear later on, in the particular case when the shell is closed at the top and when, therefore, there is only one edge (dome), half the arbitrary constants disappear from the general solutions of the equations (24.4) and (24.10) (since the functions multiplied by these constants will become infinite at the top of the shell).

For this purpose, one has to retain in the formulae for the stresses (24.6) altogether one arbitrary constant and in the formulae for the displacements (24.11) only two arbitrary constants. In correspondence with this, on the only edge of a shell which is closed at the top there must be prescribed two conditions, at least one of which must be formulated in terms of displacements.

§ 25. Symmetrical deformation of shells of revolution

Consider the particular case when the edge and surface loadings do not depend on the angle φ. Then also the deformation of the shell is

independent of this angle, i.e., it will be symmetrical about the axis of the shell. This case is obtained from the series (24.1) by omitting there all terms but the first, corresponding to $k = 0$. In this way, one will have

$$q_1 = q_{1,0}(\theta), \quad q_2 = q_{2,0}(\theta), \quad q_n = q_{n,0}(\theta). \tag{25.1}$$

In order to avoid in what follows the multiple subscripts, the left notation in (25.1) will be used in preference to that on the right, where q_1, q_2, q_n will be understood to be certain functions of the angle θ only.

The partial differential equations (23.7) for this particular case become the two independent ordinary differential equations

$$\begin{aligned} \frac{dU^*}{d\theta} &= (q_n \cos\theta - q_1 \sin\theta) R_1 R_2 \sin\theta, \\ \frac{dV^*}{d\theta} &= -q_2 R_1 R_2^2 \sin^2\theta, \end{aligned} \tag{25.2}$$

which may be integrated to give

$$\begin{aligned} U^* &= C_1 + \int_{\theta''}^{\theta} (q_n \cos\theta - q_1 \sin\theta) R_1 R_2 \sin\theta \, d\theta, \\ V^* &= C_2 - \int_{\theta''}^{\theta} q_2 R_1 R_2^2 \sin^2\theta \, d\theta, \end{aligned} \tag{25.3}$$

where C_1 and C_2 are constants of integration and the lower integration limit θ'' can be chosen arbitrarily, to suit computational convenience. This angle usually will be identified with the angle corresponding to one of the edges of the shell (Fig. 14).

Having found the auxiliary functions U^*, V^*, it is possible to write down at once, on the basis of the formulae (23.6), expressions for the stresses S^*, T_1^*

$$\begin{aligned} S^* &= \frac{C_2}{R_2^2 \sin^2\theta} - \frac{1}{R_2^2 \sin^2\theta} \int_{\theta''}^{\theta} q_2 R_1 R_2^2 \sin^2\theta \, d\theta, \\ T_1^* &= \frac{C_1}{R_2 \sin^2\theta} + \frac{1}{R_2 \sin^2\theta} \int_{\theta''}^{\theta} (q_n \cos\theta - q_1 \sin\theta) R_1 R_2 \sin\theta \, d\theta, \end{aligned} \tag{25.4}$$

and also, on the basis of the third equation (23.4), an expression for the

stress T_2^*

$$T_2^* = q_n R_2 - \frac{C_1}{R_1 \sin^2\theta} - \frac{1}{R_1 \sin^2\theta}\int_{\theta''}^{\theta} (q_n \cos\theta - q_1 \sin\theta) R_1 R_2 \sin\theta \, d\theta. \tag{25.5}$$

It follows from these formulae that the components of symmetrical surface loading q_n, q_1 cause only direct stresses T_1^*, T_2^* in the shell, while the component q_2 causes only shear stresses.

It is readily understood that the first of the formulae (25.4) corresponds to the torsion of the shell about its axis. If for this purpose q_2 is equal to zero, the shell will be twisted by edge forces only. Let the shear force S'' act on the edge $\theta = \theta''$. Then the first of the formulae (25.4) with $q_2 = 0$ gives the following law of variation of the shear stress in the shell:



Fig. 15.

$$S^* = \frac{(R_2'' \sin\theta'')^2}{R_2^2 \sin^2\theta} S''. \tag{25.6}$$

It will be noted that

$$2\pi (R_2'' \sin\theta'')^2 S'' = \mathfrak{M}, \tag{25.7}$$

where $\mathfrak{M}$ is the moment, twisting the shell about its axis.

Hence, in a shell of revolution, the shear stress due to torsion by moments, applying to its edges, is given by

$$\sigma_t = \frac{S^*}{\delta} = \frac{\mathfrak{M}}{2\pi\delta R_2^2 \sin^2\theta} = \frac{\mathfrak{M}}{2\delta\Omega}, \tag{25.8}$$

where Ω is the area of the parallel circle along which the stress is being considered.

Great practical interest attaches to another variation of the symmetrical deformation of shells of revolution, in fact, to the case when the shell is deformed by symmetrical loadings q_1, q_n causing in it only direct stresses. This second case must be employed in the analysis of domes and reservoirs, and in future, when using the term "symmetrical deformation of shells of revolution", it will in fact refer to this case.

Given the stress $T_1^* = T_1''$ on the edge $\theta = \theta''$, one can find the constant C_1 in the second of the formulae (25.4)

$$C_1 = T_1'' R_2'' \sin^2\theta''. \tag{25.9}$$

Hence the second of the formulae (25.4) and the formula (25.5) may be written

$$T_1^* = \frac{R_2'' \sin^2\theta''}{R_2 \sin^2\theta} T_1'' + \frac{1}{R_2 \sin^2\theta} \int_{\theta''}^{\theta} (q_n \cos\theta - q_1 \sin\theta) R_1 R_2 \sin\theta \, d\theta,$$

$$T_2^* = q_n R_2 - \frac{R_2'' \sin^2\theta''}{R_1 \sin^2\theta} T_1'' - \frac{1}{R_1 \sin^2\theta} \int_{\theta''}^{\theta} (q_n \cos\theta - q_1 \sin\theta) R_1 R_2 \sin\theta \, d\theta. \tag{25.10}$$

These last formulae completely determine the state of stress in symmetrically deformed shells of revolution (on the basis of the membrane theory). It will be noted that the first of these formulae may be obtained if the shell shown in Fig. 15 and subjected to surface loads $q_1(\theta)$, $q_n(\theta)$ and forces T_1'' along the upper edge is cut by an arbitrary plane parallel to the upper edge and if one sets equal to zero the sum of the projections on the axis of the shell of all forces acting on its severed part. Thus, this formula is the condition for the equilibrium of an element of shell which has finite dimensions. The requirement for satisfying this condition uniquely determines in the case under consideration all forces in the shell down to its lower edge, as soon as the loading on the upper edge is given.

In conclusion, it will be observed that in the particular case when the shell has only one edge, it being closed at the top $\theta'' = 0$ (dome without opening, Fig. 12), the formulae (25.10) take the form

$$T_1^* = \frac{1}{R_2 \sin^2\theta} \int_0^{\theta} (q_n \cos\theta - q_1 \sin\theta) R_1 R_2 \sin\theta \, d\theta,$$

$$T_2^* = q_n R_2 - \frac{1}{R_1 \sin^2\theta} \int_0^{\theta} (q_n \cos\theta - q_1 \sin\theta) R_1 R_2 \sin\theta \, d\theta. \tag{25.11}$$

§ 26. The membrane theory of domes

As an example of the application of the formulae derived in the previous section, several different forms of domes will now be compared from the point of view of the membrane theory. For these calculations, it will be assumed that the domes are loaded by their own weight. The components of this loading for a dome of arbitrary form are given by (Fig. 16)

$$q_1 = q \sin\theta, \quad q_n = -q \cos\theta, \tag{26.1}$$

where q is the weight of the dome per unit area of its surface.



Fig. 16.

Substituting these expressions for q_1 and q_n into the formulae (25.11), one finds

$$T_1^* = -\frac{q}{R_2 \sin^2\theta}\int_0^\theta R_1 R_2 \sin\theta\, d\theta,$$

$$T_2^* = -qR_2\cos\theta + \frac{q}{R_1\sin^2\theta}\int_0^\theta R_1 R_2 \sin\theta\, d\theta. \tag{26.2}$$

These results will now be applied to shells the radii of curvature of which are given by the formulae

$$R_1 = \frac{R_0}{(1+\gamma\sin^2\theta)^{3/2}}, \qquad R_2 = \frac{R_0}{(1+\gamma\sin^2\theta)^{1/2}}. \tag{26.3}$$

These radii of curvature correspond to surfaces, generated by rotation of second order curves about their axis of symmetry; thus, one obtains

for $\gamma = 0$, spheres,
for $\gamma = -1$, paraboloids,
for $\gamma > -1$, ellipsoids,
for $\gamma < -1$, hyperboloids.

The parameter R_0 is equal to the value of the radius of curvature for $\theta = 0$, i.e., for the vertex of the dome. Substituting (26.3) into (26.2) and carrying out the integration, the following expressions for the forces T_1^*, T_2^* are obtained:

for the spherical dome

$$T_1^* = -\frac{qR_0}{1+\cos\theta}, \quad T_2^* = -qR_0\left(\cos\theta - \frac{1}{1+\cos\theta}\right); \tag{26.4}$$

for the parabolic dome

$$T_1^* = -\frac{qR_0}{3}\left(\frac{1}{\cos^2\theta} + \frac{1}{1+\cos\theta}\right),$$
$$T_2^* = -qR_0\left[1 - \frac{1}{3}\left(1 + \frac{\cos^2\theta}{1+\cos\theta}\right)\right]; \tag{26.5}$$

for the elliptic dome

$$T_1^* = -\frac{qa}{2}\,\frac{\sqrt{1-\varepsilon^2\cos^2\theta}}{\sin^2\theta}\left\{\frac{(1-\cos\theta)(1+\varepsilon^2\cos\theta)}{1-\varepsilon^2\cos^2\theta}+\right.$$

$$\left.+\frac{1-\varepsilon^2}{\varepsilon}\ln\left[\sqrt{\frac{1+\varepsilon}{1-\varepsilon}}\sqrt{\frac{1-\varepsilon\cos\theta}{1+\varepsilon\cos\theta}}\right]\right\}, \qquad (26.6)$$

$$T_2^* = -\frac{qa\cos\theta}{\sqrt{1-\varepsilon^2\cos^2\theta}} - \frac{1-\varepsilon^2\cos^2\theta}{1-\varepsilon^2}\,T_1^*.$$

In the last two formulae, 'a' is the horizontal semi-axis of the ellipse (the radius of the base of the dome) and ε its eccentricity, so that

$$\varepsilon^2 = 1 - \frac{b^2}{a^2} = \frac{\gamma}{1+\gamma}.$$

These results will now be used to compare the four different domes, shown in Fig. 17:

Dome I is spherical ($R_0 = R = 1.25r$);

Dome II is parabolic ($R_0 = r$);

Dome III is elliptic ($R_0 = 2r$, $\varepsilon^2 = 0.75$);

Dome IV is also elliptic, but differs from Dome III in that it is not formed by half an ellipsoid, but by a smaller part of it, since the tangent to the meridian of the dome along its edge is not vertical ($R_0 = 1.625r$, $\varepsilon^2 = 0.6$).

All four domes have the same height ($h = \frac{1}{2}r$) and cover the same area (radius r). The weight q likewise will be assumed to be the same for the four shells.

In Fig. 17, the variations of the forces T_1^*, T_2^* with the height of the domes are shown. They were calculated from the formulae (26.4), (26.5), (26.6), and have been graphed to the same scale. It follows from these curves that, from the point of view of the magnitude of the stresses, the greatest advantage is offered by that dome which has the smallest radius of curvature at the apex, i.e., the parabolic dome. From the same point of view, the least advantageous dome is the elliptic dome III. However, these are not the only factors which are essential for the choice of the form of a dome. The dome must be such that the bending in the shell will be unimportant. In order to remove bending, it is necessary that the line of support of the dome must assimilate the

load acting on it and for this purpose its deformation must coincide with the circumferential lengthening of the shell in accordance with the membrane theory. Only under these conditions will the membrane state of stress prevail and the calculations correspond to reality (§ 20).



Fig. 17.

Let the forces acting along the edge of the dome be resolved into two components, acting vertically and horizontally respectively. The vertical component Q_z will be transmitted to the wall on which the dome rests, while the assimilation of the horizontal component Q_x requires a special structural element, called a thrust ring (Fig. 18).

If one compares the domes under consideration from the point of view

of the required thrusts, one arrives at the following results:

$$Q_{x\mathrm{I}} = 0.375qR,$$
$$Q_{x\mathrm{II}} = 0.487qR,$$
$$Q_{x\mathrm{III}} = 0.$$
$$Q_{x\mathrm{IV}} = 0.190qR,$$

where R is the radius of the spherical dome.



Fig. 18.

Thus, the thrust ring of the largest area would be required for dome II which, from this point of view, will be the least advantageous design. Dome III does not require a ring at all. However, its shape has the essential defect that it leads to considerable hoop stresses near the edge of the shell. Among the materials used for thin domes is reinforced concrete which is much weaker in tension than in compression. In view of this, if the shell of shape III is selected, it has to be constructed with variable thickness, the thickness increasing toward the edge. Further, attention should be drawn to the fact that in shell II the hoop force T_2^* does not change its sign along the whole of the meridian, it being compressive everywhere. But since the thrust ring absorbing the loading Q_x will be stretched, it is evident in this case that the deformation of the support ring cannot be arranged to be the same as that of the edge of the shell (since they are of opposite sign). In the domes I, III and IV, the hoop forces change sign from compression at the apex of the dome to tension near the edge. The horizontal circles on which the change of sign of the circumferential force occurs will be called the 'line of transition'. The presence of a line of transition in a shell is favourable in the sense that for similar domes the sign of the circumferential stress will coincide with that of the stress in the support ring. Hence the area of the section of the support ring may be selected in such a way that the stretching of the edge of the shell will be equal to that of the support ring.

The stress in the support ring may be calculated by use of the formula

$$\sigma_k = \frac{Q_x r}{\Omega_k} = -\frac{T_1^0 r}{\Omega_k}\cos\theta_0, \tag{26.7}$$

where

T_1^0 is the value of the force T_1^* at the edge of the shell,

r is the radius of the support ring (approximately equal to the radius of the edge of the shell),

Ω_k is the sectional area of the support ring,

θ_0 is the angle corresponding to the edge of the shell.

Hence the hoop stress at the edge of the dome will be equal to

$$\sigma = -\frac{T_2^0}{\delta}. \tag{26.8}$$

Further, let Young's modulus of the material of the support ring be equal to E_k and that of the material of the shell equal to E. As a rule, Poisson's ratio for reinforced concrete is assumed to be equal to zero. Then, comparison of the extension of the edge of the shell and of the support ring leads to the formula

$$-\frac{T_1^0 r}{E_k \Omega_k} \cos\theta_0 = \frac{T_2^0}{E\delta}, \tag{26.9}$$

whence one obtains for the required area of the cross-section of the support ring

$$\Omega_k = -\frac{E}{E_k}\frac{T_1^0}{T_2^0} r\delta \cos\theta_0. \tag{26.10}$$

It follows from this formula that the area of the cross section of the support ring, necessary for the dome to be in a membrane state of stress, is proportional to $\frac{T_1^0}{T_2^0}$, i.e., to the ratio of the meridional and the hoop forces at the edge of the shell.

As is seen from the graphs in Fig. 17, this ratio is very large for shell I and hence a very rigid support ring is required. In this sense, the more advantageous shape is exhibited by the dome IV, since it has a sufficiently steep edge ($\cos\theta_0$ is relatively small) and the quantity $-\frac{T_1^0}{T_2^0}$ is less than unity.

With respect to the domes, shown in Fig. 17, the following final assessments may be given:

Dome I is uneconomical, since it requires a very stiff support ring;

Dome II is unacceptable, since there is no transition line and therefore the hoop force at its edge will have the same sign as at the apex. Formula (26.10) gives a negative value for Ω_k which physically corresponds to it being impossible to find a dome of this shape which is stressed in agreement with the membrane theory;

Dome III does not require a support ring, but considerable tensile hoop

stresses act in the neighbourhood of its support, so that the thickness of the shell must be increased there;

Dome IV is suitable, since it may be placed in a membrane state of stress by use of a support ring of relatively small stiffness.

Thus, dome IV is the most acceptable design of the four types under consideration. Other equally or even more acceptable shapes are possible and it is clear from the above discussion what criteria must be used to compare the shapes of domes.

Sometimes domes are spherical and in order to obtain a sufficiently high transition line and a sufficiently steep tangent at the edge of the shell one has to resort near the support to a transition arc by gradually diminishing the radius of curvature of the meridian. For details regarding this problem the reader is referred to the book [66].

§ 27. The membrane theory of pressure vessels

As a second example, consider the application of the membrane theory to the stress analysis of pressure vessels and their caps.

In this case, the loading will be uniform normal pressure

$$q_n = p = \text{constant},$$

the other components of the loading being equal to zero.

Substituting this loading into the formulae (25.10), one finds

$$T_1^* = T_1'' \frac{R_2'' \sin^2\theta''}{R_2 \sin^2\theta} + \frac{p}{R_2 \sin^2\theta} \int_{\theta''}^{\theta} R_1 R_2 \sin\theta \cos\theta \, d\theta =$$

$$= T_1'' \frac{R_2'' \sin^2\theta''}{R_2 \sin^2\theta} + \frac{p}{R_2 \sin^2\theta} \int_{\theta''}^{\theta} R_2 \sin\theta \, d(R_2 \sin\theta) =$$

$$= \frac{pR_2}{2} + \frac{C}{R_2 \sin^2\theta}, \tag{27.1}$$

$$T_2^* = -\frac{R_2}{R_1} T_1^* + pR_2 = \frac{pR_2}{2}\left(2 - \frac{R_2}{R_1}\right) - \frac{C}{R_1 \sin^2\theta},$$

where

$$C = (T_1'' - \tfrac{1}{2}pR_2'')R_2'' \sin^2\theta''. \tag{27.2}$$

Consider first a vessel having the form of a complete sphere. Then

$R_1 = R_2 = R = \text{constant}$ and the formulae (27.1) give

$$T_1^* = \frac{pR}{2} + \frac{C}{R\sin^2\theta}, \quad T_2^* = \frac{pR}{2} - \frac{C}{R\sin^2\theta}. \tag{27.3}$$

The constant C in this case must necessarily be set equal to zero, since otherwise the solution would become infinite at the points $\theta = 0$, $\theta = \pi$ (which belong to the complete sphere).

Hence one obtains

$$T_1^* = T_2^* = \frac{pR}{2} = \text{const.} \tag{27.4}$$

Thus the complete thin-walled sphere, loaded by uniform internal pressure, is found to be in a state of uniform tension. (For external pressure, the stresses would change sign and instead of uniform tension one would obtain uniform compression). Hence it appears that the complete sphere is the ideal form for a shell loaded by uniform normal pressure (in the sense of uniform utilization of the material). However, reservoirs of this form are relatively rarely used, mainly due to the difficulty experienced in the manufacture of complete spherical shells. (Since no section of a sphere can be developed on to the plane, the complete sphere must be composed of a large number of segments, each of which must be bent beforehand in a suitable manner).

A much more convenient shape from the point of view of production as well as from other considerations (for example, dimensional) is exhibited by cylindrical reservoirs, closed by lids of one shape or other. The larger part of the surface of such vessels is developable and, as a consequence, it can be bent from plane sheets. The ends which represent a relatively small part of the surface of the reservoir and which as a rule are very curved, can without difficulty be manufactured by forging or rolling using a matrix.



Fig. 19.

The membrane theory will now be applied to composite shells consisting of a cylinder and two ends. For this purpose, the cylinder and the cap will be treated separately and in this way the possibility of joining

given shells without violation of the requirements of the membrane theory will be explained. Applying the formulae (27.1) to the cylindrical part of the vessel, i.e., letting there

$$R_1 = \infty,\ R_2 = r = \text{const},\ \theta = \theta'' = \frac{\pi}{2},$$

one obtains

$$T_1^* = T_1'',\ T_2^* = pr. \tag{27.5}$$

The force T_1'' is determined from the condition that the axial forces stretching the reservoir must be equal to the resultant force due to the pressure acting on the ends of the vessel. Therefore

$$T_1^* = T_1'' = p\frac{\pi r^2}{2\pi r} = \frac{pr}{2}, \tag{27.6}$$

$$T_2^* = pr.$$

Thus, by the membrane theory, the cylindrical part of the pressure vessel is stretched by constant forces:

in the longitudinal direction

$$T_1^* = \frac{pr}{2}, \tag{27.7}$$

in the circumferential direction

$$T_2^* = pr.$$



Fig. 20.

As regards the forces arising in the ends of the vessel, their magnitude and distribution will depend on the shape of the ends.

Three of the most commonly used types of pressure vessel caps are shown in Fig. 20, namely, caps of the spherical, elliptical and composite types. The last one is formed by a combination of toroidal and spherical shells.

Applying the formulae (27.1) to the spherical cap, one obtains

$$T_1^* = T_2^* = \frac{pR}{2}. \tag{27.8}$$

In other words, by the membrane theory, the spherical end is subject to uniform tensile forces $T^* = \frac{pR}{2}$.

Consider now the cylindrical shell to which the spherical end is attached. It is seen from Fig. 20 that in joining these two shells one of the basic conditions for the existence of the membrane state of stress has been violated; namely, the force

$$Q_x = T_1^* \cos\theta_0 = \frac{pR}{2}\cos\theta_0, \tag{27.9}$$

may be transferred to the cylindrical shell only by shearing forces $\left(\text{cf. below for the case } \theta_0 = \frac{\pi}{2}\right)$. Hence it is clear that the stresses actually arising in vessels of the above type will differ from the stresses which follow from the membrane theory, since it is impossible to neglect the bending in the neighbourhood of the joints between spherical and cylindrical shells.

Next, the formulae (27.1) will be applied to the elliptical end for which (cf. the previous section) the radii of curvature are given by the expressions

$$R_1 = \frac{r(1+\gamma)^{1/2}}{(1+\gamma\sin^2\theta)^{3/2}}, \quad R_2 = \frac{r(1+\gamma)^{1/2}}{(1+\gamma\sin^2\theta)^{1/2}}. \tag{27.10}$$

Hence

$$\begin{aligned} T_1^* &= \frac{pR_2}{2} = \frac{pr}{2}\,\frac{(1+\gamma)^{1/2}}{(1+\gamma\sin^2\theta)^{1/2}}, \\ T_2^* &= \frac{pR_2}{2}\left(2 - \frac{R_2}{R_1}\right) = \frac{pr}{2}\,\frac{1-\gamma\sin^2\theta}{(1+\gamma\sin^2\theta)^{1/2}}(1+\gamma)^{1/2}, \end{aligned} \tag{27.11}$$

where $\gamma = \dfrac{r^2}{h^2} - 1$, h being the height of the cap and r the radius of the reservoir.

Studying now the junction between the cylindrical and elliptical shell, it is seen that in this case there is no radial component at the edge of the cap $\left(\text{i.e., at } \theta = \frac{\pi}{2}\right)$ and therefore the cap of elliptical form does not demand the presence of shearing forces at the edge of the cylindrical shell. Thus, in this case, one of the conditions for the existence of the membrane state of stress is fulfilled.

However, in addition, the hoop forces in the cylindrical and elliptical shells must be equal along their junction (in order to ensure the continuity of the circumferential deformations).

Comparing the force at the edge of the cylinder

$$T_2^* = pr$$

with the force on the edge of the ellipsoidal shell

$$T_2^* = \frac{pr}{2}(1 - \gamma),$$

it appears that they will only be equal for $\gamma = -1$, i.e., for $\frac{h}{r} \to \infty$, a case which is of no practical interest. Thus, although the ellipsoidal cap violates the requirements of the membrane theory to a lesser degree than the spherical cap, in this case also not all the conditions for the existence of the membrane state of stress can be fulfilled.

For most elliptical caps the height is half the radius of the vessel. In this case $\gamma = 3$ and the hoop forces at the edge of the cap are $T_2^* = -pr$, i.e., equal in value and opposite in sign to the hoop force at the edge of the cylindrical part of the reservoir. Hence, for this choice of dimensions of the cap, bending moments will occur;



Fig. 21.

Table 1

θ_0	0	5	10	15	20	25	30	35	40	45	50
$T_1^* : pr$	1.000	0.988	0.960	0.912	0.860	0.810	0.756	0.709	0.669	0.634	0.603
$T_2^* : pr$	1.000	0.968	0.875	0.732	0.559	0.381	0.165	0.087	−0.161	−0.317	−0.459

θ_0	55	60	65	70	75	80	85
$T_1^* : pr$	0.576	0.555	0.539	0.524	0.514	0.506	0.502
$T_2^* : pr$	−0.581	−0.693	−0.787	−0.863	−0.925	−0.966	−0.977

however, they will not be large (cf. § 59), so that the sum of the stresses due to direct forces and moments in the cap and the cylindrical part of the reservoir will only slightly differ from that given by the membrane theory, i.e., it will be close to

$$\sigma = \frac{pr}{\delta}.$$

Table 1 gives the values for T_1^*, T_2^* in the elliptical cap as calculated from (27.11), using $\gamma = 3$. These results are shown graphically in Fig. 21.

The composite cap is characterized by the radius r of its base, the transverse radius (radius of the meridian of the torus) r_0, the radius R and the marginal angle θ_0 of the sphere. Since the joint between the sphere and the torus is to be smooth, the following relation must hold between these quantities (Fig. 22):

$$r - r_0 = (R - r_0) \sin \theta_0. \tag{27.12}$$

Denoting by ν the ratio of the height of the cap to the radius r of the cylinder, one finds

$$\nu = \frac{R - (R - r_0) \cos \theta_0}{r},$$

whence, using the previous formula, one can write

$$\frac{r_0}{R} = \frac{1 - \cos \theta - \nu \sin \theta_0}{\nu(1 - \sin \theta_0) - \cos \theta_0}. \tag{27.13}$$



Fig. 22.



Fig. 23.

This last formula gives the relationship between the radius of the torus and the radius of the sphere as a function of the marginal angle θ_0 and the relative height of the end.

The most frequently used case is $\nu = \frac{1}{2}$ when

$$\frac{r_0}{R} = \frac{2 - \sin\theta_0 - 2\cos\theta_0}{1 - \sin\theta_0 - 2\cos\theta_0}. \tag{27.14}$$

Fig. 23 shows four different composite caps having the same height ($\nu = \frac{1}{2}$) and different ratios $\frac{r_0}{R}$. In fact, the dimensions of the caps in Fig. 23 are

a) $R = 2r$, $r_0 = \frac{3}{8}r$, $\sin\theta_0 = \frac{5}{13}$;

b) $R = 1.5r$, $r_0 = 0.25r$, $\sin\theta_0 = 0.6$;

c) $R = 1.353r$, $r_0 = 0.1466r$, $\theta_0 = 45°$;

d) $R = 1.25r$, $r_0 = 0$, $\sin\theta_0 = 0.8$.

Thus, the spherical end is a special case of the composite end (for $r_0 = 0$).

Cap a) of Fig. 23 has the same radius of curvature of the meridian at the apex, cap b) the same radius of curvature of the meridian at the edge as the elliptical end with the same value of ν which, as has been stated above, corresponds to the optimal case.

Applying (27.1) to the torus and taking into consideration that in this case

$$R_1 = r_0,\ R_2 = \frac{r - r_0(1 - \sin\theta)}{\sin\theta} \tag{27.15}$$

and that the force T_1^* on the upper edge of the torus must (for equilibrium) be equal to the corresponding force at the edge of the sphere $\left(\text{i.e., } T_1 = \frac{pR}{2}\right)$, one will have

$$T_1^* = \frac{pR_2}{2} = \frac{pr}{2}\,\frac{1 - \frac{r_0}{r}(1 - \sin\theta)}{\sin\theta}, \tag{27.16}$$

$$T_2^* = \frac{pR_2}{2}\left(2 - \frac{R_2}{R_1}\right) = \frac{pr_0}{2} - \frac{p(r - r_0)^2}{2r_0\sin^2\theta}.$$

As regards the forces in the spherical part of the cap, they have been shown earlier to be equal to

$$T_1^* = T_2^* = \frac{pR}{2}. \tag{27.17}$$

Fig. 24 shows a typical distribution of the forces along the meridian of the composite end (according to the membrane theory). It may be verified from the above formulae that the conditions for the existence of the membrane state of stress may not be completely satisfied either at the joint between the torus and the cylinder or at the joint between the torus and the sphere. In fact, it turns out to be impossible to ensure continuity of the circumferential deformations along the above mentioned joints between the shells for any relations between the dimensions of the composite cap. Thus composite ends must be analysed by use of a theory which takes bending into consideration.



Fig. 24.

Summing up the above results, it may be established that all the caps of the types discussed here fail to satisfy the requirements of the membrane theory to a greater or lesser degree. This result has general importance and it may be stated that it is impossible to design cylindrical pressure vessels which are in a membrane state of stress. (It will be noted that in the previous section, when dealing with domes, the opposite conclusion was reached).

Therefore the stress analysis of such reservoirs must take into account bending; however, as will be shown later, this fact only partly invalidates the above results, since these enter into the refined theory of pressure vessels as an essential part of the solution.

§ 28. Shells of uniform strength

As can be seen from the formulae (25.10), the forces in a shell depend on its shape as well as on its external loading. There arises the question whether it is impossible to select the shape of a shell in such a manner that the forces T_1^*, T_2^* are equal to each other and constant at all points of the shell. Such a type of design (which may be called a shell of uniform strength) would exhibit above other advantages the uniform

utilization of the material, and as a consequence, all other conditions being equal, it would give the smallest weight. Two fundamental problems of the theory of shells of uniform strength will be considered below, namely:

1. Determination of the most advantageous shapes of reservoirs for the storage of liquids;

2. Determination of the most advantageous shapes of domes.

1. Examine first the case of a tank for the storage of oil or other fluids, starting from the principle of uniform strength. The loading in this case will be the hydrostatic pressure

$$q_n = p_0 + z\rho, \tag{28.1}$$

where p_0 is the pressure at the top of the reservoir and ρ is the specific gravity of the fluid. The z axis will be directed downwards along the axis of the reservoir with the origin at the top of the reservoir.

As a result of the symmetry of the loading, the unknown shape of the vessel will undoubtedly be that of a body of revolution. Letting in the equations (23.4)

$$q_1 = q_2 = S^* = 0, \quad T_1^* = T_2^* = T_0^* = \text{constant},$$

it is then found that the first two of these equations are satisfied identically, while the third assumes the form

$$\left(\frac{1}{R_1} + \frac{1}{R_2}\right) T_0 = p_0 + z\rho. \tag{28.2}$$

Using (23.3), one may write

$$\frac{1}{\cos\theta} \frac{d(R_2 \sin\theta)}{d\theta} = \frac{d(R_2 \sin\theta)}{d(\sin\theta)} = R_1, \tag{28.3}$$

or, introducing the new notation

$$x = R_2 \sin\theta, \ \xi = \sin\theta, \tag{28.4}$$

one arrives at

$$R_1 = \frac{dx}{d\xi}. \tag{28.5}$$

Substituting in (28.2) the values of R_1 and R_2 in terms of the new variables, one finds

$$T_0 \left(\frac{d\xi}{dx} + \frac{\xi}{x}\right) = p_0 + z\rho. \tag{28.6}$$

There remains to deduce the dependence between z, x and ξ. The

tangent of the angle between the normal to the shell and the z axis (i.e., the angle θ) will be equal to

$$\tan\theta = \frac{dz}{dx}.$$

Expressing $\tan\theta$ in terms of $\sin\theta$ and introducing ξ, one can write

$$\frac{dz}{dx} = \frac{\xi}{\sqrt{1-\xi^2}} \quad \text{for the interval } 0 \leqslant \theta \leqslant \frac{\pi}{2},$$

$$\frac{dz}{dx} = -\frac{\xi}{\sqrt{1-\xi^2}} \quad \text{for the interval } \frac{\pi}{2} \leqslant \theta \leqslant \pi.$$

Replacing z in these formulae by the expression (28.6), one obtains the two differential equations

$$\begin{aligned} &\frac{d^2\xi}{dx^2} + \frac{1}{x}\frac{d\xi}{dx} - \frac{\xi}{x^2} - \frac{\rho}{T_0}\frac{\xi}{\sqrt{1-\xi^2}} = 0, \\ &\frac{d^2\xi}{dx^2} + \frac{1}{x}\frac{d\xi}{dx} - \frac{\xi}{x^2} + \frac{\rho}{T_0}\frac{\xi}{\sqrt{1-\xi^2}} = 0, \end{aligned} \tag{28.7}$$

the first of which determines the shape of the meridian of the shell of uniform strength in the interval $0 \leqslant \theta \leqslant \frac{\pi}{2}$ (i.e., the shape of the upper part of the reservoir), the second the shape of the meridian in the interval $\frac{\pi}{2} \leqslant \theta \leqslant \pi$ (i.e., the shape of the lower part of the reservoir).

The equations (28.7) are non-linear and may only be integrated approximately. Replacing the absolute coordinates of the meridian of the shell x and z by the non-dimensional quantities

$$x_1 = \sqrt{\frac{\rho}{T_0}}\, x, \quad z_1 = \sqrt{\frac{\rho}{T_0}}\, z, \tag{28.8}$$

the formulae (28.6) and (28.7) are reduced to the form

$$\frac{d\xi}{dx_1} + \frac{\xi}{x_1} = \frac{p_0}{\sqrt{\rho T_0}} + z_1 = \lambda + z_1, \tag{28.9}$$

$$\begin{aligned} &\frac{d^2\xi}{dx_1^2} + \frac{1}{x_1}\frac{d\xi}{dx_1} - \left(\frac{1}{x_1^2} + \frac{1}{\sqrt{1-\xi^2}}\right)\xi = 0, \\ &\frac{d^2\xi}{dx_1^2} + \frac{1}{x_1}\frac{d\xi}{dx_1} - \left(\frac{1}{x_1^2} - \frac{1}{\sqrt{1-\xi^2}}\right)\xi = 0. \end{aligned} \tag{28.10}$$

It is now clear that the unknown shape of the shell is completely determined by the single non-dimensional parameter

$$\lambda = \frac{p_0}{\sqrt{T_0 \rho}}. \tag{28.11}$$

The purpose of the second parameter $\frac{\rho}{T_0}$ is to determine the dimensions of the shell, since its knowledge permits not only the calculation of the non-dimensional coordinates x_1, z_1, but also of the absolute coordinates x, z.

Fig. 25 shows a typical shape of the meridian of a shell of uniform strength. As is clear from this sketch, the reservoir has the shape of a drop in that it has a plane base on which it rests and which smoothly fits into the meridian.



Fig. 25.



Fig. 26.

That the unknown shape of the reservoir must exactly coincide with the form of a supported drop may be verified by taking into consideration that the surface tension of a liquid is constant, while the pressure inside a drop varies according to a hydrostatic law. Hence the equations deduced above are essentially the equations of the theory of capillarity, where they have been sufficiently well studied. In particular, equation (28.2) was obtained by Laplace and it is, as a rule, associated with his name.

No time will be devoted here to methods of analytic solution of the equations (28.9), (28.10). However, a simple graphical method due to Kelvin for determining the form of drops (or, what is the same thing, the shape of reservoirs of uniform strength) will be described.

In this method, the meridian of the drop is made up of a series of small arcs of circles, the radius of each of these circles being given by the following scheme. Let (Fig. 26) $R_1^1 = P_1M_1$ and $R_2^1 = P_1N_1$ be the magnitudes of the radii of curvature of the surface of the drop at the point P_1. Their knowledge permits construction of the arc of the circle P_1P_2 which will be very close to the corresponding element of the arc of the meridian of the drop. Next, the equation (28.2) will be written for the points P_1 and P_2,

$$\begin{aligned} \frac{1}{R_1'} + \frac{1}{R_2'} &= \frac{p_0}{T_0} + \frac{\rho}{T_0} z_1, \\ \frac{1}{R_1''} + \frac{1}{R_2''} &= \frac{p_0}{T_0} + \frac{\rho}{T_0} z_2, \end{aligned} \tag{28.12}$$

Here z_1, z_2 are the values of z at the points P_1, P_2 and R_1'', R_2'' are the values of the radii of curvature at the point P_2. On the basis of P_1P_2, one may now determine from the drawing the difference of the heights of the points P_1 and P_2 and likewise the radius $R_2'' = P_2N_2$.

Subtracting the first equation (28.12) from the second, one finds

$$R_1'' = \frac{1}{\frac{\rho}{T_0}(z_2 - z_1) + \frac{1}{R_1'} + \frac{1}{R_2'} - \frac{1}{R_2''}}. \tag{28.13}$$

By calculating the radius of curvature of the meridian at the point P_2 by means of this formula, one may construct the arc of the circle P_2P_3 (with centre at M_2 and $M_2P_2 = R_1''$), etc.

Denoting the distance $z_{i+1} - z_i$ by Δz and beginning the process of construction at the top of the reservoir, where

$$R_1 = R_2 = 2\frac{T_0}{p_0}, \tag{28.14}$$

one may thus draw step by step the entire meridian of the drop (Fig. 27). Fig. 28 shows the meridians of shells of uniform strength obtained for $\lambda = 0.5$, $\lambda = 1.0$, $\lambda = 2.0$. It is seen that a decrease in the value of the pressure at the top of the reservoir leads to a decrease of the height over width ratio. Two extreme cases will be noted: when $\lambda \to \infty$, the form of the reservoir approaches the form of a sphere, while for $\lambda \to 0$, the transverse dimension of the reservoir becomes infinitely large, so that in the limit the fluid is contained between two parallel walls.

The pressure at the top of the vessel of a considered shape must be maintained constant and equal to the calculated value, since otherwise



Fig. 28.



Fig. 27.



Fig. 29.

the shell will not be stressed uniformly and, besides, it may develop wrinkles. Fig. 29 shows a reservoir of uniform strength (constructed starting from the value $\lambda \approx 1.1$) with zero pressure at the top, in order to study the effect of the pressure. As is seen from the graphs in the same figure, the stress distribution in that shell is not at all uniform and near the plane base the forces tend to infinity which indicates that in this region there occurs appreciable bending. This is, of course, not taken into consideration by the membrane theory. Reservoirs having the shape of drops are sometimes used in practice.

2. As has already been mentioned, the basic loading for domes is ordinarily considered to be due to their weight. An attempt will now be made to select the shape of a dome, starting from the requirement that the stresses throughout the shell are to be constant.

The components of loading in this case will be

$$q_1 = q \sin \theta, \quad q_n = -q \cos \theta. \tag{28.15}$$

Putting in the equation (23.4)

$$T_1^* = T_2^* = T^*,$$

assuming besides that the deformation of the shell does not depend on the angle φ and that

$$S^* = q_2 = 0,$$

one will have

$$\begin{gathered} \frac{dT^*}{d\theta} = -qR_1 \sin \theta, \\ \left(\frac{1}{R_1} + \frac{1}{R_2}\right) T^* = -q \cos \theta. \end{gathered} \tag{28.16}$$

The essential difference between this and the preceding problem is that it is impossible to assume T^* to be constant, since then the first of the equations (28.16) cannot be satisfied.

Solving the second of these equations for R_1, one finds

$$R_1 = -\frac{R_2}{1 + \frac{q}{T^*} R_2 \cos \theta}. \tag{28.17}$$

At the same time, the relation (23.3) can be used to obtain a different expression for R_1 in terms of R_2, in fact,

$$R_1 = \frac{1}{\cos \theta} \frac{d(R_2 \sin \theta)}{d\theta}. \tag{28.18}$$

Comparing the equations (28.17) and (28.18), one obtains the differential equation

$$\frac{d(R_2 \sin\theta)}{d\theta} = -\frac{R_2 \cos\theta}{1 + \frac{q}{T^*} R_2 \cos\theta}, \tag{28.19}$$

which may be simplified by introduction of the new variable

$$x = R_2 \sin\theta \tag{28.20}$$

and by use of the formulae

$$q = \rho\delta, \quad T^* = \sigma\delta, \tag{28.21}$$

where ρ is the specific gravity of the material of the shell and σ is the stress in the shell under the action of the force T^*. Then one will have

$$\frac{dx}{d\theta} = -\frac{x}{\tan\theta + \frac{\rho}{\sigma} x}. \tag{28.22}$$

Since the stresses at all sections of the shell are equal, the ratio $\frac{\rho}{\sigma}$ will be constant. For this purpose, one has to consider the thickness δ of the shell to be variable in agreement with the second of the formulae (28.21) and the first of the equations (28.16).

Thus, in the present problem, a uniform stress field throughout the shell may not be achieved at the expense of the shape of the dome only; it is also necessary to select a suitable law of variation of the thickness of the shell along the meridian. This law can be found, if one introduces into the first of the equations (28.16) the values for q and T^* from (28.21).

Then one will have

$$\frac{d\delta}{d\theta} = -\frac{\rho}{\sigma} \delta R_1 \sin\theta, \tag{28.23}$$

whence

$$\ln\left(\frac{\delta}{\delta_0}\right) = -\frac{\rho}{\sigma} \int_0^\theta R_1 \sin\theta \, d\theta, \tag{28.24}$$

where δ_0 is the thickness of the shell at $\theta = 0$, i.e., at the apex of the dome. The integral on the right-hand side of the formula (28.24) has a

simple geometrical meaning, since the quantity

$$R_1 \sin\theta\, d\theta$$

is the projection of an element of arc of the meridian on the axis of the shell. Therefore

$$\int_0^\theta R_1 \sin\theta\, d\theta = z, \tag{28.25}$$

where z is the vertical coordinate of the point under consideration (the origin of z being at the apex of the dome). Thus the thickness of the shell must change according to the law

$$\delta = \delta_0 e^{-\frac{\varrho}{\sigma} z}. \tag{28.26}$$

The functional dependence of z on θ (determination of which is equivalent to finding the shape of the meridian of the dome) can be established by integration of the equation (28.22). Introducing for this purpose instead of the actual coordinates x and z of the meridian the non-dimensional coordinates

$$x_1 = -\frac{\rho}{\delta} x, \quad z_1 = -\frac{\rho}{\delta} z, \tag{28.27}$$

the equation (28.22) may be written in the form

$$\frac{dx_1}{d\theta} = -\frac{x_1}{\tan\theta - x_1}. \tag{28.28}$$

Integrating this equation, using the initial condition $\theta = 0$, $x_1 = 0$, one finds $x_1 = f(\theta)$; the second coordinate of the meridian of the dome can now be calculated from the formula

$$z_1 = -\frac{\rho}{\sigma} \int_0^\theta R_1 \sin\theta\, d\theta = \int_0^\theta \frac{dx_1}{d\theta} \tan\theta\, d\theta, \tag{28.29}$$

which is obtained by taking into consideration the expressions (23.3), (28.20), (28.25), and (28.27).

Thus, the determination of the non-dimensional coordinates of the meridian of the shell is reduced to the solution of the differential equation (28.28). Apparently this last integration can only be carried out approximately, as this has been done by G. Megareus [73] from whose paper

the following table has been taken:

Table 2

x_1	z_1	e^{z_1}	x_1	z_1	e^{z_1}
0.2	0.0100	1.0101	2.2	1.4138	4.1116
0.4	0.0402	1.0410	2.4	1.6320	5.6519
0.6	0.0910	1.0953	2.6	2.096	8.139
0.8	0.1632	1.1773	2.8	2.508	12.28
1.0	0.2580	1.2943	3.0	2.972	19.52
1.2	0.3768	1.4576	3.2	3.496	32.98
1.4	0.5216	1.6847	3.4	4.100	60.34
1.6	0.6946	2.0029	3.6	4.800	121.51
1.8	0.8988	2.4567	3.8	5.76	317.53
2.0	1.1374	3.1187	4.0	7.22	1365.5

It is clear from the above study that this table exhausts the problem under consideration, since the thickness of the shell δ is determined by (28.26) as a function of e^{z_1}. The form of the dome of uniform strength, constructed on the basis of Table 2, is shown in Fig. 30.

It follows from this sketch, and also directly from Table 2, that the thickness of the dome must be changed considerably along the meridian. For example, if the height of the dome is taken to be equal to half the radius of the base, the thickness at the edge of the shell must be approximately 2.5 times larger than the thickness at the apex. But if the height of the dome is made equal to the radius of the base, this ratio is raised to 20. Thus it is impossible to make the height of the dome too large if it is intended to avoid the necessity of a considerable change of the thickness of the shell. The dome then turns out to be too shallow and it leads to an appreciable thrust. Further, since a shell of the shape under consideration is subject to uniform compression at all points, it has, of course, no line of transition and therefore, as has been established in § 26, it is impossible to create for it the conditions necessary for the existence of the membrane state of stress. In view of this situation, the above shape of dome may be called "most advantageous" in a limited sense only. The shape is convenient from the point of view of the stress distribution at some distance from the edge, but it is quite useless from the point of



Fig. 30.

view of the possibility of ensuring the proper boundary conditions. But the last are very important and must always be taken into consideration in a dome design. Therefore a dome of the above type has, to the author's knowledge, not found practical application.

§ 29. "Wind" type loading (The case k = 1)

In the stress analysis of shells of revolution, the second place in practical importance (after symmetrical loading) belongs to external loads the components of which are given by the formulae

$$q_1 = q_{1,1} \cos \varphi, \quad q_2 = q_{2,1} \sin \varphi, \quad q_n = q_{n,1} \cos \varphi, \tag{29.1}$$

obtained from (24.2) for $k = 1$.

This loading is ordinarily said to be of the "wind type" since the wind pressure on a dome may, to a first approximation, be represented by components of the form (29.1). It will be shown that in the case of such loading (as for the symmetrical type) the equations of the membrane theory can be integrated by quadrature for shells of revolution of arbitrary shape.

The basic differential equation (24.4) takes in this case the form

$$\frac{1}{R_1 R_2 \sin\theta} \frac{d}{d\theta}\left[\frac{R_2^2 \sin\theta}{R_1} \frac{dU_1^*}{d\theta}\right] - \frac{1}{R_1 \sin^2\theta} U_1^* = F_1(\theta), \tag{29.2}$$

where

$$F_1(\theta) = \frac{1}{R_1 R_2 \sin\theta} \frac{d}{d\theta}\left[(q_{n,1}\cos\theta - q_{1,1}\sin\theta) R_2^3 \sin^2\theta\right] - \\ - R_2(q_{n,1} - q_{2,1}\sin\theta). \tag{29.3}$$

In this equation, the new auxiliary function

$$Y = U_1^* R_2 \sin\theta. \tag{29.4}$$

will now be introduced instead of U_1^*. Taking into consideration the relation (23.3), the equation (29.2) can then be rewritten

$$\frac{d}{d\theta}\left(\frac{1}{R_1 \sin\theta} \frac{dY}{d\theta}\right) = R_1 F(\theta), \tag{29.5}$$

so that Y can be determined by two successive integrations.

The first integration gives

$$\frac{1}{R_1 \sin\theta} \frac{dY}{d\theta} = \int R_1 F_1(\theta)\, d\theta = \\ = \int \frac{1}{R_2 \sin\theta} \frac{d}{d\theta}\left[(q_{n,1}\cos\theta - q_{1,1}\sin\theta) R_2^3 \sin^2\theta\right] d\theta - \\ - \int (q_{n,1} - q_{2,1}\sin\theta) R_1 R_2\, d\theta. \tag{29.6}$$

Further, integrating the right-hand side by parts, one finds

$$\frac{dY}{d\theta} = C_1 R_1 \sin\theta + \Phi R_1 \sin\theta, \tag{29.7}$$

where C_1 is an arbitrary constant,

$$\Phi = (q_{n,1}\cos\theta - q_{1,1}\sin\theta)R_2^2 \sin\theta - \\ - \int_{\theta''}^{\theta} (q_{n,1}\sin\theta + q_{1,1}\cos\theta - q_{2,1}) R_1 R_2 \sin\theta \, d\theta, \tag{29.8}$$

and the lower limit of integration θ'' can be fixed arbitrarily. In the further discussion, θ'' will be identified with the angle determining the upper edge of the shell (which in the general case will be bounded by two paralliel circles — Fig. 14).

The second integration now leads to

$$Y = C_2 + C_1 \int_{\theta''}^{\theta} R_1 \sin\theta \, d\theta + \int_{\theta''}^{\theta} \Phi R_1 \sin\theta \, d\theta, \tag{29.9}$$

where C_2 is another arbitrary constant.

Reverting now from Y to U_1^* and then, with the help of the formulae (24.3) and (23.6), from U_1^* to T_1^*, one finds

$$T_1^* = \frac{1}{R_2^2 \sin^3\theta}\left\{C_2 + C_1 \int_{\theta''}^{\theta} R_1 \sin\theta \, d\theta + \int_{\theta''}^{\theta} \Phi R_1 \sin\theta \, d\theta\right\} \cos\varphi = T^*_{1,1}\cos\varphi. \tag{29.10}$$

Further, the third equation (23.4) gives

$$T_2^* = \left\{q_{n,1}R_2 - \frac{1}{R_1 R_2 \sin^3\theta}\left[C_2 + C_1 \int_{\theta''}^{\theta} R_1 \sin\theta \, d\theta + \right.\right. \\ \left.\left. + \int_{\theta''}^{\theta} \Phi R_1 \sin\theta \, d\theta\right]\right\} \cos\varphi = T^*_{2,1}\cos\varphi. \tag{29.11}$$

Finally, the shear force S^* may be determined from the first equation (23.7)

$$\frac{\partial V^*}{d\varphi} = R_2^2 \sin^2\theta \frac{\partial S^*}{\partial\varphi} = -\frac{R_2^2 \sin\theta}{R_1}\frac{\partial U^*}{\partial\theta} + (q_n\cos\theta - q_1 \sin\vartheta) R_2^3 \sin^2\theta =$$

$$= \left[C_2 \operatorname{cotan}\theta - C_1 \left(R_2 \sin\theta - \operatorname{cotan}\theta \int_{\theta''}^{\theta} R_1 \sin\theta\, d\theta \right) - \Phi R_2 \sin\theta + \right.$$

$$\left. + (q_{n,1}\cos\theta - q_{1,1}\sin\theta) R_2^3 \sin^2\theta + \operatorname{cotan}\theta \int_{\theta''}^{\theta} \Phi R_1 \sin\theta\, d\theta \right] \cos\varphi. \quad (29.12)$$

Substituting here

$$S^* = S_1^* \sin\varphi,$$

one will have

$$S^* = \frac{\cos\theta}{R_2^2 \sin^3\theta} \left\{ C_2 - C_1 \left(R_2 \frac{\sin^2\theta}{\cos\theta} - \int_{\theta''}^{\theta} R_1 \sin\theta\, d\theta \right) - \Phi \frac{R_2 \sin^2\theta}{\cos\theta} + \right.$$

$$\left. + (q_{n,1}\cos\theta - q_{1,1}\sin\theta) \frac{R_2^3 \sin^3\theta}{\cos\theta} + \int_{\theta''}^{\theta} \Phi R_1 \sin\theta\, d\theta \right\} \sin\varphi =$$

$$= \left[T^*_{1,1}\cos\theta - \frac{C_1}{R_2 \sin\theta} + \chi(\theta) \right] \sin\varphi = S_1^* \sin\varphi, \quad (29.13)$$

where

$$\chi(\theta) = \frac{1}{R_2 \sin\theta} \int_{\theta''}^{\theta} (q_{n,1}\sin\theta + q_{1,1}\cos\theta - q_{2,1}) R_1 R_2 \sin\theta\, d\theta. \quad (29.14)$$

The two constants C_1 and C_2 in the obtained solution must be determined from given values of the forces T_1^* and S^* at the upper edge of the shell. Letting in the formulae (29.10) and (29.13) $\theta = \theta''$, one finds

$$\begin{aligned} C_2 &= (R_2'' \sin\theta'')^3 T^*_{1,1}, \\ C_1 &= T_{1,1}'' R_2'' \sin\theta'' \cos\theta'' - S_1'' R_2'' \sin\theta''. \end{aligned} \quad (29.15)$$

It follows from these formulae that for $\theta'' = 0$, i.e., if the dome does not have an opening at the apex,

$$C_1 = C_2 = 0.$$

By the way, all the formulae obtained in this section may likewise be deduced by cutting the shell along an arbitrary parallel circle and by considering the equilibrium of the severed part of the shell under the influence of all forces acting on it.

As an example for the above theory, the forces arising in a spherical dome

subject to wind pressure will be determined. The dome will be assumed to be a hemisphere and the wind pressure will be represented by the components

$$q_1 = q_2 = 0, \qquad q_n = -p \sin\theta \cos\varphi. \tag{29.16}$$

In other words, it will be assumed that the wind exerts only normal pressure which varies in such a manner that it vanishes at the apex of the dome and along the meridian determined by the plane perpendicular to the wind direction. The pressure attains its maximum on the windward side and its minimum on the leeward side (Fig. 31).



Fig. 31.

The formulae (29.16) may, of course, only be regarded as giving first approximations to the stresses due to wind loading; however, they are often used in practical calculations. For the determination of T_1^*, T_2^*, S^*, the formulae (29.10), (29.11) and (29.13) with C_1 and C_2 equal to zero may be used directly, since the dome is closed at the apex.

Letting in these formulae

$$R_1 = R_2 = R, \; q_{1,1} = q_{2,1} = 0, \; q_{n,1} = -p \sin\theta, \; \theta'' = 0,$$

one will have

$$T^*_{1,1} = -\frac{pR}{\sin^3\theta} \int_0^\theta \left[\cos\theta \sin\theta - \frac{(2+\cos\theta)(1-\cos\theta)^2}{3\sin\theta}\right] d\theta =$$

$$= -\frac{pR}{3} \frac{\cos\theta}{\sin^3\theta} (2+\cos\theta)(1-\cos\theta)^2, \tag{29.17}$$

$$S_1^* = -\frac{pR}{3} \frac{(2+\cos\theta)(1-\cos\theta)^2}{\sin^3\theta},$$

$$T^*_{2,1} = -pR\left[\sin\theta - \frac{\cos\theta}{3\sin^3\theta}(2+\cos\theta)(1-\cos\theta)^2\right].$$

Fig. 32 shows the dependence of the coefficients $T^*_{1,1}$, $T^*_{2,1}$, S_1^* on the height of the dome.



Fig. 32.

§ 30. The membrane theory of shells formed by rotation of curves of second order

It has been shown above that for $k = 0$ and $k = 1$ (i.e.,for symmetrical and 'wind' loadings) the equation (24.4) can be integrated by quadrature whatever the shape of the shell of revolution. For $k \geqslant 2$, this can no longer be done and for the study of the equation (24.4) one has to consider R_1 and R_2 as functions of the angle θ. Under this condition, attempts at obtaining closed solutions have been unsuccessful for the majority of shells and one has had to be satisfied with series type solutions (cf., for example, [63]). Some space will be devoted here to one family of shells for which the equation (24.4) may be integrated in closed form for any values of k; namely, to the family of shells formed by rotation of second order curves about an axis of symmetry. As has already been stated in § 26, the radii of curvature of such shells are expressed by the formulae

$$R_1 = \frac{R_0}{(1 + \gamma \sin^2 \theta)^{3/2}}, \quad R_2 = \frac{R_0}{(1 + \gamma \sin^2 \theta)^{1/2}}, \tag{30.1}$$

whence it follows that in the present case

$$\frac{R_2^3}{R_1} = R_0^2 = \text{constant}. \tag{30.2}$$

In order to use (30.2), let the equation (24.4) be written in the form

$$\frac{R_2^2 \sin\theta}{R_1} \frac{d}{d\theta}\left[\frac{R_2^2 \sin\theta}{R_1} \frac{dU_k^*}{d\theta}\right] - k^2 \frac{R_2^3}{R_1} U_k^* = F_k(\theta) R_2^3 \sin^2\theta. \tag{30.3}$$

Introduce now the new argument ξ, connected with θ by the relation

$$\xi = \int_{\frac{\pi}{2}}^{\theta} \frac{R_1 \, d\theta}{R_2^2 \sin\theta} = \frac{1}{R_0} \int_{\frac{\pi}{2}}^{\theta} \frac{d\theta}{\sin\theta \sqrt{1 + \gamma \sin^2\theta}} =$$

$$= \frac{1}{R_0} \ln\left(\frac{\sqrt{1+\gamma}\sin\theta}{\sqrt{1 + \gamma \sin^2\theta} + \cos\theta}\right). \tag{30.4}$$

Then one finds for the shells under consideration

$$\frac{d^2U_k^*}{d\xi^2} - k^2R_0^2U_k^* = F_k(\theta)R_2^3\sin^2\theta. \tag{30.5}$$

Now it is known from the theory of linear differential equations that the general solution of the equation (30.5) may be obtained as the sum of any of its particular integrals and of the general solution of the homogeneous equation

$$\frac{d^2U_k^*}{d\xi^2} - k^2R_0^2U_k^* = 0. \tag{30.6}$$

Further, if the solution of the homogeneous equation has been found, one may determine the particular solution by means of the method of variation of parameters. Therefore, the present investigation will be limited to the equation (30.6).

Its general solution is

$$U_k^* = C_1e^{kR_0\xi} + C_2e^{-kR_0\xi}, \tag{30.7}$$

which after replacement of ξ by its value (30.4) becomes

$$U_k^* = B_1\left[\frac{\sin\theta}{\sqrt{1+\gamma\sin^2\theta}+\cos\theta}\right]^k + B_2\left[\frac{\sqrt{1+\gamma\sin^2\theta}+\cos\theta}{\sin\theta}\right]^k, \tag{30.8}$$

where B_1 and B_2 are other constants of integration, differing from the previous constants by some factors.

Further, proceeding from the auxiliary function U_k^* to the forces $T^*_{1,k}$, one finds, using (23.6),

$$T^*_{1,k} = \frac{1}{R_0}\,\frac{\sqrt{1+\gamma\sin^2\theta}}{\sin^2\theta}\left[B_1\left(\frac{\sin\theta}{\sqrt{1+\gamma\sin^2\theta}+\cos\theta}\right)^k + \right.$$
$$\left. + B_2\left(\frac{\sqrt{1+\gamma\sin^2\theta}+\cos\theta}{\sin\theta}\right)^k\right], \tag{30.9}$$

after which the remaining forces in the shell may be determined with help of the formulae of § 23.

It is important to note that both integration constants in (30.9) will be non-zero only when the shell has two boundaries, i.e., when the shell has the shape of a belt. When the shell is closed at the top, one has to set $B_2 = 0$ in the solution obtained above, in order to exclude from it that part of the solution which becomes infinite for $\theta = 0$. If, however, the shell is completely closed so that its middle surface contains the point $\theta = 0$ as well as the point $\theta = \pi$, then one has to set both the

constants of integration in (30.9) equal to zero. In this last case, the particular solution of the equation (30.5) which remains finite at the stated two points will simultaneously be the solution of the problem under consideration.

The meaning of the process of omitting arbitrary constants from the solution is completely explained by the decrease in the number of boundaries, since this decrease is accompanied by a corresponding reduction in the number of boundary conditions. For complete shells without any boundaries, the presence of arbitrary constants in the solutions is unnecessary.

§ 31. The membrane theory of spherical shells.

The shells considered in the previous section include spherical shells as a special case (corresponding to $\gamma = 0$). For this case, the equation (24.4) takes the form

$$\frac{d^2U_k^*}{d\theta^2} + \operatorname{cotan}\theta \frac{dU_k^*}{d\theta} - \frac{k^2}{\sin^2\theta} U_k^* =$$

$$= \frac{R_0^2}{\sin\theta} \frac{d}{d\theta} [(q_{n,k}\cos\theta - q_{1,k}\sin\theta)\sin^2\theta] - kR_0^2(kq_{n,k} - q_{2,k}\sin\theta) \quad (31.1)$$

and, by (30.8), the solution of the homogeneous equation

$$\frac{d^2U_k^*}{d\theta^2} + \operatorname{cotan}\theta \frac{dU_k^*}{d\theta} - \frac{k^2}{\sin^2\theta} U_k^* = 0 \quad (31.2)$$

will be

$$U_k^* = B_1 \tan^k \frac{\theta}{2} + B_2 \operatorname{cotan}^k \frac{\theta}{2}, \quad (31.3)$$

By use of this solution, the general solution of the equation (31.1) may be found by the method of variation of parameters. However, in many cases, this general solution may be obtained in a simpler manner, starting from the following information.

Consider the differential equation

$$\frac{d^2Z}{d\theta^2} + \operatorname{cotan}\theta \frac{dZ}{d\theta} - \frac{k^2}{\sin^2\theta} Z + n(n+1)Z = 0. \quad (31.4)$$

The functions satisfying this equation are called spherical harmonics and there are two distinct types, the functions $P_n^k(\cos\theta)$ which are of the first order and are finite at $\theta = 0$, and the functions $Q_n^k(\cos\theta)$ which are of the second order and become infinite at $\theta = 0$.

Hence, the general solution of the differential equation (31.4) may be written in the form

$$Z = C_1 P_n^k + C_2 Q_n^k. \tag{31.5}$$

Assuming now the right-hand side of the equation (31.1) to be replaced by the series

$$F_k = \sum_n \alpha_n P_n^k, \tag{31.6}$$

this equation may be rewritten

$$\frac{d^2 U_k^*}{d\theta^2} + \operatorname{cotan}\theta \frac{dU_k^*}{d\theta} - \frac{k^2}{\sin^2\theta} U_k^* = \sum_n \alpha_n P_n^k. \tag{31.7}$$

It is now readily verified that, in view of the fact that the functions P_n^k obey the equation (31.4), a particular solution of (31.7) will be given by

$$U_k^* = -\sum_n \frac{\alpha_n}{n(n+1)} P_n^k, \tag{31.8}$$

whence it is clear that in all those cases where the right-hand side of the equation (31.8) involves a finite or an infinite number of spherical harmonics, a particular integral of this equation can be written down immediately.

For integral values of the indices n and k, the functions P_n^k can be expressed in terms of trigonometric functions. The corresponding formulae can be found, for example, in the second part of the 'Tables of Special Functions' by Y. N. Shpilrein. In this manner, one may often without special difficulty select an expression of the form (29.6) for a given $F_k(\theta)$, cf., the example at the end of § 33.

§ 32. The analysis of domes, resting on columns

As an example of the application of the theory presented in § 30, consider the analysis of an elliptical dome resting on a number of equidistant supports instead of on a continuous foundation. Let the number of supports be n and the width of each support be determined by the angle φ_0 (see Fig. 33). Let the shell be loaded by its own weight.



Fig. 33.

Although the components of this loading do not depend on the angle φ, nevertheless the stress distribution in the shell will in this case be a function of θ as well as φ, since the last angle enters into the formulation of the boundary conditions. Assuming that the pressure acting on each support is uniformly distributed, one obtains the distribution of the force T_1 at the edge of the shell, shown in Fig. 34 (where the edge of the shell is shown as a straight line). The force T_1^0 will be equal to the weight of the dome divided by the number of supports and their width, i.e.,

$$T_1^0 = \frac{Q}{nr\varphi_0}. \tag{32.1}$$

Between the supports, the boundary stress T_1 will vanish. This step function type of distribution of the edge loading will now be represented



Fig. 34.

by a Fourier series in φ. Using the known formulae of the theory of these series, one finds

$$T_1 = \frac{T_1^0}{2\pi}\left\{n\varphi_0 + 4\sum_{m=1}^{\infty}\frac{(-1)^m}{m}\sin\left(\frac{mn}{2}\varphi_0\right)\cos(mn\varphi)\right\}. \tag{32.2}$$

This formula holds true for $\theta = 90°$.

On the other hand, the force T_1^* in a shell having the shape of an ellipsoid can be represented in the form

$$T_1^* = T^*_{1,0} + \sum_{k=1}^{\infty} T^*_{1,k}\cos(k\varphi), \tag{32.3}$$

where $T^*_{1,0}$ is the solution obtained in § 26 for the dome on a continuous foundation and $T^*_{1,k}$ is the solution of the equation (30.6), given in § 30.

Since the dome has no opening at the apex, one has to omit in (30.9) all terms which become infinite at $\theta = 0$. Then

$$T^*_{1,k} = B_k\frac{\sqrt{1+\gamma\sin^2\theta}}{\sin^2\theta}\left(\frac{\sin\theta}{\sqrt{1+\gamma\sin^2\theta}+\cos\theta}\right)^k, \tag{32.4}$$

where $\gamma = \dfrac{\varepsilon^2}{1-\varepsilon^2}$ (ε being the eccentricity of the ellipse). The values of the constants B_k in the series (32.3) must be determined by comparison of the coefficients of this series (for $\theta = 90°$) with the corresponding coefficients of the series (32.2).

Hence one finds

$$\frac{B_k}{(1+\gamma)^{\frac{mn-1}{2}}} = \frac{2}{\pi} T_1{}^0 \frac{(-1)^m}{m} \sin\left(\frac{mn}{2}\varphi_0\right), \tag{32.5}$$

or

$$B_k = B_{mn} = \frac{2}{\pi}(-1)^m \frac{(1+\gamma)^{\frac{mn-1}{2}}}{m} T_1{}^0 \sin\left(\frac{mn}{2}\varphi_0\right). \tag{32.6}$$

Thus, ultimately,

$$T_1{}^* = T^*{}_{1,0} + \frac{2}{\pi} T_1{}^0 \frac{\sqrt{1+\gamma\sin^2\theta}}{\sqrt{1+\gamma}\sin^2\theta} \sum_{m=1}^{\infty} \frac{(-1)^m}{m} \times$$

$$\times \left[\frac{\sqrt{1+\gamma}\sin\theta}{\sqrt{1+\gamma\sin^2\theta}+\cos\theta}\right]^{mn} \sin\left(\frac{nm}{2}\varphi_0\right)\cos(mn\varphi). \tag{32.7}$$

Further, using the equations of equilibrium for an element of a membrane, it is easy to obtain also expressions for the two other forces S^* and $T_2{}^*$,

$$T_2{}^* = T^*{}_{2,0} - \frac{2}{\pi} T_1{}^0 \frac{(1+\gamma\sin^2\theta)^{3/2}}{\sqrt{1+\gamma}\sin^2\theta} \sum_{m=1}^{\infty} \frac{(-1)^m}{m} \times$$

$$\times \left[\frac{\sqrt{1+\gamma}\sin\theta}{\sqrt{1+\gamma\sin^2\theta}+\cos\theta}\right]^{mn} \sin\left(mn\frac{\varphi_0}{2}\right)\cos(mn\varphi),$$

$$S^* = -\frac{2}{\pi} T_1{}^0 \frac{1+\gamma\sin^2\theta}{\sqrt{1+\gamma}\sin^2\theta} \sum_{m=1}^{\infty} \frac{(-1)^m}{m} \times \tag{32.8}$$

$$\times \left[\frac{\sqrt{1+\gamma}\sin\theta}{\sqrt{1+\gamma\sin^2\theta}+\cos\theta}\right]^{mn} \sin\left(mn\frac{\varphi_0}{2}\right)\sin(mn\varphi).$$

It will be noted that the convergence of the series (32.7), (32.8) becomes worse for larger θ. In this respect, their convergence depends on the quantity $\dfrac{n\varphi_0}{2\pi}$, i.e., on the ratio of the width of the supports to the distance between them, the convergence deteriorating as this ratio decreases.

For example, for

$$\frac{n\varphi_0}{2\pi} = \frac{1}{4},$$

one has to retain about 15 terms in order to obtain from the series (32.7) and (32.8) sufficiently accurate results near the edge of the shell.

A numerical example will now be considered using the data

$$n = 6, \quad \frac{n\varphi_0}{2\pi} = \frac{1}{4}, \quad \gamma = 3.$$

This value of γ corresponds to $\frac{h}{r} = \frac{1}{2}$, where h is the height of the dome and r the radius of the base.



Fig. 35.

Fig. 35 shows the distribution of the edge force T_1^*, obtained by substituting the above values in (32.2) and by retaining the first twenty terms (not counting those terms which are identically zero). The graph illustrates the convergence of the series (32.2).



Fig. 36.

Fig. 36 shows the graphs for the forces T_1^* and T_2^*, the curves II

referring to the meridian through the centre of a support, the curves III to the meridian through the centre between two supports. The curves I give the variation of these forces for a dome on a continuous foundation. It is clear from these graphs that the forces in a dome, resting on sufficiently many columns, differ only in the immediate neighbourhood of the edges to an appreciable degree from the corresponding forces in a dome on a continuous foundation. As the angle θ decreases and the apex of the dome is approached, the curves II and III tend asymptotically to the general limit, namely curve I.

	Θ	90°	80°	70°	60°	50°	40°	30°	20°	10°	0°	
$T_1 : qa$	Continuous support	—0.70	—0.66	—0.65	—0.66	—0.69	—0.74	—0.80	—0.89	—0.97	—1.00	I
	Dome on columns —centre of support	—2.76	—1.72	—1.24	—0.97	—0.85	—0.81	—0.83	—0.90	—0.97	—1.00	II
	Dome on columns —centre of span	0.00	—0.15	—0.28	—0.42	—0.54	—0.66	—0.77	—0.88	—0.97	—1.00	III
$T_2 : qa$	Continuous —support	2.76	2.48	2.01	1.58	1.11	0.63	0.09	—0.43	—0.84	—1.00	I
	Dome on columns —centre of support	11.05	6.56	4.14	2.58	1.56	0.79	0.14	—0.41	—0.84	—1.00	II
	Dome on columns centre of span	0.00	0.42	0.67	0.81	0.72	0.46	0.04	—0.45	—0.84	—1.00	III

§ 33. Affine transformations in the membrane theory

In the preceding sections, the membrane theory has been applied to shells of revolution and a general method of solution has been established, based on the expansion of the external loading and of all the forces in the shell in trigonometric series in terms of the angle φ. As was noted by F. Dischinger [68], this method may be used for the analysis of more complicated shells (for example, domes and caps which have oval planform).

Consider a shell of arbitrary form in a membrane state of stress under the influence of surface loadings q_1, q_2, q_n and the corresponding boundary forces. Let the Cartesian coordinates of its middle surface be x, y, z. Further, let there be obtained from this shell by means of a linear transformation another shell with the following coordinates of its middle surface:

$$\bar{x} = c_1 x, \quad \bar{y} = c_2 y, \quad \bar{z} = c_3 z, \tag{33.1}$$

where c_1, c_2, c_3 are constant coefficients.

It turns out that, if this second shell is loaded in a completely definite

manner (its load distribution being related to that of the first shell), all the forces in the second shell may be determined by a very simple calculation in terms of the forces in the first shell (which will be assumed known) instead of by solving again differential equations.

The relation between the loadings of the two shells, which must be satisfied so that the above procedure will be possible, will now be established.

For this purpose, consider a small right-angled element of the first shell, the sides of the element being lines of principal curvature of the surface. The sides of this element will then be given by

$$ds_1 = A_1 d\alpha_1, \quad ds_2 = A_2 d\alpha_2. \tag{33.2}$$

Denote the direction cosines of the angles between ds_1 and the axes x, y, z by l_1, l_2, l_3. Similarly denote by m_1, m_2, m_3 the direction cosines of the angles between ds_2 and the same axes.

To this element of the first shell there will correspond an element of the second shell with the sides

$$\begin{aligned} d\bar{s}_1 &= \sqrt{c_1^2 l_1^2 + c_2^2 l_2^2 + c_3^2 l_3^2}\, ds_1, \\ d\bar{s}_2 &= \sqrt{c_1^2 m_1^2 + c_2^2 m_2^2 + c_3^2 m_3^2}\, ds_2, \end{aligned} \tag{33.3}$$

which (in the general case) will no longer be right-angled. The cosine of the angle between the directions $d\bar{s}_1$, $d\bar{s}_2$ may be calculated from the formula

$$\cos(d\bar{s}_1, d\bar{s}_2) = \frac{c_1^2 l_1 m_1 + c_2^2 l_2 m_2 + c_3^2 l_3 m_3}{\sqrt{c_1^2 l_1^2 + c_2^2 l_2^2 + c_3^2 l_3^2}\cdot\sqrt{c_1^2 m_1^2 + c_2^2 m_2^2 + c_3^2 m_3^2}}. \tag{33.4}$$

All the internal and external forces acting on the element of the first shell will now be resolved in the directions x, y, z. Then the conditions for equilibrium of this element can be written as follows:

$$\begin{gathered} \Sigma X_j = 0, \quad \Sigma Y_j = 0, \quad \Sigma Z_j = 0, \\ \Sigma (y_j Z_j - z_j Y_j) = 0, \quad \Sigma (z_j X_j - x_j Z_j) = 0, \\ \Sigma (x_j Y_j - y_j X_j) = 0, \end{gathered} \tag{33.5}$$

where X_j, Y_j, Z_j denote the projections of a definite (internal or external) force acting on the element and x_j, y_j, z_j are the coordinates of its point of application. The summation extends over all internal and external forces.

Let the forces X_j, Y_j, Z_j of the first element correspond to forces $\bar{X}_j, \bar{Y}_j, \bar{Z}_j$ of the second element, applied to the points

$$\bar{x}_j = c_1 x_j, \quad \bar{y}_j = c_2 y_j, \quad \bar{z}_j = c_3 z_j. \tag{33.6}$$

Then the equilibrium conditions for the second element are

$$\Sigma \bar{X}_j = 0,\ \Sigma \bar{Y}_j = 0,\ \Sigma \bar{Z}_j = 0,$$
$$\Sigma (c_2 y_j \bar{Z}_j - c_3 z_j \bar{Y}_j) = 0,\ \Sigma (c_3 z_j \bar{X}_j - c_1 x_j \bar{Z}_j) = 0, \qquad (33.7)$$
$$\Sigma (c_1 x_j \bar{Y}_j - c_2 y_j \bar{X}_j) = 0,$$

from which it is clear that, if one lets

$$\bar{X}_j = X_j,\ \bar{Y}_j = Y_j,\ \bar{Z}_j = Z_j,$$

i.e., if one simply transfers the forces acting on the first element to the corresponding points of the second element without changing their magnitudes, then the last three equations (33.7) will remain unsatisfied.

But if one takes

$$\bar{X}_j = c_1 X_j,\ \bar{Y}_j = c_2 Y_j,\ \bar{Z}_j = c_3 Z_j, \qquad (33.8)$$

then fulfillment of the equilibrium conditions of the first element (33.5) will automatically ensure satisfaction of all the equilibrium conditions of the second element.

However, it must still be shown that the internal forces which will act in the second shell in accordance with (33.8) will be tangential to the middle surface (since the appearance of normal shearing forces would be equivalent to a violation of the membrane state of stress.)

Consider now the internal force $T_1 * ds_2$, acting on an element of the first shell in the direction ds_1. In transferring the force to the element of the second shell in agreement with (33.8), its components will be changed in the same manner as the components of ds_1. Therefore the internal force $\bar{T}_1 * d\bar{s}_2$ of the second element, corresponding to the force



Fig. 37.

$T_1^* ds_2$, will have the same direction as $d\bar{s}_1$, i.e., it will act tangentially to the middle of the second surface shell. This same reasoning may be repeated for all the forces and in this way it may be shown that the second shell for the above law of calculation of all external and internal forces will be in a membrane state of stress, provided this state of stress applies to the first shell.

There remains now to establish formulae giving the forces and the surface loading for the transition from the first to the second shell (or vice versa).

Fig. 37 shows an element of the first shell with the forces acting on it and the corresponding rhombic element of the second shell. The internal forces acting on this second element have components in the directions $d\bar{s}_1$, $d\bar{s}_2$. In this way, by the law of transition (33.8), one finds

$$\bar{T}_1^* d\bar{s}_2 = \sqrt{c_1^2 l_1^2 + c_2^2 l_2^2 + c_3^2 l_3^2}\, T_1^* ds_2. \tag{33.9}$$

Substituting here for ds_2 its value from the second of the formulae (33.3), one will have

$$\bar{T}_1^* = \frac{\sqrt{c_1^2 l_1^2 + c_2^2 l_2^2 + c_3^2 l_3^2}}{\sqrt{c_1^2 m_1^2 + c_2^2 m_2^2 + c_3^2 m_3^2}}\, T_1^*. \tag{33.10}$$

In a similar manner it can be shown that

$$\bar{T}_2^* = \frac{\sqrt{c_1^2 m_1^2 + c_2^2 m_2^2 + c_3^2 m_3^2}}{\sqrt{c_1^2 l_1^2 + c_2^2 l_2^2 + c_3^2 l_3^2}}\, T_2^*, \quad \bar{S}^* = S^*. \tag{33.11}$$

Further, denote by X, Y, Z the components in the directions x, y, z of the surface loading on the first shell and by $\bar{X}$, $\bar{Y}$, $\bar{Z}$ those on the second shell.

By (33.8), one will have the following formulae

$$\begin{aligned} \bar{X}\, d\bar{\Omega} &= c_1 X\, d\Omega, \\ \bar{Y}\, d\bar{\Omega} &= c_2 Y\, d\Omega, \\ \bar{Z}\, d\bar{\Omega} &= c_3 Z\, d\Omega, \end{aligned} \tag{33.12}$$

where $d\Omega$ is the area of an element of the middle surface of the first shell and $d\bar{\Omega}$ is the area of the corresponding element of the second shell.

Denote by n_1, n_2, n_3 the cosines of the angles between the normal to the middle surface of the first shell and the axes x, y, z. Then the quantity $n_1 d\Omega$ will be the projection of the area $d\Omega$ on the plane yz. Under the affine coordinate transformation, this area becomes $c_2 c_3 n_1 d\Omega$.

In a similar manner, the other two projections of $d\Omega$ may be transformed, as a result of which one obtains for $d\bar{\Omega}$ the expression

$$d\bar{\Omega} = \sqrt{c_2^2 c_3^2 n_1^2 + c_3^2 c_1^2 n_2^2 + c_1^2 c_2^2 n_3^2}\, d\Omega. \tag{33.13}$$

Taking this result into consideration, one finds the following final formulae for the calculation of the surface loading

$$\begin{aligned}
\bar{X} &= \frac{c_1}{\sqrt{c_2^2 c_3^2 n_1^2 + c_3^2 c_1^2 n_2^2 + c_1^2 c_2^2 n_3^2}} X, \\
\bar{Y} &= \frac{c_2}{\sqrt{c_2^2 c_3^2 n_1^2 + c_3^2 c_1^2 n_2^2 + c_1^2 c_2^2 n_3^2}} Y, \\
\bar{Z} &= \frac{c}{\sqrt{c_2^2 c_3^2 n_1^2 + c_3^2 c_1^2 n_2^2 + c_1^2 c_2^2 n_3^2}} Z.
\end{aligned} \tag{33.14}$$

The above results may be used (for membrane analysis) to replace a shell of one shape by one of another shape which permits the deduction of a number of interesting results by very simple means.

This information will now be applied to the problem of the stresses in an oval-shaped cap, loaded by uniform normal pressure p. For this purpose, it will be assumed that the cap is half an ellipsoid with semi-axes a, b and h (h being the height of the cap, $2a$ and $2b$ its length and width).

The analytic expressions for the middle surface of such a cap are

$$\begin{aligned}
\bar{x} &= a \sin\theta \cos\varphi, \\
\bar{y} &= b \sin\theta \sin\varphi, \\
\bar{z} &= h \cos\theta.
\end{aligned} \tag{33.15}$$

Further, consider the hemisphere given by

$$\begin{aligned}
x &= h \sin\theta \cos\varphi, \\
y &= h \sin\theta \sin\varphi, \\
z &= h \cos\theta.
\end{aligned} \tag{33.16}$$

Comparing the formulae (33.15) and (33.16), it is clear that the equations for the ellipsoidal cap may be obtained from those for the hemisphere by means of the linear coordinate transformation

$$c_1 = \frac{a}{h}, \quad c_2 = \frac{b}{h}, \quad c_3 = 1. \tag{33.17}$$

This result permits one to replace the calculation ofthe ellipsoidal cap by that of the hemispherical cap, loaded in a corresponding manner (Fig. 38).



Fig. 38.

Let the ellipsoidal cap be loaded by an external uniform normal pressure p and find the corresponding loading on the sphere.

The cosines of the angles between the normal to the ellipsoid and the axes x, y, z are given by

$$\cos(x,n) = \frac{c_2 \sin\theta\cos\varphi}{\sqrt{c_2^2\sin^2\theta\cos^2\varphi + c_1^2\sin^2\theta\sin^2\varphi + c_1^2c_2^2\cos^2\theta}},$$

$$\cos(y,n) = \frac{c_1 \sin\theta\sin\varphi}{\sqrt{c_2^2\sin^2\theta\cos^2\varphi + c_1^2\sin^2\theta\sin^2\varphi + c_1^2c_2^2\cos^2\theta}}, \qquad (33.18)$$

$$\cos(z,n) = \frac{c_1c_2\cos\theta}{\sqrt{c_2^2\sin^2\theta\cos^2\varphi + c_1^2\sin^2\theta\sin^2\varphi + c_1^2c_2^2\cos^2\theta}}.$$

Multiplying the pressure by these direction cosines, one obtains $\bar{X}$, $\bar{Y}$, $\bar{Z}$, i.e., the components in the x, y, z directions of the external loading on the ellipsoidal cap. Now the corresponding components for the sphere may be calculated from (33.14), where the cosines n_1, n_2, n_3 may be determined from (33.18) by letting there $c_1 = c_2 = 1$. Thus one will have

$$X = -p\frac{c_2}{c_1}\sin\theta\cos\varphi,\quad Y = -p\frac{c_1}{c_2}\sin\theta\sin\varphi,\quad Z = -pc_1c_2\cos\theta. \qquad (33.19)$$

Taking into consideration that the cosines between the directions

x, y, z and the unit vectors $\mathbf{e}_1$, $\mathbf{e}_2$, $\mathbf{e}_3$ (for the sphere) are given by (Fig. 39)

	x	y	z
$\mathbf{e}_1$	$\cos\theta\cos\varphi$	$\cos\theta\sin\varphi$	$-\sin\theta$
$\mathbf{e}_2$	$-\sin\varphi$	$\cos\varphi$	0
$\mathbf{e}_n$	$\sin\theta\cos\varphi$	$\sin\theta\sin\varphi$	$\cos\theta$

it is found that the uniform normal pressure on the ellipsoidal cap corresponds to a loading on the hemisphere with the components

$$q_1 = -\frac{p}{c_1c_2}(c_2^2\cos^2\varphi + c_1^2\sin^2\varphi - c_1^2c_2^2)\sin\theta\cos\theta,$$

$$q_2 = -\frac{p}{c_1c_2}(c_1^2 - c_2^2)\sin\theta\cos\varphi\sin\varphi, \tag{33.20}$$

$$q_n = -\frac{p}{c_1c_2}(c_2^2\sin^2\theta\cos^2\varphi + c_1^2\sin^2\theta\sin^2\varphi + c_1^2c_2^2\cos^2\theta).$$

This loading may be written in the form

$$\begin{aligned} q_1 &= q_{1,0} + q_{1,2}\cos 2\varphi, \\ q_2 &= q_{2,0} + q_{2,2}\sin 2\varphi, \\ q_n &= q_{n,0} + q_{n,2}\cos 2\varphi, \end{aligned} \tag{33.21}$$

where

$$\begin{aligned} q_{1,0} &= -\frac{p}{2c_1c_2}(c_1^2 + c_2^2 - 2c_1^2c_2^2)\cos\theta\sin\theta, \\ q_{2,0} &= 0, \\ q_{n,0} &= -\frac{p}{2c_1c_2}[(c_1^2 + c_2^2)\sin^2\theta + 2c_1^2c_2^2\cos^2\theta], \end{aligned} \tag{33.22}$$

$$\begin{aligned} q_{1,2} &= \frac{p}{2c_1c_2}(c_1^2 - c_2^2)\sin\theta\cos\theta, \\ q_{2,2} &= -\frac{p}{2c_1c_2}(c_1^2 - c_2^2)\sin\theta, \\ q_{n,2} &= \frac{p}{2c_1c_2}(c_1^2 - c_2^2)\sin^2\theta. \end{aligned} \tag{33.23}$$

Thus, the problem has been reduced to the analysis of a hemisphere subject to loading of the form (24.1) for the particular case when the series contains only those terms for which $k = 0$ and $k = 2$. These

two cases will now be considered separately:

(a) Determine the stresses caused in a hemisphere by the symmetrical loading (33.22).

Using for this purpose directly the formulae (25.11), one will have

$$T_{1,0}^* = -\frac{1}{h\sin^2\theta}\int_0^\theta ph^2c_1c_2\cos\theta\sin\theta\,d\theta = -\frac{phc_1c_2}{2},$$

$$T_{2,0}^* = q_{n,0}R_2 - T_{1,0}^*\frac{R_2}{R_1} = -\frac{ph}{2c_1c_2}[c_1^2c_2^2 + (c_1^2+c_2^2-2c_1^2c_2^2)\sin^2\theta]; \tag{33.24}$$

(b) Find the forces induced in a hemisphere by the loading (33.23). In this case, the differential equation (31.1) may be written

$$\frac{d^2U_2^*}{d\theta^2} + \operatorname{cotan}\theta\frac{dU_2^*}{d\theta} - \frac{4}{\sin^2\theta}U_2^* = -3ph^2\frac{c_1^2-c_2^2}{c_1c_2}\sin^2\theta. \tag{33.25}$$

Using Shpilrein's Tables of Spherical Functions (Part II, p. 91), it is seen that,



Fig. 39.

$$P_{2,2}(\cos\theta) = 3\sin^2\theta, \tag{33.26}$$

where $P_{2,2}$ denotes the spherical harmonic of the first kind ($n = 2$, $k = 2$).

Hence, the general solution of the equation (33.25) may be written down immediately (§ 31)

$$U_2^* = B\tan^2\frac{\theta}{2} + \\ + \frac{ph^2}{2c_1c_2}(c_1^2 - c_2^2)\sin^2\theta. \tag{33.27}$$

It is now easy (by use of the formulae of § 23, specialized to the present particular case) to obtain expressions for the forces in a spherical shell, subject to the loading (33.23). The results are

$$T_1^* = \left\{\frac{B}{h\sin^2\theta}\tan^2\frac{\theta}{2} + \frac{ph}{2c_1c_2}(c_1^2 - c_2^2)\right\}\cos 2\varphi,$$

$$T_2^* = -\left\{\frac{B}{h\sin^2\theta}\tan^2\frac{\theta}{2} + \frac{ph}{2c_1c_2}(c_1^2 - c_2^2)\cos^2\theta\right\}\cos 2\varphi, \tag{33.28}$$

$$S^* = \left\{\frac{-B}{h\sin^2\theta}\tan^2\frac{\theta}{2} + \frac{ph}{2c_1c_2}(c_1^2 - c_2^2)\cos\theta\right\}\sin 2\varphi.$$

It will be assumed that the ellipsoidal end rests on a perfectly smooth support which cannot assimilate shear forces S^*. This being so, the same property must be imposed on the hemispherical end. In order that the formulae (33.28) satisfy this requirement, one has to put the constant B equal to zero.

Adding now the results obtained under a) and b) above, one finds that the forces in a hemispherical cap subject to the loading (33.21) are

$$T_1^* = -\frac{phc_1c_2}{2}\left(1 - \frac{c_1^2 - c_2^2}{c_1^2c_2^2}\cos 2\varphi\right),$$

$$T_2^* = -\frac{ph}{2c_1c_2}[c_1^2c_2^2 + (c_1^2 + c_2^2 - 2c_1^2c_2^2)\sin^2\theta + \\ + (c_1^2 - c_2^2)\cos^2\theta\cos 2\varphi], \tag{33.29}$$

$$S^* = \frac{ph}{2c_1c_2}(c_1^2 - c_2^2)\cos\theta\sin 2\varphi.$$

The forces in the ellipsoidal cap may now be determined by means of the formulae (33.10) and (33.11) which, taking into consideration that in the present case

$$\begin{aligned} l_1 &= \cos\theta\cos\varphi, & m_1 &= -\sin\varphi, \\ l_2 &= \cos\theta\sin\varphi, & m_2 &= \cos\varphi, \\ l_3 &= -\sin\theta, & m_3 &= 0, \end{aligned} \tag{33.30}$$

give

$$\bar{T}_1^* = -\frac{phc_1c_2}{2}\left[1 - \frac{c_1^2 - c_2^2}{c_1^2c_2^2}\cos 2\varphi\right] \times \\ \times \frac{\sqrt{c_1^2\cos^2\theta\cos^2\varphi + c_2^2\cos^2\theta\sin^2\varphi + \sin^2\theta}}{\sqrt{c_1^2\sin^2\varphi + c_2^2\cos^2\varphi}},$$

$$\bar{T}_2^* = -\frac{ph}{2c_1c_2}[c_1^2c_2^2 + (c_1^2 + c_2^2 - 2c_1^2c_2^2)\sin^2\theta + (c_1^2 - c_2^2)\cos^2\theta\cos 2\varphi] \times \\ \times \frac{\sqrt{c_1^2\sin^2\varphi + c_2^2\cos^2\varphi}}{\sqrt{c_1^2\cos^2\theta\cos^2\varphi + c_2^2\cos^2\theta\sin^2\varphi + \sin^2\theta}}, \tag{33.31}$$

$$\bar{S}^* = \frac{ph}{2c_1c_2}(c_1^2 - c_2^2)\cos\theta\sin 2\varphi.$$

These last expressions completely determine the stresses in an ellipsoidal cap (on a smooth support) loaded by uniform external normal pressure p and they give the solution of this problem in closed form.

It is of the greatest interest to obtain the values of the forces at three points, namely, at the apex of the cap and at the points of intersection of the edge of the cap and the major and minor axes of the elliptic base. One finds

a) at the apex of the shell ($\theta = 0$, $\varphi = 0$):

$$\bar{T}_1^* = -\frac{phc_1^2}{2}\left(1 - \frac{c_1^2 - c_2^2}{c_1^2 c_2^2}\right) = -\frac{pa^2}{2h}\left(1 - \frac{h^2}{b^2}\varepsilon^2\right),$$

$$\bar{T}_2^* = -\frac{ph}{2c_1^2}\left[c_1^2 c_2^2 + (c_1^2 - c_2^2)\right] = -\frac{pb^2}{2h}\left(1 + \frac{h^2}{b^2}\varepsilon^2\right), \tag{33.32}$$

$$\bar{S}^* = 0,$$

where $\varepsilon^2 = 1 - \left(\frac{b}{a}\right)^2$ and $\bar{T}_1^*$ acts in the direction of the major, $\bar{T}_2^*$ in the direction of the minor axis of the base of the shell;

b) at the edge of the shell and at the end of the major axis:

$$\left(\theta = \frac{\pi}{2},\ \varphi = 0\right),$$

$$\bar{T}_1^* = -\frac{phc_1}{2}\left(1 - \frac{c_1^2 - c_2^2}{c_1^2 c_2^2}\right) = -\frac{pa}{2}\left(1 - \frac{h^2}{b^2}\varepsilon^2\right),$$

$$\bar{T}_2^* = \frac{phc_1 c_2^2}{2}\left(1 - \frac{c_1^2 + c_2^2}{c_1^2 c_2^2}\right) = \frac{pa}{2}\,\frac{b^2}{h^2}\left(1 - 2\frac{h^2}{a^2} - \frac{h^2}{b^2}\varepsilon^2\right), \tag{33.33}$$

$$\bar{S}^* = 0;$$

c) at the edge of the shell and at the end of the minor axis:

$$\left(\theta = \frac{\pi}{2},\ \varphi = \frac{\pi}{2}\right),$$

$$\bar{T}_1^* = -\frac{phc_2}{2}\left(1 + \frac{c_1^2 - c_2^2}{c_1^2 c_2^2}\right) = -\frac{pb}{2}\left(1 + \frac{h^2}{b^2}\varepsilon^2\right),$$

$$\bar{T}_2^* = \frac{phc_1^2 c_2}{2}\left[1 - \frac{c_1^2 + c_2^2}{c_1^2 c_2^2}\right] = \frac{pb}{2}\,\frac{a^2}{h^2}\left(1 - \frac{2h^2}{a^2} - \frac{h^2}{b^2}\varepsilon^2\right), \tag{33.34}$$

$$\bar{S}^* = 0.$$

It should be noted that the condition that the shear forces vanish at the edge of the shell can be replaced by any distribution of these forces.

In particular, by suitable choice of the constant B, one may arrive (for T_1 and S) at the case of a cap of the shape of half a triaxial ellipsoid attached to a tube of elliptic cross-section, the entire system being in a membrane state of stress.

§ 34. The displacements in a shell of revolution under symmetrical deformation

So far, all the considered problems of the membrane theory have been formulated in such a way that the determination of the forces was possible independently of the displacements. In other words, all these problems were statically determined, so that hitherto no problem has arisen with regard to the displacements. (It should be noted that the majority of problems of the membrane theory can indeed be solved under this heading.) An example of a statically indeterminate problem will be given later on (in § 37).

The determination of the displacements in membranes of revolution (as has already been indicated in §§ 25, 26) leads to the integration of equations which are completely analogous to those which had to be solved to obtain the stresses in the same shells. Therefore only a few problems of this type will be discussed here; these will include the evaluation of the displacements in shells of revolution under symmetrical deformations (this section) and the determination of pure bending displacements for shells of revolution of positive and negative Gaussian curvature (next section).

In the case of symmetrical deformations, the displacements u, v, w do not depend on φ and hence the equations (23.13) take the form

$$\frac{d\xi_0}{d\theta} = \frac{R_1^2 + R_2^2 + 2\mu R_1 R_2}{R_1 \sin\theta}\,\frac{T_1^*}{E\delta} - \frac{R_2(R_2 + \mu R_1)}{E\delta \sin\theta}\,q_n,$$
$$\frac{d\zeta_0}{d\theta} = \frac{2(1+\mu)R_1}{R_2 \sin\theta}\,\frac{S^*}{E\delta}, \tag{34.1}$$

where ξ_0 and ζ_0 are the values of ξ and ζ [see (23.12)] corresponding to symmetrical deformation.

Hence, using (23.10) and (23.12), one finds

$$u_0 = \xi_0 \sin\theta = u_0^{**} + u_0^*,$$
$$v_0 = \zeta_0 R_2 \sin\theta = v_0^{**} + v_0^*,$$
$$w_0 = -u_0 \operatorname{cotan}\theta + \frac{R_2}{E\delta}(T_2^* - \mu T_1^*) = w_0^{**} + w_0^*, \tag{34.2}$$

where

$$u_0^{**} = C_1 \sin\theta,\quad v_0^{**} = C_2 R_2 \sin\theta,\quad w_0^{**} = -C_1\cos\theta, \tag{34.3}$$

$$u_0^{*} = \frac{\sin\theta}{E\delta}\int_{\theta_1}^{\theta}\left[\frac{R_1^2+R_2^2+2\mu R_1R_2}{R_1\sin\theta}T_1^{*} - R_2\frac{(R_2+\mu R_1)q_n}{\sin\theta}\right]d\theta,$$

$$v_0^{*} = \frac{2(1+\mu)R_2\sin\theta}{E\delta}\int_{\theta_2}^{\theta}\frac{R_1}{R_2\sin\theta}S^{*}d\theta, \tag{34.4}$$

$$w_0^{*} = -u_0^{*}\operatorname{cotan}\theta + \frac{R_2}{E\delta}(T_2^{*} - \mu T_1^{*}).$$

The displacements u_0^{**}, v_0^{**}, w_0^{**} cause not only ε_1, ε_2, ω, but also κ_1, κ_2, τ to vanish, and it follows therefore that these displacements correspond to a space displacement of the shell as a rigid body. In this respect, the displacement v_0^{**} corresponds to a rotation of the shell about its axis through an angle C_2. The displacements u_0^{**}, w_0^{**}, however, cause a translation of the shell in the direction of the same axis through the distance (Fig. 40).

$$\Delta_z^{**} = -u_0^{**}\sin\theta + w_0^{**}\cos\theta = -C_1.$$

If the lower integration limit θ_1 in (34.4) corresponds to the parallel circle on which the axial displacement $\Delta_z = -u_0\sin\theta + w_0\cos\theta$ vanishes and if the integration limit θ_2 corresponds to the parallel circle on which the displacement v_0 (and consequently also the angle of twist) vanishes, then the constants C_1 and C_2 must be set equal to zero. It should be noted in this context that in essence any section of the shell, perpendicular to the axis of the shell, can be selected as the point of reference for the displacement Δ_z and for the angle of twist. The last is clear from the fact that a change in the constants C_1 and C_2 (for fixed values of θ_1 and θ_2) has no effect on the deformation of the middle surface of the shell (and therefore also not on the stresses).



Fig. 40.

It follows from the above that the formulae (34.2) can always be written in the form

$$u_0 = u_0^{*},\quad v_0 = v_0^{*},\quad w_0 = w_0^{*}, \tag{34.5}$$

omitting the rigid body displacements of the shell. Then the axial dis-

placement Δ_z will be measured from an arbitrarily selected parallel circle the position of which is determined by the angle θ_1. It is most convenient to take the origin of Δ_z in the plane of one of the edges of the shell. Correspondingly, the angle of rotation (for torsion of the shell) will be measured from the section determined by the angle θ_2. This section likewise is most conveniently made to coincide with the plane of one of the edges of the shell.

§ 35. Deformation of shells of revolution without extension or shearing of the middle surface

Deformations of a shell of revolution without extension or shearing of the middle surface must satisfy the differential equations (23.10), viz.,

$$\begin{aligned}
\varepsilon_1 R_1 &= \frac{\partial u^{**}}{\partial \theta} + w^{**} = 0, \\
\varepsilon_2 R_2 &= \frac{1}{\sin\theta}\,\frac{\partial v^{**}}{\partial \varphi} + u^{**}\operatorname{cotan}\theta + w^{**} = 0, \\
R_2\omega &= \frac{R_2}{R_1}\,\frac{\partial v^{**}}{\partial \theta} - v^{**}\operatorname{cotan}\theta + \frac{1}{\sin\theta}\,\frac{\partial u^{**}}{\partial \varphi} = 0.
\end{aligned} \tag{35.1}$$

In agreement with the result proved in § 23, the solution of this system reduces to the integration of the equation

$$\frac{1}{R_1 R_2 \sin\theta}\,\frac{\partial}{\partial \theta}\left[\frac{R_2^2 \sin\theta}{R_1}\,\frac{\partial \zeta^{**}}{\partial \theta}\right] + \frac{1}{R_1 \sin^2\theta}\,\frac{\partial^2 \zeta^{**}}{\partial \varphi^2} = 0, \tag{35.2}$$

where

$$\zeta^{**} = \frac{v^{**}}{R_2 \sin\theta}.$$

Considering the case when the shell of revolution is bounded by two of its parallel circles, the solution of the equations (35.1), (35.2) will be sought in the form

$$\begin{aligned}
u^{**} &= \sum_{k=0}^{\infty} u_k^{**} \cos k\varphi + \sum_{k=1}^{\infty} \bar{u}_k^{**} \sin k\varphi, \\
v^{**} &= \sum_{k=1}^{\infty} v_k^{**} \sin k\varphi + \sum_{k=0}^{\infty} \bar{v}_k^{**} \cos k\varphi, \\
w^{**} &= \sum_{k=0}^{\infty} w_k^{**} \cos k\varphi + \sum_{k=1}^{\infty} \bar{w}_k^{**} \sin k\varphi.
\end{aligned} \tag{35.3}$$

Substituting (35.3) into (35.1), one obtains the following system of algebraic and ordinary differential equations for the coefficients of the series:

$$\frac{du_k^{**}}{d\theta} + u_k^{**} = 0,$$

$$\frac{k}{\sin\theta} v_k^{**} + u_k^{**} \operatorname{cotan}\theta + w_k^{**} = 0, \tag{35.4}$$

$$\frac{R_2}{R_1}\frac{dv_k^{**}}{d\theta} - v_k^{**}\operatorname{cotan}\theta - \frac{k}{\sin\theta} u_k^{**} = 0,$$

$$\frac{d\bar{u}_k^{**}}{d\theta} + \bar{w}_k^{**} = 0,$$

$$-\frac{k}{\sin\theta}\bar{v}_k^{**} + \bar{u}_k^{**}\operatorname{cotan}\theta + \bar{w}_k^{**} = 0, \tag{35.5}$$

$$\frac{R_2}{R_1}\frac{d\bar{v}_k^{**}}{d\theta} - \bar{v}_k^{**}\operatorname{cotan}\theta + \frac{k}{\sin\theta}\bar{u}_k^{**} = 0.$$

Substitution of the series for v^{**} in (35.2) leads to the equation

$$\frac{1}{R_1 R_2 \sin\theta}\frac{d}{d\theta}\left[\frac{R_2^2 \sin\theta}{R_1}\frac{d\zeta_k^{**}}{d\theta}\right] - \frac{k^2}{R_1 \sin^2\theta}\zeta_k^{**} = 0, \tag{35.6}$$

where

$$\zeta_k^{**} = \frac{v_k^{**}}{R_2 \sin\theta}.$$

The same equation is also obtained for

$$\xi_k^{**} = \frac{\bar{v}_k^{**}}{R_2 \sin\theta}.$$

As is known from § 20, the series (35.3) must contain, firstly, rigid body displacements of the shell and, secondly, pure bending displacements. It has been shown in the previous section that the first terms in these series, corresponding to $k = 0$, i.e., u_0^{**}, v_0^{**}, w_0^{**}, lead to rigid body displacements of the shell of revolution (translation in the direction of the axis of the shell and rotation about this axis).

It may be shown (by substitution in the formulae for κ_1, κ_2, τ) that the next terms in the series (35.3), corresponding to $k = 1$, likewise lead to rigid body displacements of the shell (translation in a direction perpendicular to the axis of the shell and rotation about an analogous direction).

Thus, the expressions

$$\begin{aligned} u^{**} &= u_0^{**} + u_1^{**} \cos\varphi + \bar{u}_1^{**} \sin\varphi, \\ v^{**} &= \bar{v}_0^{**} + \bar{v}_1^{**} \cos\varphi + v_1^{**} \sin\varphi, \\ w^{**} &= w_0^{**} + w_1^{**} \cos\varphi + \bar{w}_1^{**} \sin\varphi \end{aligned} \tag{35.7}$$

correspond to displacements of the shell of revolution without deformation. In this way, the formulae (35.7) exhaust all the degrees of freedom of a rigid body (three small translations and three small rotations) and hence it must be expected that all the remaining terms in the series (35.3) give deformations of the shell which do not involve extension and shearing, i.e., they correspond to pure bending.

Hence the study of the different types of pure bending of shells of revolution leads to the integration of the equation (35.6) or, what is the same thing, of the system (35.4). (35.5) for values of $k \geqslant 2$. For $k = 0$ and $k = 1$, these equations can be integrated by quadrature (for the case $k = 0$, this has been shown in the previous section, for the case $k = 1$, it is left to the reader to do so using the results of § 29). For $k \geqslant 2$, solution of the equation (35.6) will only be possible once the shape of the shell is known (i.e., when the radii R_1 and R_2 are given as functions of θ). The following gives the deduction and study of the pure bending displacements of the sphere (shell of revolution with positive Gaussian curvature) and of the catenoid (shell of revolution with negative Gaussian curvature). It will appear that there is a certain difference between shells of these two types (as regards application of the membrane theory).

I. *Pure bending displacements for spherical shells.*

Equation (35.6) will now be applied to the particular case when the shell has the form of a frustum of a sphere. Putting $R_1 = R_2 = R = \text{constant}$, one will have

$$\sin\theta \frac{d}{d\theta}\left(\sin\theta \frac{d\zeta_k^{**}}{d\theta}\right) - k^2 \zeta_k^{**} = 0, \tag{35.8}$$

and hence, since

$$d\left(\ln \tan\frac{\theta}{2}\right) = \frac{d\theta}{\sin\theta}, \tag{35.9}$$

one finds

$$\zeta_k^{**} = C_1 \tan^k \frac{\theta}{2} + C_2 \operatorname{cotan}^k \frac{\theta}{2}. \tag{35.10}$$

Thus

$$v_k^{**} = \left(C_k' \tan^k \frac{\theta}{2} + C_k'' \operatorname{cotan}^k \frac{\theta}{2}\right) \sin\theta, \tag{35.11}$$

where a factor k is included in the integration constants. Substituting this expression for v_k^{**} into the third of the equations (35.4), one obtains

$$u_k^{**} = \left(C_k' \tan^k \frac{\theta}{2} - C_k'' \operatorname{cotan}^k \frac{\theta}{2}\right) \sin\theta. \tag{35.12}$$

Finally, the second of the equations (35.4) gives

$$w_k^{**} = -C_k'(k + \cos\theta) \tan^k \frac{\theta}{2} - C_k''(k - \cos\theta) \operatorname{cotan}^k \frac{\theta}{2}. \tag{35.13}$$

In quite an analogous order, it is easy to determine the coefficients with bars

$$\begin{aligned} \bar{v}_k^{**} &= \left(\bar{C}_k' \tan^k \frac{\theta}{2} + \bar{C}_k'' \operatorname{cotan}^k \frac{\theta}{2}\right) \sin\theta, \\ \bar{u}_k^{**} &= -\left(\bar{C}_k' \tan^k \frac{\theta}{2} - \bar{C}_k'' \operatorname{cotan}^k \frac{\theta}{2}\right) \sin\theta, \\ \bar{w}_k^{**} &= \bar{C}_k'(k + \cos\theta) \tan^k \frac{\theta}{2} + \bar{C}_k''(k - \cos\theta) \operatorname{cotan}^k \frac{\theta}{2}, \end{aligned} \tag{35.14}$$

where $\bar{C}_k'$, $\bar{C}_k''$ are constants of integration.

Introducing the coefficients (35.11), (35.12), (35.13) and (35.14) into the series (35.3) and beginning the summation in these series with $k = 2$, there are obtained the most general expressions for the pure bending displacements of shells of the form of a spherical belt.

As is already known to the reader (§§ 20, 21), half the boundary conditions in the momentless theory must be given in terms of the displacements (and, moreover, in the tangential direction), in order that the pure bending displacements entering into the general solution of the differential equations of this theory should either be completely removed or be bounded in some manner. In this connection, it is important to know just what tangential fastening of the edges of the shell will ensure the absence of pure bending. In the particular case under consideration (the spherical segment), there are two necessary conditions which may be disposed of in an arbitrary manner on the two edges of the shell.

Let the edge $\theta = \theta_1$ be fixed with regard to tangential displacement along the tangent to the parallel circle at α_1, and the edge $\theta = \theta_2$ with

regard to tangential displacement along the same tangent at α_2 (Fig. 41).

In other words, let

$$\begin{aligned} -u\sin\alpha_1 + v\cos\alpha_1 &= 0, \text{ for } \theta = \theta_1, \\ -u\sin\alpha_2 + v\cos\alpha_2 &= 0, \text{ for } \theta = \theta_2, \end{aligned} \tag{35.15}$$

where α_1 and α_2, generally speaking, may be functions of φ; however, for the sake of simplicity, consideration will be limited to the case where both these angles are constants.

Substituting the series (35.3) into (35.15), one obtains

$$\left.\begin{aligned} -u_k^{**}\sin\alpha_1 + \bar{v}_k^{**}\cos\alpha_1 &= 0 \\ -\bar{u}_k^{**}\sin\alpha_1 + v_k^{**}\cos\alpha_1 &= 0 \end{aligned}\right\} \text{for } \theta = \theta_1,$$
$$\left.\begin{aligned} -u_k^{**}\sin\alpha_2 + \bar{v}_k^{**}\cos\alpha_2 &= 0 \\ -\bar{u}_k^{**}\sin\alpha_2 + v_k^{**}\cos\alpha_2 &= 0 \end{aligned}\right\} \text{for } \theta = \theta_2. \tag{35.16}$$

These equalities will now be considered as two linear algebraic systems with the unknowns $\sin\alpha_1$, $\cos\alpha_1$ and $\sin\alpha_2$, $\cos\alpha_2$ respectively. Obviously, these systems cannot have solutions which are identically zero (since it is impossible for the sine and cosine of the same angle to be simultaneously zero). Hence the determinants of these systems must vanish, i.e., the following equalities must hold:



Fig. 41.

$$u_k^{**}v_k^{**} = \bar{u}_k^{**}\bar{v}_k^{**} \text{ for } \theta = \theta_1,\ \theta = \theta_2. \tag{35.17}$$

Substituting here the expressions for u_k^{**}, v_k^{**}, $\bar{u}_k^{**}$, $\bar{v}_k^{**}$ from (35.11), (35.12) and (35.14), it is found that

$$\begin{aligned} (C_k'^2 + \bar{C}_k'^2)\tan^{2k}\frac{\theta_1}{2} - (C_k''^2 + \bar{C}_k''^2)\operatorname{cotan}^{2k}\frac{\theta_1}{2} &= 0, \\ (C_k'^2 + \bar{C}_k'^2)\tan^{2k}\frac{\theta_2}{2} - (C_k''^2 + \bar{C}_k''^2)\operatorname{cotan}^{2k}\frac{\theta_2}{2} &= 0. \end{aligned} \tag{35.18}$$

These equations will be considered as a linear homogeneous algebraic system with the unknowns

$$X = C_k'^2 + \bar{C}_k'^2,\ Y = C_k''^2 + \bar{C}_k''^2$$

and it will be shown that this system can only have a trivial solution, i.e. the zero solution. In fact, the determinant of the system (35.18) is

$$\Delta = -\begin{vmatrix} \tan^{2k}\frac{\theta_1}{2}, & \operatorname{cotan}^{2k}\frac{\theta_1}{2} \\ \tan^{2k}\frac{\theta_2}{2}, & \operatorname{cotan}^{2k}\frac{\theta_2}{2} \end{vmatrix} =$$

$$= \left(\tan\frac{\theta_2}{2}\operatorname{cotan}\frac{\theta_1}{2}\right)^{2k} - \left(\tan\frac{\theta_1}{2}\operatorname{cotan}\frac{\theta_2}{2}\right)^{2k}. \qquad (35.19)$$

Equating this determinant to zero, one finds

$$\left(\tan\frac{\theta_1}{2}\right)^{4k} = \left(\tan\frac{\theta_2}{2}\right)^{4k}. \qquad (35.20)$$

But $\theta_1 \neq \theta_2$ and, besides, θ_1 and θ_2 lie in the range 0 to π. Therefore the equality (35.20) is impossible.

Thus, the only possible solution of the system (35.18) will be $X = 0$, $Y = 0$, from which follows directly that

$$C_k' = C_k'' = \bar{C}_k' = \bar{C}_k'' = 0.$$

In other words, the adopted boundary conditions make all terms in the series (35.3) become zero, i.e., they completely remove pure bending displacements. It will be noted that the same conclusion may be reached by fixing one edge completely in the tangential direction and by leaving the other edge free of any constraint. This formulation of the boundary conditions corresponds to

$$u = v = 0 \text{ for } \theta = \theta_1 \text{ or for } \theta = \theta_2.$$

The above discussion shows that for shells of the form considered here (the spherical frustum), two zero boundary conditions for the tangential displacements completely ensure the existence of the membrane state of stress irrespective of whether these conditions are given at one and the same or at both edges of the shell. This deduction, obtained for a particular example, has general validity and may be extended to all shells of revolution of positive Gaussian curvature bounded by two parallel circles. In this context, it should still be noted that it is very difficult to realize in a design tangential fixing of the edges of a shell without restraining at the same time the normal displacements. In view of this the edge of the shell will not only become subject to tangential but also to normal constraints which are more than enough to ensure the absence (or boundedness) of pure bending displacements.

In conclusion, it should be noted that, if the spherical shell is closed at the top (spherical dome or cap), then one must put in the formulae (35.11) to (35.14)

$$C_k'' = \bar{C}_k'' = 0,$$

since otherwise the solution will become infinite at the point $\theta = 0$ which now belongs to the shell. In this particular case, the absence of pure bending displacements will be ensured by means of one zero boundary condition, formulated in terms of tangential displacements.

However, if the spherical shell is complete, so that it contains the point $\theta = 0$ as well as the point $\theta = \pi$, then in (35.11) to (35.14) one has to put equal to zero not only C_k'', $\bar{C}_k''$, but also C_k', $\bar{C}_k'$ (since, if the first becomes infinite for $\theta = 0$, the second does so for $\theta = \pi$).

Thus, in this last case,

$$u^{**} = v^{**} = w^{**} = 0,$$

i.e., pure bending (displacements without extension or shearing) of a complete spherical shell is impossible. This result has general validity



Fig. 42.



Fig. 43.

and may be extended to all complete convex shells of revolution. Fig. 42 shows the deformations of a hemisphere, corresponding to its being in a state of pure bending, determined by the formulae (35.14) for $k = 2$.

2. Pure bending displacements of catenoid shells.

The name "catenoid" will be given to the surface of negative Gaussian curvature, generated by rotation of a catenary (Fig. 43). The radii of curvature of the catenoid are

$$R_2 = -R_1 = \frac{r_0}{\sin^2\theta}, \tag{35.21}$$

where r_0 is the radius of the smallest parallel circle of the surface. For catenoid shells, the differential equation (35.6) can be written in the form

$$\sin^3\theta \frac{d}{d\theta}\left[\frac{1}{\sin\theta}\frac{d\zeta_k^{**}}{d\theta}\right] + k^2\zeta_k^{**} = 0. \tag{35.22}$$

Introducing here the new dependent and independent variables

$$\zeta_k^{**} = z\sin\theta, \quad \psi = \ln\tan\frac{\theta}{2}, \tag{35.23}$$

the equation (35.22) becomes

$$\frac{d^2z}{d\psi^2} + (k^2 - 1)z = 0. \tag{35.24}$$

Hence

$$z = C_k'\cos\sqrt{k^2-1}\,\psi + C_k''\sin\sqrt{k^2-1}\,\psi. \tag{35.25}$$

Proceeding from z to ζ_k^{**}, and then to v_k^{**}, using (35.6) and (35.21), one finds

$$v_k^{**} = C_k'\cos\sqrt{k^2-1}\,\psi + C_k''\sin\sqrt{k^2-1}\,\psi. \tag{35.26}$$

Now, the quantity u^{**} may be found by use of the third of the formulae (35.4) which for the case of the catenoid may be written in terms of the new independent variable ψ

$$ku_k^{**} = -\frac{dv_k^{**}}{d\psi} + v_k^{**}\tanh\psi \qquad \left(\cos\theta = -\tanh\psi,\ \sin\theta = \frac{1}{\cosh\psi}\right). \tag{35.27}$$

Hence

$$u_k^{**} = \frac{\sqrt{k^2-1}}{k}(C_k'\sin\sqrt{k^2-1}\,\psi - C_k''\cos\sqrt{k^2-1}\,\psi) + \\ + \frac{\tanh\psi}{k}(C_k'\cos\sqrt{k^2-1}\,\psi + C_k''\sin\sqrt{k^2-1}\,\psi). \tag{35.28}$$

It is now easy to determine also w^{**} which by the second of the equations (35.4) and the formulae (35.21), (35.23) becomes

$$w_k^{**} = u_k^{**} \sinh \psi - k v_k^{**} \cosh \psi. \tag{35.29}$$

By a quite analogous reasoning, one finds

$$\begin{aligned}
\bar{v}_k^{**} &= \bar{C}_k' \cos \sqrt{k^2 - 1}\psi + \bar{C}_k'' \sin \sqrt{k^2 - 1}\psi, \\
\bar{u}_k^{**} &= -\frac{\sqrt{k^2 - 1}}{k} (\bar{C}_k' \sin \sqrt{k^2 - 1}\psi - \bar{C}_k'' \cos \sqrt{k^2 - 1}\psi) - \\
&\quad - \frac{\tanh \psi}{k} (\bar{C}_k' \cos \sqrt{k^2 - 1}\psi + \bar{C}_k'' \sin \sqrt{k^2 - 1}\psi), \\
\bar{w}_k^{**} &= - k \bar{v}_k^{**} \cosh \psi + \bar{u}_k^{**} \sinh \psi.
\end{aligned} \tag{35.30}$$

The expressions (35.26), (35.28), (35.29), (35.30), on substitution in the series (35.3), give the pure bending displacements of catenoid shells bounded by two parallel circles.

The different variations of tangential constraint of these two edges will now be studied in relation to the problem of elimination of pure bending displacements.

Consider first the boundary conditions

$$v = 0 \text{ for } \psi = \psi_1 \text{ and } \psi = \psi_2 \ (\theta = \theta_1, \ \theta = \theta_2). \tag{35.31}$$

One obtains from (35.31) after substitution of the series (35.3) for v

$$v_k^{**} = 0, \ \bar{v}_k^{**} = 0 \text{ for } \psi = \psi_1, \ \psi = \psi_2. \tag{35.32}$$

The first of these equalities, in expanded form, may be written

$$\begin{aligned}
C_k' \cos \sqrt{k^2 - 1}\psi_1 + C_k'' \sin \sqrt{k^2 - 1}\psi_1 = 0, \\
C_k' \cos \sqrt{k^2 - 1}\psi_2 + C_k'' \sin \sqrt{k^2 - 1}\psi_2 = 0.
\end{aligned} \tag{35.33}$$

In order that this system may have non-zero solutions, the determinant

$$\begin{vmatrix} \cos \sqrt{k^2 - 1}\psi_1, & \sin \sqrt{k^2 - 1}\psi_1 \\ \cos \sqrt{k^2 - 1}\psi_2, & \sin \sqrt{k^2 - 1}\psi_2 \end{vmatrix} = \sin \sqrt{k^2 - 1}(\psi_2 - \psi_1) \tag{35.34}$$

must vanish and this will be so, if

$$\psi_2 - \psi_1 = \frac{m\pi}{\sqrt{k^2 - 1}}, \tag{35.35}$$

where m and k are any integers ($k \geqslant 2$).

One thus arrives at the conclusion that the above formulated zero boundary conditions at the edges of the catenoid do not, generally speaking, ensure that

$$u_k^{**} = v_k^{**} = w_k^{**} = 0$$

at all points of the middle surface.

By considering the second of the equalities (35.32), one finds that the equalities

$$\bar{u}_k^{**} = \bar{v}_k^{**} = \bar{w}_k^{**} = 0$$

likewise do not secure the adopted boundary conditions. Thus, the tangential constraints of the edges of the catenoid, introduced above, do not eliminate pure bending displacements and therefore they do not ensure the existence of a membrane state of stress in the catenoid. Consider other variations of tangential constraint of the two edges of the shell, for example,

$$u = 0 \text{ for } \psi = \psi_1 \text{ and } \psi = \psi_2$$

or

$$u = 0 \text{ for } \psi = \psi_1,\ v = 0 \text{ for } \psi = \psi_2, \text{ etc.}$$

It is seen that catenoids (shells with negative Gaussian curvature) differ essentially from spherical frusta (shells with positive Gaussian curvature). The difference between them consists of the fact that those variations of the tangential constraints of the edges of the shells which secure the existence of a membrane state of stress in spherical frusta, generally speaking, do not secure it for the catenoid.

In this connection, the idea has been proposed in Ref. [4] that shells of negative Gaussian curvature will not, in general, be in a membrane state of stress. (In other words, that for any tangential constraint of the edges pure bending will occur). However, this statement is incorrect, as may be verified by considering the case of complete tangential constraint of one of the edges of the shell, i.e., the case

$$u = 0,\ v = 0 \text{ for } \psi = \psi_1. \tag{35.36}$$

One finds from these conditions

$$\left.\begin{aligned} u_k^{**} &= 0,\ \bar{u}_k^{**} = 0 \\ v_k^{**} &= 0,\ \bar{v}_k^{**} = 0 \end{aligned}\right\} \text{for } \psi = \psi_1, \tag{35.37}$$

which by use of (35.27), (35.28) reduce to the system

$$\begin{aligned} C_k' \cos \sqrt{k^2 - 1}\psi_1 + C_k'' \sin \sqrt{k^2 - 1}\psi_1 &= 0, \\ C_k' \sin \sqrt{k^2 - 1}\psi_1 - C_k'' \cos \sqrt{k^2 - 1}\psi_1 &= 0, \end{aligned} \tag{35.38}$$

the determinant of the coefficients of which

$$\Delta = \begin{vmatrix} \cos \sqrt{k^2 - 1}\psi_1, & + \sin \sqrt{k^2 - 1}\psi_1 \\ \sin \sqrt{k^2 - 1}\psi_1, & - \cos \sqrt{k^2 - 1}\psi_1 \end{vmatrix} =$$

$$= - \{\cos^2 \sqrt{k^2 - 1}\psi_1 + \sin^2 \sqrt{k^2 - 1}\psi_1\} = - 1 \qquad (35.39)$$

is always distinct from zero. Thus, the system (35.38) has only the trivial solution ,

$$C_k' = C_k'' = 0.$$

An analogous result can be proved for $\bar{C}_k'$, $\bar{C}_k''$. These results show that a catenoid shell one edge of which is completely fixed with regard to tangential displacement offers the possibility of the existence of a membrane state of stress. For this, there may be given at the other edge the forces T_1^*, S^* (in which case the problem will be statically determinate). There may also be given displacements in which case the absence of bending in the catenoid shell will be more than ensured (having in mind zero boundary conditions). The results obtained above for the particular case of the catenoid have general validity for all shells of revolution with negative Gaussian curvature, bounded by two parallel circles; in fact, the necessary and sufficient condition for the elimination of pure bending in such shells is the introduction of a total constraint with regard to tangential displacement of one edge of the shell.

§ 36. The Equations of the membrane theory for cylindrical shells of arbitrary shape

Consider a cylindrical shell of arbitrary shape. The position of a point on its middle surface can be given by the coordinates x and s, where x



Fig. 44.

is the distance of the point from some definite plane perpendicular to the axis of the cylinder and s is the length of the arc in the circumferential direction measured from some definite generator (Fig. 44a). The coordinate

lines of this system are the generators and the contours. Both Lamé parameters will be equal to unity, while one of the two principal radii of curvature, R_1, is equal to infinity and the other, $R_2 = r$, is a function of the arc length s only.

Using the general equations of the membrane theory, these results lead to the following differential equations for cylindrical shells of arbitrary shape

$$\begin{aligned} \frac{\partial T_1^*}{\partial x} + \frac{\partial S^*}{\partial s} + q_1 &= 0, \\ \frac{\partial S^*}{\partial x} + \frac{\partial T_2^*}{\partial s} + q_2 &= 0, \\ T_2^* &= q_n r, \end{aligned} \tag{36.1}$$

where q_1, q_2, q_n are the components of the surface loading in the directions x, s and the normal to the middle surface.

Using (20.3), the strains of the middle surface of cylindrical shells may be written

$$\begin{aligned} \varepsilon_1 &= \frac{\partial u}{\partial x}, \\ \varepsilon_2 &= \frac{\partial v}{\partial s} + \frac{w}{r}, \\ \omega &= \frac{\partial u}{\partial s} + \frac{\partial v}{\partial x}. \end{aligned} \tag{36.2}$$

where ε_1 is the extension along the generator and ε_2 the circumferential extension. The positive directions for the forces in a cylindrical shell are shown in Fig. 44b.

Equations (36.1) can be integrated in closed form. Similarly, the differential equations for the displacements may be integrated in closed form.

The solution of the membrane theory of cylindrical shells, obtained in this manner, contains a number of arbitrary functions of the variable s with the help of which the boundary conditions may be satisfied. There is no purpose served by presenting here all the calculations in the general case, since the examples studied below explain sufficiently how the equations (36.1) must be solved.

§ 37. Determination of the stresses in tubes with arbitrary cross-section, loaded by uniform normal pressure

Using membrane theory, a complete cylindrical tube of arbitrary cross-section, loaded by uniform normal pressure p will now be studied. The ends of the shell will be two cross-sections perpendicular to the axis of the shell. The coordinate x (§ 36) will be measured from one of the end-sections. Then the other end-section of the tube will be determined by the coordinate L (the length of the tube). The radius of curvature of the cross-section of the shell will be assumed to be a continuous and at least four times differentiable function of the arc coordinate s.



Fig. 45.

It will be required to solve the problem for two types of boundary conditions:

1) for $x = 0,\ x = L$: $T_1 = 0,\ v = 0$;

2) for $x = 0,\ x = L$: $u = 0,\ v = 0$.

The first type is statically determinate, while the second which corresponds to rigid fixing of the edges of the shell is statically indeterminate.

For the present problem the differential equations (36.1) take the form

$$\frac{\partial T_1^*}{\partial x} + \frac{\partial S^*}{\partial s} = 0, \quad \frac{\partial S^*}{\partial x} + \frac{\partial T_2^*}{\partial s} = 0, \quad T_2^* = pr. \tag{37.1}$$

The third of these equations directly determines the hoop stress in the tube

$$T_2^* = pr. \tag{37.2}$$

Substituting this value for T_2^* into the second equation (37.1) and integrating it with respect to x, one obtains

$$S^* = -px\frac{dr}{ds} + f_1(s), \tag{37.3}$$

where $f_1(s)$ is an arbitrary function of the arc length s. This function may be determined from the condition that at the centre section of the tube the shear stresses must be equal to zero, as a result of the symmetry of the above boundary conditions.

On this basis, one obtains the equation

$$S^*_{x=\frac{L}{2}} = 0 = -p\frac{L}{2}\frac{dr}{ds} + f_1(s), \tag{37.4}$$

whence

$$S^* = p\left(\frac{L}{2} - x\right)\frac{dr}{ds}. \tag{37.5}$$

Substituting this value for S^* into the first equation (37.1) and integrating again with respect to x, one will have

$$T_1^* = p\left[x\frac{x-L}{2}\frac{d^2r}{ds^2} + f_2(s)\right]. \tag{37.6}$$

From here on, the methods of solution of the above problems will differ, their course depending on the differences in the boundary conditions.

1. *The statically determinate type of boundary conditions.*

In this case, the force T_1^* at $x = 0$ and $x = L$ will be equal to zero. Hence, it is found that in (37.6) $f_2(s) = 0$ and therefore

$$T_1^* = px\frac{x-L}{2}\frac{d^2r}{ds^2}. \tag{37.7}$$

The formulae (37.2), (37.5), (37.7) completely determine all the forces in the tube.

Now one may write down for the displacements u, v, w the system of differential equations

$$\begin{aligned}
\varepsilon_1 &= \frac{\partial u}{\partial x} = \frac{1}{E\delta}(T_1^* - \mu T_2^*) = \frac{p}{E\delta}\left[-\mu r + \frac{x(x-L)}{2}\frac{d^2r}{ds^2}\right],\\
\varepsilon_2 &= \frac{\partial v}{\partial s} + \frac{w}{r} = \frac{1}{E\delta}(T_2^* - \mu T_1^*) = \frac{p}{E\delta}\left[r - \mu\frac{x(x-L)}{2}\frac{d^2r}{ds^2}\right],\\
\omega &= \frac{\partial u}{\partial s} + \frac{\partial v}{\partial x} = \frac{2(1+\mu)}{E\delta}S^* = \frac{2(1+\mu)p}{E\delta}\left(\frac{1}{2}L - x\right)\frac{dr}{ds}.
\end{aligned} \tag{37.8}$$

Integrating the first of these equations with respect to x, one finds

$$u = -\frac{px}{E\delta}\left[\mu r - \frac{x}{2}\left(\frac{1}{3}x - \frac{1}{2}L\right)\frac{d^2r}{ds^2}\right] + f_3(s). \tag{37.9}$$

In order to evaluate the arbitrary function $f_3(s)$, use will be made of the

fact that, by the symmetry of the boundary conditions, the displacement u must vanish at the section $x = \frac{L}{2}$. Hence

$$f_3(s) = -\frac{pL}{2E\delta}\left(\mu r + \frac{1}{12}L^2\frac{d^2r}{ds^2}\right) \tag{37.10}$$

and, consequently,

$$u = \mu\frac{pr}{E\delta}\left(\frac{1}{2}L - x\right) + \frac{1}{6}\frac{p}{E\delta}\left(x^3 - \frac{3}{2}Lx^2 + \frac{1}{4}L^3\right)\frac{d^2r}{ds^2}. \tag{37.11}$$

Substituting (37.11) into the third equation (37.8) and integrating with respect to x, one will have

$$v = \frac{(2+\mu)}{2}\frac{px(L-x)}{E\delta}\frac{dr}{ds} - \frac{px}{24E\delta}(x^3 - 2Lx^2 + L^3)\frac{d^3r}{ds^3} + f_4(s). \tag{37.12}$$

In order to make this expression satisfy the boundary conditions $v = 0$ at $x = 0$ and $x = L$, it is sufficient to let $f_4(s) = 0$. Substituting the expression thus obtained for v into the second equation (37.8), one finds for the normal deflection (which is generally of greatest interest)

$$w = \frac{pr}{E\delta}\left\{r + x(x-L)\frac{d^2r}{ds^2} + \frac{x}{24}(x^3 - 2Lx^2 + L^3)\frac{d^4r}{ds^4}\right\}. \tag{37.13}$$

2. *The statically indeterminate type of boundary conditions*

In this case, the arbitrary function $f_2(s)$ in (37.6) may be determined only after obtaining the displacement u.

The first equation (37.8) with $f_2(s) \neq 0$ takes the form

$$\frac{\partial u}{\partial x} = \frac{p}{E\delta}\left[-\mu r + \frac{x(x-L)}{2}\frac{d^2r}{ds^2} + f_2(s)\right]. \tag{37.14}$$

Integrating this equation with respect to x, one finds

$$u = \frac{px}{E\delta}\left[-\mu r + \frac{x}{2}\left(\frac{x}{3} - \frac{L}{2}\right)\frac{d^2r}{ds^2} + f_2(s)\right] + f_3(s). \tag{37.15}$$

The two arbitrary functions $f_2(s)$, $f_3(s)$ in this formula will be determined by the conditions that $u = 0$ for $x = 0$ and $x = L$ which lead to

$$\begin{aligned} f_3(s) &= 0, \\ f_2(s) &= \mu r + \frac{1}{12}L^2\frac{d^2r}{ds^2}. \end{aligned} \tag{37.16}$$

Hence one obtains for u

$$u = \frac{px}{12E\delta}(2x^2 - 3Lx + L^2)\frac{d^2r}{ds^2}. \tag{37.17}$$

Now, $f_2(s)$ having been found, the force T_1^* is completely determined by (37.6)

$$T_1^* = \frac{p}{2}\left(x^2 - Lx + \frac{1}{6}L^2\right)\frac{d^2r}{ds^2} + \mu pr. \tag{37.18}$$

Substituting (37.17) into the third equation (37.8) and integrating with respect to x, one finds

$$v = -\frac{px^2}{24E\delta}(x - L)^2\frac{d^3r}{ds^3} - \frac{(1+\mu)px}{E\delta}(x - L)\frac{dr}{ds} + f_4(s). \tag{37.19}$$

In this expression, the function $f_4(s)$, on the basis of the boundary conditions $v = 0$ for $x = 0$, $x = L$, must be set equal to zero.

Now one may obtain from the formula

$$w = \frac{r}{E\delta}(T_2^* - \mu T_1^*) - r\frac{\partial v}{\partial s} \tag{37.20}$$

for the normal displacement w

$$w = \frac{pr}{E\delta}\left\{r + \frac{2+\mu}{2}x(x - L)\frac{d^2r}{ds^2} + \frac{1}{24}x^2(x - L)^2\frac{d^4r}{ds^4}\right\}. \tag{37.21}$$

All the forces and displacements have now been determined for the second (statically indeterminate) type of problem under consideration.

The above results will now be applied to the particular case of a tube with an elliptical cross-section.



Fig. 46.

For an ellipse,

$$r = \frac{b^2}{a}\frac{1}{(1 - \varepsilon^2\cos^2\varphi)^{3/2}}, \tag{37.22}$$

where $2a$ and $2b$ are the major and minor axes of the ellipse, ε — is the eccentricity $\left[\varepsilon^2 = 1 - \left(\frac{b}{a}\right)^2\right]$ and φ is the angle between the normal to the ellipse and its minor axis (Fig. 46).

This angle is connected with the arc length s by the differential relation

$$ds = r\,d\varphi, \tag{37.23}$$

which permits one to replace differentiation with respect to the arc s by differentiation with respect to φ; this step is required because (37.22) gives r as a function of φ.

In applying the above formulae for the forces and deflections one has to know the first four derivatives of r with respect to s. On the basis of (37.22), (37.23), one finds

$$\frac{dr}{ds} = \frac{1}{r}\frac{dr}{d\varphi} = -\frac{3}{2}\varepsilon^2\frac{\sin 2\varphi}{1-\varepsilon^2\cos^2\varphi},$$

$$\frac{d^2r}{ds^2} = \frac{1}{r}\frac{d}{d\varphi}\left(\frac{dr}{ds}\right) = -\frac{3a}{b^2}\varepsilon^2\frac{\cos 2\varphi - \varepsilon^2\cos^2\varphi}{\sqrt{1-\varepsilon^2\cos^2\varphi}},$$

$$\frac{d^3r}{ds^3} = \frac{1}{r}\frac{d}{d\varphi}\left(\frac{d^2r}{ds^2}\right) = \frac{6a^2}{b^4}\varepsilon^2[1-\tfrac{3}{4}\varepsilon^2-\tfrac{1}{2}\varepsilon^2(1-\tfrac{1}{2}\varepsilon^2)\cos^2\varphi]\sin 2\varphi, \tag{37.24}$$

$$\frac{d^4r}{ds^4} = \frac{1}{r}\frac{d}{d\varphi}\left(\frac{d^3r}{ds^3}\right) = \frac{12a^3}{b^6}\varepsilon^2(1-\varepsilon^2\cos^2\varphi)^{3/2}[(1-\tfrac{3}{4}\varepsilon^2)\cos 2\varphi -$$

$$-\tfrac{1}{2}\varepsilon^2(1-\tfrac{1}{2}\varepsilon^2)(\cos^2\varphi - 3\sin^2\varphi)\cos^2\varphi].$$

With these expressions available, one may determine the maximum values of the stresses and deflections in elliptical tubes subject to uniform normal pressure. Consideration will here be limited to the statically determinate version of the problem.

By (37.2) the direct stress induced by the force T_2^* reaches its maximum at the point where r has its maximum value, i.e., for the ellipse at the end of the minor axis. By (37.22), this maximum will be equal to

$$|\sigma_2|_{\max} = \frac{\max(T_2^*)}{\delta} = \frac{pa^2}{b\delta}. \tag{37.25}$$

By (37.5), the shearing stress will attain its maximum value at the ends of the shell for values of φ which correspond to the maxima of $\frac{dr}{ds}$. Equating $\frac{d^2r}{ds^2}$ to zero, one obtains for this angle the equation

$$\cos 2\varphi - \varepsilon^2\cos^2\varphi = 0, \tag{37.26}$$

whence

$$\cos\varphi = \frac{1}{\sqrt{2-\varepsilon^2}}, \quad \sin\varphi = \frac{\sqrt{1-\varepsilon^2}}{\sqrt{2-\varepsilon^2}}. \tag{37.27}$$

Introducing these values for $\sin\varphi$ and $\cos\varphi$ into the first formula (37.24) and substituting it thereafter into (37.5), one finds

$$\tau_{\max} = \frac{\max S^*}{\delta} = \frac{3}{4}\frac{pL}{\delta}\left(\frac{a}{b} - \frac{b}{a}\right). \tag{37.28}$$

By (37.7), the direct stress, due to the force T_1^*, will reach its maximum value at the centre section $\left(\text{for } x = \frac{L}{2}\right)$ at the end points of the major and minor axes of the ellipse. The values there will be

$$\begin{aligned} \sigma_1' &= \frac{T_1^*}{\delta} = \frac{3}{8}\frac{pL^2}{b\delta}\varepsilon^2 \quad \text{(at the end of the minor axis)}, \\ \sigma_1'' &= \frac{T_1^*}{\delta} = -\frac{3}{8}\frac{paL^2}{b^2\delta}\varepsilon^2 \quad \text{(at the end of the major axis)}. \end{aligned} \tag{37.29}$$

It should be noted that the stresses (37.29) must be augmented (or reduced) by the stresses due to axial tension (or compression) of the shell (if such should be present). As regards the displacements in the shell, only the values of the normal displacements at the centre section $\left(x = \frac{L}{2}\right)$ at the ends of the major and minor axes of the ellipse $\left(\varphi = 0, \varphi = \frac{\pi}{2}\right)$ will be given. In fact, at the end of the minor axis,

$$w_b = \frac{pa^4}{E\delta b^2}\left[1 + \frac{3}{4}\frac{L^2}{a^2}\varepsilon^2 + \frac{5}{32}\frac{L^4}{a^4}\varepsilon^2\left(1 - \frac{\varepsilon^2}{4}\right)\right], \tag{37.30}$$

while at the end of the major axis

$$w_a = -\frac{pa^4}{E\delta b^2}\left[-\frac{b^6}{a^6} + \frac{3}{4}\frac{L^2b^2}{a^4}\varepsilon^2 + \frac{5}{32}\frac{L^4}{a^2b^2}\varepsilon^2\left(1 - \frac{3}{4}\varepsilon^2\right)\right]. \tag{37.31}$$

In conclusion the reader's attention will be drawn to the fact that all the formulae of this section, giving the displacements and stresses in a tube subject to uniform normal pressure, will become infinite as the length of the tube tends to infinity (the only exception being the particular case when the tube has a circular plan form). Hence it is clear that the above formulae do not apply to tubes of sufficiently large length. For the analysis of long tubes, one has to take into consideration their bending stiffness in the transverse direction, which, in principle, determines also the strains.

The results, obtained above for a particular loading and for a particular

shape of shell has general validity for the theory of cylindrical shells. In fact, the applicability of the membrane theory, as a rule, depends on the length of a shell. As soon as a cylindrical shell is sufficiently long, no formulation of the boundary conditions at its ends will ensure the proper boundedness of the pure bending displacements in the middle portion of the shell (unless the cross-section of the shell has been specially selected for a given type of loading to exclude the dependence of the transverse bending of the shell on its length. In particular, for uniform normal pressure, such a special cross-section is the circle).

§ 38. The membrane theory of cylindrical vaults

During the era of brick and stone constructions, the roofing of rectangular areas was often achieved by cylindrical vaults which, for the purpose of stress analysis, can be treated as arches. In order to ensure the proper functioning of the roof, one has to give it solid foundations along the straight edges, while the curvilinear edges need not be supported.

Such an approach practically indicates the need for supporting the straight edges of a vault on continuous walls which will divide the interior space of the building into a number of separate rooms (in the case that several vaults are involved). However, in many cases, such a subdivision of the interior of a building will be undesirable, and in some



Fig. 47.

cases unacceptable. Thus, for example, the usefulness of factory premises, large stores or markets, hangars and garages, as a rule, increases with their size. In such cases, stone or brick vaults are still sometimes being used for roofs.

The progress in reinforced concrete technology has led to quite a different problem related to the cylindrical roof. The contemporary roof has small thickness and may be considered to be a shell, mainly supported along its curvilinear edges.

The advantage of transmitting the load on the roof along a curvilinear edge arises from the fact that the supports in this case have the form of arches and that they may be made sufficiently strong without their having to be solid walls. Further, it turns out that the distance between such supports may be made very large, several times the distance between straight supports of a vault. All this points towards the use of a number of adjoining cylindrical shells for the purpose of roofing large spaces with a minimum obstruction by supports. These supports then take the form of pillars with acceptably large spacing between them.



Fig. 48.

Consider the stresses in a thin cylindrical roof from the point of view of the membrane theory, using as an example a shell with the radius of curvature

$$r = \frac{r_0}{(1 + \gamma \sin^2 \varphi)^{3/2}}. \tag{38.1}$$

In this case, the contour of the cylinder will be a second order curve: for $\gamma = 0$, a circular, for $\gamma = -1$, a parabolic, for $\gamma > 1$, an elliptic, for $\gamma < -1$, a hyperbolic arc. Hence, using (38.1), one may study a family of roofs varying greatly in shape, and arrive at a number of results of a general nature.

Denoting the weight of the roof per unit area of its middle surface by q, the equations (36.1) applicable to the present problem may be written

$$\frac{\partial T_1^*}{\partial x} + \frac{1}{r}\frac{\partial S^*}{\partial \varphi} = 0,$$

$$\frac{\partial S^*}{\partial x} + \frac{1}{r}\frac{\partial T_2^*}{\partial \varphi} = -q \sin \varphi, \qquad (38.2)$$

$$T_2^* = -qr \cos \varphi,$$



Fig. 49.

where φ is the angle between the normal to the roof and the vertical, related to the arc coordinate s by $r\,d\varphi = ds$ (Fig. 49) and r is given by (38.1).

Carrying out the integration of the system (38.2) with respect to x in the same manner as in the preceding section, one obtains

$$T_2^* = -qr_0 \frac{\cos \varphi}{(1 + \gamma \sin^2 \varphi)^{3/2}},$$

$$S^* = f_1(\varphi) - qx \frac{2 + \gamma(2 + \cos^2 \varphi)}{1 + \gamma \sin^2 \varphi} \sin \varphi,$$

$$T_1^* = f_2(\varphi) - \frac{x}{r_0}(1 + \gamma \sin^2 \varphi)^{3/2} \frac{df_1}{d\varphi} - \qquad (38.3)$$

$$- \frac{qx^2}{2r_0}(1 + \gamma \sin^2 \varphi)^{3/2}\left[1 - 3(1 + \gamma)\frac{1 - \gamma \sin^2 \varphi}{(1 + \gamma \sin^2 \varphi)^2}\right] \cos \varphi.$$

The two arbitrary functions $f_1(\varphi)$ and $f_2(\varphi)$ in these formulae will be determined by the condition that at the curvilinear boundaries, i.e., for $x = -l/2$, $x = +l/2$ (taking the origin for x the centre of the span), the force $T_1^* = 0$.

This condition corresponds to the case where the roof has no intermediate supports between its ends and the edge supports are analogous to those of a beam, freely supported at its ends. The more complicated, statically indeterminate case when, in addition to the terminal supports, there are intermediate supports and the roof is analogous to a beam with several supports will not be considered here.

Subjecting the last of the formulae (38.3) to the above boundary condition, one finds

$$\frac{df_1}{d\varphi} = 0,$$

$$f_2 = \frac{ql^2}{8r_0}(1 + \gamma \sin^2 \varphi)^{3/2}\left[1 - 3(1 + \gamma)\frac{1 - \gamma \sin^2 \varphi}{(1 + \gamma \sin^2 \varphi)^2}\right] \cos \varphi. \qquad (38.4)$$

By the first of these equalities,

$$f_1 = C = \text{constant.}$$

Substituting this value of f_1 into the second of the expressions (38.3), it is seen that the constant C must be set equal to zero, since, in view of the symmetry of the loading about the plane $\varphi = 0$, the shear stress S^* must be an odd function of φ.

As a result, the formulae (38.3) assume the following final form:

$$T_2^* = -qr_0 \frac{\cos\varphi}{(1+\gamma\sin^2\varphi)^{3/2}},$$

$$S^* = -qx \frac{2+\gamma(2+\cos^2\varphi)}{1+\gamma\sin^2\varphi}\sin\varphi = \frac{2x}{l} S^*\left(\frac{l}{2}, \varphi\right), \tag{38.5}$$

$$T_1^* = -\frac{q(l^2-4x^2)}{8r_0}(1+\gamma\sin^2\varphi)^{3/2}\left[1-3(1+\gamma)\frac{1-\gamma\sin^2\varphi}{(1+\gamma\sin^2\varphi)^2}\right]\cos\varphi =$$

$$= \left(1-\frac{4x^2}{l^2}\right) T_1^*(0, \varphi),$$

where

$$S^*\left(\frac{l}{2}, \varphi\right) = -\frac{ql}{2}\frac{2+\gamma(2+\cos^2\varphi)}{1+\gamma\sin^2\varphi}\sin\varphi \tag{38.6}$$

is the value of S^* in the plane of the support $x = \frac{l}{2}$ and

$$T_1^*(0, \varphi) = \frac{ql^2}{8r_0}(1+\gamma\sin^2\varphi)^{3/2}\left[1-3(1+\gamma)\frac{1-\gamma\sin^2\varphi}{(1+\gamma\sin^2\varphi)^2}\right]\cos\varphi \tag{38.7}$$

is the value of the force T_1^* in the plane $x = 0$, i.e., at the centre section. Both these functions characterize the variation of the forces S^* and T_1^* across the width of the roof.

As regards the law of change of the forces along the roof, T_2^* remains constant, by (38.5), while S^* varies linearly and T_1^* parabolically. Thus, the changes of the forces S^* and T_1^* along the length of the roof turn out to be analogous to the laws of variation of the shear and bending stresses along the length of a freely supported and uniformly loaded beam on two supports.

Consider next the displacements of the roof, assuming that $\mu = 0$ (as is very often done for calculations referring to reinforced concrete structures). For this purpose, one may in the present case write the differential equations

$$\frac{\partial u}{\partial x} = \frac{T_1^*}{E\delta} = \frac{1}{E\delta}\left(1 - 4\frac{x^2}{l^2}\right) T_1^*(0, \varphi),$$

$$\frac{\partial v}{\partial \varphi} + w = \frac{r}{E\delta} T_2^*(\varphi), \tag{38.8}$$

$$\frac{1}{r}\frac{\partial u}{\partial \varphi} + \frac{\partial v}{\partial x} = \frac{4}{E\delta}\frac{x}{l} S^*\left(\frac{l}{2}, \varphi\right).$$

Integrating the first of these equations with respect to x, one finds

$$u = f_3(\varphi) + \frac{x}{E\delta}\left(1 - \frac{4}{3}\frac{x^2}{l^2}\right) T_1^*(0, \varphi). \tag{38.9}$$

But, in view of the symmetry of the supports of the roof at the curvilinear ends, the displacements u for $x = +\frac{l}{2}$ and $x = -\frac{l}{2}$ must be equal in magnitude and opposite in sign. Hence

$$u = \frac{x}{E\delta}\left(1 - \frac{4}{3}\frac{x^2}{l^2}\right) T_1^*(0, \varphi). \tag{38.10}$$

Now, the last of the equations (38.8), after integration with respect to x, gives

$$v = f_4(\varphi) + \frac{2x^2}{E\delta l} S^*\left(\frac{l}{2}, \varphi\right) - \frac{x^2}{2E\delta}\left(1 - \frac{2}{3}\frac{x^2}{l^2}\right)\frac{1}{r}\frac{dT_1^*(0, \varphi)}{d\varphi}. \tag{38.11}$$

Subjecting this displacement to the condition that it must vanish at the curvilinear edges, one has

$$f_4(\varphi) = \frac{5}{48}\frac{l^2}{E\delta}\frac{1}{r}\frac{dT_1^*(0, \varphi)}{d\varphi} - \frac{l}{2E\delta} S^*\left(\frac{l}{2}, \varphi\right), \tag{38.12}$$

and therefore

$$v = \frac{2}{E\delta l}\left(x^2 - \frac{l^2}{4}\right) S^*\left(\frac{l}{2}, \varphi\right) + \\ + \frac{1}{3E\delta}\left(x^2 - \frac{l^2}{4}\right)\left(\frac{x^2}{l^2} - \frac{5}{4}\right)\frac{1}{r}\frac{dT_1^*(0, \varphi)}{d\varphi}. \tag{38.13}$$

Substituting this result into the second equation (38.8), one finds for the radial displacement

$$w = \frac{1}{E\delta}\left\{rT_2^*(\varphi) - \left(x^2 - \frac{l^2}{4}\right)\left[\frac{2}{l}\frac{dS^*\left(\frac{l}{2}, \varphi\right)}{d\varphi} + \right.\right. \\ \left.\left. + \frac{1}{3}\left(\frac{x^2}{l^2} - \frac{5}{4}\right)\frac{1}{r}\frac{d^2T_1^*(0, \varphi)}{d\varphi^2}\right]\right\}. \tag{38.14}$$

The formulae (38.10), (38.13), (38.14) determine all the displacements of the cylindrical roof loaded by its own weight. The quantities $T_1^*(0, \varphi)$, $S^*\left(\frac{l}{2}, \varphi\right)$, $T_2^*(\varphi)$ in these expressions are determined by (38.6), (38.7) and (38.5). In view of the complexity of the above results, there is no purpose in giving explicit formulae for the displacements.

The obtained results will now be used to compare the four different roofs shown in Fig. 50 for which the height, length, width and weight per unit length are the same.



Fig. 50.

The cross-sections of these roofs will be the same curves which were investigated in § 26 as the meridian curves of domes. In fact, the section

of roof (I) is an arc of a circle of radius R, roof (II) is an arc of a parabola, roof (III) is one half of the ellipse $\gamma = 3$, $r_0 = 1.60R$, roof IV is an arc of the ellipse $\gamma = 1.5$, $r_0 = 1.30R$. Fig. 50 shows to the same scale for all four shells the variations of the forces T_2^*, S^*, T_1^* with the height of each roof, calculated from the formulae obtained above. It is seen from these curves that normal and shear forces $T_2^*(x, \varphi_0)$, $S^*(x, \varphi_0)$ arise at the straight edges of roofs, subject to the conditions of the membrane state of stress. Both these forces must be absorbed by corresponding edge supports, so that along the straight boundaries there will be required edge girders which will be subject to bending and extension. For this purpose, the displacements of the edge beams under the loads acting on them must be equal to the displacements of the straight edges of the roof, as calculated from the formulae (38.10), (38.13), (38.14).

As it happens, not all these requirements can be fulfilled simultaneously and hence it will be impossible to design a roof which is in a membrane state of stress. In view of this situation, the analysis of thin skin roofs must take account of their bending stiffness.

The corresponding theory will be presented in Chapter III of this book. However, the membrane theory of roofs should not be considered useless, since (as will become clear in the further discussion), although it does not give a general solution of the problem, it leads in the simplest manner to one of the essential parts of the solution. In addition, the method permits the deduction of certain conclusions regarding the suitability of one or the other type of cross-section for a roof and regarding the appropriate design of the edge girders. For example, a study of the graphs in Fig. 50 shows that for the roofs (III) and (IV) the edge beams may have small bending stiffness, since the edge forces T_2^* for these roofs are small. However, the beams will require large extensional strength, in order that they may absorb the considerable shear forces at the edges, which are characteristic for this type of roof.

Hence the conclusion is reached that for the roofs (III) and (IV) the ideal edge girder will be a flexible, but very strong rope. In contrast, for the roofs (I) and (II), the edge forces T_2^* will be appreciable and therefore these roofs require deep edge girders. In this respect, the parabolic roof (II), in general, exhibits irrational features in that the pressure transmitted along the straight edges even exceeds the weight of the roof. This contradicts the basic principle accepted to-day by which the major part of the load should be transmitted to the curved boundaries.

CHAPTER III

THE ANALYSIS OF CYLINDRICAL SHELLS

§ 39. Historical introduction

In the theory of cylindrical shells, the fundamental problems are concerned with the analysis of complete cylindrical shells (tubes) and with the analysis of partial cylindrical shells, the boundaries of which are a pair of generators and a pair of cross-sections of the cylinder (cylindrical plates). The customary methods of solution of these two fundamental problems employ double and single trigonometric series respectively. Greater usefulness attaches to the method of single Fourier series which permits the solutions to be subjected to arbitrary boundary conditions along two edges of the shell. Utilization of one or the other method is made essentially more difficult by the complexity and the high order of the differential equations of the problems in view of which a great deal of attention must be given to the simplification of the initial formulae. In this connection, it has been found that the choice of one or the other system of simplifications depends on the ratios of the dimensions of the cylindrical shells.

Thus, it will be convenient to subdivide cylindrical shells into the following classes:

(a) Very long shells (thin walled rods) for which the length is many times greater than the average value of the radius of curvature (or the maximum dimension of the cross section);

(b) long shells for which the length is several times the average radius of curvature;

(c) medium length shells for which the length is comparable with the average radius of curvature;

(d) short shells for which the length is some fraction of the average radius of curvature.

For long and very long shells, V. Z. Vlasov [88] has proposed a special theory which may be called the "semi-membrane" theory. In this theory, the moments M_1, H and the normal shear force N_1 are neglected in the equilibrium equations for a element shell (which has led to the suggestion of the above name).

Using in addition to the above simplifications several additional assumptions (in particular, neglecting the strain ε_2 and the shear strain ω), Vlasov reduced the analysis of circular cylindrical shells to the solution of an equation of the form

$$\frac{\partial^4 \Phi_1}{\partial \eta^4} + \frac{\partial^2 \Phi_1}{\partial \eta^2} + i2b^2 \frac{\partial^2 \Phi_1}{\partial \xi^2} = F_1(\xi, \eta), \tag{39.1}$$

where $2b^2$ is a constant and F_1 is a given function of ξ and η. Later on this equation was extended by Vlasov to apply to non-circular cylindrical shells. In this last case, it takes the form

$$\frac{\partial^2}{\partial \eta^2} \rho \frac{\partial^2 \Phi_1}{\partial \eta^2} + \frac{\partial}{\partial \eta}\left(\frac{1}{\rho} \frac{\partial \Phi_1}{\partial \eta}\right) + i2b^2 \frac{\partial^2 \Phi_1}{\partial \xi^2} = F_2(\xi, \eta), \tag{39.2}$$

where $\rho(\eta)$ is the radius of curvature of the cross-section of the shell, divided by its mean value. In this way the foundations were laid for the general theory of thin-walled rods.

After adding the assumption that the cross-section of the shell remains undeformed, one may develop a semi-membrane theory which has proved very useful for the analysis of thin walled rods with open profiles [90]. Subsequently this approximate method was placed on a sound foundation in the works of G. I. Dzhanelidze [101] and A. L. Gol'denweizer [100]. In connection with the analysis of thin-walled rods, one should also mention the engineering theory of torsion of tubes of non-circular cross-section, developed by A. A. Umanski [112]. As regards long shells, it will be shown below that one may obtain even simpler equations than (39.1), (39.2), namely

$$\frac{\partial^4 \Phi_1}{\partial \eta^4} + i2b^2 \frac{\partial^2 \Phi_1}{\partial \xi^2} = F_1(\xi, \eta), \tag{39.3}$$

$$\frac{\partial^2}{\partial \eta^2}\left(\rho \frac{\partial^2 \Phi_1}{\partial \eta^2}\right) + i2b^2 \frac{\partial^2 \Phi_1}{\partial \xi^2} = F_2(\xi, \eta). \tag{39.4}$$

The first of these equations refers to circular, the second to non-circular shells.

It will be noted that for non-circular shells the transition from (39.2) to (39.4) simplifies the problem in form rather than in essence, since the omitted term is necessary for the transformation. However, when speaking of circular cylindrical shells, the replacement of the equation (39.1) by (39.3) gives an essential simplification. A theory arising from the equation (39.3) was proposed by S. Feinberg [113] and worked out in detail by the Author in the book [27].

For short and medium length shells, one has to employ a principally different scheme of simplification, based on the neglect of the tangential displacements in the formulae for the change of the curvature and twist, and likewise of the normal shear force in the second equilibrium equation (as has been mentioned in § 17, these two simplifications are interrelated). As a result of the above simplifying assumptions, the analysis of circular cylindrical shells under arbitrary loading may be reduced to the solution of the differential equation

$$\Delta\Delta\Phi + i2b^2 \frac{\partial^2 \Phi}{\partial \xi^2} = F_2(\xi, \eta), \tag{39.5}$$

where $\Delta(\ldots) = \dfrac{\partial^2(\ldots)}{\partial \eta^2} + \dfrac{\partial^2(\ldots)}{\partial \xi^2}$.

This system of simplifications was first recommended by Kh. M. Mushtari (see [21] and earlier work by the same author). However, the final equation (39.5) seems to have appeared first in the work of Feinberg [113], devoted to a valuable criticism of the book by Vlasov [87]. The detailed method for the analysis of cylindrical plates, based on the equation (39.5), was developed by the Author of this book [27]. Later on, this equation was employed by A. I. Lur'e [18], Vlasov [91] and their pupils. Starting from equation (39.1), Lur'e succeeded in solving the problem of the stress concentration in a circular cylindrical shell, weakened by a small circular cut-out [102].

In connection with the appearance of the complex transformation of the differential equations of the theory of shells [32], it was found possible to obtain a sufficiently simple, general equation embracing all the types of cylindrical shells listed above [106]. Adapted to shells of arbitrary cross-section, this equation has the form

$$\Delta\rho\Delta\tilde{T} + \frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial \tilde{T}}{\partial \eta}\right) + i2b^2 \frac{\partial^2 \tilde{T}}{\partial \xi^2} = F(\xi, \eta). \tag{39.6}$$

Neglecting in this equation the term

$$\frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial \tilde{T}}{\partial \eta}\right)$$

and putting $\rho = 1$, one obtains an equation of the form (39.5).

Alternatively, neglecting in (39.6) the term $\dfrac{\partial^2 \tilde{T}}{\partial \xi^2}$ in comparison with $\dfrac{\partial^2 \tilde{T}}{\partial \eta^2}$ (with the exception of the last term on the left hand side of the

equation (39.6), since it has the factor $i2b^2$ which has a very large modulus), one obtains an equation of the form (39.2). Finally, applying both the above simplifying assumptions, one finds equations of the form (39.3), (39.4). Thus, equation (39.6) actually comprises all the above fundamental variants of the approximate theory of cylindrical shells (circular as well as non-circular). Based on this equation, it has been possible to develop an effective method for the analysis of tubes with non-circular cross-sections and of arbitrary length [106].

In conclusion, it is necessary to dwell on the analysis of cylindrical shells reinforced by equidistant transverse ribs (a problem of considerable practical importance). When the ribs are sufficiently numerous, a significant simplification is achieved by treating the shell as structurally "anisotropic". This method is based on the replacement of the shell with ribs by an approximately equivalent shell without ribs, which has different bending stiffness in the two principal directions.

In such a case, the analysis of a circular cylindrical shell, reinforced by frequent ribs, reduces to the solution of an equation of the form

$$\frac{\partial^2}{\partial\eta^2}\Delta(\tilde{T}) + \frac{\partial^2\tilde{T}}{\partial\eta^2} + i2a^2\frac{\partial^2\tilde{T}}{\partial\xi^2} = F(\xi,\eta), \tag{39.7}$$

where $2a^2$ is a constant (see § 45).

§ 40. The equations of the theory of cylindrical shells in complex form

In this development of a general theory of cylindrical shells it is proposed to discuss the problem in terms of complex forces.

Determining the position of a point on the cylindrical surface by the coordinates x and s (i.e., the distance along the generator and the length of arc around a contour — see Fig. 51), it is convenient to introduce instead of these dimensional coordinates the two dimensionless quantities



Fig. 51.

$$\xi = \frac{x}{r_0}, \quad \eta = \frac{s}{r_0}, \tag{40.1}$$

where r_0 is a constant quantity, characteristic for the shell and having the dimension of length. For example, one may take for r_0 the radius of the circle the circumference of which is equal to that of the cross-section

of the shell, i.e.,

$$r_0 = \frac{2s_0}{\pi}$$

(s_0 — being a quarter of the length of arc of the transverse section of the cylinder). In the examples given below, the maximum value of the radius of curvature of the cross-section of the cylinder has been taken as r_0.

The Lamé parameters in the given case are

$$A_1 = A_2 = r_0, \tag{40.2}$$

whence the equations of shell theory in terms of complex forces [equations (16.10)], may for the present be written in the form

$$\begin{aligned}
&\frac{\partial \tilde{T}_1}{\partial \xi} + \frac{\partial \tilde{S}}{\partial \eta} = -q_1 r_0, \\
&\frac{\partial \tilde{S}}{\partial \xi} + \frac{\partial \tilde{T}_2}{\partial \eta} + \frac{i}{2b^2}\frac{1}{\rho}\frac{\partial \tilde{T}}{\partial \eta} = -q_2 r_0, \\
&\tilde{T}_2 - \frac{i}{2b^2}\rho \Delta(\tilde{T}) = \rho \tilde{q}_n r_0,
\end{aligned} \tag{40.3}$$

where

$$\begin{aligned}
&\rho(\eta) = \frac{r}{r_0}, \\
&4b^4 = 12(1-\mu^2)\frac{r_0^2}{\delta^2}, \\
&\Delta(\ldots) = \frac{\partial^2(\ldots)}{\partial \xi^2} + \frac{\partial^2(\ldots)}{\partial \eta^2}, \\
&\tilde{T} = \tilde{T}_1 + \tilde{T}_2, \\
&\tilde{q}_n = q_n + i\frac{(1+\mu)}{2b^2}\left(\frac{\partial q_1}{\partial \xi} + \frac{\partial q_2}{\partial \eta}\right) \approx q_n.
\end{aligned} \tag{40.4}$$

The complex forces in these formulae are related to the forces and moments by means of the expressions (16.8), viz.,

$$\begin{aligned}
\tilde{T}_1 &= T_1 - i\frac{2b^2}{r_0}\frac{M_2 - \mu M_1}{1-\mu^2}, \\
\tilde{T}_2 &= T_2 - i\frac{2b^2}{r_0}\frac{M_1 - \mu M_2}{1-\mu^2}, \\
\tilde{S} &= S + i\frac{2b^2}{r_0}\frac{H}{1-\mu}.
\end{aligned} \tag{40.5}$$

Also q_1, q_2, q_n are the components of the surface loading in the directions x, s and along the normal to the middle surface.

Eliminating the unknown $\tilde{S}$ from the equations (40.3), one finds

$$\begin{aligned} &\frac{\partial^2 \tilde{T}}{\partial \xi^2} - \Delta(\tilde{T}_2) - \frac{i}{2b^2}\frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial \tilde{T}}{\partial \eta}\right) = r_0\left(\frac{\partial q_2}{\partial \eta} - \frac{\partial q_1}{\partial \xi}\right), \\ &\tilde{T}_2 - \frac{i}{2b^2}\rho\Delta(\tilde{T}) = \tilde{q}_n r_0 \rho. \end{aligned} \tag{40.6}$$

Substituting now for $\tilde{T}_2$ from the second into the first equation (40.6), one arrives at the following differential equation of fourth order in a single unknown — the auxiliary function $\tilde{T}$:

$$\Delta[\rho\Delta(\tilde{T})] + \frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial \tilde{T}}{\partial \eta}\right) + i2b^2\frac{\partial^2 \tilde{T}}{\partial \xi^2} = i2b^2 r_0\left[\Delta(\rho\tilde{q}_n) + \frac{\partial q_2}{\partial \eta} - \frac{\partial q_1}{\partial \xi}\right]. \tag{40.7}$$

The analysis of cylindrical shells of arbitrary form has thus been reduced to the solution of this equation, since, once $\tilde{T}$ is known, one may immediately find all the complex forces and then the complex displacements. It will now be shown how this may be accomplished.

The third of the equations (40.3) gives directly

$$\tilde{T}_2 = i\frac{\rho}{2b^2}\Delta(\tilde{T}) + \tilde{q}_n r_0 \rho, \tag{40.8}$$

and hence, since $\tilde{T}_1 = \tilde{T} - \tilde{T}_2$,

$$\tilde{T}_1 = \tilde{T} - i\frac{\rho}{2b^2}\Delta(\tilde{T}) - \tilde{q}_n \rho r_0. \tag{40.9}$$

Substituting this value for $\tilde{T}_2$ into the second of the equations (40.3), one has

$$\frac{\partial \tilde{S}}{\partial \xi} = -\frac{i}{2b^2}\left\{\frac{\partial}{\partial \eta}[\rho\Delta(\tilde{T})] + \frac{1}{\rho}\frac{\partial \tilde{T}}{\partial \eta}\right\} - r_0\left[\frac{\partial(\tilde{q}_n\rho)}{\partial \eta} + q_2\right]. \tag{40.10}$$

Further, on the basis of the first of the equations (40.3) and the formula (40.9), one may write

$$\frac{\partial \tilde{S}}{\partial \eta} = -\frac{\partial \tilde{T}}{\partial \xi} + i\frac{\rho}{2b^2}\frac{\partial}{\partial \xi}[\Delta(\tilde{T})] + r_0\left(\rho\frac{\partial \tilde{q}_n}{\partial \xi} - q_1\right). \tag{40.11}$$

The formulae (40.10) and (40.11) together determine the complex force $\tilde{S}$ in terms of $\tilde{T}$. Thus all the complex forces have been expressed in terms of this auxiliary function $\tilde{T}$.

There remains to express the complex displacements in terms of $\tilde{T}$. Using the formulae (16.11), (16.12) and (4.23) and applying them to cylindrical shells (taking into consideration that for this case $A_1=A_2=r_0$, $R_1=\infty$, $R_2=\rho r_0$), one obtains for the determination of the complex displacements the relations

$$\begin{aligned} r_0\tilde{\varepsilon}_1 &= \frac{\partial\tilde{u}}{\partial\xi} = \frac{r_0}{E\delta}(\tilde{T}_1 - \mu\tilde{T}_2), \\ r_0\tilde{\varepsilon}_2 &= \frac{\partial\tilde{v}}{\partial\eta} + \frac{\tilde{w}}{\rho} = \frac{r_0}{E\delta}(\tilde{T}_2 - \mu\tilde{T}_1), \\ r_0\tilde{\omega} &= \frac{\partial\tilde{u}}{\partial\eta} + \frac{\partial\tilde{v}}{\partial\xi} = \frac{2(1+\mu)r_0}{E\delta}\tilde{S}. \end{aligned} \tag{40.12}$$

$$\begin{aligned} r_0^2\tilde{\kappa}_1 &= -\frac{\partial^2\tilde{w}}{\partial\xi^2} = i\frac{2b^2r_0}{E\delta}(\tilde{T}_2 - T_2^*), \\ r_0^2\tilde{\kappa}_2 = r_0\frac{\partial\tilde{\psi}}{\partial\eta} &= -\frac{\partial}{\partial\eta}\left(\frac{\partial\tilde{w}}{\partial\eta} - \frac{\tilde{v}}{\rho}\right) = i\frac{2b^2r_0}{E\delta}(\tilde{T}_1 - T_1^*), \\ r_0^2\tilde{\tau} = r_0\frac{\partial\tilde{\psi}}{\partial\xi} &= -\frac{\partial^2\tilde{w}}{\partial\xi\partial\eta} + \frac{1}{\rho}\frac{\partial\tilde{v}}{\partial\xi} = -i\frac{2b^2r_0}{E\delta}(\tilde{S} - S^*). \end{aligned} \tag{40.13}$$

in which T_1^*, T_2^*, S^* are any solutions of the membrane equations, i.e., in the given case solutions of the equations

$$\begin{aligned} \frac{\partial T_1^*}{\partial\xi} + \frac{\partial S^*}{\partial\eta} &= -q_1r_0, \\ \frac{\partial S^*}{\partial\xi} + \frac{\partial T_2^*}{\partial\eta} &= -q_2r_0, \\ T_2^* &= q_n\rho r_0. \end{aligned} \tag{40.14}$$

But, as has been established in Chapter II, the system of equations of the membrane theory applicable to cylindrical shells can always be integrated. For example, in the particular case when q_1, q_2 and q_n do not depend on ξ, one has for the solutions of the equations (40.14) the expressions

$$\begin{aligned} T_2^* &= q_nr_0\rho, \\ S^* &= -\xi r_0\left(\frac{dq_n\rho}{d\eta} + q_2\right), \\ T_1^* &= \frac{\xi^2}{2}r_0\left[\frac{d^2q_n\rho}{d\eta^2} + \frac{dq_2}{d\eta}\right] - q_1r_0\xi, \end{aligned} \tag{40.15}$$

which must be introduced in the above case on the right hand sides of the formulae (40.13).

The two systems (40.12) and (40.13) together determine the complex displacements in terms of the complex forces or, since the complex forces can be expressed in terms of the auxiliary function $\tilde{T}$, it may also be said that they determine the complex displacements in terms of $\tilde{T}$.

It must be emphasized that the systems (40.12) and (40.13) will usually be only approximate, — exact to terms of order $\frac{\delta}{r_0}$ compared with unity, since terms of that order were repeatedly neglected in the derivation of the equations (16.11), (16.12). Therefore, in the process of transformation and solution of the equations (40.12) and (40.13), there will be discovered inconsistencies in small terms which must be removed by corresponding arguments.

Having found the general solution of the systems (40.12) and (40.13), i.e., having determined $\tilde{u}$, $\tilde{v}$, $\tilde{w}$, one may immediately find also the displacements u, v, w, since they are equal to the real parts of the former. On the basis of the system (40.12) and taking into consideration that the complex forces can be expressed in terms of the auxiliary function $\tilde{T}$ which is a solution of the equation (40.7), one may obtain by (40.8), (40.9) and (40.10) the following expressions for the derivatives of the complex displacements:

$$\frac{\partial \tilde{u}}{\partial \xi} = \frac{r_0}{E\delta}\left[\tilde{T} - i\,\frac{1+\mu}{2b^2}\,\rho\Delta(\tilde{T})\right] - (1+\mu)\,\frac{r_0^2}{E\delta}\,\rho\tilde{q}_n,$$

$$\frac{\partial^2 \tilde{v}}{\partial \xi^2} = -\frac{r_0}{E\delta}\left\{\left(1 + i\,\frac{1+\mu}{\rho b^2}\right)\frac{\partial \tilde{T}}{\partial \eta} + i\,\frac{1+\mu}{2b^2}\,\frac{\partial}{\partial \eta}\left[\rho\Delta(\tilde{T})\right]\right\} -$$

$$- \frac{(1+\mu)r_0^2}{E\delta}\,\frac{\partial(\rho\tilde{q}_n)}{\partial \eta} - \frac{2(1+\mu)}{E\delta}\,r_0^2 q_2, \qquad (40.16)$$

$$\frac{\partial^2 \tilde{w}}{\partial \xi^2} = \frac{r_0}{E\delta}\,\rho\left[\Delta(\tilde{T}) + i\,\frac{1+\mu}{2b^2}\,\frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\,\frac{\partial \tilde{T}}{\partial \eta}\right)\right] + \frac{(1+\mu)r_0^2\rho}{E\delta}\left(\frac{\partial q_1}{\partial \xi} + \frac{\partial q_2}{\partial \eta}\right).$$

These expressions, directly linking the derivatives of the complex displacements with respect to ξ with the auxiliary function $\tilde{T}$, will repeatedly be used in what follows.

§ 41. The theory of cylindrical shells, reinforced by transverse ribs

In order to ensure the strength and stability of cylindrical shells, it is often convenient to reinforce them by closely spaced transverse

stiffeners (Fig. 52). The analysis of such shells turns out to be a very difficult problem, if it is desired to satisfy exactly the conditions which prevail at the junction between the rings and the actual skin. However, at the present time, no use will be made of this complicated approach. Instead, an approximate method will be employed which consists of distributing the bending stiffness and tensile strength of each rib uniformly over the width of the bay, supported by the rib, and of adding it to the corresponding stiffness of the shell in the circumferential direction. Under these conditions, the shell with ribs is replaced in the analysis by an approximately equivalent shell without ribs, where this last shell exhibits different elastic properties in the longitudinal and circumferential directions, i.e., it is anisotropic (or better "orthotropic"). If the ribs are sufficiently closely spaced and their number is sufficiently large, then the described method involves relatively small errors. At the same time, the method greatly simplifies the problem. These two properties are the reason for the wide application which the method has found recently. Anisotropic behaviour of the above type may be called constructional, since it does not result from a property of the material, but from the manner in which it is distributed.



Fig. 52.

The relations between the forces, moments and strains of the middle surface for cylindrical shells, reinforced by transverse equidistant ribs and conceived as constructionally anisotropic will now be established. For this purpose, it will be assumed that the ribs possess bending and extensional stiffness in their own plane only and that the resistance to displacements perpendicular to their plane and to torsion may be neglected.

Then it is obvious that the ribs will not influence the shear displacement or the torsion of the shell, as a result of which one will have for S and H the usual formulae

$$S = \frac{E\delta}{2(1+\mu)}\omega, \quad H = \frac{E\delta^3}{12(1+\mu)}\tau \tag{41.1}$$

The remaining forces and moments require a special study. The

formulae for their determination can be deduced, if one takes into account that for transverse bending the axis of rotation of the cross-section will pass through the centre of gravity of the profile, formed by the rib and the associated shell section. Let the distance of this point from the middle surface be denoted by z_0 (Fig. 53). Then the strains



Fig. 53.

of a fibre of the shell parallel to the middle surface may be represented by

$$e_{xx} = \varepsilon_1 + z\kappa_1,$$

$$e_{\eta\eta} = \frac{1}{1 + \dfrac{z'}{r - z_0}} (\varepsilon_2' + z'\kappa_2') \approx \varepsilon_2' + z'\kappa_2', \tag{41.2}$$

where z is the distance measured from the middle surface (in the direction of the convex side) and $z' = z + z_0$ is the distance from the centre of gravity of the profile measured in the same direction. Also, ε_2' and $\kappa_2' \approx \kappa_2$ are the direct strain and parameter for the change of curvature of the neutral axis of the profile. Hence the stresses in the shell can be written in the form

$$\sigma_{xx} = \frac{E}{1 - \mu^2}[\varepsilon_1 + z\kappa_1 + \mu(\varepsilon_2' + z'\kappa_2')], \qquad -\frac{\delta}{2} \leqslant z \leqslant \frac{\delta}{2},$$

$$\sigma_{\eta\eta} = \frac{E}{1 - \mu^2}[\varepsilon_2' + z'\kappa_2' + \mu(\varepsilon_1 + z\kappa_1)], \qquad -\frac{\delta}{2} \leqslant z \leqslant \frac{\delta}{2}, \tag{41.3}$$

$$\sigma_{\eta\eta} = E(\varepsilon_2' + z\kappa_2') \qquad z_0 - \frac{\delta}{2} \geqslant z \geqslant -\left(h - z_0 + \frac{\delta}{2}\right).$$

In the brackets on the right the limits are indicated between which these formulae hold true, where h is the height of the profile.

The first of the formulae (41.3) will now be integrated with respect

to z over the thickness of the shell. Then one obtains

$$T_1 = \int_{-\frac{\delta}{2}}^{+\frac{\delta}{2}} \sigma_{xx} dz = \frac{E\delta}{1-\mu^2} [\varepsilon_1 + \mu(\varepsilon_2' + z_0\kappa_2')]. \tag{41.4}$$

But $\varepsilon_2' + z_0\kappa_2' = \varepsilon_2$, where ε_2 is the extension of the middle surface. Hence one obtains for T_1 the usual expression

$$T_1 = \frac{E\delta}{1-\mu^2} (\varepsilon_1 + \mu\varepsilon_2). \tag{41.5}$$

Similarly, multiplying the first of the formulae (41.3) by z and integrating over the thickness, one obtains the usual formula for M_1

$$M_1 = \frac{E\delta^3}{12(1-\mu^2)} (\kappa_1 + \mu\kappa_2). \tag{41.6}$$

Next, the stress $\sigma_{\eta\eta}$ will be integrated over the entire area of the profile (which comprises the area of the section of the rib Ω and the area of the associated shell section $l\delta$) taking into consideration for this purpose both the second and the third of the formulae (41.3). This gives

$$T_2 l = E\left[\left(\Omega + \frac{l\delta}{1-\mu^2}\right)\varepsilon_2 + \mu \frac{l\delta}{1-\mu^2} \varepsilon_1\right], \tag{41.7}$$

or

$$T_2 = \frac{E\delta}{1-\mu^2}\left[\left(1 + \frac{(1-\mu^2)\Omega}{l\delta}\right)\varepsilon_2 + \mu\varepsilon_1\right]. \tag{41.8}$$

Finally, multiplying $\sigma_{\eta\eta}$ by z' and integrating again over the entire area of the profile, one finds

$$M_2 l = E\left[J\kappa_2 + \mu \frac{\delta^3 l}{12(1-\mu^2)} \kappa_1\right], \tag{41.9}$$

where J is the moment of inertia of the profile (including the associated shell portion).

It will be noted that the bending stiffness of the rib per unit length of bay between ribs, i.e., the quantity $\frac{EJ}{l}$, is obviously considerably larger than the stiffness of the cylindrical panel $\frac{E\delta^3}{12(1-\mu^2)}$. The area of the cross-section of the rib per unit length of bay between ribs, i.e., the

quantity $\frac{\Omega}{l}$, obviously turns out to be only a fraction of the thickness δ of the shell.

The above observations will now be used to simplify the formulae (41.8) and (41.9) to the following forms:

$$\begin{aligned} T_2 &\approx \frac{E\delta}{1-\mu^2}(\varepsilon_2 + \mu\varepsilon_1), \\ M_2 &\approx \frac{EJ}{l}\kappa_2. \end{aligned} \tag{41.10}$$

Formulae (41.1), (41.5), (41.6) and (41.10) express the dependence between the forces, moments and strains of the middle surface for cylindrical shells, reinforced by transverse ribs.

Now the equations of equilibrium for the element of a constructionally anisotropic cylindrical shell will be established. Applying the general equations of the first chapter to shells of the present shape and taking into consideration that the bending stiffness of the panel is to be neglected in comparison with the bending stiffness of the rib, one has to neglect in the equilibrium equations the moments M_1 and H in comparison with M_2 and will thus obtain

$$\begin{aligned} &\frac{\partial T_1}{\partial \xi} + \frac{\partial S}{\partial \eta} = -q_1 r_0, \\ &\frac{\partial S}{\partial \xi} + \frac{\partial T_2}{\partial \eta} + \frac{N_2}{\rho} = -q_2 r_0, \\ &\frac{\partial N_2}{\partial \eta} - \frac{T_2}{\rho} + q_n r_0 = 0, \\ &r_0 N_2 = \frac{\partial M_2}{\partial \eta}. \end{aligned} \tag{41.11}$$

Here, the fifth equilibrium equation, as a result of the omission of M_1 and H, has not to be retained and the sixth equation reduces to

$$T_{12} = T_{21} = S.$$

The system (41.11) consists of four equations for five unknowns. The missing equation may be obtained from the compatibility relations for the middle surface (5.1). These last, adapted to cylindrical shells, have

the form

$$\frac{\partial \kappa_2}{\partial \xi} - \frac{\partial \tau}{\partial \eta} = 0,$$

$$\frac{\partial \kappa_1}{\partial \eta} - \frac{\partial \tau}{\partial \xi} + \frac{1}{r_0 \rho}\left(\frac{\partial \omega}{\partial \xi} - \frac{\partial \varepsilon_1}{\partial \eta}\right) = 0, \tag{41.12}$$

$$\frac{\kappa_1}{\rho} + \frac{1}{r_0}\left(\frac{\partial^2 \varepsilon_1}{\partial \eta^2} + \frac{\partial^2 \varepsilon_2}{\partial \xi^2} - \frac{\partial^2 \omega}{\partial \xi \partial \eta}\right) = 0.$$

[Cf. the formulae (5.1) and (40.1) and (40.2)] Eliminating between these equations κ_1 and τ, one finds

$$r_0 \frac{\partial^2 \kappa_2}{\partial \xi^2} + \frac{\partial^2}{\partial \eta^2}\left[\rho\left(\frac{\partial^2 \varepsilon_1}{\partial \eta^2} + \frac{\partial^2 \varepsilon_2}{\partial \xi^2} - \frac{\partial^2 \omega}{\partial \xi \partial \eta}\right)\right] + \frac{\partial}{\partial \eta}\left[\frac{1}{\rho}\left(\frac{\partial \varepsilon_1}{\partial \eta} - \frac{\partial \omega}{\partial \xi}\right)\right] = 0. \tag{41.13}$$

There still remains to introduce in these formulae for the strains their expressions in terms of the forces and moments (41.1), (41.5), (41.10). In this way one arrives at the relation

$$\frac{r_0^2 l \delta}{J}\frac{\partial^2 M_2}{\partial \xi^2} + r_0\left\{\frac{\partial^2}{\partial \eta^2}\rho\left[\frac{\partial^2 (T_1 - \mu T_2)}{\partial \eta^2} + \frac{\partial^2 (T_2 - \mu T_1)}{\partial \xi^2} - 2(1+\mu)\frac{\partial^2 S}{\partial \xi \partial \eta}\right] + \right.$$

$$\left. + \frac{\partial}{\partial \eta}\frac{1}{\rho}\left[\frac{\partial (T_1 - \mu T_2)}{\partial \eta} - 2(1+\mu)\frac{\partial S}{\partial \xi}\right]\right\} = 0. \tag{41.14}$$

This last formula may be transformed to a more convenient form, if one takes into consideration that by (41.11)

$$2\frac{\partial^2 S}{\partial \xi \partial \eta} = -\frac{\partial^2 T_1}{\partial \xi^2} - \frac{\partial^2 T_2}{\partial \eta^2} - \frac{1}{r_0}\frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial M_2}{\partial \eta}\right) - r_0\left(\frac{\partial q_1}{\partial \xi} + \frac{\partial q_2}{\partial \eta}\right),$$

$$T_2 = \frac{\rho}{r_0}\frac{\partial^2 M_2}{\partial \eta^2} + q_n \rho r_0, \quad \frac{\partial S}{\partial \xi} = -\frac{\partial T_2}{\partial \eta} - \frac{1}{r_0 \rho}\frac{\partial M_2}{\partial \eta} - q_2 r_0. \tag{41.15}$$

Substituting from (41.15) into (41.14), one has

$$\frac{r_0 l \delta}{J}\frac{\partial^2 M_2}{\partial \xi^2} + \frac{\partial^2}{\partial \eta^2}[\rho \Delta (T_1 + T_2)] + \frac{\partial}{\partial \eta}\left[\frac{1}{\rho}\frac{\partial (T_1 + T_2)}{\partial \eta}\right] +$$

$$+ \frac{(1+\mu)}{r_0}\left\{\frac{\partial}{\partial \eta}\frac{1}{\rho}\frac{\partial}{\partial \eta}\rho\frac{\partial^2 M_2}{\partial \eta^2} + \frac{\partial^2}{\partial \eta^2}\rho\frac{\partial}{\partial \eta}\frac{1}{\rho}\frac{\partial M_2}{\partial \eta} + 2\frac{\partial}{\partial \eta}\left(\frac{1}{\rho^2}\frac{\partial M_2}{\partial \eta}\right)\right\} +$$

$$+ (1+\mu) r_0\left[\frac{\partial^2}{\partial \eta^2}\rho\left(\frac{\partial q_1}{\partial \xi} + \frac{\partial q_2}{\partial \eta}\right) + \frac{\partial}{\partial \eta}\frac{1}{\rho}\left(\frac{\partial q_n \rho}{\partial \eta} + q_2\right)\right] = 0. \tag{41.16}$$

The relation so obtained is complicated enough. However, fortunately

the most cumbersome of its terms (in fact, the term involving M_2 and contained between braces) is unimportant and may be neglected, as will be shown somewhat later when applying the above theory to circular cylinders (§ 45).

Another equation involving the same two unknowns (M_2 and $T = T_1 + T_2$) may be obtained from (41.11). Eliminating from these equations all unknowns except T_1 and M_2, one finds

$$r_0 \frac{\partial^2 T_1}{\partial \xi^2} - \frac{\partial^2}{\partial \eta^2}\left[\rho \frac{\partial^2 M_2}{\partial \eta^2}\right] - \frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial M_2}{\partial \eta}\right) = r_0^2\left[\frac{\partial^2 (q_n \rho)}{\partial \eta_2} + \frac{\partial q_2}{\partial \eta} - \frac{\partial q_1}{\partial \xi}\right]. \tag{41.17}$$

Adding this equation to the equation

$$r_0 \frac{\partial^2 T_2}{\partial \xi^2} - \rho \frac{\partial^4 M_2}{\partial \xi^2 \partial \eta^2} = \rho r_0^2 \frac{\partial^2 q_n}{\partial \xi^2}, \tag{41.18}$$

obtained from the last two equations of (41.11), one has

$$r_0 \frac{\partial^2 (T_1+T_2)}{\partial \xi^2} - \Delta\left(\rho \frac{\partial^2 M_2}{\partial \eta^2}\right) - \frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial M_2}{\partial \eta}\right) = r_0^2\left[\Delta(\rho q_n) + \frac{\partial q_2}{\partial \eta} - \frac{\partial q_1}{\partial \xi}\right]. \tag{41.19}$$

The equations (41.16) and (41.19) will now be rewritten and at the same time the first of these equations will be simplified in the above stated manner:

$$\begin{gathered} \frac{\partial^2 (T_1 + T_2)}{\partial \xi^2} - \frac{1}{r_0}\left\{\Delta\left[\rho \frac{\partial^2 M_2}{\partial \eta^2}\right] + \frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial M_2}{\partial \eta}\right)\right\} = r_0 F_1(\xi, \eta), \\ \frac{4a^4}{r_0}\frac{\partial^2 M_2}{\partial \xi^2} + \frac{\partial^2}{\partial \eta^2}[\rho \Delta (T_1+T_2)] + \frac{\partial}{\partial \eta}\left[\frac{1}{\rho}\frac{\partial (T_1+T_2)}{\partial \eta}\right] = r_0 F_2(\xi, \eta), \end{gathered} \tag{41.20}$$

where

$$4a^4 = \frac{r_0^2 l \delta}{J},$$

$$F_1(\xi, \eta) = \Delta(\rho q_n) + \frac{\partial q_2}{\partial \eta} - \frac{\partial q_1}{\partial \xi}, \tag{41.21}$$

$$F_2(\xi, \eta) = -(1+\mu)\left\{\frac{\partial^2}{\partial \eta^2}\rho\left(\frac{\partial q_1}{\partial \xi} + \frac{\partial q_2}{\partial \eta}\right) + \frac{\partial}{\partial \eta}\frac{1}{\rho}\left(\frac{\partial q_n \rho}{\partial \eta} + q_2\right)\right\}.$$

The analysis of cylindrical shells of arbitrary shape, reinforced by equidistant transverse ribs of equal strength also leads to the solution of the system (41.20).

Unfortunately, a complex transformation of the equations (41.20) is not possible or, more correctly, is only possible in the case when $\rho = 1$, i.e., when the cylinder is circular. In this last case, one may introduce the complex auxiliary function

$$\tilde{V} = T_1 + T_2 - i\frac{2a^2}{r_0} M_2, \tag{41.22}$$

which satisfies the differential equation

$$\frac{\partial^2}{\partial \eta^2} \Delta(\tilde{V}) + \frac{\partial^2 \tilde{V}}{\partial \eta^2} + i2a^2 \frac{\partial^2 \tilde{V}}{\partial \xi^2} = i2a^2 F_1. \tag{41.23}$$

This particular case is considered in detail in § 45.

§ 42. The analysis of cylindrical plates

The results of § 40 will now be applied to the analysis of curved plates, removed from circular cylindrical shells by two cuts along generators and two cuts perpendicular to the axis of the shell.

For circular cylindrical shells

$$\rho = \frac{r}{r_0} = 1,$$

and the fundamental differential equation (40.7) takes the form

$$\Delta\Delta(\tilde{T}) + \frac{\partial^2 \tilde{T}}{\partial \varphi^2} + i2b^2 \frac{\partial \tilde{T}}{\partial \xi^2} = i2b^2 r_0 \left[\Delta(q_n) + \frac{\partial q_2}{\partial \varphi} - \frac{\partial q_1}{\partial \xi} \right], \tag{42.1}$$



Fig. 54.

where by (40.4)

$$\Delta(\ldots) = \frac{\partial^2(\ldots)}{\partial \xi^2} + \frac{\partial^2(\ldots)}{\partial \varphi^2},$$

$$4b^4 = \frac{12(1-\mu^2) r_0^2}{\delta^2}.$$

In the present particular case, it is more customary to take instead of η the symbol φ, where φ has the simple geometrical meaning of the angle corresponding to the arc length s. This angle will always be measured from the plane of symmetry of the cylindrical plate (see Fig. 54).

In practical problems, it is ordinarily possible to assume that the

curvilinear edges of cylindrical plates rest freely on supports which are absolutely rigid in their planes. The boundary conditions at the curvilinear edges thus reduce to the equalities

$$v = w = T_1 = M_1 = 0, \tag{42.2}$$

which hold true for $\xi = 0$, $\xi_0 = \dfrac{L}{r_0}$ (where L is the length of the plate and the origin for ξ has been taken at one of the curvilinear edges). As regards the boundary conditions at the straight edges ($\varphi = \varphi_0$ and $\varphi = -\varphi_0$), they may vary greatly, so that in solving the equations (42.1) one has, if possible, to preserve the possibility of leaving them arbitrary.

A solution, satisfying all the above mentioned requirements, can be obtained by expanding the components of the surface loading in ordinary trigonometric series in terms of the coordinate ξ. Let these expansions have the form

$$\begin{aligned} q_1 &= \sum_{m=1}^{\infty} q_1^{(m)} \cos \lambda_m \xi, \\ q_2 &= \sum_{m=1}^{\infty} q_2^{(m)} \sin \lambda_m \xi, \\ q_n &= \sum_{m=1}^{\infty} q_n^{(m)} \sin \lambda_m \xi, \end{aligned} \tag{42.3}$$

where

$$\lambda_m = m \frac{\pi r_0}{L}, \tag{42.4}$$

and $q_1^{(m)}$, $q_2^{(m)}$, $q_n^{(m)}$ are functions of φ only which may be determined by use of the general formulae for calculating Fourier coefficients.

Substituting (42.3) on the right hand side of (42.1), the solution of this equation will itself be sought in the form of the series

$$\tilde{T} = \sum_{m=1}^{\infty} \tilde{T}^{(m)} \sin \lambda_m \xi. \tag{42.5}$$

In this way, the partial differential equation (42.1) leads to the following set of independent ordinary differential equations

$$\begin{aligned} \Delta_m[\Delta_m(\tilde{T}^{(m)})] + \frac{d^2 \tilde{T}^{(m)}}{d\varphi^2} - i2b^2 \lambda_m^2 \tilde{T}^{(m)} = \\ = i2b^2 r_0 \left[\Delta_m(q_n^{(m)}) + \frac{dq_2^{(m)}}{d\varphi} + \lambda_m q_1^{(m)} \right], \end{aligned} \tag{42.6}$$

where

$$\Delta_m(\ldots) = \frac{d^2(\ldots)}{d\varphi^2} - \lambda_m{}^2(\ldots) \tag{42.7}$$

and there will be as many equations as there were terms retained in the series (42.3).

Since the system of equations (42.6) is linear, its general solution may be obtained by adding any of its particular integrals to the general solution of the homogeneous equation

$$\Delta_m[\Delta_m(\bar{T}^{(m)})] + \frac{d^2\bar{T}^{(m)}}{d\varphi^2} - i2b^2\lambda_m{}^2\bar{T}^{(m)} = 0. \tag{42.8}$$

If the surface loading is a sufficiently smooth function of the angle φ, one may take for this purpose as a close approximation to a particular integral the expression

$$\bar{T}_{part}{}^{(m)} = -\frac{r_0}{\lambda_m{}^2}\left\{\Delta_m[q_n{}^{(m)}] + \frac{dq_2{}^{(m)}}{d\varphi} + \lambda_m q_1{}^{(m)}\right\}, \tag{42.9}$$

which will be obtained, if one omits on the left hand side of (42.6) all but the last term.

Employment of this formula is justified on the basis that the magnitude of the components of the surface loading have been assumed to be non-increasing for differentiation with respect to φ, so that on substitution of (42.9) on the left hand side of (42.6) one may neglect all terms except those with the very large factor $2b^2\lambda_m{}^2$.

By the way, the formula (42.9) coincides with the solution which would be obtained for the problem on the basis of the membrane theory. In fact, the equations of the membrane theory in the given case can be written

$$\begin{gathered}\frac{\partial T_1{}^*}{\partial\xi} + \frac{\partial S^*}{\partial\varphi} = -r_0\sum_{m=1}^{\infty} q_1{}^{(m)}\cos\lambda_m\xi, \\ \frac{\partial S^*}{\partial\xi} + \frac{\partial T_2{}^*}{\partial\varphi} = -r_0\sum_{m=1}^{\infty} q_2{}^{(m)}\sin\lambda_m\xi, \\ T_2{}^* = r_0\sum q_n{}^{(m)}\sin\lambda_m\xi.\end{gathered} \tag{42.10}$$

Hence, if $T_1{}^*$, $T_2{}^*$, S^* are sought in the form

$$\begin{gathered}T_1{}^* = \sum T_{1,m}{}^*\sin\lambda_m\xi,\ T_2{}^* = \sum T_{2,m}{}^*\sin\lambda_m\xi, \\ S^* = \sum S_m{}^*\cos\lambda_m\xi,\end{gathered} \tag{42.11}$$

one will have for the coefficients in these series the system

$$\begin{gathered}\lambda_m T_{1,m}^* + \frac{dS_m^*}{d\varphi} = -r_0 q_1^{(m)}, \\ -\lambda_m S_m^* + \frac{dT_{2,m}^*}{d\varphi} = -r_0 q_2^{(m)}, \\ T_{2,m}^* = r_0 q_n^{(m)},\end{gathered} \tag{42.12}$$

from which follows

$$\begin{gathered}T_{2,m}^* = r_0 q_n^{(m)}, \\ S_m^* = \frac{r_0}{\lambda_m}\left[\frac{dq_n^{(m)}}{d\varphi} + q_2^{(m)}\right], \\ T_{1,m}^* = -\frac{r_0}{\lambda_m^2}\left[\frac{d^2 q_n^{(m)}}{d\varphi^2} + \frac{dq_2^{(m)}}{d\varphi}\right] - \frac{r_0}{\lambda_m} q_1^{(m)},\end{gathered} \tag{42.13}$$

and

$$T_m^* = T_{1,m}^* + T_{2,m}^* = -\frac{r_0}{\lambda_m^2}\left\{\Delta_m[q_n^{(m)}] + \frac{dq_2^{(m)}}{d\varphi} + \lambda_m q_1^{(m)}\right\}, \tag{42.14}$$

which coincides with (42.9), if one takes into consideration that

$$\text{for } M_1 = M_2 = 0,\ T_m^* = \bar{T}^{(m)}.$$

One thus arrives at the important conclusion that (at least in the case under consideration) one may take as the particular integral of the differential equations of the theory of elastic shells the solution of the membrane theory. Later on, it will be repeatedly verified that this method turns out to be admissible in many cases, so that the determination of particular integrals of the equations of the theory of shells does not as a rule cause any difficulties and reduces to a range of problems which have been dealt with in the preceding chapter.

These results make it possible to consider the present problem of the stress analysis of cylindrical plates as a homogeneous problem, i.e., to put in all formulae

$$q_1^{(m)} = q_2^{(m)} = q_n^{(m)} = 0.$$

Having obtained the homogeneous solution, it is always possible to generalize it to the non-homogeneous problem. For this purpose, it is sufficient to add to the expressions found for the forces, moments and displacements the corresponding solution of the membrane theory.

Thus, attention will be concentrated on the integration of the homo-

geneous equation (42.8) and in what follows $\tilde{T}_1$, $\tilde{T}_2$, $\tilde{S}$, $\tilde{u}$, $\tilde{v}$, $\tilde{w}$ will not denote the general expressions for these complex forces and complex displacements, but merely the expressions corresponding to the homogeneous problem.

The solution of (42.8) must be sought in the form

$$\tilde{T}^{(m)} = Ce^{\gamma\varphi}, \tag{42.15}$$

where C and γ are constants.

Substituting (42.15) into (42.8) and dividing the final expression by $Ce^{\gamma\varphi}$, one arrives at the following bi-quadratic equation for γ:

$$(\gamma^2 - \lambda_m^2)^2 + \gamma^2 - i2b^2\lambda_m^2 = 0, \tag{42.16}$$

whence

$$\gamma^2 = \lambda_m^2 - \tfrac{1}{2} \pm \sqrt{i2b^2\lambda_m^2 + (\lambda_m^2 - \tfrac{1}{2})^2}. \tag{42.17}$$

In this last expression, one may neglect under the root sign the second term on comparison with the first. This step is justified, since in the problem under consideration the parameter $2b^2 \gg \lambda_m^2$ and λ_m^2 is usually a quantity of the same order as unity.

After this simplification, one has

$$\gamma^2 = \lambda_m^2 - \tfrac{1}{2} \pm (1 + i)b\lambda_m = b\lambda_m[f_m \pm (1 + i)], \tag{42.18}$$

where

$$f_m = \frac{\lambda_m^2 - \frac{1}{2}}{b\lambda_m}. \tag{42.19}$$

Taking the square root of the expression (42.18), one finds for γ the four values.

$$\begin{aligned} \gamma_{1,2} &= \pm (c_1 + id_1), \\ \gamma_{3,4} &= \pm (c_2 - id_2), \end{aligned} \tag{42.20}$$

where

$$\begin{aligned} c_1 &= \sqrt{\frac{b\lambda_m}{2}}\sqrt{\sqrt{(1 + f_m)^2 + 1} + 1 + f_m}, \\ d_1 &= \sqrt{\frac{b\lambda_m}{2}}\sqrt{\sqrt{(1 + f_m)^2 + 1} - 1 - f_m}, \\ c_2 &= \sqrt{\frac{b\lambda_m}{2}}\sqrt{\sqrt{(1 - f_m)^2 + 1} - 1 + f_m}, \\ d_2 &= \sqrt{\frac{b\lambda_m}{2}}\sqrt{\sqrt{(1 - f_m)^2 + 1} + 1 - f_m}. \end{aligned} \tag{42.21}$$

Hence one may write for the auxiliary function $\tilde{T}^{(m)}$ the expression

$$\tilde{T}^{(m)} = \tilde{C}_1 e^{\gamma_1 \varphi} + \tilde{C}_2 e^{\gamma_2 \varphi} + \tilde{C}_3 e^{\gamma_3 \varphi} + \tilde{C}_4 e^{\gamma_4 \varphi}, \tag{42.22}$$

where $\tilde{C}_1$, $\tilde{C}_2$, $\tilde{C}_3$, $\tilde{C}_4$ are constants of integration which have been specially identified to indicate that they are complex quantities. Strictly speaking, the constants $\tilde{C}_j$ as well as the exponents γ_j should carry an index m; however, in order to avoid formulae with double indices, this has not been done and instead the reader will be asked to keep this circumstance in mind.

Now, having constructed the solution of the homogeneous problem in the form of the series (42.5), one may obtain, in an analogous form, the expressions for all the complex forces. Substituting (42.5) into (40.8), (40.9), (40.10), taking (42.22) into consideration and putting there $\rho = 1$, $q_1 = q_2 = q_n = 0$, one has

$$\tilde{T}_1 = \sum \tilde{T}_1^{(m)} \sin \lambda_m \xi, \quad \tilde{T}_2 = \sum \tilde{T}_2^{(m)} \sin \lambda_m \xi, \quad \tilde{S} = \sum \tilde{S}^{(m)} \cos \lambda_m \xi, \tag{42.23}$$

where

$$\tilde{T}_1^{(m)} = \sum_{j=1}^{j=4} \tilde{C}_j \left[1 - \frac{i}{2b^2} (\gamma_j^2 - \lambda_m^2) \right] e^{\gamma_j \varphi} \approx \sum_{j=1}^{j=4} \tilde{C}_j e^{\gamma_j \varphi}. \tag{42.24}$$

$$\tilde{T}_2^{(m)} = \frac{i}{2b^2} \sum_{j=1}^{j=4} (\gamma_j^2 - \lambda_m^2) \tilde{C}_j e^{\gamma_j \varphi},$$

$$\tilde{S}^{(m)} = -\lambda_m \sum_{j=1}^{j=4} \frac{1}{\gamma_j} C_j \left[1 - \frac{i}{2b^2} (\gamma_j^2 - \lambda_m^2) \right] e^{\gamma_j \varphi} \approx -\lambda_m \sum_{j=1}^{j=4} \frac{1}{\gamma_j} C_j e^{\gamma_j \varphi}. \tag{42.25}$$

Introducing next these expressions in (40.12) and (40.13), one obtains equations for the determination of the complex displacements. For this purpose, the last will be sought in the form of the series

$$\tilde{u} = \sum_m \tilde{u}_m \cos \lambda_m \xi, \quad \tilde{v} = \sum \tilde{v}_m \sin \lambda_m \xi, \quad \tilde{w} = \sum \tilde{w}_m \sin \lambda_m \xi, \tag{42.26}$$

the coefficients of which, by virtue of (40.12), (40.13) and (42.23), will be subject to the relations

$$\begin{aligned}
-\lambda_m \tilde{u}_m &= \frac{r_0}{E\delta} (\tilde{T}_1^{(m)} - \mu \tilde{T}_2^{(m)}), \\
\frac{d\tilde{v}_m}{d\varphi} + \tilde{w}_m &= \frac{r_0}{E\delta} (\tilde{T}_2^{(m)} - \mu \tilde{T}_1^{(m)}), \\
\frac{d\tilde{u}_m}{d\varphi} + \lambda_m \tilde{v}_m &= \frac{2(1+\mu) r_0}{E\delta} \tilde{S}^{(m)}, \\
\lambda_m^2 \tilde{w}_m &= i 2b^2 \frac{r_0}{E\delta} \tilde{T}_2^{(m)},
\end{aligned} \tag{42.27}$$

$$-\frac{d^2\tilde{w}_m}{d\varphi^2}+\frac{d\tilde{v}_m}{d\varphi}=i2b^2\frac{r_0}{E\delta}\tilde{T}_1^{(m)},$$
$$\lambda_m\left(\frac{d\tilde{w}_m}{d\varphi}-\tilde{v}_m\right)=i2b^2\frac{r_0}{E\delta}\tilde{S}^{(m)}, \tag{42.27}$$

the first and fourth of which immediately give

$$\tilde{w}_m=i\frac{2b^2}{\lambda_m^2}\frac{r_0}{E\delta}\tilde{T}_2^{(m)},$$
$$\tilde{u}_m=-\frac{1}{\lambda_m}\frac{r_0}{E\delta}(\tilde{T}_1^{(m)}-\mu\tilde{T}_2^{(m)})\approx-\frac{1}{\lambda_m}\frac{r_0}{E\delta}\tilde{T}_1^{(m)}. \tag{42.28}$$

After this, one obtains from the third equation

$$\tilde{v}_m=\frac{1}{\lambda_m}\frac{2(1+\mu)r_0}{E\delta}\tilde{S}^{(m)}+\frac{1}{\lambda_m^2}\frac{r_0}{E\delta}\frac{d}{d\varphi}[\tilde{T}_1^{(m)}-\mu\tilde{T}_2^{(m)}]. \tag{42.29}$$

Substituting in (42.28) and (42.29) for $\tilde{T}_1^{(m)}$, $\tilde{T}_2^{(m)}$, $\tilde{S}^{(m)}$ their expressions given by (42.25), one has

$$\tilde{w}_m=-\frac{r_0}{E\delta}\frac{1}{\lambda_m^2}\sum_{j=1}^{j=4}(\gamma_j^2-\lambda_m^2)\tilde{C}_je^{\gamma_j\varphi},$$
$$\tilde{u}_m\approx-\frac{r_0}{E\delta}\frac{1}{\lambda_m}\sum_{j=1}^{j=4}\tilde{C}_je^{\gamma_j\varphi}, \tag{42.30}$$
$$\tilde{v}_m\approx\frac{r_0}{E\delta}\frac{1}{\lambda_m^2}\sum_{j=1}^{j=4}\frac{\gamma_j^2-(2+\mu)\lambda_m^2}{\gamma_j}\tilde{C}_je^{\gamma_j\varphi}.$$

One is now faced with the problem of deducing from the complex forces and displacements the real forces, moments and displacements respectively. This can be done by separating real and imaginary parts in the above expressions, where the constants $\tilde{C}_1$, $\tilde{C}_2$, $\tilde{C}_3$, $\tilde{C}_4$ must be assumed to be complex.

No space will be devoted here to the purely formal manipulations which by now should be sufficiently clear. However, the final results will be written down. They give for the displacements, the angle of rotation ψ, the stress and moment resultants the series

$$u=\sum u_m\cos\lambda_m\xi,\qquad v=\sum v_m\sin\lambda_m\xi,\qquad w=\sum w_m\sin\lambda_m\xi,$$
$$\psi=\sum\psi_m\cos\lambda_m\xi,$$
$$T_1=\sum T_1^{(m)}\sin\lambda_m\xi,\ T_2=\sum T_2^{(m)}\sin\lambda_m\xi,\ S=\sum S^{(m)}\cos\lambda_m\xi, \tag{42.31}$$
$$N_1=\sum N_1^{(m)}\cos\lambda_m\xi,\ N_2=\sum N_2^{(m)}\sin\lambda_m\xi,$$
$$M_1=\sum M_1^{(m)}\sin\lambda_m\xi,\ M_2=\sum M_2^{(m)}\sin\lambda_m\xi,\ H=\sum H^{(m)}\cos\lambda_m\zeta,$$

where the coefficients will expressed by formulae of one of the following two types:

$$\begin{aligned}(\mathrm{I}) = {} & (\alpha C_1+\beta C_2)\Phi_1+(\alpha C_2-\beta C_1)\Phi_2+(\alpha C_3-\beta C_4)\Phi_3+(\alpha C_4+\beta C_3)\Phi_4+\\ & +(\alpha' C_1'+\beta' C_2')\Psi_1+(\alpha' C_2'-\beta' C_1')\Psi_2+\\ & +(\alpha' C_3'-\beta' C_4')\Psi_3+(\alpha' C_4'+\beta' C_3')\Psi_4,\\ (\mathrm{II}) = {} & (\alpha C_4+\beta C_3)\Phi_1+(\alpha C_3-\beta C_4)\Phi_2+(\alpha C_2-\beta C_1)\Phi_3+(\alpha C_1+\beta C_2)\Phi_4+\\ & +(\alpha' C_4'+\beta' C_3')\Psi_1+(\alpha' C_3'-\beta' C_4')\Psi_2+\\ & +(\alpha' C_2'-\beta' C_1')\Psi_3+(\alpha' C_1'+\beta' C_2')\Psi_4.\end{aligned}$$

In fact, the coefficients of u_m, w_m, $T_1^{(m)}$, $T_2^{(m)}$, $N_1^{(m)}$, $M_1^{(m)}$, $M_2^{(m)}$ are determined by formulae of the type (I), the coefficients of v_m, $S^{(m)}$, $H^{(m)}$, $N_2^{(m)}$, ψ_m by those of the type (II). In those formulae:

C_j, C_j' are eight, real, arbitrary constants by means of which one can satisfy on each of the two straight edges of the cylindrical plate four edge conditions;

α, β, α', β' are parameters which take for each of the coefficients a special value;

Φ_j, Ψ_j are the following combinations of trigonometric and hyperbolic functions:

$$\begin{aligned}\Phi_1 &= \cosh c_1\varphi \cos d_1\varphi, & \Psi_1 &= \cosh c_2\varphi \cos d_2\varphi,\\ \Phi_2 &= \sinh c_1\varphi \sin d_1\varphi, & \Psi_2 &= \sinh c_2\varphi \sin d_2\varphi,\\ \Phi_3 &= \cosh c_1\varphi \sin d_1\varphi, & \Psi_3 &= \cosh c_2\varphi \sin d_2\varphi,\\ \Phi_4 &= \sinh c_1\varphi \cos d_1\varphi, & \Psi_4 &= \sinh c_2\varphi \cos d_2\varphi.\end{aligned} \tag{42.32}$$

Table 3 gives the formulae for the calculation of the parameters α, β, α', β' for all the coefficients of the series (42.31).

The above information makes it possible to construct the series (42.31) for given shell dimensions. The number of terms in these series will correspond to the number of terms in the series for the surface loading, i.e., in the series (42.3). For this, the terms corresponding to each value of m must be subjected individually to the boundary conditions at the straight edges of the cylindrical plate (in a similar manner this must be done in the method of Maurice Lévy for ordinary plates). Hence it is clear that the complexity of the calculations increases proportionally to the number of terms retained in the series (42.3).

Mostly, cylindrical plates are analyzed for loadings which do not vary along their length (for example, roofs under their own weight or shells subject to uniform normal pressure).

The expansion of the constant quantity B in a trigonometric series for the interval $0 \leqslant \xi \leqslant \xi_0$ is known to have the form

$$B = \frac{4}{\pi} B \sum_{m=1}^{\infty} \frac{1}{m} \sin \lambda_m \xi, \tag{42.33}$$

where the summation extends only over the odd integers m and the λ_m are determined by (42.4). This series does not converge fast (especially not near the ends of the interval). Nevertheless, in order to simplify the calculations, it is customary to approximate the loading by a single term of the given series, i.e., to replace the rectangular load distribution along the length of the shell by a sinusoidal distribution of equal area.

Firstly, this simplified approach is justified by its safety, since it must invariably lead to overestimates of the stresses and deflections (the external load having been redistributed from the supports to the middle of the span without changing the total load). Secondly, it is justified by the fact that the series for the displacements, forces and moments (at least at those sections where they attain maximum values) converge more rapidly than the series for the loading, so that the error in the calculations is found to be smaller than that incurred by retaining in (42.33) only the first term.

Thus, in what follows, it will be assumed that the series (42.31) contain only first terms corresponding to $m = 1$. The coefficients of these terms will be distinguished by primes (for example, u', T_1', ..., etc.). In addition, the notation

$$\lambda_1 = \frac{\pi r_0}{L} = \lambda, \tag{42.34}$$

will be adopted, i.e., the subscript of λ_1 will be omitted.

Further, one has to design a convenient scheme for the computations which in spite of the above stated simplifications will still be very involved. Such a practical scheme will now be given [98], having in mind the case which, while being simplest, occurs most often in practice, namely when the boundary conditions at the straight edges are the same and the loading is symmetrical with respect to the plane $\varphi = 0$.

Under these circumstances, the coefficients u_m, w_m, $T_1^{(m)}$, $T_2^{(m)}$, $N_1^{(m)}$, $M_1^{(m)}$, $M_2^{(m)}$ will be even and the coefficients v_m, ψ_m, $H^{(m)}$, $S^{(m)}$, $N_2^{(m)}$ odd functions of φ, as a consequence of which one must put

$$C_3 = C_4 = C_3' = C_4' = 0.$$

With the help of the remaining four integration constants the solution

Table 3

Formulae for determining α, β, α', β'

u_m	α	β	α'	β'	Type of formula
	$\frac{1}{2b}$	$-\frac{1+(1+\mu)f_m}{2b}$	$-\frac{1}{2b}$	$-\frac{1-(1+\mu)f_m}{2b}$	I
v_m	$-\frac{d_1}{b\lambda_m}\left[1-\frac{\mu}{2}f_m+\right.$ $\left.+\frac{1}{2}\sqrt{1+(1+f_m)^2}\right]$	$\frac{c_1}{b\lambda_m}\left[1-\frac{\mu}{2}f_m-\right.$ $\left.-\frac{1}{2}\sqrt{1+(1+f_m)^2}\right]$	$-\frac{d_2}{b\lambda_m}\left[1+\frac{\mu}{2}f_m-\right.$ $\left.-\frac{1}{2}\sqrt{1+(1-f_m)^2}\right]$	$\frac{c_2}{b\lambda_m}\left[1+\frac{\mu}{2}f_m+\right.$ $\left.+\frac{1}{2}\sqrt{1+(1-f_m)^2}\right]$	II
w_m	1, 0	0, 0	1, 0	0, 0	I
$r_0\psi_m$	$-c_1+\alpha_{vm}$	$-d_1+\beta_{vm}$	$-c_2+\alpha'_{vm}$	$-d_2+\beta'_{vm}$	II
$\frac{r_0}{E\delta}T_1^{(m)}$	$-\frac{\lambda_m}{2b}$	$\frac{\lambda_m}{2b}(1+f_m)$	$\frac{\lambda_m}{2b}$	$\frac{\lambda_m}{2b}(1-f_m)$	I
$\frac{r_0}{E\delta}T_2^{(m)}$	0, 0	$-\frac{\lambda_m^2}{2b^2}$	0, 0	$\frac{\lambda_m^2}{2b^2}$	I
$\frac{r_0}{E\delta}S^{(m)}$	$\frac{\lambda_m}{2b^2}d_1$	$-\frac{\lambda_m}{2b^3}c_1$	$-\frac{\lambda_m}{2b^2}d_2$	$\frac{\lambda_m}{2b^2}c_2$	II
$\frac{r_0}{E\delta}N_1^{(m)}$	$\frac{\lambda_m}{4b^4}(\lambda_m^2-c_1^2+d_1^2)$	$-\frac{c_1d_1\lambda_m}{2b^4}$	$\frac{\lambda_m}{4b^4}(\lambda_m^2-c_2^2+d_2^2)$	$-\frac{c_2d_2\lambda_m}{2b^4}$	I
$\frac{r_0}{E\delta}N_2^{(m)}$	$\frac{c_1}{4b^4}(\lambda_m^2-c_1^2+3d_1^2)$	$\frac{d_1}{4b^4}(\lambda_m^2-3c_1^2+d_1^2)$	$\frac{c_2}{4b^4}(\lambda_m^2-c_2^2+3d_2^2)$	$\frac{d_2}{4b^4}(\lambda_m^2-3c_2^2+d_2^2)$	II
$\frac{1}{E\delta}M_1^{(m)}$	$-\frac{\lambda_m}{4b^3}[\mu-(1-\mu)f_m]$	$-\mu\frac{\lambda_m}{4b^3}$	$\frac{\lambda_m}{4b^3}[\mu+(1-\mu)f_m]$	$-\mu\frac{\lambda_m}{4b^3}$	I
$\frac{1}{E\delta}M_2^{(m)}$	$-\frac{\lambda_m}{4b^3}[1+(1-\mu)f_m]$	$-\frac{\lambda_m}{4b^3}$	$\frac{\lambda_m}{4b^3}[1-(1-\mu)f_m]$	$-\frac{\lambda_m}{4b^3}$	I
$\frac{1}{E\delta}H^{(m)}$	$-\frac{(1-\mu)c_1\lambda_m}{4b^4}$	$-\frac{(1-\mu)d_1\lambda_m}{4b^4}$	$-\frac{(1-\mu)c_2\lambda_m}{4b^4}$	$-\frac{(1-\mu)d_2\lambda_m}{4b^4}$	II

may be subjected to boundary conditions at one of the rectilinear edges (for example, at the edge $\varphi = \varphi_0$), while, by virtue of the symmetry of the deformation, they will be automatically satisfied at the other edge.

It is convenient to consider beforehand the following four types of boundary conditions:

$$\left.\begin{aligned} u' &= 1, \quad v' = w' = \psi' = 0 \\ v' &= 1, \quad u' = w' = \psi' = 0 \\ w' &= 1, \quad u' = v' = \psi' = 0 \\ r_0\psi' &= 1, \quad u' = v' = w' = 0 \end{aligned}\right\} \text{ for } \varphi = \varphi_0 \tag{42.35}$$

by determining for each of them the values of the constants C_1, C_2, C_1', C_2'.

Substituting these four constants into the formulae for the forces S, T_2, N_2 and the moment M_2, the boundary values of these quantities, corresponding to the above types of boundary conditions at the straight edges, will now be obtained. The results may be presented in the form of the following table:

	$u' = 1$	$v' = 1$	$w' = 1$	$r_0\psi' = 1$	(*)
$\frac{r_0}{E\delta} S'$	a_{11}	a_{12}	a_{13}	a_{14}	
$\frac{r_0}{E\delta} T_2'$	a_{21}	a_{22}	a_{23}	a_{24}	
$\frac{r_0}{E\delta} N_2'$	a_{31}	a_{32}	a_{33}	a_{34}	
$\frac{1}{E\delta} M_2'$	a_{41}	a_{42}	a_{43}	a_{44}	

The coefficients a_{jk} in this table completely characterize the elastic properties of the straight edges. Once they are known, the forces and moments at the edges can be presented as linear functions of the edge displacements and the angle of rotation (strictly speaking this may be done with regard to the coefficients u', v', ..., T_2', S_1', ...).

The corresponding expressions will have the form

$$\begin{aligned} \frac{r_0}{E\delta} S' &= a_{11}u' + a_{12}v' + a_{13}w' + a_{14}(r_0\psi') + \frac{r_0}{E\delta} s, \\ \frac{r_0}{E\delta} T_2' &= a_{21}u' + a_{22}v' + a_{23}w' + a_{24}(r_0\psi') + \frac{r_0}{E\delta} t, \end{aligned} \tag{42.36}$$

$$\frac{r_0}{E\delta} N_2' = a_{31}u' + a_{32}v' + a_{33}w' + a_{34}(r_0\psi') + \frac{r_0}{E\delta} n,$$
$$\frac{1}{E\delta} M_2' = a_{41}u' + a_{42}v' + a_{43}w' + a_{44}(r_0\psi') + \frac{1}{E\delta} m, \tag{42.36}$$

where the quantities s, t, n and m must be equal to the boundary values of S', T_2', N_2' and M_2' for the boundary conditions

$$u = v = w = \psi = 0,$$

i.e., for rigidly clamped straight edges. They will only differ from zero when the surface loading on the shell is distinct from zero, whence it is clear in the formulae (42.36) that they represent the particular integrals of the problem which were to be taken from the membrane theory.

It will now be assumed that the membrane problem for the given surface loading has been solved and that the corresponding values of the displacements and of the angle of rotation u^*, v^*, w^*, ψ^* are known. In order to arrive at the general solution, one must add these results to the solution of the homogeneous problem which consequently will have the form

$$u = u_0 + u^*, \quad v = v_0 + v^*, \quad w = w_0 + w^*, \quad \psi = \psi_0 + \psi^*, \tag{42.37}$$

where u_0, v_0, w_0, ψ_0 are the expressions for the displacements (involving the constants of integration) the determination of which has been explained above. Thus the conditions for the rigid clamping of the straight edges reduce to

$$u_0' = -u^{*\prime}, \quad v_0' = v^{*\prime}, \quad w_0' = w^{*\prime}, \quad \psi_0' = \psi^{*\prime} \tag{42.38}$$

which are to hold at $\varphi = \varphi_0$. [As before, the primes indicate the coefficients of the first terms in the expansions (42.31)].

Hence it follows that the quantities s, t, n and m are given by the formulae

$$\frac{r_0}{E\delta} s = -a_{11}u^{*\prime} - a_{12}v^{*\prime} - a_{13}w^{*\prime} - a_{14}(r\psi^{*\prime}) + \frac{r_0}{E\delta} S^{*\prime},$$
$$\frac{r_0}{E\delta} t = -a_{21}u^{*\prime} - a_{22}v^{*\prime} - a_{23}w^{*\prime} - a_{24}(r\psi^{*\prime}) + \frac{r_0}{E\delta} T_2^{*\prime}, \tag{42.39}$$
$$\frac{r_0}{E\delta} n = -a_{31}u^{*\prime} - a_{32}v^{*\prime} - a_{33}w^{*\prime} - a_{34}(r\psi^{*\prime}),$$
$$\frac{r_0}{E\delta} m = -a_{41}u^{*\prime} - a_{42}v^{*\prime} - a_{43}w^{*\prime} - a_{44}(r\psi^{*\prime}),$$

where $u^{*\prime}$, $v^{*\prime}$, $w^{*\prime}$, $S^{*\prime}$, $T_2^{*\prime}$ are understood to be the boundary values of the particular integrals taken from the membrane theory.

By means of these formulae, one may fill in the fifth column (*) of the table on page 206 which was intended for the free terms in the expressions (42.36).

The availability of the expressions (42.36) makes it much simpler to reveal the statically indeterminate nature of composite shells with supports at their straight edges. This fact justifies the effort of setting up the stiffness table. Further, the execution of the stress analysis of cylindrical plates by use of the intermediate stiffness table has one more important advantage. In fact, by the theorem of virtual work, the coefficients a_{jk} must be symmetrical so that

$$a_{jk} = a_{kj}. \tag{42.40}$$

The accuracy of the computations can be assessed by the degree to which these conditions are fulfilled.

Thus, by constructing tables of the above type, one is in a position to check the computations which is very desirable in view of their great complexity. However, it should be noted that, since the solution of this section has been obtained by neglecting a number of small terms, the conditions (42.40) may be fulfilled exactly and nevertheless this will not ensure the same degree of accuracy of the computations. Therefore a 10—15% violation of (42.40) must be considered legitimate and only disagreements exceeding this limit must be interpreted as indications of arithmetical errors in the computations.

§ 43. The evaluation of the stresses in oval shells, composed of four cylindrical plates

A thin-walled cylinder with its cross-section formed by four smoothly joined arcs of circles two of which have the radius r_1 and two the radius r_2 (Fig. 55) will now be considered and the strains and stresses due to uniform normal pressure evaluated.

The radius of curvature of the shell whose section is shown in Fig. 55 varies discontinuously and therefore the formulae deduced in § 37 are not applicable. Its stress analysis may be approached by dividing the shell into four interconnected cylindrical plates. In this way, the problem is reduced to the analysis of these cylindrical plates subject to uniform normal pressure with special consideration of the conditions at their common boundaries.

All four plates will be deformed symmetrically with respect to their

planes $\varphi = 0$, and the deformations of opposite plates will obviously be equal. Hence, only two cylindrical plates have to be considered (for example, the plates I and II of Fig. 56) with statically indeterminate conditions along their junctions. Below, this analysis will be performed for a specific shell and the calculations will be carried through in the same order which has been indicated in the preceding section.



Fig. 55.



Fig. 56.

As a first step, the membrane solution for a cylindrical shell loaded by uniform normal pressure $q_n = p = \text{constant}$ will be determined. Representing this load distribution in the form of the series (42.33) and retaining in the series only the first term, one has

$$q_n = \frac{4}{\pi} p \sin \lambda\xi = q_n' \sin \lambda\xi, \quad q_1 = q_2 = 0. \tag{43.1}$$

Then the equations (42.10) give

$$T_2^* = \frac{4}{\pi} p r_0 \sin \lambda\xi, \quad T_1^* = S^* = 0. \tag{43.2}$$

Forming next the equations for the displacements

$$\begin{aligned} \frac{\partial u}{\partial \xi} &= \frac{r_0}{E\delta}(T_1^* - \mu T_2^*) = -\mu \frac{4}{\pi} \frac{p r_0^2}{E\delta} \sin \lambda\xi, \\ \frac{\partial v}{\partial \varphi} + w &= \frac{r_0}{E\delta}(T_2^* - \mu T_1^*) = \frac{4}{\pi} \frac{p r_0^2}{E\delta} \sin \lambda\xi, \\ \frac{\partial u}{\partial \varphi} &+ \frac{\partial v}{\partial \xi} = 0, \end{aligned} \tag{43.3}$$

one finds

$$\begin{aligned} u^* &= u_1^* \cos \lambda\xi = \frac{4}{\pi}\,\frac{\mu}{\lambda}\,\frac{pr_0^2}{E\delta}\cos\lambda\xi, \\ v^* &= 0, \\ w^* &= \frac{4}{\pi}\,\frac{pr_0^2}{E\delta}\sin\lambda\xi. \end{aligned} \tag{43.4}$$

The expressions (43.2) and (43.4) will be used later on as particular integrals of this problem, where one will have for the shell I the radius $r_0 = r_1$ and for the shell II the radius $r_0 = r_2$.

I. Calculation of the stiffness table for the edges of the first cylindrical plate

Given data:

$$\frac{r_1}{\delta} = 150,\quad \frac{r_1}{L} = 0.625,\quad \varphi_0 = 45°,\quad \lambda = \frac{\pi r_1}{L} = 1.964.$$

$$4b^4 = 12(1-\mu^2)\frac{r_1^2}{\delta^2} = 2.45.10^5,\quad b = 15.72.$$

Calculation of the roots of the characteristic Equation (42.16)

$$f = \frac{\lambda^2 - \frac{1}{2}}{b\lambda} = 0.108,$$

$$\begin{aligned} c_1 &= 6.37,\quad d_1 = 2.42,\quad c_2 = 2.65,\quad d_2 = 5.84, \\ c_1\varphi_0 &= 5.01,\quad d_1\varphi_0 = 1.90,\quad c_2\varphi_0 = 2.08,\quad d_2\varphi_0 = 4.59. \end{aligned}$$

The boundary values of the functions Φ and Ψ:

$$\begin{aligned} &\Phi_1(\varphi_0) = -24.2,\ \Phi_2(\varphi_0) = 70.9,\ \Phi_3(\varphi_0) = 7.09,\ \Phi_4(\varphi_0) = -24.2, \\ &\Psi_1(\varphi_0) = -0.496,\ \Psi_2 = -3.91,\ \Psi_3 = -4.04,\ \Psi_4(\varphi_0) = -0.481. \end{aligned}$$

On the basis of the following table and the boundary values of the functions Φ and Ψ, the boundary values of the displacements and of the angle of rotation will be expressed in terms of the constants of integration by the following formulae:

$$\begin{aligned} u' &= 1.86C_1 + 3.16C_2 - 0.088C_1' + 0.138C_2', \\ v' &= -0.05C_1 - 10.75C_2 + 0.612C_1' + 0.201C_2', \\ w' &= -24.2C_1 + 70.9C_2 - 0.496C_1' - 3.91C_2', \\ r_1\psi' &= -326C_1 + 414C_2 + 21.7C_1' - 13.74C_2'. \end{aligned} \tag{43.5}$$

Table 4

Values of the coefficients α, β, α', β'

	α	β	α'	β'
u'	$3.19 \cdot 10^{-2}$	$-3.71 \cdot 10^{-2}$	$-3.19 \cdot 10^{-2}$	$-2.67 \cdot 10^{-2}$
v'	$-1.37 \cdot 10^{-1}$	$4.70 \cdot 10^{-2}$	$-6.70 \cdot 10^{-2}$	$1.44 \cdot 10^{-2}$
w'	1.00	0.00	1.00	0.00
$r_1\Psi'$	-6.51	-2.37	-2.72	-5.70
$\frac{r_1}{E\delta} S'$	$9.63 \cdot 10^{-3}$	$-25.4 \cdot 10^{-3}$	$-23.3 \cdot 10^{-3}$	$10.55 \cdot 10^{-3}$
$\frac{r_1}{E\delta} T_2'$	0.00	$-7.82 \cdot 10^{-3}$	0.00	$7.82 \cdot 10^{-3}$
$\frac{r_1}{E\delta} N_2'$	$-4.97 \cdot 10^{-4}$	$-1.105 \cdot 10^{-3}$	$1.072 \cdot 10^{-3}$	$4.03 \cdot 10^{-4}$
$\frac{1}{E\delta} M_2'$	$-1.37 \cdot 10^{-4}$	$-1.26 \cdot 10^{-4}$	$1.15 \cdot 10^{-4}$	$-1.26 \cdot 10^{-4}$
$\frac{r_1}{E\delta} T_1'$	$-6.25 \cdot 10^{-2}$	$7.03 \cdot 10^{-2}$	$6.25 \cdot 10^{-2}$	$5.46 \cdot 10^{-2}$

Employing the given expressions, one may set up the four systems of equations corresponding to the case for $\varphi = \varphi_0$:

$$\begin{aligned} u' &= 1, \quad v' = w' = \psi' = 0, \\ v' &= 1, \quad u' = w' = \psi' = 0, \\ w' &= 1, \quad u' = v' = \psi' = 0, \\ r_1\psi' &= 1, \quad u' = v' = w' = 0. \end{aligned} \tag{43.6}$$

Thus, the following table of values of the constants of integration is obtained; the fifth column (*) gives the constants, calculated on the basis of the assumption that the edges of the shell are rigidly clamped, so that there

$$u' = v' = w' = \psi' = 0. \tag{43.7}$$

This column may be easily calculated from the preceding ones. In fact, the conditions (43.7) reduce to the system of equations, obtained from (42.36), (42.37),

$$u_0' = -u^{*\prime}, \quad v_0' = -v^{*\prime}, \quad w_0' = -w^{*\prime}, \quad \psi_0' = -\psi^{*\prime}, \tag{43.8}$$

Table 5

	$u' = 1$	$v' = 1$	$w' = 1$	$r_1\psi' = 1$	(*)
C_1	0.381	0.216	0.0380	0.00374	$-0.0961\,q'$
C_2	0.162	0.00318	0.00354	$-6.63\cdot10^{-4}$	$-0.0283\,q'$
C_1'	2.82	2.22	0.214	$2.3\cdot10^{-4}$	$-0.644\,q'$
C_2'	0.206	-1.56	-0.455	-0.0351	$0.0037\,q'$

where u_0 .... refer to the solutions of the homogeneous problem and u^* ...., to the particular integrals. For the loading case under consideration, the last are given by (43.4)

$$\begin{aligned} v^* &= \psi^* = 0, \\ u^{*\prime} &= \frac{\mu}{\lambda}\frac{4}{\pi}\frac{pr_1^2}{E\delta} = \frac{\mu}{\lambda}q', \\ w^{*\prime} &= \frac{4}{\pi}\frac{pr_1^2}{E\delta} = q'. \end{aligned} \tag{43.9}$$

Hence, it is seen that the fifth column (*) may be obtained by multiplying the first column by $-\frac{\mu}{\lambda}q'$ $\left(\text{where } q' = \frac{4}{\pi}\frac{pr_1^2}{E\delta}\right)$, the third by $-q'$ and by adding these results.

On the basis of Table 5 and of the boundary values of the auxiliary functions Φ and Ψ, one may write the following expressions for the boundary forces and moments in terms of the integration constants

$$\begin{aligned} \frac{r_1}{E\delta}S' &= 1.562C_1 + 1.295C_2 + 0.0537C_1' + 0.0889C_2', \\ \frac{r_1}{E\delta}T_2' &= 0.555C_1 + 0.1895C_2 + 0.0306C_1' - 0.00388C_2', \\ \frac{r_1}{E\delta}N_2' &= [90.3C_1 - 8.5C_2 + 1.06C_1' - 4.30C_2']10^{-3}, \\ \frac{1}{E\delta}M_2' &= [12.24C_1 - 6.66C_2 - 0.549C_1' - 0.388C_2']10^{-3}. \end{aligned} \tag{43.10}$$

Substituting here the values of C_1, C_2, C_1', C_2' from Table 5, one

obtains the stiffness table for the edge of the shell:

Table 6

	$u' = 1$	$v' = 1$	$w' = 1$	$r_1\psi = 1$	(*)
$\frac{r_1}{E\delta} S'$	$9.76 \cdot 10^{-1}$	$3.20 \cdot 10^{-1}$	$3.46 \cdot 10^{-2}$	$1.88 \cdot 10^{-3}$	$-1.83 \cdot 10^{-1} q'$
$\frac{r_1}{E\delta} T_2'$	$3.27 \cdot 10^{-1}$	$1.94 \cdot 10^{-1}$	$3.02 \cdot 10^{-2}$	$2.09 \cdot 10^{-3}$	$9.20 \cdot 10^{-1} q'$
$\frac{r_1}{E\delta} N_2'$	$3.51 \cdot 10^{-2}$	$2.85 \cdot 10^{-2}$	$5.6 \cdot 10^{-3}$	$4.87 \cdot 10^{-4}$	$-1.1 \cdot 10^{-2} q'$
$\frac{1}{E\delta} M_2'$	$1.93 \cdot 10^{-3}$	$2.01 \cdot 10^{-3}$	$5.02 \cdot 10^{-4}$	$6.37 \cdot 10^{-5}$	$-8.0 \cdot 10^{-4} q'$

The fifth column (*) of this table contains the values of the boundary forces and moments for the boundary conditions (43.7). It has been computed in the manner stated in the preceding section, where, as before,

$$q' = \frac{4}{\pi} p \frac{r_1^2}{E\delta}.$$

A study of the first four columns of this table shows that the terms in it possess the necessary symmetry about the principal diagonal, thus confirming the accuracy of the computations.

It is true that this symmetry is not complete, but (considering that the formulae which have been employed entail certain errors and also that all calculations have been carried out on a slide rule) the deviations are within the limits admissible in any technical calculations.

II. Calculation of the table stiffness for the edges of the second cylindrical plate

In an analogous manner, one can obtain the influence coefficients for the second cylindrical plate.

The results will be given here without explanation:

$$\frac{r_2}{\delta} = 40, \quad \frac{r_2}{L} = \frac{1}{6}, \quad \lambda = \frac{\pi}{6} = 0.524, \quad \varphi_0 = 45°,$$

$$4b^4 = 12(1 - \mu^2)\frac{r_2^2}{\delta^2} = 1.745.10^4, \quad b = 8.12,$$

$$f = -0.053,$$

$c_1 = 2.31$, $d_1 = 0.915$, $c_2 = 0.959$, $d_2 = 2.21$,
$c_1\varphi_0 = 1.820$, $d_1\varphi_0 = 0.719$, $c_2\varphi_0 = 0.753$, $d_2\varphi_0 = 1.735$,
$\Phi_1 = 2.38$, $\Phi_2 = 1.98$, $\Phi_3 = 2.09$, $\Phi_4 = 2.26$,
$\Psi_1 = -0.211$, $\Psi_2 = 0.815$, $\Psi_3 = 1.278$, $\Psi_4 = -0.1345$.

Table 7

	α	β	α'	β'
u'	$6.15\cdot10^{-2}$	$-6.66\cdot10^{-2}$	$-6.15\cdot10^{-2}$	$-5.63\cdot10^{-2}$
v'	$3.68\cdot10^{-1}$	$1.38\cdot10^{-1}$	$-1.74\cdot10^{-1}$	$3.84\cdot10^{-1}$
w'	1.00	0.00	1.00	0.00
$r_2\psi'$	−2.683	−0.777	−1.132	−1.826
$\frac{r_2}{E\delta}S'$	$3.63\cdot10^{-3}$	$-9.19\cdot10^{-3}$	$-8.76\cdot10^{-3}$	$3.81\cdot10^{-3}$
$\frac{r_2}{E\delta}T_2'$	0.00	$-2.08\cdot10^{-3}$	0.00	$2.08\cdot10^{-3}$
$\frac{r_2}{E\delta}N_2'$	$-3.16\cdot10^{-4}$	$-7.74\cdot10^{-4}$	$7.8\cdot10^{-4}$	$3.26\cdot10^{-4}$
$\frac{1}{E\delta}M_2'$	$-2.54\cdot10^{-4}$	$-2.44\cdot10^{-4}$	$2.33\cdot10^{-4}$	$-2.44\cdot10^{-4}$
$\frac{r_2}{E\delta}T_1'$	$-3.22\cdot10^{-2}$	$3.43\cdot10^{-2}$	$3.22\cdot10^{-2}$	$3.02\cdot10^{-2}$

$$\begin{aligned} u' &= 0.279C_1 - 0.037C_2 + 0.0596C_1' - 0.0378C_2', \\ v' &= -1.12C_1 - 0.456C_2 - 0.476C_1' - 0.273C_2', \\ w' &= 2.38C_1 + 1.98C_2 - 0.211C_1' + 0.815C_2', \\ -r_2\psi' &= 4.45C_1 + 7.36C_2 - 2.49C_1' + 1.20C_2'. \end{aligned} \tag{43.11}$$

Table 8

	$u'=1$	$v'=1$	$w'=1$	$r_2\psi'=1$	(*)
C_1	3.17	0.561	0.430	0.065	$-2.24\,q^{(2)}$
C_2	−1.97	−1.475	−1.070	−0.317	$2.20\,q^{(2)}$
C_1'	−2.64	−2.765	−1.278	−0.160	$2.79\,q^{(2)}$
C_2'	−5.19	1.225	+2.18	+0.537	$0.79\,q^{(2)}$

$$q^{(2)} = \frac{4}{\pi}\frac{pr_2^2}{E\delta}. \tag{43.12}$$

$$\begin{aligned}
\frac{r_2}{E\delta}S' &= [2.79C_1 - 1.318C_2 - 0.349C_1' - 1.17C_2']10^{-2},\\
\frac{r_2}{E\delta}T_2' &= [0.412C_1 - 0.496C_2 - 0.170C'_1 - 0.043C_2']10^{-2},\\
\frac{r_2}{E\delta}N_2' &= [9.0C_1 - 24.1C_2 - 5.21C_1' + 9.56C_2']10^{-4},\\
\frac{1}{E\delta}M_2' &= [-1.23C_1 - 10.85C_2 + 1.5C_1' + 2.42C_2']10^{-4}.
\end{aligned} \tag{43.13}$$

Table 9

	$u' = 1$	$v' = 1$	$w' = 1$	$r_2\psi' = 1$	(*)
$\frac{r_2}{E\delta}S_1$	$1.83\cdot10^{-1}$	$3.07\cdot10^{-2}$	$5.1\cdot10^{-3}$	$2.6\cdot10^{-4}$	$-1.1\cdot10^{-1}q^{(2)}$
$\frac{r_2}{E\delta}T_2'$	$2.27\cdot10^{-2}$	$1.38\cdot10^{-2}$	$8.3\cdot10^{-3}$	$1.87\cdot10^{-3}$	$9.75\cdot10^{-1}q^{(2)}$
$\frac{r_2}{E\delta}N_2'$	$4.0\cdot10^{-3}$	$6.7\cdot10^{-3}$	$5.72\cdot10^{-3}$	$1.42\cdot10^{-3}$	$-8\cdot10^{-3}q^{(2)}$
$\frac{1}{E\delta}M_2'$	$3.5\cdot10^{-4}$	$1.42\cdot10^{-3}$	$1.42\cdot10^{-3}$	$4.38\cdot10^{-4}$	$-1.66\cdot10^{-3}q^{(2)}$

III. The joints between the cylindrical plates

Along a common straight edge of the plates I and II the following equalities must hold (Fig. 57):

$$\begin{aligned}
&u_I' = u_{II}', \quad v_I' = -v_{II}', \quad w_I' = w_{II}', \quad \psi_I' = -\psi_{II}',\\
&S_I' = -S_{II}', \quad \underset{(I)}{T_2'} = \underset{(II)}{T_2'}, \quad \underset{(I)}{N_2'} = -\underset{(II)}{N_2'}, \quad \underset{(I)}{M_2'} = \underset{(II)}{M_2'}.
\end{aligned} \tag{43.14}$$

(Since the positive directions of u, w, S and N_2 for both plates are the same and the positive directions for v, ψ, T_2, M_2 are opposite).

With the stiffness tables for both plates being available, one may write down on the basis of the eight relations above the following four equations with the four unknowns u_1, v_1, w_1, ψ_1 (where, for the sake of



Fig. 57.

brevity, the subscript I will in future be omitted):

$$(1)\quad 0.976u' + 0.320v' + 0.0346w' + 0.00188(r_1\psi') - 0.183q' =$$
$$= -0.686u' + 0.115v' - 0.0191w' + 0.00026(r_1\psi') + 0.029q',$$

$$(2)\quad 0.327u' + 0.194v' + 0.302w' + 0.0021(r_1\psi') + 0.920q' =$$
$$= 0.111u' - 0.0518v' + 0.0312w' - 0.00187(r_2\psi') + 0.260q',$$

$$(3)\quad 0.035u' + 0.0285v' + 0.0056w' + 0.00049(r_2\psi') - 0.011\,q' =$$
$$= -0.0150u' + 0.0252v' - 0.021w' + 0.00142(r_2\psi') + 0.0021q',$$

$$(4)\quad 0.00193u' + 0.00201v' + 0.000502w' + 0.0000637(r_1\psi') - \qquad (43.15)$$
$$- 0.0008q' = 0.00035u' - 0.00142v' + 0.00142w' -$$
$$- 0.000117(r_1\psi') - 0.00019q'.$$

Transferring all the terms to the left hand side of these equations, one has

$$1.662u' + 0.205v' + 0.0537w' + 0.00162(r_1\psi') - 0.212q' = 0,$$
$$0.216u' + 0.246v' - 0.0010w' + 0.00397(r_1\psi') + 0.660q' = 0, \qquad (43.16)$$
$$0.050u' + 0.0038v' + 0.0267w' - 0.00093(r_1\psi') - 0.132q' = 0,$$
$$0.00158u' + 0.00343v' - 0.00092w' + 0.000181(r_1\psi') - 0.00068q' = 0.$$

Hence one obtains for the displacements and the rotation at the edges of the first plate

$$u' = 0.475q',\ v' = -4.93q',\ w' = 4.24q',\ (r_1\psi') = 115q'. \qquad (43.17)$$

Similarly, the boundary values of the displacements and rotation

for the second plate are

$$u_{II}' = u_I' = 0.475q', \quad v_{II} = -v_I' = 4.93q', \quad w_{II}' = w_I' = 4.24q',$$

$$(r_2\psi')_{II} = -(r_2\psi')_I = -\frac{r_2}{r_1}115q' = -30.7q'. \tag{43.18}$$

From the displacements at the edges of both plates one may determine the constants C_1, C_2, C_1', C_2' for each plate (taking advantage here of the tables which have already been prepared for these constants):

a) first plate

$$\begin{aligned} C_1 &= (0.181 - 1.061 + 0.161 + 0.430 - 0.096)q' = -0.385q', \\ C_2 &= (0.077 - 0.057 + 0.015 - 0.076 - 0.028)q' = -0.028q', \\ C_1' &= (1.34 - 10.95 + 0.906 + 0.026 - 0.64)q' = -9.32q', \\ C_2' &= (0.098 + 7.69 - 1.93 - 4.03 + 0.004)q' = 1.83q'; \end{aligned} \tag{43.19}$$

b) second plate:

$$\begin{aligned} C_1 &= (1.51 + 2.77 + 1.82 - 1.99 - 0.159)q' = 3.85q', \\ C_2 &= (-0.935 - 7.27 - 4.54 + 9.73 - 0.156)q' = -2.86q', \\ C_1' &= (-1.255 - 13.62 - 5.41 + 4.91 + 0.198)q' = -15.17q', \\ C_2' &= (-2.47 + 6.05 + 9.24 - 16.45 + 0.056)q' = -3.57q'. \end{aligned} \tag{43.20}$$

Having obtained all the constants, one can now write down the expressions for any of the displacements, forces and moments in an oval shell. Thus, for example, for the first plate:

$$\begin{aligned} w' &= (-0.385\Phi_1 - 0.028\Phi_2 - 9.31\Psi_1 + 1.83\Psi_2 + 1)q', \\ \frac{r_1}{E\delta}S' &= (-0.01\Phi_3 - 0.00301\Phi_4 + 0.056\Psi_3 + 0.236\Psi_4)q', \\ \frac{r_1}{E\delta}T' &= (0.0221\Phi_1 + 0.0288\Phi_2 - 0.481\Psi_1 + 0.623\Psi_2)q', \\ \sigma'_{M_2} &= \frac{6M_2'}{\delta^2} = (0.0505\Phi_1 - 0.0402\Phi_2 - 1.17\Psi_1 + 0.623\Psi_2)\frac{4}{\pi}\frac{pr_1}{\delta}; \end{aligned} \tag{43.21}$$

for the second plate:

$$\begin{aligned} w' &= (3.85\Phi_1 - 2.86\Phi_2 - 15.17\Psi_1 - 3.57\Psi_2 + 0.071)q', \\ \sigma_{T_1}' &= \frac{T_1'}{\delta} = (-0.833\Phi_1 - 0.210\Phi_2 - 2.24\Psi_1 + 1.286\Psi_2)\frac{4}{\pi}\frac{pr_1}{\delta}, \end{aligned} \tag{43.22}$$

$$\sigma_{S'} = \frac{S'}{\delta} = (0.0937\Phi_3 + 0.151\Phi_4 + 0.333\Psi_3 + 0.446\Psi_4)\frac{4}{\pi}\frac{pr_1}{\delta},$$
$$\sigma'_{M_2} = \frac{6M_2'}{\delta^2} = (0.252\Phi_1 + 1.50\Phi_2 - 2.39\Psi_1 - 4.08\Psi_2)\frac{4}{\pi}\frac{pr_1}{\delta}, \tag{43.22}$$

where Φ_j and Ψ_j are the functions of the angle φ, defined by (42.32), the angle being measured from the plane of symmetry of each plate.

The formulae (43.21) and (43.22) give the variation of w', S', T_1', M_2' over the transverse section of the oval shell or, more accurately, the coefficients of the terms in the series (42.31), corresponding to $w = 1$. On this basis, the following table may be evaluated:

Table 10

φ	0	15°	25°	35°	45°	60°	75°	90°
$w' : \frac{pr_1^2}{E\delta}$	−11.1	+0.87	+17.7	+25.4	$\frac{+6.1}{+5.1}$	−4.3	−12.3	−14.4
$v' : \frac{pr_1^2}{E\delta}$	0.00	2.19	0.68	−3.32	$\frac{-6.9}{-6.85}$	−6.3	−4.0	0.00
$\sigma_{T_1}' : \frac{pr_1}{\delta}$	−0.585	+0.663	+1.86	+1.63	$\frac{-0.87}{-1.11}$	−2.41	−3.52	−3.91
$\sigma_{S'} : \frac{pr_1}{\delta}$	0.00	+0.05	−0.36	−1.06	$\frac{-1.25}{-1.23}$	−0.92	−0.57	0.00
$\sigma_{T_2}' : \frac{pr_1}{\delta}$	1.29	1.34	1.30	1.05	$\frac{0.625}{0.665}$	0.470	0.370	0.330
$\sigma_{M_2}' : \frac{pr_1}{\delta}$	−1.42	−0.88	+0.60	+2.32	$\frac{-0.14}{-0.32}$	−1.94	−2.71	−2.72

In using this table, one must take into consideration that here the same origin has been taken for the angle φ in both plates, namely, the angle $\varphi = 0$ corresponds to the plane of symmetry of the first plate and the angle $\varphi = 90°$ to the apex of the second plate.

The results in Table 10 are shown graphically in Figs. 58, 59.

First consider Fig. 58, showing on an exaggerated scale the deformation of the oval cross-section of the cylindrical shell under discussion when loaded by an internal pressure. This curve, first calculated in 1938, was for a long time considered incorrect. It shows naturally that an internal pressure must induce at the ends of the minor and major axes of the oval deformations of different signs, so that the eccentricity of the cross-section

of the shell will tend to decrease. This is the same as would be the case if the radius of curvature of the oval were a continuous function of the arc length (see § 35). However, for shells with discontinuously changing radii of curvature, the deformation of the cross-section, as shown by Fig. 58, is more complicated. Experimental results (shown dotted in



Fig. 58.



Fig. 59.

Fig. 58) fully confirm the predictions of the theory, and not only qualitatively, but also quantitatively. It is essential to further note that, as can be seen from Table 10, the bending stresses in the problem under consideration are not at all less significant than the membrane stresses (i.e., the stresses, uniformly distributed through the thickness of the shell.)

Hence it is clear that the membrane theory does not apply to this problem.

§ 44. The simplified theory of long cylindrical plates

The above formulae for the analysis of cylindrical plates may be used to investigate short as well as relatively long cylindrical plates.

If one has only the study of long cylindrical plates in mind, the theory can be essentially simplified; since this case is of considerable practical interest in connection with the stress analysis of thin-walled reinforced roofs, it should be treated here in detail. For this purpose, as before, only the first terms corresponding to $m = 1$ in the expansions of the load distribution (42.3) will be retained.

If the length L of the cylindrical plate is several times its radius r_0, the parameter

$$f = \frac{\lambda^2 - \frac{1}{2}}{b\lambda} \tag{44.1}$$

will be small and may be neglected compared with unity. Introducing

this simplification into the formulae (42.21), one has

$$c_1 = d_2 = \sqrt{\frac{b\lambda}{2}}\sqrt{\sqrt{2}+1} = \nu\cos\frac{\pi}{8},$$
$$c_2 = d_1 = \sqrt{\frac{b\lambda}{2}}\sqrt{\sqrt{2}-1} = \nu\sin\frac{\pi}{8}, \tag{44.2}$$

where

$$\nu = \sqrt[4]{2}\sqrt{b\lambda}. \tag{44.3}$$

The adoption of these formulae corresponds to writing equation (42.1) in the form

$$\frac{\partial^4\tilde{T}}{\partial\varphi^4} + i2b^2\frac{\partial^2\tilde{T}}{\partial\xi^2} = 0, \tag{44.4}$$

i.e., it corresponds to neglecting $\frac{\partial^2\tilde{T}}{\partial\xi^2}$ and $\tilde{T}$ compared with $\frac{\partial^2\tilde{T}}{\partial\varphi^2}$. (In equation (44.4) as well as in later formulae, terms depending on the surface loading have been omitted, since the homogeneous problem is of prime interest). Introducing analogous simplifications into the formulae (40.8), (40.9), (40.11) and (40.16) expressing the complex stresses and displacements in terms of the auxiliary function $\tilde{T}$, one finds

$$\tilde{T}_1 \approx \tilde{T},\ \tilde{T}_2 \approx \frac{i}{2b^2}\frac{\partial^2\tilde{T}}{\partial\varphi^2},\ \frac{\partial\tilde{S}}{\partial\xi} \approx -\frac{i}{2b^2}\frac{\partial^3\tilde{T}}{\partial\varphi^3}, \tag{44.5}$$

$$\frac{\partial\tilde{u}}{\partial\xi} \approx \frac{r_0}{E\delta}\tilde{T},\ \frac{\partial^2\tilde{v}}{\partial\xi^2} \approx -\frac{r_0}{E\delta}\frac{\partial\tilde{T}}{\partial\varphi},\ \frac{\partial^2\tilde{w}}{\partial\xi^2} \approx \frac{r_0}{E\delta}\frac{\partial^2\tilde{T}}{\partial\varphi^2}. \tag{44.6}$$

The solution corresponding to the first term of the series (42.31) will now be sought in the form

$$\tilde{T} = \tilde{T}'\sin\lambda\xi,\ \tilde{T}_1 = \tilde{T}_1'\sin\lambda\xi,\ \tilde{T}_2 = \tilde{T}_2'\sin\lambda\xi,\ \tilde{S} = \tilde{S}'\cos\lambda\xi,$$
$$\tilde{u} = \tilde{u}'\cos\lambda\xi,\ \tilde{v} = \tilde{v}'\sin\lambda\xi,\ \tilde{w} = \tilde{w}'\sin\lambda\xi. \tag{44.7}$$

Substitution of these expressions in (44.5) and (44.6) gives

$$\tilde{T}_1' \approx \tilde{T}',\ \tilde{T}_2' \approx \frac{i}{2b^2}\frac{d^2\tilde{T}'}{d\varphi^2},\ \tilde{S}' \approx \frac{i}{2b^2}\frac{1}{\lambda}\frac{d^3\tilde{T}'}{d\varphi^3},$$
$$\tilde{u}' \approx -\frac{r_0}{E\delta}\frac{1}{\lambda}\tilde{T}',\ \tilde{v}' \approx \frac{r_0}{E\delta}\frac{1}{\lambda^2}\frac{d\tilde{T}'}{d\varphi},\ \tilde{w}' \approx -\frac{r_0}{E\delta}\frac{1}{\lambda^2}\frac{d^2\tilde{T}'}{d\varphi^2}. \tag{44.8}$$

Consideration will now be limited to deformations of cylindrical

plates which are symmetrical with respect to the plane $\varphi = 0$. Hence one needs only retain in the general expression for $\tilde{T}'$ even functions of φ, i.e., one may write

$$\tilde{T}' = \tilde{C}_1 \cosh (c_1 + id_1)\varphi + \tilde{C}_2 \cosh (c_2 - id_2)\varphi. \tag{44.9}$$

This formula follows immediately from the formulae (42.20) and (42.22). Separating it into real and imaginary parts and letting

$$\tilde{C}_1 = C_1 - iC_2, \quad \tilde{C}_2 = C_3 + iC_4, \tag{44.10}$$

where C_1, C_2, C_3, C_4 are real arbitrary constants, one obtains by use of known formulae of the theory of hyperbolic functions

$$\tilde{T}' = R_e + iI_m, \tag{44.11}$$

where

$$\begin{aligned} R_e &= C_1\Phi_1 + C_2\Phi_2 + C_3\Psi_1 + C_4\Psi_2, \\ I_m &= C_1\Phi_2 - C_2\Phi_1 - C_3\Psi_2 + C_4\Psi_1, \end{aligned} \tag{44.12}$$

and the functions Φ and Ψ are defined by (42.32).

The present principal aim is the deduction of formulae for the direct evaluation of the coefficients a_{jk} (i.e., of the stiffness coefficients for the edges of cylindrical plates). Therefore, in what follows, the functions Φ and Ψ will be considered mainly at the straight edges, i.e., for $\varphi = \varphi_0$. But then one may write as an approximation

$$\begin{aligned} \cosh c_1\varphi &\approx \sinh c_1\varphi \approx \tfrac{1}{2}e^{c_1\varphi}, \\ \cosh c_2\varphi &\approx \sinh c_2\varphi \approx \tfrac{1}{2}e^{c_2\varphi}, \end{aligned} \tag{44.13}$$

admitting an error (near the straight boundary) of order $e^{-2c_2\varphi_0}$ in comparison with unity. As a rule, this error is relatively small (approx. 10—15%). Applying this simplification to the formulae (44.12), it is found that

$$\begin{aligned} R_e &\approx e^{c_1\varphi}(C_1 \cos d_1\varphi + C_2 \sin d_1\varphi) + e^{c_2\varphi}(C_3 \cos d_2\varphi + C_4 \sin d_2\varphi), \\ I_m &\approx e^{c_1\varphi}(C_1 \sin d_1\varphi - C_2 \cos d_1\varphi) - e^{c_2\varphi}(C_3 \sin d_2\varphi - C_4 \cos d_2\varphi), \end{aligned} \tag{44.14}$$

where the common factors $\frac{1}{2}$ have been included in the arbitrary constants.

The formulae (44.14) may likewise be represented in the form

$$\begin{aligned} R_e &\approx B_1' e^{c_1\varphi} \cos (d_1\varphi + \beta_1') + B_2' e^{c_2\varphi} \cos (d_2\varphi + \beta_2'), \\ I_m &\approx B_1' e^{c_1\varphi} \sin (d_1\varphi + \beta_1') - B_2' e^{c_2\varphi} \sin (d_2\varphi + \beta_2'), \end{aligned} \tag{44.15}$$

where B_1', B_2', β_1', β_2' are new arbitrary constants.

Differentiating R_e with respect to φ and taking for this purpose (44.2)

into consideration, one finds

$$\frac{dR_e}{d\varphi} = \nu\left[B_1' e^{c_1\varphi}\cos\left(d_1\varphi + \beta_1' + \frac{\pi}{8}\right) + \right.$$
$$\left. + B_2' e^{c_2\varphi}\cos\left(d_2\varphi + \beta_2' + \frac{3}{8}\pi\right)\right]. \qquad (44.16)$$

Hence one arrives at the following simple rule for the differentiation of R_e: for each differentiation, one has to multiply the entire expression by ν, increase the argument of the first cosine by $\frac{\pi}{8}$ and of the second by $\frac{3\pi}{8}$.

Next, differentiating I_m, one finds

$$\frac{dI_m}{d\varphi} = \nu\left[B_1' e^{c_1\varphi}\sin\left(d_1\varphi + \beta_1' + \frac{\pi}{8}\right) + \right.$$
$$\left. - B_2' e^{c_2\varphi}\sin\left(d_2\varphi + \beta_2' + \frac{3}{8}\pi\right)\right], \qquad (44.17)$$

whence one obtains for the differentiation of I_m a rule which is quite analogous to that above for differentiating R_e. Since the displacements are equal to the real parts of the corresponding complex displacements, it follows from (44.8), taking (44.11) into consideration, that

$$u' = -\frac{r_0}{E\delta}\frac{1}{\lambda}R_e, \quad v' = \frac{r_0}{E\delta}\frac{1}{\lambda^2}\frac{dR_e}{d\varphi},$$
$$w' = -\frac{r_0}{E\delta}\frac{1}{\lambda^2}\frac{d^2R_e}{d\varphi^2}. \qquad (44.18)$$

Using (44.15) and (44.16), one arrives at the following expressions for the coefficients u', v', w':

$$u' = -\frac{1}{\lambda}\frac{r_0}{E\delta}\left[B_1' e^{c_1\varphi}\cos(d_1\varphi + \beta_1') + B_2' e^{c_2\varphi}\cos(d_2\varphi + \beta_2')\right],$$

$$v' = \frac{\nu}{\lambda^2}\frac{r_0}{E\delta}\left[B_1' e^{c_1\varphi}\cos\left(d_1\varphi + \beta_1' + \frac{\pi}{8}\right) + \right.$$
$$\left. + B_2' e^{c_2\varphi}\cos\left(d_2\varphi + \beta_2' + \frac{3}{8}\pi\right)\right], \qquad (44.19)$$

$$w' = -\frac{\nu^2}{\lambda^2}\frac{r_0}{E\delta}\left[B_1' e^{c_1\varphi}\cos\left(d_1\varphi + \beta_1' + \frac{\pi}{4}\right) - B_2' e^{c_2\varphi}\sin\left(d_2\varphi + \beta_2' + \frac{\pi}{4}\right)\right].$$

To these may be added the expressions for the coefficient of the rotation ψ:

$$r_0\psi' = -\frac{dw'}{d\varphi} + v' \approx -\frac{dw'}{d\varphi} = \frac{\nu^3}{\lambda^2}\frac{r_0}{E\delta}\left[B_1' e^{c_1\varphi}\cos\left(d_1\varphi+\beta_1'+\frac{3}{8}\pi\right) - \right.$$
$$\left. - B_2' e^{c_2\varphi}\cos\left(d_2\varphi+\beta_2'+\frac{\pi}{8}\right)\right]. \quad (44.20)$$

From (44.8) and likewise from (40.5) follows that

$$T_1' \approx R_e, \qquad -\frac{2b^2}{r_0}\frac{M_2-\mu M_1}{1-\mu^2} \approx I_m,$$
$$T_2' \approx -\frac{1}{2b^2}\frac{d^2 I_m}{d\varphi^2}, \qquad -\frac{2b^2}{r_0}\frac{M_1-\mu M_2}{1-\mu^2} \approx \frac{1}{2b^2}R_e \approx 0, \quad (44.21)$$
$$S' = -\frac{1}{2b^2}\frac{1}{\lambda}\frac{d^3 I_m}{d\varphi^3}, \qquad \frac{2b^2}{r_0}\frac{H}{1-\mu} \approx \frac{1}{2b^2}\frac{1}{\lambda}\frac{d^3 R_e}{d\varphi^3}.$$

Substituting here the expressions for R_e and I_m and using their rules of differentiation, one finds

$$T_1' \approx B_1' e^{c_1\varphi}\cos(d_1\varphi+\beta_1') + B_2' e^{c_2\varphi}\cos(d_2\varphi+\beta_2'),$$
$$T_2' \approx -\frac{\nu^2}{2b^2}\left[B_1' e^{c_1\varphi}\sin\left(d_1\varphi+\beta_1'+\frac{\pi}{4}\right) - B_2' e^{c_2\varphi}\cos\left(d_2\varphi+\beta_2'+\frac{1}{4}\pi\right)\right],$$
$$S' \approx -\frac{1}{2b^2}\frac{\nu^3}{\lambda}\left[B_1' e^{c_1\varphi}\sin\left(d_1\varphi+\beta_1'+\frac{3}{8}\pi\right) + B_2' e^{c_2\varphi}\sin\left(d_2\varphi+\beta_2'+\frac{\pi}{8}\right)\right],$$
$$M_1' \approx \mu M_2', \quad (44.22)$$
$$M_2' \approx -\frac{r_0}{2b^2}\left[B_1' e^{c_1\varphi}\sin(d_1\varphi+\beta_1') - B_2' e^{c_2\varphi}\sin(d_2\varphi+\beta_2')\right],$$
$$H' \approx \frac{(1-\mu)r_0}{4b^4}\frac{\nu^3}{\lambda}\left[B_1' e^{c_1\varphi}\cos\left(d_1\varphi+\beta_1'+\frac{3}{8}\pi\right) - B_2' e^{c_2\varphi}\cos\left(d_2\varphi+\beta_2'+\frac{\pi}{8}\right)\right].$$

It is now possible to determine also the normal shear resultants, using the formulae (16.6), viz.,

$$(1+\mu)r_0 N_1 \approx \frac{\partial(M_1+M_2)}{\partial\xi}, \quad (1+\mu)r_0 N_2 \approx -\frac{\partial(M_1+M_2)}{\partial\varphi}. \quad (44.23)$$

Substituting here

$$N_1 = N_1'\cos\lambda\xi, \quad M_1 = M_1'\sin\lambda\xi,$$
$$N_2 = N_2'\sin\lambda\xi, \quad M_2 = M_2'\sin\lambda\xi, \quad (44.24)$$

one obtains

$$(1+\mu)r_0N_1' = \lambda(M_1' + M_2'),$$
$$(1+\mu)r_0N_2' = \frac{d(M_2' + M_1')}{d\varphi}. \tag{44.25}$$

Hence, by (44.22),

$$N_1' \approx -\frac{\lambda}{2b^2}\left[B_1'e^{c_1\varphi}\sin(d_1\varphi + \beta_1') - B_2'e^{c_2\varphi}\sin(d_2\varphi + \beta_2')\right],$$
$$N_2' \approx -\frac{\nu}{2b^2}\left[B_1'e^{c_1\varphi}\sin\left(d_1\varphi + \beta_1' + \frac{\pi}{8}\right) - \right. \tag{44.26}$$
$$\left. - B_2'e^{c_2\varphi}\sin\left(d_2\varphi + \beta_2' + \frac{3\pi}{8}\right)\right].$$

The set of formulae (44.19), (44.20), (44.22), and (44.26) make it possible to write down general expressions for the displacements, the angle of rotation, the forces and moments for the case when only the first terms have been retained in the series (42.31).



Fig. 60.

In what follows, it is more convenient to measure the angle φ not from the apex of the shell (as this has been done so far), but from one of its edges (see Fig. 60). For this purpose, the angle φ in the formulae (44.19), (44.22) and (44.26) will be replaced by

$$\alpha = \varphi_0 - \varphi. \tag{44.27}$$

One thus finds

$$u' = \frac{\lambda}{\nu^2}\left[B_1e^{-c_1\alpha}\cos\left(d_1\alpha+\beta_1+\frac{\pi}{4}\right) - B_2e^{-c_2\alpha}\cos\left(d_2\alpha+\beta_2-\frac{\pi}{4}\right)\right],$$
$$v' = -\frac{1}{\nu}\left[B_1e^{-c_1\alpha}\cos\left(d_1\alpha+\beta_1+\frac{\pi}{8}\right) - B_2e^{-c_2\alpha}\sin\left(d_2\alpha+\beta_2-\frac{\pi}{8}\right)\right],$$
$$w' = B_1e^{-c_1\alpha}\cos(d_1\alpha + \beta_1) + B_2e^{-c_2\alpha}\cos(d_2\alpha + \beta_2), \tag{44.28}$$
$$r_0\psi' = -\nu\left[B_1e^{-c_1\alpha}\cos\left(d_1\alpha+\beta_1-\frac{\pi}{8}\right) + B_2e^{-c_2\alpha}\sin\left(d_2\alpha+\beta_2+\frac{\pi}{8}\right)\right],$$

$$\frac{r_0}{E\delta}T_1' = -\lambda u', \tag{44.29}$$

$$\frac{r_0}{E\delta}T_2' = -\frac{\lambda^4}{\nu^4}[B_1e^{-c_1\alpha}\sin(d_1\alpha + \beta_1) - B_2e^{-c_2\alpha}\sin(d_2\alpha + \beta_2)],$$

$$\frac{r_0}{E\delta} S' = -\frac{\lambda^3}{\nu^3}\left[B_1 e^{-c_1\alpha}\sin\left(d_1\alpha + \beta_1 - \frac{\pi}{8}\right) + \right.$$

$$\left. + B_2 e^{-c_2\alpha}\cos\left(d_2\alpha + \beta_2 + \frac{\pi}{8}\right)\right],$$

$$\frac{r_0}{E\delta} N_2' = -\frac{\nu^3}{4b^4}\left[B_1 e^{-c_1\alpha}\sin\left(d_1\alpha + \beta_1 + \frac{\pi}{8}\right) - \right.$$

$$\left. - B_2 e^{-c_2\alpha}\cos\left(d_2\alpha + \beta_2 - \frac{\pi}{8}\right)\right], \quad (44.29)$$

$$\frac{1}{E\delta} M_2' = -\frac{\nu^2}{4b^4}\left[B_1 e^{-c_1\alpha}\cos\left(d_1\alpha + \beta_1 - \frac{\pi}{4}\right) - \right.$$

$$\left. - B_2 e^{-c_2\alpha}\cos\left(d_2\alpha + \beta_2 + \frac{\pi}{4}\right)\right],$$

$$M_1' \approx \mu M_2',$$

$$\frac{1}{E\delta} H' = -\frac{(1-\mu)\lambda\nu}{4b^4}\left[B_1 e^{-c_1\alpha}\cos\left(d_1\alpha + \beta_1 - \frac{\pi}{8}\right) + \right.$$

$$\left. + B_2 e^{-c_2\alpha}\sin\left(d_2\alpha + \beta_2 + \frac{\pi}{8}\right)\right],$$

where B_1, B_2, β_1, β_2 are new constants of integration. These very convenient expressions represent the simplest formulation of the approximate solution of the homogeneous problem for cylindrical plates.

On the basis of the conditions underlying their deduction, this solution may only be used near the edges of a cylindrical plate. However, it will be seen from the example below that it gives satisfactory agreement even near the apex of the shell. Thus, it may be used in the interval $0 \leqslant \alpha \leqslant \varphi_0$, i.e., over half the cross-section of the shell. This is also sufficient, since it has been assumed that the deformation of the cylindrical plate is symmetrical with respect to the plane $\varphi = 0$.

Using the formulae (44.28) and (44.29), the influence coefficients for the edges of cylindrical plates will now be obtained. For this purpose, first of all the constants of integration corresponding to the four sets of boundary conditions (42.35) will be evaluated. These constants are given in the following table (the intermediate calculations having been omitted in view of their elementary nature):

Table 11

	$u' = 1$	$v' = 1$	$w' = 1$	$r_0\psi' = 1$	(*)
$B_1 \cos \beta_1$	0.00	-0.924ν	-0.707	$-\frac{0.924}{\nu}$	—
$B_1 \sin \beta_1$	$-2.41\frac{\nu^2}{\lambda}$	-4.08ν	-4.12	$-\frac{2.32}{\nu}$	—
$B_2 \cos \beta_2$	0.00	0.924ν	1.707	$\frac{0.924}{\nu}$	—
$B_2 \sin \beta_2$	$\frac{\nu^2}{\lambda}$	2.23ν	1.707	$\frac{0.383}{\nu}$	—

Substituting these values of the constants into the formulae for the forces and moments (44.29), the following table of stiffness coefficients for the edges of the cylindrical plates is found:

Table 12

	$u' = 1$	$v' = 1$	$w' = 1$	$r_0'\psi = 1$
$\frac{r_0}{E\delta} S'$	$a_1\frac{\lambda^2}{\nu}$	$a_2\frac{\lambda^3}{\nu^2}$	$a_1\frac{\lambda^3}{\nu^3}$	$\frac{\lambda^3}{\nu^4}$
$\frac{r_0}{E\delta} T_2'$	$a_2\frac{\lambda^3}{\nu^2}$	$a_3\frac{\lambda^4}{\nu^3}$	$a_4\frac{\lambda^4}{\nu^4}$	$a_1\frac{\lambda^4}{\nu^5}$
$\frac{r_0}{E\delta} N_2'$	$a_1\frac{\lambda^3}{\nu^3}$	$a_4\frac{\lambda^4}{\nu^4}$	$a_3\frac{\lambda^4}{\nu^5}$	$a_2\frac{\lambda^4}{\nu^6}$
$\frac{1}{E\delta} M_2'$	$\frac{\lambda^3}{\nu^4}$	$a_1\frac{\lambda^4}{\nu^5}$	$a_2\frac{\lambda^4}{\nu^6}$	$a_1\frac{\lambda^4}{\nu^7}$

In this table, the quantities a_j are

$$a_1 = \frac{1}{\sin\frac{\pi}{8}} \approx 2.61, \qquad a_2 = \frac{\sqrt{2}}{\sqrt{2}-1} \approx 3.41, \tag{44.30}$$

$$a_3 = \frac{1}{(\sqrt{2}-1)\sin\frac{\pi}{8}} \approx 6.31,$$
$$a_4 = \frac{\sqrt{2}+1}{\sqrt{2}-1} \approx 5.84. \tag{44.30}$$

Thus, the expressions (44.28) and (44.29) offer the means of deducing simple formulae for the direct evaluation of stiffness tables the computation of which by the method of the preceding section would have represented a tedious problem.

Using the above simplified theory, a cylindrical roof the edges of which are reinforced by vertical beams will now be studied. Let the length of the roof be

$$L = \tfrac{4}{3}\pi r_0$$

and let it be loaded by its own weight

$$q = 144\ [\mathrm{kg/m^2}].$$

These data have been taken from A. L. Gol'denweizer's paper [98] in which the stress analysis of this roof has been executed using more accurate equations and formulae. Thanks to this circumstance, the simplified theory of this section may be compared with a theory which corresponds approximately to that of § 42. The auxiliary parameters of the shell are $\lambda = 0.75$, $4b^4 = 1.2 \times 10^5$, $\nu = 3.73$.

Substituting these values into Table 12, one finds the following values for the stiffness coefficients of the cylindrical plate under consideration:

Table 13

	$u' = 1$	$v' = 1$	$w' = 1$	$r_0\psi' = 1$	(*)
$\frac{r_0}{E\delta} S'$	0.3485 0.393 12.6%	0.09051 0.103 13%	0.01912 0.0212 11%	0.001899 0.00217 14%	$43\frac{qr_0}{E}$
$\frac{r_0}{E\delta} T_2'$	0.09051 0.103 13%	0.03391 0.0382 13%	0.008448 0.00948 12%	0.0009377 0.00114 21%	$-142\frac{qr_0}{E}$
$\frac{r_0}{E\delta} N_2'$	0.01912 0.0212 11%	0.008448 0.00948 12%	0.002469 0.00274 11%	0.0003456 0.000399 15%	$-18\frac{qr_0}{E}$
$\frac{1}{E\delta} M_2'$	0.001899 0.00217 14%	0.0009377 0.00114 21%	0.0003456 0.000399 15%	0.00007325 0.0000815 11%	$-2.0\frac{qr_0}{E}$

The upper numbers in this table were obtained by Gol'denweizer, the lower ones by use of the formulae in Table 12. The percentage errors are given on the right hand side of each column.

It is thus seen that in the given particular case the approximate formulae determine the influence coefficients for the edge of the shell with an average error of about 13% and, further, that this error is everywhere positive. In other words, the approximate formulae somewhat overestimate the stiffness of the edge of the shell. The fifth column (*) of the table contains the values of the forces and moments for the case when the edge of the shell is clamped. These values were calculated from (42.39), where the particular solutions (determined by the formulae of the membrane theory), on the basis of the given data, are

$$\begin{aligned} u^{*\prime} &= 603\frac{qr_0}{E}\cos\varphi, & S^{*\prime} &= 340q\delta\sin\varphi, \\ v^{*\prime} &= 1710\frac{qr_0}{E}\sin\varphi, & T_2^{*\prime} &= -127q\delta\cos\varphi. \\ w^{*\prime} &= 1840\frac{qr_0}{E}\cos\varphi, & N_2^* &= M_2^* = 0. \\ r_0\psi^{*\prime} &= -130\frac{qr_0}{E}\sin\varphi, \end{aligned} \tag{44.31}$$

Hence one finds the boundary values of these quantities [setting in (44.31) $\varphi = 60°$]

$$\begin{gathered} u_0^{*\prime} = 301\frac{qr_0}{E}, \quad v_0^{*\prime} = 1480\frac{qr_0}{E}, \quad w_0^{*\prime} = -920\frac{qr_0}{E}, \\ r_0\psi_0^{*\prime} = -112\frac{qr_0}{E}, \quad S_0^{*\prime} = 294q\delta, \quad T_{2,0}^{*\prime} = -63.5q\delta. \end{gathered} \tag{44.32}$$

It should be noted that these values (taken from the membrane theory) differ only very slightly from the results of Gol'denweizer, obtained by solution of the differential equation which take account of bending



Fig. 61.

moments [98]. Substituting (44.32) into (42.39), one finds the numbers in the fifth column (*) of Table 13.

The next stage in the calculations is the determination of the influence coefficients for the edge beams (referring to the same displacements and forces which have been evaluated in Table 13). For this calculation, the resistance of the beams to torsion and to bending in the plane of minimum stiffness will be neglected. As regards bending in the plane of maximum stiffness of the beam, it will be assumed that the law of plane sections applies.

Hence one may write down the following formulae, relating the displacements of the upper edges of the beams to the forces acting on them (which are to vary along the beam like $\sin \lambda\xi$ or $\cos \lambda\xi$ — see Figs. 61 and 62),

$$u_0 = \frac{r_0^2}{\lambda^2}\left(1 + \frac{h^2\Omega}{4J}\right)\frac{S^0}{E\Omega} - \frac{r_0^3 h}{2\lambda^3 EJ}(N_2^0 \cos\varphi_0 - T_2^0 \sin\varphi_0),$$

$$w_0 \cos\varphi_0 - v_0 \sin\varphi_0 = \frac{r_0^4}{\lambda^4 EJ}(N_2^0 \cos\varphi_0 - T_2^0 \sin\varphi_0 - \frac{h}{2r_0} S^0). \tag{44.33}$$

In these formulae h, Ω, J are the height, the area of the cross-section and the moment of inertia about the neutral axis of the section of the beam (which will be assumed to be rectangular).



Fig. 62.

The following equalities will be added to these equations:

$$N_2^0 \sin\varphi_0 + T_2^0 \cos\varphi_0 = 0, \quad M_2^0 = 0.$$

Setting now

$$u_0' = 1, \quad v_0' = w_0' = 0,$$
$$v_0' = 1, \quad u_0' = w_0' = 0,$$
$$w_0' = 1, \quad v_0' = u_0' = 0,$$

and taking into consideration that

$$\frac{J}{h^2\Omega} = \frac{1}{12}, \tag{44.34}$$

one obtains the following table, characterizing the stiffness of the beam:

Table 14

	$u' = 1$	$v' = 1$	$w' = 1$	$r_0\psi' = 1$	(*)
$\frac{r_0}{E\delta} S'$	$\frac{\Omega}{r_0\delta}\lambda^2$	$-\frac{\lambda^3 h\Omega}{2r_0^2\delta}\sin\varphi_0$	$\frac{\lambda^3 h\Omega}{2r_0^2\delta}\cos\varphi_0$	0	0
$\frac{r_0}{E\delta} T_2'$	$-\frac{\lambda^3 h\Omega}{2r_0^2\delta}\sin\varphi_0$	$\frac{\lambda^4 h^2\Omega}{3r_0^3\delta}\sin^2\varphi_0$	$-\frac{1}{6}\frac{\lambda^4 h^2\Omega}{r_0^3\delta}\sin 2\varphi_0$	0	$-\frac{4}{\pi}\frac{qr_0}{E\delta^2}\Omega\sin\varphi_0$
$\frac{r_0}{E\delta} N_2'$	$\frac{\lambda^3 h\Omega}{2r_0^2\delta}\cos\varphi_0$	$-\frac{1}{6}\frac{\lambda^4 h^2\Omega}{r_0^3\delta}\sin 2\varphi_0$	$\frac{1}{3}\frac{\lambda^4 h^2\Omega}{r_0^3\delta}\cos^2\varphi_0$	0	$\frac{4}{\pi}\frac{qr_0}{E\delta^2}\Omega\cos\varphi_0$
$\frac{1}{E\delta} M_2'$	0	0	0	0	0

The fifth column (*) of this table contains the values of the forces and moments, corresponding to clamping of the upper edge of the beam.

Substituting into this table the dimensions of the beam and the shell, one finds

Table 15

	$u_0' = 1$	$v_0' = 1$	$w_0' = 1$	$r_0\psi_0' = 1$	(*)
$\frac{r_0}{E\delta} S'$	0.244	− 0.017	0.0094	0	0
$\frac{r_0}{E\delta} T_2'$	− 0.017	0.0016	− 0.00093	0	$-47.8\frac{qr_0}{E}$
$\frac{r_0}{E\delta} N_2'$	0.0099	− 0.00093	0.00054	0	$27.6\frac{qr_0}{E}$
$\frac{1}{E\delta} M_2'$	0	0	0	0	0

The numbers in this table agree with those which were given by Gol'denweizer, since the calculations for the beams have not been modified.

Having obtained Tables 13 and 15 with the characteristic stiffnesses of the cylindrical plate and its reinforcing beams, one may now proceed to the determination of the edge displacements. For this purpose, the equations expressing the compatibility of the displacements of the beams and the edges of the shell may be written:

$$\begin{gathered} u_s = u_b, \quad v_s = v_b, \quad w_s = w_b, \quad \psi_s = \psi_b, \\ S_s = -S_b, \quad T_{2s} = -T_{2b}, \quad N_{2s} = -N_{2b}, \quad M_{2s} = -M_{2b}, \end{gathered} \tag{44.35}$$

where the subscripts s, b refer to the shell and the beams respectively. Using the above mentioned tables, these conditions lead to the following system of simultaneous equations:

$$\begin{aligned}
0.637u' + 0.086v' + 0.0311w' + 0.00217(r\psi') + 43\frac{qr_0}{E}0,\\
0.086u' + 0.0398v' + 0.0086w' + 0.00114(r\psi') - 190\frac{qr_0}{E} = 0,\\
0.0311u' + 0.0086v' + 0.00328w' + 0.000400(r\psi') + 10\frac{qr_0}{E} = 0,\\
0.0217u' + 0.00114v' + 0.000400w' + 0.0000815(r\psi') - 2\frac{qr_0}{E} = 0.
\end{aligned} \tag{44.36}$$

Solving this algebraic system, one finds

$$\begin{gathered}
u_0' = 380\frac{qr_0}{E}, \quad v_0' = 11\,900\frac{qr_0}{E}, \quad w_0' = -48\,000\frac{qr_0}{E},\\
r\psi_0' = 84\,200\frac{qr_0}{E},
\end{gathered} \tag{44.37}$$

while Gol'denweizer obtained the values

$$\begin{gathered}
u_0' = 480.9\frac{qr_0}{E}, \quad v_0' = 12\,200\frac{qr_0}{E}, \quad w_0' = -48\,580\frac{qr_0}{E},\\
r\psi_0' = 83\,000\frac{qr_0}{E}.
\end{gathered} \tag{44.38}$$

These two sets of results agree very closely except for u' which exhibits an appreciable difference. However, as will be clear from the further discussion, the displacement u tends to zero not far from the edge of the shell, so that the encountered appreciable error in the value of u' at the edge is quite natural. It will be verified below that in determining the maximum values of the displacement u' (or of the force T_2' proportional to it) the error of the approximate solution does not exceed the error incurred during the determination of the remaining displacements and forces.

Having obtained the values of the edge displacements, one can calculate all the constants of integration by use of Table 11. Substituting into this table the parameters of the shell and evaluating the fifth column (*) by the rules established in § 43, one obtains the following values of the constants:

Table 16

	$u_0' = 1$	$v_0' = 1$	$w_0' = 1$	$r\psi_0' = 1$	(*)
$B_1 \cos \beta_1$	0.00	− 3.44	− 0.707	− 0.248	$4\,410 \frac{qr_0}{E}$
$B_1 \sin \beta_1$	− 44.8	− 15.2	− 4.12	− 0.597	$32\,100 \frac{qr_0}{E}$
$B_2 \cos \beta_2$	0.00	3.44	1.707	0.248	$- 3\,490 \frac{qr_0}{E}$
$B_2 \sin \beta_2$	18.6	8.30	1.707	0.103	$- 16\,300 \frac{qr_0}{E}$

It follows from this table that

$$B_1 \cos \beta_1 = (0 - 40800 + 33900 - 20800 + 4410) \frac{qr_0}{E} = -23300 \frac{qr_0}{E},$$

$$B_1 \sin \beta_1 = (-17000 - 181000 + 198000 - 50200 + 32100) \frac{qr_0}{E} =$$

$$= -18100 \frac{qr_0}{E}, \quad (44.39)$$

$$B_2 \cos \beta_2 = (0 + 40800 - 82000 + 20800 - 3490) \frac{qr_0}{E} = -23900 \frac{qr_0}{E},$$

$$B_2 \sin \beta_2 = (7050 + 98600 - 82000 + 8670 - 16000) \frac{qr_0}{E} = 16000 \frac{qr_0}{E}.$$

Introducing these constants into the formulae (44.29) and taking into consideration that in this example $q\delta = 0.0865$ kg/cm, one deduces the following expressions for the forces and moments:

$$\begin{aligned}
T_2' &= e^{-c_1\alpha}[2.56 \cos d_1\alpha + 3.27 \sin d_1\alpha] + \\
&\quad + e^{-c_2\alpha}[2.26 \cos d_2\alpha - 3.38 \sin d_2\alpha] - 11 \cos \varphi, \\
M_2' &= e^{-c_1\alpha}[175 \cos d_1\alpha + 22 \sin d_1\alpha] - \\
&\quad - e^{-c_2\alpha}[175 \cos d_2\alpha - 33.5 \sin d_2\alpha], \\
T_1' &= e^{-c_1\alpha}[12.8 \cos d_1\alpha - 100 \sin d_1\alpha] - \\
&\quad - e^{-c_2\alpha}[19.5 \cos d_2\alpha + 100 \sin d_2\alpha] - 39.2 \cos \varphi, \\
S' &= e^{-c_1\alpha}[5.48 \cos d_1\alpha + 20 \sin d_1\alpha] + \\
&\quad + e^{-c_2\alpha}[19.7 \cos d_2\alpha + 4.01 \sin d_2\alpha] + 29.4 \sin \varphi.
\end{aligned} \quad (44.40)$$

These formulae contain the auxiliary functions

$$f_1(z) = e^{-0,924z} \cos(0.383z), \quad f_3(z) = e^{-0,383z} \cos(0.924z),$$
$$f_2(z) = e^{-0,924z} \sin(0.383z), \quad f_4(z) = e^{-0,383z} \cos(0.924z) \tag{44.41}$$

with $z = \nu\alpha = \nu(\varphi_0 - \varphi)$ which are shown in Fig. 63.

Table 17 contains T_1', T_2', S', M_2', as calculated from the formulae (44.40) (lower numbers) for $\varphi = 0$, 15°, 30°, 45°, 60°. The same table also gives the results calculated by Gol'denweizer (upper numbers).

Table 17

	0°	15°	30°	40°	60°
T_1' kg/cm	− 18.24 − 28	− 37.49 − 51.2	− 79.52 − 87.4	− 99.23 − 99.7	− 31.16 − 26.3
S' kg/cm	0 − 0.7	− 4.86 − 3.6	− 16.28 − 17.3	− 36.69 − 36.4	− 49.51 − 49.6
T_2' kg/cm	− 10.84 − 11.1	− 10.79 − 11.5	− 9.94 − 10.6	− 6.78 − 7.2	− 0.74 − 0.68
M_1' kg	60.61 33	58.80 62.0	42.21 43.4	14.10 12.4	0 0

Figures 64 to 67 exhibit (on the basis of this table) the distributions of the forces and moments; the results of Gol'denweizer correspond to the full lines, the approximate results to the dotted lines.

Comparison of the full and dotted lines shows that the approximate theory gives quite a correct representation of the magnitude of the forces and moments as well as of the character of their distributions. The greatest disagreements occur for $\varphi = 0$, i.e., at the apex of the shell, as had to be expected, since the formulae (44.28), (44.29) were deduced by neglecting terms causing errors which increase with the distance of the section under consideration from the edge of the shell. In view of this, the achieved accuracy can be accepted as completely satisfactory. Thus, this analysis indicates the suitability of the formulae (44.28) and (44.29) and of the corresponding Tables 11 and 12 for the evaluation of shells of the type used for thin-walled cylindrical roofs. This circumstance should be brought to the attention of engineers engaged on the design of roof structures who at the present time use more complicated methods which, however, do not lead to essentially greater accuracy than the formulae (44.28) and (44.29).



Fig. 63.



Fig. 64.



Fig. 65.



Fig. 66.



Fig. 67.

§ 45. The analysis of cylindrical plates, reinforced by transverse elastic ribs

The theory developed in § 41 will now be applied to the analysis of cylindrical plates reinforced by equidistant, transverse, elastic ribs. For this purpose, consider first of all the second equation of the system (41.20) with all its terms, i.e., in the form (41.16); in this way, the errors will be exhibited which arise from those simplifications employed to reduce this equation to the form it has in the system (41.20).

One thus has the system

$$\frac{\partial^2(T_1+T_2)}{\partial\xi^2}-\frac{1}{r_0}\left[\frac{\partial^2}{\partial\varphi^2}\Delta(M_2)+\frac{\partial^2 M_2}{\partial\varphi^2}\right]=r_0F_1(\xi,\eta),$$

$$\frac{4a^4}{r_0}\frac{\partial^2 M_2}{\partial\xi^2}+\frac{2(1+\mu)}{r_0}\left[\frac{\partial^4 M_2}{\partial\varphi^4}+\frac{\partial^2 M_2}{\partial\varphi^2}\right]+\frac{\partial^2}{\partial\varphi^2}\Delta(T_1+T_2)+ \tag{45.1}$$

$$+\frac{\partial^2(T_1+T_2)}{\partial\varphi^2}=r_0F_2(\xi,\varphi),$$

where F_1 and F_2 are the functions (41.21) of the external loading. Having in mind application of this system to the analysis of cylindrical plates, the functions F_1 and F_2 will be expressed in the form of the series

$$F_1=\sum_{m=1}^{\infty}F_{1,m}(\varphi)\sin\lambda_m\xi,\quad F_2=\sum_{m=1}^{\infty}F_{2,m}(\varphi)\sin\lambda_m\xi \tag{45.2}$$

$\left(\text{where, as before, } \lambda_m=m\frac{\pi r_0}{L}\right)$. Expressions for T_1, T_2 and M_2 will be sought in the form of similar series

$$T_1=\sum_{m=1}^{\infty}T_{1,m}(\varphi)\sin\lambda_m\xi,\quad T_2=\sum_{m=1}^{\infty}T_{2,m}(\varphi)\sin\lambda_m\xi, \tag{45.3}$$

$$M_2=\sum_{m=1}^{\infty}M_{2,m}\sin\lambda_m\xi.$$

After substituting (45.2) and (45.3) in (45.1), one obtains for the coefficients of (45.3) the following system of two ordinary differential equations:

$$\lambda_m^2T_m+\frac{1}{r_0}\left[\frac{d^2}{d\varphi^2}\Delta_m(M_{2,m})+\frac{d^2M_{2,m}}{d\varphi^2}\right]=-r_0F_{1,m}(\varphi),$$

$$\frac{1}{r_0}\left\{4a^4\lambda_m^2M_{2,m}-2(1+\mu)\left[\frac{d^4M_{2,m}}{d\varphi^4}+\frac{d^2M_{2,m}}{d\varphi^2}\right]\right\}- \tag{45.4}$$

$$-\frac{d^2}{d\varphi^2}\Delta_m(T_m)-\frac{d^2T_m}{d\varphi^2}=-r_0F_{2,m}(\varphi),$$

where

$$T_m=T_{1,m}+T_{2,m},\quad \Delta_m(\ldots)=\frac{d^2(\ldots)}{d\varphi^2}-\lambda_m^2(\ldots).$$

For reasons which have already been explained attention will be concentrated on the solution of the homogeneous problem, i.e., it

will be assumed that $F_{1,m} = F_{2,m} = 0$. The solution of the corresponding system of homogeneous differential equations must be sought in the form

$$T_m = Ae^{\gamma_m \varphi}, \quad M_{2,m} = r_0 B e^{\gamma_m \varphi}, \tag{45.5}$$

where A, B and γ_m are constants.

Substitution of (45.5) into (45.4) leads to the linear homogeneous system in the unknowns A and B:

$$\lambda_m^2 A + \gamma_m^2(\gamma_m^2 + 1 - \lambda_m^2)B = 0, \tag{45.6}$$

$$-\gamma_m^2(\gamma_m^2 + 1 - \lambda_m^2)A + [4a^4\lambda_m^2 - 2(1+\mu)\gamma_m^2(\gamma_m^2+1)]B = 0.$$

Hence, one obtains for the parameter γ_m the determinantal equation

$$\begin{vmatrix} \lambda_m^2, & \gamma_m^2(\gamma_m^2 + 1 - \lambda_m^2) \\ -\gamma_m^2(\gamma_m^2 + 1 - \lambda_m^2), & 4a^4\lambda_m^2 - 2(1+\mu)\gamma_m^2(\gamma_m^2+1) \end{vmatrix} = 0, \tag{45.7}$$

which in expanded form leads to the following fourth degree polynomial in γ_m^2:

$$\gamma_m^4(\gamma_m^2 + 1 - \lambda_m^2)^2 - \underline{2(1+\mu)\gamma_m^2(\gamma_m^2+1)\lambda_m^2} + 4a^4\lambda_m^4 = 0. \tag{45.8}$$

As will be seen from what follows, this equation has eight complex roots, the moduli of which are of order $\sqrt{a}\lambda_m$. This may likewise be verified on the basis of the results of the preceding section.

But if this is so, then the underlined centre term of the equation (45.8) will be small in comparison with the two outer terms (which are quantities of the same order). Indeed, the modulus of the ratio of this term to the last term of the equation will be a quantity of the order:

$$\left| \frac{2(1+\mu)\gamma_m^2(\gamma_m^2+1)\lambda_m^2}{4a^4\lambda_m^4} \right| \approx \frac{2(1+\mu)a^2\lambda_m^4}{4a^4\lambda_m^4} \approx \frac{1+\mu}{2a^2},$$

i.e., it will be essentially less than unity (since $2a^2 \gg 1$).

Thus the underlined term in (45.8) can be omitted without significant error.

Tracing the deduction of (45.8) back to (45.1), it is easy to show that the neglect of the above term is equivalent to omitting the underlined term in the system (45.1). Reverting still further to the equations (41.16) and (41.20), it is seen that the simplification of the present section is equivalent to that which leads from equation (41.16) to the second equation (41.20). In this way, the present simplification has been based in a certain manner on that in § 41 by showing that at least for the particular case of the circular cylinder it is completely admissible. After

rejecting in equation (45.8) the middle term, one obtains the approximate equation

$$\gamma_m{}^4(\gamma_m{}^2 + 1 - \lambda_m{}^2)^2 + 4a^4\lambda_m{}^4 = 0, \tag{45.9}$$

which can be resolved into the two bi-quadratic equations

$$\gamma_m{}^4 + (1 - \lambda_m{}^2)\gamma_m{}^2 \pm i2a^2\lambda_m{}^2 = 0, \tag{45.10}$$

the eight roots of which may be expressed by the two formulae

$$\begin{aligned}(\gamma_m)_{1,2,3,4} &= \pm c_1 \pm id_1,\\ (\gamma_m)_{5,6,7,8} &= \pm c_2 \pm id_2,\end{aligned} \tag{45.11}$$

where in the present case

$$\begin{aligned}c_1 &= \sqrt{\frac{a\lambda_m}{2}}\sqrt{\sqrt{(h+g_1)^2+g_2{}^2}+h+g_1},\\ d_1 &= \sqrt{\frac{a\lambda_m}{2}}\sqrt{\sqrt{(h+g_1)^2+g_2{}^2}-h-g_1},\\ c_2 &= \sqrt{\frac{a\lambda_m}{2}}\sqrt{\sqrt{(h-g_1)^2+g_2{}^2}+h-g_1},\\ d_2 &= \sqrt{\frac{a\lambda_m}{2}}\sqrt{\sqrt{(h-g_1)^2+g_2{}^2}-h+g_1},\end{aligned} \tag{45.12}$$

and

$$h = \frac{\lambda_m{}^2 - 1}{2a\lambda_m}, \tag{45.13}$$

$$g_1 = \frac{1}{\sqrt{2}}\sqrt{\sqrt{4+h^4}+h^2}, \quad g_2 = \frac{1}{\sqrt{2}}\sqrt{\sqrt{4+h^4}-h^2}.$$

After evaluation of the roots of the characteristic equation, one can write the following general expression for T_m:

$$T_m = A_1\Phi_1 + A_2\Phi_2 + A_3\Phi_3 + A_4\Phi_4 + A_1'\Psi_1 + A_2'\Psi_2 + A_3'\Psi_3 + A_4'\Psi_4 \tag{45.14}$$

[where the functions Φ_j and Ψ_j are defined by the formulae (42.32)]. The coefficients in the series (42.31), may be determined in terms of T_m, using the formulae of § 41 with $\rho = 1$. As a result, the coefficients u_m, v_m, w_m, ψ_m, $T_{1,m}$, $T_{2,m}$, S_m, $N_{2,m}$, $M_{2,m}$ can be represented by

Table 18

	α	β	α'	β'
$\frac{E\delta}{r_0} u_m$	$-\frac{1}{\lambda_m}\left[1+(1+\mu)\frac{c_1 d_1}{a^2}\right]$	$(1+\mu)\frac{c_1^2-d_1^2}{2a^2\lambda_m}$	$-\frac{1}{\lambda_m}\left[1-(1+\mu)\frac{c_2 d_2}{a^2}\right]$	$-(1+\mu)\frac{c_2^2-d_2^2}{2a^2\lambda_m}$
$\frac{E\delta}{r_0} v_m$	$\frac{c_1}{\lambda_m^2}\left[1-\frac{(1+\mu)\lambda_m^2}{c_1^2+d_1^2}\right]$	$\frac{d_1}{\lambda_m^2}\left[1+\frac{(1+\mu)\lambda_m^2}{c_1^2+d_1^2}\right]$	$\frac{c_2}{\lambda_m^2}\left[1-\frac{(1+\mu)\lambda_m^2}{c_2^2+d_2^2}\right]$	$\frac{d_2}{\lambda_m^2}\left[1+\frac{(1+\mu)\lambda_m^2}{c_2^2+d_2^2}\right]$
$\frac{E\delta}{r_0} w_m$	$-\frac{1}{\lambda_m^2}(c_1^2-d_1^2-\lambda_m^2)$	$-\frac{2c_1 d_1}{\lambda_m^2}$	$-\frac{1}{\lambda_m^2}(c_2^2-d_2^2-\lambda_m^2)$	$-\frac{2c_2 d_2}{\lambda_m^2}$
$E\delta\psi_m$	$\frac{d_1}{c_1^2+d_1^2}2a^2$	$\frac{c_1}{c_1^2+d_1^2}2a^2$	$-\frac{d_2}{c_2^2+d_2^2}2a^2$	$-\frac{c_2}{c_2^2+d_2^2}2a^2$
$T_{1,m}$	$1+\frac{c_1 d_1}{a^2}$	$-\frac{c_1^2-d_1^2}{2a^2}$	$1-\frac{c_2 d_2}{a^2}$	$\frac{c_2^2-d_2^2}{2a^2}$
$T_{2,m}$	$-\frac{c_1 d_1}{a^2}$	$\frac{c_1^2-d_1^2}{2a^2}$	$\frac{c_2 d_2}{a^2}$	$-\frac{c_2^2-d_2^2}{2a^2}$
S_m	$-\frac{d_1}{2a^2\lambda_m}(3c_1^2-d_1^2+1)$	$-\frac{c_1}{2a^2\lambda_m}(3d_1^2-c_1^2-1)$	$\frac{d_2}{2a^2\lambda_m}(3c_2^2-d_2^2+1)$	$\frac{c_2}{2a^2\lambda_m}(3d_2^2-c_2^2-1)$
$N_{2,m}$	$-\frac{d_1}{2a^2}$	$\frac{c_1}{2a^2}$	$\frac{d_2}{2a^2}$	$-\frac{c_2}{2a^2}$
$\frac{M_{2,m}}{r_0}$	0	$\frac{1}{2a^2}$	0	$-\frac{1}{2a^2}$

formulae of one of the following two types:

$$
\begin{aligned}
&=(\alpha A_1+\beta A_2)\Phi_1+(\alpha A_2-\beta A_1)\Phi_2+(\alpha A_3-\beta A_4)\Phi_3+(\alpha A_4+\beta A_3)\Phi_4+\\
&+(\alpha' A_1'+\beta' A_2')\Psi_1+(\alpha' A_2'-\beta' A_1')\Psi_2+(\alpha' A_3'-\beta' A_4')\Psi_3+(\alpha' A_4'+\beta' A_3')\Psi_4,\\
&=(\alpha A_4+\beta A_3)\Phi_1+(\alpha A_3-\beta A_4)\Phi_2+(\alpha A_2-\beta A_1)\Phi_3+(\alpha A_1+\beta A_2)\Phi_4+\\
&+(\alpha' A_4'+\beta' A_3')\Psi_1+(\alpha' A_3'-\beta' A_4')\Psi_2+(\alpha' A_2'-\beta' A_1')\Psi_3+(\alpha' A_1'+\beta' A_2')\Psi_4,
\end{aligned}
\tag{45.15}
$$

where u_m, $T_{1,m}$, $T_{2,m}$, $M_{2,m}$ will be expressed by formulae of the first type and v_m, $N_{2,m}$, S_m, ψ_m by formulae of the second type.

Table 18 gives the values of the coefficients α, β, α', β', corresponding to the different coefficients of the series (42.31).

No further explanation is required, since the sequence of the computations should again correspond with the recommendations of § 43. The example treated there represents a sufficiently detailed introduction to the computations involved.

§ 46. The analysis of tubes of arbitrary cross-section with freely supported ends

The preceding sections have only been concerned with cylindrical plates, i.e., with shells having four edges which are portions of circular cylinders. Proceeding now to the analysis of complete cylindrical shells (i.e., tubes), this problem will be solved in relation to tubes of arbitrary shape, assuming, however, that the cross-section has the form of a regular oval (i.e., an oval with two axes of symmetry, Fig. 68). Further, it should be emphasized that this limitation is not compulsory for the following reasoning (from the point of view of possible application of the method below) and that it has only been adopted since shells of that form are of the greatest practical interest. The origin of the coordinate x (and therefore also the origin of the non-dimensional coordinate ξ) will be taken at one of the ends of the tube. Hence the beginning and the end of the tube will be determined by $\xi = 0$, $\xi = \xi_0 = \frac{L}{r_0}$ (where L is the length of the tube). The origin of the arc s (and therefore also



Fig. 68.

the origin of $\eta = \frac{s}{r_0}$) will be placed at one of the ends of the minor axis of the oval.

In view of the hypothesis referring to the shape of the cross-section of the tube, the ratio $\rho = \frac{r}{r_0}$ will be an even periodic function of η with period $\eta_0 = \frac{2s_0}{r_0}$ (where s_0 is a quarter of the length of the circumference of the tube).

Let the external loading be due to normal pressure q_n with the other two components being identically zero. Then the fundamental differential equation of the theory of cylindrical shells (40.7) may be written

$$\Delta[\rho\Delta(\tilde{T})] + \frac{\partial}{\partial\eta}\left(\frac{1}{\rho}\frac{\partial\tilde{T}}{\partial\eta}\right) + i2b^2\frac{\partial^2\tilde{T}}{\partial\xi^2} = i2b^2 r_0\Delta(\rho q_n), \tag{46.1}$$

where

$$\Delta(\ldots) = \frac{\partial^2(\ldots)}{\partial\xi^2} + \frac{\partial^2(\ldots)}{\partial\eta^2},$$
$$4b^4 = 12(1-\mu^2)\frac{r_0^2}{\delta^2}. \tag{46.2}$$

For the problem to be fully determined, certain boundary conditions must be given at the edges of the tube. In this context, there is an essential difference between a tube and a cylindrical plate, in that the tube will always have two edges and that it will be closed with respect to the coordinate η. Hence, the solution of the equations (46.1) must in this case be a periodic function of η. In this section, consideration will be restricted to one type of boundary condition, namely, it will be assumed that the edges of the tube rest on supports which are absolutely rigid in their own planes but offer no resistance to edge moments and edge forces acting in the direction of the axis of the shell.

Mathematically, these boundary conditions take the form

$$v = w = T_1 = M_1 = 0, \tag{46.3}$$

for $\xi = 0$ and $\xi = \xi_0$.

In order to obtain the solution of the equation (46.1), satisfying the boundary conditions (46.3), one has to represent the loading in the form of the series

$$q_n = \sum_{m=1}^{\infty} q_n^{(m)} \sin\lambda_m\xi, \tag{46.4}$$

where, as before, $\lambda_m = m\dfrac{\pi r_0}{L}$ and the $q_n^{(m)}$ are functions of η only which may always be determined with the help of known formulae of the theory of Fourier series.

In the particular case of uniform pressure $q_n = p = \text{constant}$, one will have the expansion

$$q_n = p = \frac{4}{\pi} p \sum_{m=1}^{\infty} \frac{1}{m} \sin \lambda_m \xi, \tag{46.5}$$

in which the summation extends only over odd m. The series (46.5) will now be substituted into the equation (46.1) and the solution will be sought in the form

$$\tilde{T} = \sum_{m=1}^{\infty} \tilde{T}^{(m)} \sin \lambda_m \xi, \tag{46.6}$$

where the coefficients $\tilde{T}^{(m)}$ are functions of η only.

Then the partial differential equation (46.1) reduces to a set of ordinary differential equations of the general type

$$\Delta_m[\rho \Delta_m(\tilde{T}^{(m)})] + \frac{d}{d\eta}\left(\frac{1}{\rho}\frac{d\tilde{T}^{(m)}}{d\eta}\right) - i2b^2\lambda_m{}^2\tilde{T}^{(m)} = i2b^2 q_m \Delta_m(\rho), \tag{46.7}$$

where

$$\begin{aligned} q_m &= \frac{4}{\pi}\frac{pr_0}{m}, \\ \Delta_m(\ldots) &= \frac{d^2(\ldots)}{d\eta^2} - \lambda_m{}^2(\ldots). \end{aligned} \tag{46.8}$$

On the right hand side of (46.7) one has an even periodic function of η (since ρ is such a function). Hence $\tilde{T}^{(m)}$ must also be an even periodic function which may thus be sought in the form

$$\tilde{T}^{(m)} = \sum_{j=0}^{n} \tilde{T}^{(m,j)} \cos (j\nu\eta), \tag{46.9}$$

where $\nu = \dfrac{\pi r_0}{s_0}$ and the coefficients $\tilde{T}^{(m,j)}$ are as yet unknown constants which will be determined by use of Galerkin's method. Applying this

method to the equation (46.7), one may write

$$\int_0^{\eta_0}\left\{\Delta_m[\rho\Delta_m(\bar{T}^{(m)})]+\frac{d}{d\eta}\left(\frac{1}{\rho}\frac{d\bar{T}^{(m)}}{d\eta}\right)-i2b^2\lambda_m{}^2\bar{T}^{(m)}-\right.$$

$$\left.-2ib^2q_m\Delta_m(\rho)\right\}\delta(\bar{T}^{(m)})=0, \qquad (46.10)$$

where $\delta(\ldots)$ is the symbol for a variation compatible with the boundary conditions (in this case with the periodicity condition of the solution). Taking $\bar{T}^{(m)}$ in the form (46.9) and varying (independently of each other) the coefficients $\bar{T}^{(m,k)}$, one obtains the following system of $(n+1)$ algebraic equations with the unknowns $\bar{T}^{(m,k)}$:

$$\int_0^{\eta_0}\left\{\Delta_m[\rho\Delta_m(\bar{T}^{(m)})]+\frac{d}{d\eta}\left(\frac{1}{\rho}\frac{d\bar{T}^{(m)}}{d\eta}\right)-i2b^2\lambda_m{}^2\bar{T}^{(m)}-\right.$$

$$\left.-i2b^2q_m\Delta_m(\rho)\right\}\cos(k\nu\eta)\,d\eta=0, \qquad (46.11)$$

where $k=0, 1, 2 \ldots n$ and by $\bar{T}^{(m)}$ is understood the expression (46.9). Before substituting it in (46.11), it is expedient to reduce in this formula the order of the derivatives by an integration by parts which gives

$$-\int_0^{\eta_0}\left\{\rho(k^2\nu^2+\lambda_m{}^2)\left[\frac{d^2\bar{T}^{(m)}}{d\eta^2}-\lambda_m{}^2\bar{T}^{(m)}-i2b^2q_m\right]+\right.$$

$$\left.+i2b^2\lambda_m{}^2\bar{T}^{(m)}\right\}\cos(k\nu\eta)\,d\eta+k\nu\int_0^{\eta_0}\frac{1}{\rho}\frac{d\bar{T}^{(m)}}{d\eta}\sin(k\nu\eta)\,d\eta=0. \qquad (46.12)$$

Introducing now instead of $\bar{T}^{(m)}$ the expression (46.9), one has

$$\sum_{j=0}^{n}\{[(k^2\nu^2+\lambda_m{}^2)(j^2\nu^2+\lambda_m{}^2)I_1-jk\nu^2I_2-i2b^2\lambda_m{}^2I_3]\bar{T}^{(m,j)}+$$

$$+i2b^2q_m(k^2\nu^2+\lambda_m{}^2)I_4\}=0. \qquad (46.13)$$

where

$$I_1=\int_0^{\eta_0}\rho\cos(k\nu\eta)\cos(j\nu\eta)\,d\eta,\quad I_2=\int_0^{\eta_0}\frac{1}{\rho}\sin(k\nu\eta)\sin(j\nu\eta)\,d\eta,$$

$$I_3=\int_0^{\eta_0}\cos(k\nu\eta)\cos(j\nu\eta)\,d\eta,\quad I_4=\int_0^{\eta_0}\rho\cos(k\nu\eta)\,d\eta. \qquad (46.14)$$

Replacing in these integrals η by the new variable $z = \nu\eta$ and noting that $\eta_0 = \dfrac{\pi}{\nu}$, one has

$$I_1 = \frac{1}{\nu}\int_0^{\pi} \rho \cos kz \cos jz\, dz = \frac{1}{2\nu}\int_0^{\pi} \rho \cos (k+j)z\, dz + \frac{1}{2\nu}\int_0^{\pi} \rho \cos (k-j)z\, dz,$$

$$I_2 = \frac{1}{\nu}\int_0^{\pi} \frac{1}{\rho} \sin kz \sin jz\, dz = \frac{1}{2\nu}\int_0^{\pi} \frac{1}{\rho} \cos (k-j)z\, dz - \frac{1}{2\nu}\int_0^{\pi} \frac{1}{\rho} \cos (k+j)z\, dz,$$

$$I_3 = \frac{1}{\nu}\int_0^{\pi} \cos kz \cos jz\, dz, \tag{46.15}$$

$$I_4 = \frac{1}{\nu}\int_0^{\pi} \rho \cos kz\, dz.$$

Hence it follows, first of all, that

$$\begin{aligned} &\text{for } k \neq j : && I_3 = 0, \\ &\text{for } k = j > 0 : && I_3 = \frac{\pi}{2\nu}, \\ &\text{for } k = j = 0 : && I_3 = \frac{\pi}{\nu}. \end{aligned} \tag{46.16}$$

Further, since ρ is an even periodic function of η with period $2\eta_0$, it will also be an even periodic function of z (with period 2π). Hence the integral I_4 will be equal to

$$I_4 = \frac{\pi}{2\nu}\rho_k, \tag{46.17}$$

where ρ_k is a coefficient of the expansion

$$\rho = \tfrac{1}{2}\rho_0 + \rho_1 \cos \nu\eta + \rho_2 \cos 2\nu\eta + \ldots + \rho_k \cos k\nu\eta + \ldots, \tag{46.18}$$

i.e., a coefficient of the expansion of the function $\rho(\eta)$ in a Fourier series in terms of the arc length of the circumferential section.

A similar series applies also for the inverse function, namely

$$\frac{1}{\rho} = \frac{1}{2}\left(\frac{1}{\rho}\right)_0 + \left(\frac{1}{\rho}\right)_1 \cos \nu\eta + \left(\frac{1}{\rho}\right)_2 \cos 2\nu\eta + \ldots + \left(\frac{1}{\rho}\right)_k \cos k\nu\eta + \ldots, \tag{46.19}$$

where

$$\left(\frac{1}{\rho}\right)_k = \frac{2}{\pi}\int_0^{\pi} \frac{1}{\rho}\cos kz\,dz. \tag{46.20}$$

On the basis of the above discussion, the integrals I_1 and I_2 can be expressed in terms of the coefficients of the series (46.18) and (46.19) by the formulae

$$\begin{aligned} I_1 &= \frac{\pi}{4\nu}(\rho_{k+j} + \rho_{k-j}), \\ I_2 &= \frac{\pi}{4\nu}\left[\left(\frac{1}{\rho}\right)_{k-j} - \left(\frac{1}{\rho}\right)_{k+j}\right]. \end{aligned} \tag{46.21}$$

Now all the coefficients of the system (46.13) have been determined and it can be written in the form

$$\begin{aligned} &\beta_{0,0}^{(m)}\tilde{T}^{(m,0)} + \beta_{0,1}^{(m)}\tilde{T}^{(m,1)} + \beta_{0,2}^{(m)}\tilde{T}^{(m,2)} + \ldots + \beta_{0,n}^{(m)}\tilde{T}^{(m,n)} = f_0^{(m)}, \\ &\beta_{1,0}^{(m)}\tilde{T}^{(m,0)} + \beta_{1,1}^{(m)}\tilde{T}^{(m,1)} + \beta_{1,2}^{(m)}\tilde{T}^{(m,2)} + \ldots + \beta_{1,n}^{(m)}\tilde{T}^{(m,n)} = f_1^{(m)}, \\ &\quad\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots \\ &\quad\ldots\ldots\ldots\ldots \\ &\quad\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots \\ &\beta_{n,0}^{(m)}\tilde{T}^{(m,0)} + \beta_{n,1}^{(m)}\tilde{T}^{(m,1)} + \beta_{n,2}^{(m)}\tilde{T}^{(m,2)} + \ldots + \beta_{n,n}^{(m)}\tilde{T}^{(m,n)} = f_n^{(m)}, \end{aligned} \tag{46.22}$$

where for $\beta_{jk}^{(m)}$ and $f_k^{(m)}$ the following formulae have been obtained:

$$\begin{aligned} \beta_{kk} &= \frac{\rho_0 + \rho_{2k}}{2}(k^2\nu^2 + \lambda_m^2)^2 + \frac{k^2\nu^2}{2}\left[\left(\frac{1}{\rho}\right)_{2k} - \left(\frac{1}{\rho}\right)_0\right] - i2b^2\lambda_m^2, \\ \beta_{jk} &= \tfrac{1}{2}(\rho_{k+j} + \rho_{k-j})(k^2\nu^2 + \lambda_m^2)(j^2\nu^2 + \lambda_m^2) + \\ &\quad + \frac{kj\nu^2}{2}\left[\left(\frac{1}{\rho}\right)_{k+j} - \left(\frac{1}{\rho}\right)_{k-j}\right], \\ f_k^{(m)} &= -i2b^2(k^2\nu^2 + \lambda_m^2)\rho_k q_m, \qquad \beta_{jk} = \beta_{kj}. \end{aligned} \tag{46.23}$$

These general expressions do not apply to $\beta_{0,0}^{(m)}$ which is given by

$$\beta_{0,0}^{(m)} = (\lambda_m^2\rho_0 - i4b^2)\lambda_m^2. \tag{46.24}$$

Thus, when the Fourier series for the functions ρ and $\frac{1}{\rho}$ are known as functions of the arc length of the circumferential section of the tube, the construction of the system (46.22) will present no difficulty. It should be noted that the same system could be derived without the use of

Galerkin's method by substituting the series (46.9), (46.18), (46.19) in the equations (46.7) and by comparing the coefficients of the corresponding trigonometric functions.

The obtained solution must therefore be considered a Fourier type solution of the equation (46.7). Since the above direct method involves multiplication of trigonometric series and subsequent replacement of the indices, it has been considered preferable to follow Galerkin's method which yields the same results but simplifies the computations. It is then not an accident that the method of Galerkin in this case leads to a solution which completely coincides with the Fourier type solution. The fact is that for the solution of linear problems the above mentioned method satisfies the differential equations with least square accuracy (for given series of approximating functions). But it is known that this same property attaches to solutions of equations in the form of trigonometric series. Hence, if in applying the method of Galerkin the solution is sought in the form of a finite trigonometric series (as this has been done above), then the coefficients of this series (if the problem is linear) will always coincide with the coefficients of the Fourier series.

There remains to find out how many terms must be retained in the series (46.6) and (46.9) respectively. This question is very important, because inclusion of any extra term complicates significantly the computations, arising in the analysis of tubes.

In the analysis of cylindrical plates, only the first terms in the series (46.6) corresponding to $m = 1$ have been retained, i.e., the solution was taken in the form

$$\tilde{T} = \tilde{T}' \sin \lambda\xi, \tag{46.25}$$

corresponding to replacement of the uniform normal pressure loading by

$$q_n = \frac{4}{\pi} p \sin \lambda\xi. \tag{46.26}$$

It has been shown that in spite of this sweeping simplification the maximum values of the deflections and displacement components involve errors ordinarily not exceeding 10—15% and directed towards the safe side. Since the above problem has been analyzed by use of a method analogous to that applied to cylindrical plates and since it is closely related to it, there is no reason to assume that more significant errors will arise, if one makes use of the degree of approximation expressed by the formulae (46.25) and (46.26).

Thus, in the series (46.6), one may only retain the first term. As

regards the series (46.9) the number of terms in it must be selected depending on the shape of the cross-section of the tube.

Namely, if the series (46.18) and (46.19) for the form of the shell converge rapidly, one may retain in the series (46.9) only two or three terms. Conversely, if the series for ρ and $\frac{1}{\rho}$ converge slowly, the series (46.9) may require four or five terms, but never a larger number of terms. In this context, the algebraic system (46.22), in as much as the solution is taken in the form (46.25), will only contain as many equations as the number of terms retained in the series (46.9).

In the following section, an unfavourable example for the application of this method will be presented, namely the case of a tube whose cross-section is formed by four circular arcs. Then the functions ρ and $\frac{1}{\rho}$ will be discontinuous, in that they exhibit step changes, and therefore the series (46.18) and (46.19) will converge slowly.

Further, since it is impossible to differentiate these series, the mathematical legality of applying the above method to this problem may, in general, be questioned. Nevertheless, the results presented below for the case when in the series (46.9) six terms have been retained are in good agreement with those for the same shell in § 43 by use of another method (by subdividing it into cylindrical plates) as well as with given experiments.

§ 47. The analysis of a cylindrical shell with abruptly changing radius of curvature

As an example of the application of the theory of the previous section, the analysis of an oval shaped cylindrical shell will be considered the shape of which is close to that studied in § 43 (by a different method). In fact, a thin-walled cylinder will be investigated which is subject to uniform internal pressure and the cross-section of which is formed by two pairs of circular arcs. Fig. 69 shows this cross-section together with an ellipse of the same eccentricity.



—— Ellipse
------- Oval, formed by arcs

Fig. 69.

The analysis will be based on the following data:

$$\frac{r_2}{r_1} = 0.318, \qquad \frac{r_1}{r_2} = 3.14, \qquad \varphi_0 = 45°,$$

$$L = 1.47r_1, \qquad \lambda = \frac{\pi r_0}{L} = \frac{\pi r_1}{L} = 2.14, \qquad \lambda^2 = 4.58,$$

$$\frac{r_0}{\delta} = \frac{r_1}{\delta} = 175, \qquad 2b^2 = \sqrt{12(1-\mu^2)}\,\frac{r_1}{\delta} = 578, \tag{47.1}$$

$$s_0 = \frac{\pi}{4}(r_1 + r_2) = 1.035r_1, \qquad \eta_0 = 1.035, \qquad \nu = \frac{\pi}{\eta_0} = 3.04,$$

$$\nu^2 = 9.25, \qquad s_1 = \frac{\pi}{4}r_1, \qquad \frac{s_1}{s_0} = \frac{r_1}{r_1 + r_2} = 0.758 = \alpha.$$

First of all, the coefficients in the expansions of the functions ρ and $\frac{1}{\rho}$ in Fourier series in terms of the arc length of the oval will be calculated. In this case, ρ will be a step function of the arc length, namely, for

$$\begin{aligned} &0 \leqslant s \leqslant s_1, \quad \rho = 1, \quad && \frac{1}{\rho} = 1, \\ &s_1 \leqslant s \leqslant s_0, \quad \rho = 0.318, \quad && \frac{1}{\rho} = 3.14. \end{aligned} \tag{47.2}$$

Hence

$$\rho_k = \frac{2}{\pi}\int_0^{\pi} \rho \cos kz\,dz = \frac{2}{\pi}\left[\int_0^{\alpha\pi} \cos kz\,dz + 0.318\int_{\alpha\pi}^{\pi} \cos kz\,dz\right] =$$

$$= \frac{1}{k}\,0.434 \sin(0.758k\pi), \tag{47.3}$$

$$\rho_0 = \frac{2}{\pi}\left[\int_0^{\alpha\pi} dz + 0.318\int_{\alpha\pi}^{\pi} dz\right] = 2[\alpha + 0.318(1-\alpha)] = 1.67.$$

$$\left(\frac{1}{\rho}\right)_k = \frac{2}{\pi}\int_0^{\pi} \frac{1}{\rho}\cos kz\,dz = \frac{2}{\pi}\left[\int_0^{\alpha\pi} \cos kz\,dz + 3.14\int_{\alpha\pi}^{\pi} \cos kz\,dz\right] =$$

$$= -\frac{1.362}{k}\sin \alpha k\pi = -\frac{1.362}{k}\sin(0.758k\pi), \tag{47.4}$$

$$\left(\frac{1}{\rho}\right)_0 = 2[\alpha + 3.14(1-\alpha)] = 3.04.$$

On the basis of these formulae, the following table of values of ρ_k

and $\left(\frac{1}{\rho}\right)_k$ (up to $k = 8$) may be evaluated:

Table 19

k	0	1	2	3	4	5	6	7	8
ρ_k	1.67	0.299	−0.216	0.110	−0.011	−0.053	+0.071	−0.050	0.010
$\left(\frac{1}{\rho}\right)_k$	3.04	−0.937	0.679	−0.343	0.034	0.167	−0.224	0.158	−0.032

Substituting these values in the formulae (46.23) and (46.24), one finds the coefficients β_{jk} (corresponding to $m = 1$) and also the free terms f_k of the algebraic system (46.22).

Table 20

j, k	0.0	0.1	0.2	0.3	0.4	1.1	1.2	1.3
$\beta_{j,k}$	$35-i5300$	18.9	-41.1	44.2	-7.52	$128-i2650$	123	-146

j, k	1.4	2.2	2.3	2.4	3.3	3.4	4.4
$\beta_{j,k}$	69	$1380-i2650$	480	-493	$6560-i2650$	1720	$19200-i2650$

Table 21

k	0	1	2	3	4
f_k	$-5620ipr_1$	$-3040ipr_1$	$6620ipr_1$	$-7120ipr_1$	$1210ipr_1$

Hence, in this case, the algebraic system (46.22) may be written in the following manner (retaining in it five equations):

$$
\begin{aligned}
(35-5300i)\tilde{T}^{(0)}+18.9\tilde{T}^{(1)}-41.1\tilde{T}^{(2)}+44.2\tilde{T}^{(3)}-7.52\tilde{T}^{(4)} &= -i5620pr_1,\\
18.9\tilde{T}^{(0)}+(128-2650i)\tilde{T}^{(1)}+123\tilde{T}^{(2)}-146\tilde{T}^{(3)}+69\tilde{T}^{(4)} &= -i3040pr_1,\\
-41.1\tilde{T}^{(0)}+123\tilde{T}^{(1)}+(1380-2650i)\tilde{T}^{(2)}+480\tilde{T}^{(3)}-493\tilde{T}^{(4)} &= i6620pr_1,\\
44.2\tilde{T}^{(0)}-146\tilde{T}^{(1)}+480\tilde{T}^{(2)}+(6560-2650i)\tilde{T}^{(3)}+1720\tilde{T}^{(4)} &= -i7120pr_1,\\
-7.52\tilde{T}^{(0)}+69\tilde{T}^{(1)}-493\tilde{T}^{(2)}+1720\tilde{T}^{(3)}+(19200-2650i)\tilde{T}^{(4)} &= i1210pr_1.
\end{aligned}
\tag{47.5}
$$

The solutions of this problem are

$$\begin{aligned}
\tilde{T}^{(0)} &= (1.042 - i0.034)pr_1, \\
\tilde{T}^{(1)} &= (1.23 + i0.078)pr_1, \\
\tilde{T}^{(2)} &= (-2.28 + i0.798)pr_1, \\
\tilde{T}^{(3)} &= (0.600 - i0.930)pr_1, \\
\tilde{T}^{(4)} &= (-0.138 + i0.148)pr_1.
\end{aligned} \tag{47.6}$$

Thus, retaining in the series (46.6) only one term, one has

$$\begin{aligned}
\tilde{T} = \tilde{T}' \sin\lambda\xi = pr_1[&1.042 - 0.034i + (1.23 + 0.078i)\cos\nu\eta + \\
&+ (-2.28 + 0.798i)\cos 2\nu\eta + (0.600 - 0.930i)\cos 3\nu\eta + \\
&+ (-0.138 + 0.148i)\cos 4\nu\eta]\sin\lambda\xi
\end{aligned} \tag{47.7}$$

and

$$\begin{aligned}
\Delta(\tilde{T}) = -pr_1[&4.77 + 0.157i + (17.1 + 1.079i)\cos\nu\eta + \\
&+ (-94.8 + 33.2i)\cos 2\nu\eta + (52.7 - 81.6i)\cos 3\nu\eta + \\
&+ (-21.0 + 22.6i)\cos 4\nu\eta]\sin\lambda\xi.
\end{aligned}$$

The formulae of § 40 now permit the determination of all the complex forces and complex displacements. In this context, in correspondence with the accepted degree of accuracy of the calculations, the quantities ρ and $\frac{1}{\rho}$ in these formulae refer to their expressions in the form of the series (46.18) and (46.19), the first nine coefficients of which are given in Table 19.

Further, the quantity q_n in the formulae must be interpreted as

$$q_n = \frac{4}{\pi} p \sin\lambda\xi,$$

with the remaining components of the loading having been set equal to zero.

Reasoning in this manner, one obtains

$$\begin{aligned}
\tilde{T}_1' &= \tilde{T}' - \frac{i}{2b^2}\rho\left(\frac{d^2\tilde{T}'}{d\eta^2} - \lambda^2\tilde{T}'\right) - \frac{4}{\pi}pr_1\rho = \\
&= pr_1\{[-0.018 - 0.034i + (0.855 + 0.078i)\cos\nu\eta + \\
&+ (-2.00 + 0.798i)\cos 2\nu\eta + (0.464 - 0.93i)\cos 3\nu\eta - \\
&- (0.124 - 0.148i)\cos 4\nu\eta] + \rho[-0.0003 + 0.0083i - \\
&- (0.0019 - 0.029i)\cos\nu\eta - (0.057 + 0.164i)\cos 2\nu\eta + \\
&+ (0.141 + 0.091i)\cos 3\nu\eta - (0.039 + 0.036i)\cos 4\nu\eta]\};
\end{aligned}$$

$$\tilde{T}_2' = \rho\left[\frac{i}{2b^2}\Lambda_m(\tilde{T}') + \frac{4}{\pi}pr_1\right] = [1.27 - 0.008i +$$
$$+ (0.0019 - 0.029i)\cos\nu\eta + (0.057 + 0.164i)\cos 2\nu\eta -$$
$$- (0.141 + 0.092i)\cos 3\nu\eta + (0.039 + 0.036i)\cos 4\nu\eta]pr_1\rho,$$
$$\tilde{w}' = \frac{pr_1^2}{E\delta}\rho[1.042 - 0.034i + (3.72 + 0.24i)\cos\nu\eta +$$
$$+ (-20.7 + 7.25i)\cos 2\nu\eta + (11.1 - 17.8i)\cos 3\nu\eta + \qquad (47.8)$$
$$+ (-4.6 + 4.9i)\cos 4\nu\eta],$$

where $\tilde{T}_1', \ldots, w'$ are the coefficients in the formulae

$$\tilde{T}_1 = \tilde{T}_1'\sin\lambda\xi,\ \tilde{T}_2 = \tilde{T}_2'\sin\lambda\xi,\ \tilde{S} = \tilde{S}'\cos\lambda\xi,\ \tilde{w} = \tilde{w}'\sin\lambda\xi.$$

Separating in these expressions real and imaginary parts, one obtains the following formulae for the forces, moments and the normal displacement w:

$$w' = |\tilde{w}'|_{\text{Real}} = \frac{pr_1^2}{E\delta}\rho[1.042 + 3.72\cos\nu\eta - 20.7\cos 2\nu\eta +$$
$$+ 11.5\cos 3\nu\eta - 4.6\cos 4\nu\eta],$$
$$T_1' = |\tilde{T}_1'|_{\text{Real}} = pr_1[-(0.018 + 0.0003\rho) + (0.855 - 0.002\rho)\cos\nu\eta -$$
$$- (2.00 + 0.06\rho)\cos 2\nu\eta + (0.46 + 0.141\rho)\cos 3\nu\eta -$$
$$- (0.124 + 0.039\rho)\cos 4\nu\eta], \qquad (47.9)$$
$$T_2' = |\tilde{T}_2'|_{\text{Real}} = pr_1[1.27 + 0.002\cos\nu\eta + 0.057\cos 2\nu\eta -$$
$$- 0.141\cos 3\nu\eta + 0.039\cos 4\nu\eta]\rho,$$
$$\frac{M_2' - \mu M_1'}{1-\mu^2} = \frac{pr_1^2}{2b^2}[(0.034 - 0.0083\rho) - (0.078 + 0.029\rho)\cos\nu\eta -$$
$$- (0.798 - 0.164\rho)\cos 2\nu\eta + (0.93 - 0.09\rho)\cos 3\nu\eta -$$
$$- (0.148 - 0.036\rho)\cos 4\nu\eta],$$
$$\frac{M_1' - \mu M_2'}{1-\mu^2} = \frac{pr_1^2}{2b^2}\rho[0.008 + 0.029\cos\nu\eta - 0.164\cos 2\nu\eta +$$
$$+ 0.092\cos 3\nu\eta - 0.036\cos 4\nu\eta].$$

Multiplying the last of the formulae (47.9) by Poisson's ratio μ and adding it to the second last expression, one obtains the most interesting of the internal moments in the shell, namely the moment M_2, on which depends the deformation of the cross-section of the cylinder.



Fig. 70.

If one takes $\mu = 0.3$, one finds in this way

$$M_2' = \frac{pr_1^2}{2b^2}[0.034 - 0.0107\rho - $$
$$- (0.078 + 0.0207\rho)\cos\nu\eta - $$
$$- (0.798 - 0.115\rho)\cos 2\nu\eta + $$
$$+ (0.936 - 0.064\rho)\cos 3\nu\eta - $$
$$- (0.148 - 0.026\rho)\cos 4\nu\eta].$$

Now one may evaluate the displacements and stresses at any point of the middle surface. Fig. 70 shows the graph of the deformation of the cross-section of the tube, as given by the first of the formulae (47.9).

Table 22 below presents a comparison of the deduced results with those obtained by experiment (the theoretical and experimental values of the radial displacement w at the three most characteristic points of the shell, lying in the plane $x = L/2$).

Table 22

	$\nu\eta = 0$	$\nu\eta = \frac{\pi}{2}$	$\nu\eta = \pi$
Theoretical	$-9.0\frac{pr_1^2}{E\delta}$	$17.2\frac{pr_1^2}{E\delta}$	$-12.6\frac{pr_1^2}{E\delta}$
Experimental	$-6.5\frac{pr_1^2}{E\delta}$	$15.9\frac{pr_1^2}{E\delta}$	$-11.9\frac{pr_1^2}{E\delta}$

A study of this table will lead to the conclusion that the method developed above is completely acceptable . The study of the capabilities of this method has purposely been based on an unfavourable example for which the trigonometric series for ρ and $\frac{1}{\rho}$ converge slowly. Nevertheless, by retaining in the expressions (46.9) only five terms, results were obtained which exhibit satisfactory accuracy. Hence there is no doubt that for tubes with smoother cross-sections it will be sufficient to retain in the series (46.9) three to four terms with a corresponding simplification of the calculations.

It is important to note in conclusion that the method of § 46 in comparison with the method of § 43 has the advantage that it is general

and may be applied to tubes of arbitrary cross-section, while the method of § 43 is specialized and may only be used to analyze tubes whose cross-sections may be assumed to be formed by a number of cylindrical plates.

§ 48. The analysis of tubes for arbitrary end conditions

The method of § 46 for the analysis of tubes is based on the representation of the solution in the form of double Fourier series (in terms of the coordinates ξ and η), thus permitting only the study of one type of boundary condition in the problem, namely, the case when the edges of the tube are freely supported and when the supports do not resist displacements along the tube.

In order to obtain a solution of the same problem for arbitrary boundary conditions, one has to seek it in the form of an ordinary Fourier series (using the circumstance that for closed cylindrical shells the solution will always be a periodic function of the coordinate η). As in § 46, it will then be assumed that the cross-section of the tube has two axes of symmetry and that the loading on the tube is uniform, normal, internal pressure. Then the differential equation (46.1) takes the form

$$\Delta[\rho\Delta(\tilde{T})] + \frac{\partial}{\partial\eta}\left(\frac{1}{\rho}\frac{\partial\tilde{T}}{\partial\eta}\right) + i2b^2\frac{\partial^2\tilde{T}}{\partial\xi^2} = i2b^2pr_0\frac{d^2\rho}{d\eta^2}, \tag{48.1}$$

and its general solution for the problem under consideration can be written in the form of the series

$$\tilde{T} = \sum_{k=0}^{\infty}\tilde{T}^{(k)}\cos k\nu\eta, \tag{48.2}$$

where the coefficients $\tilde{T}^{(k)}$ are functions of ξ only and $\nu = \frac{\pi r_0}{s_0}$ (as in § 46, s_0 is a quarter of the length of the circumference of the shell).

The series (48.2) must be substituted into (48.1) to obtain [after expanding the right hand side of (48.1) in a series analogous to (48.2)] the system of ordinary differential equations for the determination of the $\tilde{T}^{(k)}(\xi)$. It is readily seen that the calculations necessary for the deduction of this system of equations will be quite analogous to those in § 46, the only difference being that the role played in § 46 by the constant multiplier λ^2 will now be taken by the differential operator $-\frac{d^2(\ldots)}{d\xi^2}$.

Hence one can immediately write down the following infinite system

of linear differential equations with constant coefficients for the $\tilde{T}^{(k)}$:

$$\begin{aligned}
&D_{0,0}[\tilde{T}^{0}] + D_{0,1}[\tilde{T}^{(1)}] + D_{0,2}[\tilde{T}^{(2)}] + \ldots + D_{0,n}[\tilde{T}^{(n)}] + \ldots = f_0,\\
&D_{1,0}[\tilde{T}^{(0)}] + D_{1,1}[\tilde{T}^{(1)}] + D_{1,2}[\tilde{T}^{(2)}] + \ldots + D_{1,n}[\tilde{T}^{(n)}] + \ldots = f_1,\\
&\cdots\cdots\cdots

[since, as a result of the integration of the system (48.3), there occur $4(n + 1)$ complex arbitrary constants]. For the determination of these constants, one must give at each of the two ends of the tube up to four boundary conditions (in terms of displacements and rotations or forces and moments) and, in agreement with the general type of solution under consideration, all the quantities given at the edges of the shell must be expanded in Fourier series of the form

$$F(\eta) = \sum_{k=0}^{\infty} a_k \cos k\nu\eta, \tag{48.7}$$

where the a_k are constant coefficients.

Further, in order to obtain the degree of accuracy accepted above, i.e., retaining in the series (48.7) only the first $(n + 1)$ terms and comparing the coefficients in these series with the coefficients in the corresponding series of the deduced solution (for $\xi = 0$ and $\xi = \xi_0$, that is, for the values of ξ corresponding to the ends of the shell), a system of $8(n + 1)$ linear algebraic equations is obtained which permits the determination of all the constants of integration in the solution. Hence the problem under consideration will have been solved completely.

It will be seen from the above discussion that, although the method of solution of the problem encounters no fundamental difficulties, nevertheless, for $n = 3$ to 5, it will lead to very involved computations.

§ 49. On the semi-membrane theory of cylindrical shells

From 1932 onwards, V. Z. Vlasov [87, 4] has proposed a number of versions of a theory of cylindrical shells which differed more or less from each other. The most valuable of these, for a reason which will become clear from what follows, will be called the semi-membrane theory of cylindrical shells. The necessity for such a theory follows from the following considerations:

As has been shown previously (Chap. II), the accuracy of the solution given by the momentless theory, generally speaking, depends on the smoothness of the shape of the shell, on the smoothness of its loading and on the formulation of the boundary conditions. However, for cylindrical shells, these three factors must be supplemented by an additional one, namely the length of the shell (§ 37); as the length increases, the accuracy of the membrane theory diminishes without dependence on the degree to which the other conditions for the existence of the membrane state of stress are satisfied. In physical terms, this indicates that for a sufficiently great length the type of support of the ends of the tube has little influence on the stresses and strains in its centre section

and it is not possible to avoid the appearance of significant bending stresses (if they are only due to the external loading).

It is essential to note in this context that the bending under discussion here will be caused mainly by the deformation of the cross-section of the tube, i.e., by the moment M_2. The bending due to deformation of the generators (i.e., by the moment M_1) and due to torsion oft the middle surface (i.e., by the moment H), will be insignificant provided the supports of the ends of the shell obey the requirements of the membrane theory.

Since for long (and very long) cylindrical shells the membrane theory is inadequate, there arises the necessity of constructing a theory of these shells which might occupy the central position between the membrane and the general theory, starting from the equations (40.7). As is clear from the above discussion, a first step towards the development of such an intermediate theory must be to neglect the moments M_1 and H (and therefore also the force N_1) in the equilibrium equations for a shell element.

As a result of this simplification, one will have

$$\begin{aligned} &\frac{\partial T_1}{\partial \xi} + \frac{\partial S}{\partial \eta} + q_1 r_0 = 0, \\ &\frac{\partial S}{\partial \xi} + \frac{\partial T_2}{\partial \eta} + \frac{N_2}{\rho} + q_2 r_0 = 0, \\ &\frac{\partial N_2}{\partial \eta} - \frac{T_2}{\rho} + q_n r_0 = 0, \\ &N_2 = \frac{1}{r_0}\frac{\partial M_2}{\partial \eta}. \end{aligned} \tag{49.1}$$

This system coincides with the system (41.11), which is natural, since in § 41 exactly the same assumptions have been made for shells reinforced by ribs.

The relationships between the forces and strains will be expressed by the usual formulae

$$\begin{gathered} T_1 = \frac{E\delta}{1-\mu^2}(\varepsilon_1 + \mu\varepsilon_2), \quad T_2 = \frac{E\delta}{1-\mu^2}(\varepsilon_2 + \mu\varepsilon_1), \quad S = \frac{E\delta}{2(1+\mu)}\omega, \\ M_2 = \frac{E\delta^3}{12(1-\mu^2)}(\kappa_2 + \mu\kappa_1), \end{gathered} \tag{49.2}$$

where

$$\varepsilon_1 = \frac{1}{r_0}\frac{\partial u}{\partial \xi}, \quad \varepsilon_2 = \frac{1}{r_0}\left(\frac{\partial v}{\partial \eta} + \frac{w}{\rho}\right), \quad \omega = \frac{1}{r_0}\left(\frac{\partial u}{\partial \eta} + \frac{dv}{\partial \xi}\right),$$
$$\kappa_2 = -\frac{1}{r_0^2}\frac{\partial}{\partial \eta}\left(\frac{\partial w}{\partial \eta} - \frac{v}{\rho}\right). \tag{49.3}$$

It also follows as a result of the neglecting of the moment

$$M_1 = \frac{E\delta^3}{12(1-\mu^2)}(\kappa_1 + \mu\kappa_2)$$

that

$$\kappa_1 \approx -\mu\kappa_2, \tag{49.4}$$

which approximately reduces the last of the formulae (49.2) to the form

$$M_2 = \frac{E\delta^3}{12}\kappa_2. \tag{49.5}$$

Eliminating from the system (49.1) all the unknowns except T_1 and M_2, one obtains the equation

$$r_0\frac{\partial^2 T_1}{\partial \xi^2} - \frac{\partial^2}{\partial \eta^2}\left(\rho\frac{\partial^2 M_2}{\partial \eta^2}\right) - \frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial M_2}{\partial \eta}\right) =$$
$$= r_0^2\left[\frac{\partial^2(q_n\rho)}{\partial \eta^2} + \frac{\partial q_2}{\partial \eta} - \frac{\partial q_1}{\partial \xi}\right], \tag{49.6}$$

which is identical to (41.17).

Vlasov obtained a second equation involving the same unknowns from the condition of compatibility of strains (41.13)

$$r_0\frac{\partial^2 \kappa_2}{\partial \xi^2} + \frac{\partial^2}{\partial \eta^2}\left[\rho\left(\frac{\partial^2 \varepsilon_1}{\partial \eta^2} + \frac{\partial^2 \varepsilon_2}{\partial \xi^2} - \frac{\partial^2 \omega}{\partial \xi \partial \eta}\right)\right] + \frac{\partial}{\partial \eta}\left[\frac{1}{\rho}\left(\frac{\partial \varepsilon_1}{\partial \eta} - \frac{\partial \omega}{\partial \xi}\right)\right] = 0, \tag{49.7}$$

which he simplified beforehand by letting (cf. [4], p. 482)

$$\omega = \varepsilon_2 = 0. \tag{49.8}$$

After this simplification, equation (49.7) may be rewritten in the form

$$r_0\frac{\partial^2 \kappa_2}{\partial \xi^2} + \frac{\partial^2}{\partial \eta^2}\left(\rho\frac{\partial^2 \varepsilon_1}{\partial \eta^2}\right) + \frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial \varepsilon_1}{\partial \eta}\right) = 0. \tag{49.9}$$

Replacing here the strains by their expressions in terms of the forces

and moments, one finds

$$\frac{12r_0}{\delta^2}\frac{\partial^2 M_2}{\partial \xi^2} + W(T_1) - \mu W(T_2) = 0, \tag{49.10}$$

where $W(\ldots)$ is Vlasov's operator

$$W(\ldots) = \frac{\partial^2}{\partial \eta^2}\left[\rho \frac{\partial^2(\ldots)}{\partial \eta^2}\right] + \frac{\partial}{\partial \eta}\left(\frac{1}{\rho}\frac{\partial(\ldots)}{\partial \eta}\right). \tag{49.11}$$

Further, neglecting in equation (49.10) the term multiplied by Poisson's ratio μ, one obtains finally from (49.6) and (49.10) the differential equations

$$\begin{gathered}\frac{12r_0}{\delta^2}\frac{\partial^2 M_2}{\partial \xi^2} + W(T_1) = 0, \\ r_0 \frac{\partial^2 T_1}{\partial \xi^2} - W(M_2) = r_0^2\left[\frac{\partial^2 \rho q_n}{\partial \eta^2} + \frac{\partial q_2}{\partial \eta} - \frac{\partial q_1}{\partial \xi}\right].\end{gathered} \tag{49.12}$$

A general defect of the above discussion is the large number of arbitrary assumptions leading to the five conditions

$$M_1 = H = \varepsilon_2 = \omega = \mu = 0.$$

Several of these conditions are superfluous from the point of view of the fundamental idea of the semi-membrane theory (as formulated at the beginning of this section).

Thus, for example, the condition $\omega = 0$ is unacceptable for the solution of torsion problems of tubes and therefore this important problem of the theory of long (and very long) thin walled rods will fall outside the range of the developed theory.

Now it is not difficult to show that the defects indicated above are not at all natural to the equations (49.12), but rather to the above method of their derivation. In fact, it is not necessary to invoke the conditions (49.8) for the transition from the formula (49.7) to the formula (49.9) and it is sufficient for this purpose to assume that the derivatives $\frac{\partial^2 \omega}{\partial \xi \partial \eta}$, $\frac{\partial^2 \varepsilon_2}{\partial \xi^2}$ and $\frac{\partial \omega}{\partial \xi}$ may be neglected in comparison with $\frac{\partial^2 \varepsilon_1}{\partial \eta^2}$ and $\frac{\partial \varepsilon_1}{\partial \eta}$ (respectively) which are, of course, not at all equivalent to the conditions (49.8) and which represent considerably weaker restrictions. Since the derivatives of the strains are connected with each other by the equations (49.1), (49.2), it is clear (in this context) that the deduction of the system (49.12) need not be based on a number of unrelated assumptions, referring to different forces, moments and strains, but can be deduced from a certain

deeper and more general principle. It may be shown that this single principle, sufficient for establishing equations of the form (49.12), involves the neglect of the term $\frac{\partial^2 f}{\partial \xi^2}$ in comparison with $\frac{\partial^2 f}{\partial \eta^2}$ (where f, any function characteristic for the problem under consideration, may be a displacement, a force or a moment).

Indeed, reverting to the general equations (40.7) and performing there the indicated simplification (with the exception of the term with the very large factor: $i2b^2$), one will have

$$W(\tilde{T}) + i2b^2 \frac{\partial^2 \tilde{T}}{\partial \xi^2} = i2b^2 r_0 \left[\frac{\partial^2 \rho q_n}{\partial \eta^2} + \frac{\partial q_2}{\partial \eta} - \frac{\partial q_1}{\partial \xi} \right]. \tag{49.13}$$

Separating real and imaginary parts, a system of two equations is obtained, the structure of which is identical to that of the system (49.12). The unknowns in this system are $T_1 + T_2$, instead of T_1 in the system (49.12), and M_2, as in the system (49.12). This last result follows from the fact that, in agreement with the accepted principle of simplification, one has

$$M_1 \approx \mu M_2. \tag{49.14}$$

Having determined the auxiliary function $\tilde{T}$ from the equation (49.13), all the complex forces may be found using the formulae (40.8) to (40.11). For this purpose, following the basic idea of the simplification, one has to put in these formulae

$$\Delta(\ldots) = \frac{\partial^2(\ldots)}{\partial \eta^2} + \frac{\partial^2(\ldots)}{\partial \xi^2} \approx \frac{\partial^2(\ldots)}{\partial \eta^2}.$$

Further, the equations (40.12) and (40.13) may be employed for the determination of the complex displacements.

Thus it is seen that the principal difference between the usual treatment of the semi-membrane theory and its treatment above is due to the fact that in the usual discussion certain strains (ε_2, ω) are arbitrarily put equal to zero, whereas in the above discussion all the strains, forces and moments enter, generally speaking, as non-zero quantities the determination of which, however, is subsequently achieved by use of a single simplification. Such an approach retains all the advantages of the semi-membrane theory (since the same fundamental equations are obtained) and it removes a number of its serious defects.

It should not be concluded from this that the proposed semi-membrane theory is any less 'physical' than the usual theory. The neglect of $\frac{\partial^2(\ldots)}{\partial \xi^2}$

in comparison with $\frac{\partial^2(\ldots)}{\partial\eta^2}$, translated into the language of physical ideas, indicates that the variations of all displacements and stresses in the direction along the cylindrical shell are assumed to be smoother than those in the circumferential direction of the shell. If the length of the shell under consideration is sufficiently large, the state of stress in it will usually satisfy this requirement (since the local state of stress of the edge effect type will either not be taken into account or it may be assumed to have been eliminated by the formulation of membrane boundary conditions at the ends of the tube).

In conclusion, it may be noted that from the above discussion follows a simple criterion for an error estimate of the solution of the semi-membrane theory which involves a comparison of the values of $\frac{\partial^2 f}{\partial\xi^2}$ and $\frac{\partial^2 f}{\partial\eta^2}$ (where f may be any displacement or force). This remark refers, of course, only to the semi-membrane theory generalized in the above stated manner. The error of a theory based on the condition $\omega = 0$ may in individual problems considerably exceed the stated estimate.

CHAPTER IV

SHELLS OF REVOLUTION

§ 50. Historical remarks.

Shells of revolution, including the circular cylindrical shells considered in the preceding chapter, have many technical applications. Hence many investigations have been devoted to this class of shells and the greatest advances have been made in the analysis of circular cylindrical and spherical shells. However, circular cylindrical shells have been discussed in sufficient detail in the last chapter and therefore they will receive no further attention here. The first significant success in the analysis of spherical shells is to be found in the work of H. Reissner [159] who reduced the differential equations for symmetrical deformations of such shells to a convenient form and then applied the asymptotic method for their integration [145]. He also discovered the possibility of reducing the order of the differential equations of this problem by means of their complex transformation, so that the analysis of spherical shells for symmetrical loading was found to reduce to the integration of a single second order differential equation.

A short time after the appearance of the article [159], E. Meissner [155, 154] was able to generalize Reissner's result to symmetrical deformations of shells of revolution of arbitrary shape (and even of variable thickness). In this way, the difficulties arising in the analysis of shells of revolution under symmetrical loading were largely overcome, particularly since the asymptotic method was shown to be a simple and sufficiently accurate process for the integration of the relevant differential equations. However, a long time after the appearance of the above results, efforts were still directed not so much towards approximate but towards mathematically exact solutions of these equations [146, 148, 162 et al.]. These results of the Zürich school (a name which in the history of shell theory refers to the group of investigators led by Meissner and Reissner) are to a great extent useless, since they are inconvenient for practical applications. In particular, in the analysis of spherical shells by use of hypergeometric series [155, 146], one has to retain more than twenty terms. The lack of purpose in seeking mathematically accurate solutions

of the equations of shell theory becomes quite clear if one takes into consideration that these equations (as a result of their deduction) involve errors of order δ/R in comparison with unity. Hence there is little sense in retaining in their solutions terms of smaller order than δ/R. However, it may be shown that in the integration of the equations for the symmetrical deformation of shells of revolution this degree of accuracy is already achieved by the asymptotic method which must therefore be employed irrespective of the difference between the solutions obtained by this method and the so-called "exact solutions". This idea was apparently stated explicitly for the first time in the Author's doctoral dissertation (1945). The same conclusion was reached independently by A. I. Lur'e who employed it subsequently in his monograph [18].

As regards the development of simplified methods for the analysis of shells of revolution under symmetrical loadings, special mention should be made of I. Ia. Shtaerman [140] and P. L. Pasternak [157]. Shtaerman in his work gave, in addition, a very clear deduction of the equations of the problem by establishing the analogy between the problems of the symmetrical deformation of shells of revolution and of the bending of arches on elastic foundations [142, 143].

The simplest and most frequently applied approximate method of integration of the equations for symmetrical deformations of shells of revolution, based on the omission of terms of order up to $\sqrt{\delta/R}$ (compared with unity) inclusively, is referred to, in practice, as the "method of Geckeler". However, it isim possible to acknowledge this title as justified, because, in fact, it is the result of the efforts of a number of the above-mentioned authors. Thus, at the present time, the analysis of shells of revolution under symmetrical loading has been studied in sufficient detail and the complex transformation of the equations halving the order of the differential equations of the problem has in this respect played an important role.

The analysis of shells of revolution under unsymmetrical loading is more complicated. The most important loading of this type is antisymmetrical and is sometimes referred to as 'wind' loading. For spherical shells, the corresponding problem was solved in the dissertation of E. Schwerin [160] who (evidently to please his teacher and opponent H. Reissner) transformed the differential equations in the manner typical of the Zürich school. He thus obtained the solution in the form of a badly converging hyper-geometric series, a result which was also reached by the Author of this book. In this connection, two quadratures and also the possibility of a complex transformation were discovered so that the analysis of spherical shells under 'wind' type loading was found

to reduce to the integration of a single second order equation. This last result has recently been generalized in the work [134] to shells of revolution of arbitrary shape.

As regards spherical shells with arbitrary loading, this general problem was solved first by A. Havers [151] (or, more correctly, by A. van der Neut [156], since Havers merely applied to the problem of stress analysis the transformation which van der Neut employed for the stability analysis of spherical shells). This problem was solved by use of other methods by V. V. Sokolovskii [136], Iu. V. Repman [135], A. L. Gol'denweizer [129] and the Author [133].

In this context, it should be noted that both Havers as well as Gol'denweizer gave the transformation for the homogeneous problem only, whence their results may not be applied directly to the stability and vibration analysis of spherical shells. If this is taken into consideration, the transformation proposed in the paper [133] may be given preference, since it may be found to be more convenient for the solution of problems of the above two types. However, if one restricts discussion to the homogeneous problem, the solution by Gol'denweizer [129] is of greater interest. Based on the works of the preceding writer, I. N. Vekua [125, 126] formulated the homogeneous problem of the theory of spherical shells, expressing its solutions in terms of four analytic functions of one complex variable.

Thus, the analysis of spherical shells under arbitrary loading, in its final form developed in detail by the Russian school, has reached at the present time a stage of completeness and, if one is orientated towards the asymptotic integration of the differential equations, the problem of computations is less cumbersome than might be expected.

As regards results for other types of shells of revolution, the solution for conical shells due to A. E. H. Love [49] and applicable for arbitrary loading should be mentioned. This same author indicated that for arbitrary shells of revolution, bounded by parallel circles, a first approximation to a general solution may be obtained in the form of the sum of the solutions of the membrane equations and of the equations for the so-called 'edge effect'. Integrals of the latter equations are expressed in terms of rapidly changing functions of the distance from the edge of the shell. This idea was subsequently used by Love in his book [49], however, without justification and likewise without taking notice of possible simplifications of the equations of the edge effect.

Both these questions have been studied in great detail in a number of papers by A. L. Gol'denweizer [8, 9] and also in the work of Yu. N. Rabotnov [34] and Kh. M. Mushtari [25]. These papers by the Russian

scientists essentially defined the conditions for which rapidly decaying solutions of the equations of the theory of shells may be obtained and studied a number of possible special cases.

It is more convenient to consider the problem of the analysis of shells of revolution under arbitrary load in complex form. It then turns out that the corresponding differential equations may be transformed in much the same way as this was possible in the membrane theory. As a result, the analysis of shells of revolution reduces to the solution of a system of two differential equations of fourth order. Firstly, one may obtain from this system the known results for symmetrical deformations of shells of revolution, i.e., the solution of this problem may be reduced to the integration of a single equation of second order. Further, analogous results can be obtained from it also for the so called 'wind type' loading which, as has already been mentioned, was hitherto only known to be applicable to spherical shells.

For the family of shells the radii of curvature of which are given by

$$\left(\frac{1}{R_1} - \frac{1}{R_2}\right) \cdot \frac{1}{\sin^2 \theta} = \text{const.},$$

the basic system of differential equations for shells of revolution disintegrates by means of a repeated application of a complex transformation into two independent second order equations one of which is close to the equation of the membrane theory, while the other is close to the equation for symmetrical deformations, and this result is true for any loading. These results may be extended approximately also to shells of revolution of arbitrary shape.

Thus, the complex transformation of the differential equations of shell theory, as applied to shells of revolution, is found to be useful and it leads to an essential extension of the knowledge referring to such shells.

In this survey the valuable work of B. G. Galerkin [128], A. I. Lur'e [131] and G. S. Shapiro [139] has not been mentioned, since their contributions do not refer to the theory of thin, but to the theory of thick shells.

§ 51. The differential equations for shells of revolution in "complex forces" and their transformation

The position of points on the middle surface of the shell of revolution of arbitrary shape will be determined by the angles θ and φ, shown in Fig. 71, in the same way as this was done in Chapter II. Further, let R_1

be the radius of curvature of the meridian and R_2 the radius of curvature of the normal section, tangential to the parallel circle. This second radius is equal to the segment of the perpendicular to the middle surface between this surface and the axis of the shell. Obviously both these radii will be functions of the angle θ only.

The Lamé parameters in this case are determined by the expressions

$$A_1 = R_1, \quad A_2 = R_2 \sin\theta, \tag{51.1}$$

and the Codazzi-Gauss conditions reduce to the relation

$$\frac{dR_2 \sin\theta}{d\theta} = R_1 \cos\theta. \tag{51.2}$$

In correspondence with the above, the differential equations of the theory of shells in terms of complex forces [equations (16.10)] for shells of revolution take the form

$$\begin{aligned}
&\frac{1}{R_1}\frac{\partial \tilde{T}_1}{\partial\theta} + \frac{\operatorname{cotan}\theta}{R_2}(\tilde{T}_1 - \tilde{T}_2) + \frac{1}{R_2\sin\theta}\frac{\partial \tilde{S}}{\partial\varphi} + i\frac{c}{R_1^2}\frac{\partial \tilde{T}}{\partial\theta} = -q_1,\\
&\frac{1}{R_1}\frac{\partial \tilde{S}}{\partial\theta} + 2\frac{\operatorname{cotan}\theta}{R_2}\tilde{S} + \frac{1}{R_2\sin\theta}\frac{\partial \tilde{T}_2}{\partial\varphi} + i\frac{c}{R_2^2\sin\theta}\frac{\partial \tilde{T}}{\partial\varphi} = -q_2,\\
&\frac{\tilde{T}_1}{R_1} + \frac{\tilde{T}_2}{R_2} - ic\Delta(\tilde{T}) = q_n,
\end{aligned} \tag{51.3}$$

where q_1, q_2, q_n are the components of the surface loading in the directions θ, φ and along the normal to the middle surface,

$$\Delta(\,) = \frac{1}{R_1^2}\frac{\partial^2(\ldots)}{\partial\theta^2} + \left(\frac{\operatorname{cotan}\theta}{R_1R_2} - \frac{1}{R_1^3}\frac{dR_1}{d\theta}\right)\frac{\partial(\ldots)}{\partial\theta} + \frac{1}{R_2^2\sin^2\theta}\frac{\partial^2(\ldots)}{\partial\varphi^2}, \tag{51.4}$$



Fig. 71.

$$\begin{aligned}
c &= \frac{\delta}{\sqrt{12(1-\mu^2)}},\\
\tilde{T}_1 &= T_1 - \frac{i}{c}\frac{M_2 - \mu M_1}{1-\mu^2},\\
\tilde{T}_2 &= T_2 - \frac{i}{c}\frac{M_1 - \mu M_2}{1-\mu^2},\\
\tilde{S} &= S + \frac{i}{c}\frac{H}{1-\mu},\\
\tilde{T} &= \tilde{T}_1 + \tilde{T}_2.
\end{aligned} \tag{51.5}$$

Letting $c = 0$ in the system (51.3), the equations reduce to the system

(23.4), i.e., to the differential equations of the membrane theory of shells of revolution. Thus these two systems have quite a lot in common. This suggests that a transformation of the system (51.3) might be accomplished in an analogous manner as this has been done in § 23 during transformation of the membrane equations.

In fact, introduce two new auxiliary functions

$$\begin{aligned} \tilde{U} &= \tilde{T}_1 R_2 \sin^2\theta - ic\frac{R_2}{R_1}\sin\theta\cos\theta\frac{\partial\tilde{T}}{\partial\theta}, \\ \tilde{V} &= \tilde{S}R_2^2\sin^2\theta, \end{aligned} \tag{51.6}$$

which for $c = 0$ will be identical with the functions U and V of the membrane theory of shells of revolution [formulae (23.6)]. Replacing $\tilde{T}_2$ in the second equation (51.3) by the expression

$$\tilde{T}_2 = \tilde{T} - \tilde{T}_1 \tag{51.7}$$

and eliminating from this equation $\tilde{T}_1$ and $\tilde{S}$ with the help of (51.6), one has, on the basis of the condition (51.2),

$$\frac{\partial\tilde{V}}{\partial\theta} - \frac{R_1}{\sin\theta}\frac{\partial\tilde{U}}{\partial\varphi} - icR_2\cos\theta\frac{\partial^2\tilde{T}}{\partial\theta\,\partial\varphi} + R_1(R_2+ic)\sin\theta\frac{\partial\tilde{T}}{\partial\varphi} = \\ = -q_2R_1R_2^2\sin^2\theta. \tag{51.8}$$

Further, introduce in the first and third equations of the system (51.3) for $\tilde{T}_1$ the function $\tilde{U}$. After certain manipulations involving the formulae (51.2) and (51.4), this gives

$$\frac{1}{R_1R_2\sin^2\theta}\frac{\partial\tilde{U}}{\partial\theta} - \frac{1}{R_1R_2}\frac{\cos\theta}{\sin^3\theta}\tilde{U} - \frac{\operatorname{cotan}\theta}{R_2}\tilde{T}_2 + \frac{1}{R_2\sin\theta}\frac{\partial\tilde{S}}{\partial\varphi} + \\ + ic\operatorname{cotan}\theta\Delta(\tilde{T}) - ic\frac{\operatorname{cotan}\theta}{R_2^2\sin^2\theta}\frac{\partial^2\tilde{T}}{\partial\varphi^2} - ic\frac{\operatorname{cotan}^2\theta}{R_1^2}\frac{\partial\tilde{T}}{\partial\theta} = -q_1 \tag{51.9}$$

and

$$\frac{\tilde{U}}{R_1R_2\sin^2\theta} + ic\frac{\operatorname{cotan}\theta}{R_1^2}\frac{\partial\tilde{T}}{\partial\theta} + \frac{\tilde{T}_2}{R_2} - ic\Delta(\tilde{T}) = q_n. \tag{51.10}$$

Multiplying (51.10) by cotan θ and adding it to (51.9), one finds

$$\frac{\partial\tilde{U}}{\partial\theta} + \frac{R_1}{R_2^2\sin\theta}\frac{\partial\tilde{V}}{\partial\varphi} - ic\frac{R_1}{R_2}\operatorname{cotan}\theta\frac{\partial^2\tilde{T}}{\partial\varphi^2} = (q_n\cos\theta - q_1\sin\theta)R_1R_2\sin\theta. \tag{51.11}$$

Next, the function $\tilde{V}$ will be eliminated from the equations (51.8) and

(51.11) by multiplying (51.11) by $\frac{R_2^2 \sin\theta}{R_1}$ and by subsequently differentiating (51.8) with respect to φ and (51.11) with respect to θ. As a result one arrives at the following differential equation in two unknowns

$$G(\tilde{U}) - \left[1 - ic\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\right]\frac{\partial^2 \tilde{T}}{\partial \varphi^2} = f(\theta, \varphi), \tag{51.12}$$

in which

$$f(\theta, \varphi) = \frac{1}{R_1 R_2 \sin\theta}\left\{\frac{\partial}{\partial\theta}\left[(q_n \cos\theta - q_1 \sin\theta) R_2^3 \sin^2\theta\right] + \right.$$

$$\left. + \frac{\partial q_2}{\partial \varphi} R_1 R_2^2 \sin^2\theta\right\}, \tag{51.13}$$

$$G(\ldots) = \frac{1}{R_1 R_2 \sin\theta}\frac{\partial}{\partial\theta}\left[\frac{R_2^2 \sin\theta}{R_1}\frac{\partial(\ldots)}{\partial\theta}\right] + \frac{1}{R_2 \sin^2\theta}\frac{\partial^2(\ldots)}{\partial\varphi^2}. \tag{51.14}$$

It will be noted that the operators $\Delta(\ldots)$ and $G(\ldots)$ are connected by the relation

$$G(\ldots) = R_2 \Delta(\ldots) + \left(\frac{1}{R_1} - \frac{R_2}{R_1^2}\right)\operatorname{cotan}\theta \frac{\partial(\ldots)}{\partial\theta}, \tag{51.15}$$

as a result of which the equation (51.10) can be written in the form

$$-icG(\tilde{T}) + \tilde{T} + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\tilde{U} = q_n R_2. \tag{51.16}$$

The expressions (51.12) and (51.16) represent a system of two linear partial differential equations in two unknowns — the auxiliary functions $\tilde{T}$ and $\tilde{U}$.

Thus, as the result of the above discussion, the analysis of shells of revolution of arbitrary shape subject to any type of loading has been reduced to the solution of the system

$$\begin{aligned} &G(\tilde{U}) - \left[1 - ic\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\right]\frac{\partial^2 \tilde{T}}{\partial\varphi^2} = f(\theta, \varphi), \\ &-icG(\tilde{T}) + \tilde{T} + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\tilde{U} = q_n R_2, \end{aligned} \tag{51.17}$$

which for $c = 0$ takes the form

$$\begin{aligned} &G(\tilde{U}) - \frac{\partial^2 \tilde{T}}{\partial\varphi^2} = f(\theta, \varphi), \\ &\tilde{T} + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\tilde{U} = q_n R_2. \end{aligned} \tag{51.18}$$

Eliminating $\tilde{T}$, one arrives at the equation

$$G(\tilde{U}) + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\frac{\partial^2\tilde{U}}{\partial\varphi^2} = f(\theta, \varphi) + R_2\frac{\partial^2 q_n}{\partial\varphi^2}, \qquad (51.19)$$

which completely coincides with the equation (23.8). This was to be expected, since for $c = 0$ the original equations (51.3) reduce to the system of equations of the membrane theory. Thus, the system (51.17) includes as a particular case the fundamental differential equations of the membrane theory of shells of revolution. Hence it may be considered a generalization of these equations to shells of revolution which are not only subject to membrane stresses, but also to bending stresses.

§ 52. General method for solution of the system (51.17)

If a shell of revolution is bounded by one or two parallel circles, as is frequently the case in practical problems, it will be complete with respect to the coordinate φ and hence the components of the external surface and edge loadings will be periodic functions of this coordinate with period 2π. As a consequence, the components of the surface loading may be expanded in Fourier series in terms of φ and the functions $\tilde{U}$, $\tilde{V}$ and $\tilde{T}$ may be sought in the form of such series. Then the system (51.17) breaks up into a series of systems of ordinary differential equations. This method is of general importance and applies to any type of loading. As has already been noted in § 22, a study of loadings with the components

$$q_1 = q_{1,k}\cos k\varphi, \quad q_2 = q_{2,k}\sin k\varphi, \quad q_n = q_{n,k}\cos k\varphi, \qquad (52.1)$$

where $q_{1,k}$, $q_{2,k}$, $q_{n,k}$ are functions of θ, will thus lead to the solution of the problem in its general form, since any loading can be expressed as a sum (finite or infinite) of loadings of the form (52.1). Hence, in what follows consideration will be restricted to loadings of this type.

After substituting (52.1) into the system (51.17), its solution will be sought in the form

$$\tilde{U} = \tilde{U}^{(k)}\cos k\varphi, \qquad \tilde{T} = \tilde{T}^{(k)}\cos k\varphi, \qquad (52.2)$$



Fig. 72.

where $\tilde{U}^{(k)}$, $\tilde{T}^{(k)}$ are functions of θ only.

In this way one obtains, after elimination of common trigonometric terms, the following system of two ordinary differential equations for $\tilde{U}^{(k)}$ and $\tilde{T}^{(k)}$:

$$G_k[\tilde{U}^{(k)}] + k^2\left[1 - ic\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\right]\tilde{T}^{(k)} = f_k(\theta),$$

$$-icG_k[\tilde{T}^{(k)}] + \tilde{T}^{(k)} + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\,\tilde{U}^{(k)} = R_2 q_{n,k}, \tag{52.3}$$

where

$$f_k(\theta) = \frac{1}{R_1 R_2 \sin\theta}\left\{\frac{d}{d\theta}\left[(q_{n,k}\cos\theta - q_{1,k}\sin\theta)R_2^3\sin^2\theta\right] + \right.$$

$$\left. + kq_{2,k}R_1R_2^2\sin^2\theta\right\}. \tag{52.4}$$

$$G_k(\ldots) = \frac{1}{R_1R_2\sin\theta}\,\frac{d}{d\theta}\left[\frac{R_2^2\sin\theta}{R_1}\,\frac{d(\ldots)}{d\theta}\right] - \frac{k^2}{R_2\sin^2\theta}\,(\ldots). \tag{52.5}$$

Integration of the system (52.3) leads to the determination of the auxiliary functions $\tilde{U}$ and $\tilde{T}$ for the loading (52.1). Since, on the one hand, any loading can be obtained in terms of loadings of the type (52.1) and, on the other hand, having found $\tilde{U}$ and $\tilde{T}$ one can immediately evaluate all the complex forces by the help of the formulae (51.6), (51.11) and (51.7), it may be stated that the problem under consideration has been reduced to the integration of the system (52.3).

§ 53. Determination of the displacements

The relations between the complex forces and complex displacements (§ 34) for shells of revolution are expressed by the formulae

$$R_1\tilde{\varepsilon}_1 = \frac{\partial\tilde{u}}{\partial\theta} + \tilde{w} = \frac{R_1}{E\delta}(\tilde{T}_1 - \mu\tilde{T}_2),$$

$$R_2\tilde{\varepsilon}_2 = \frac{1}{\sin\theta}\,\frac{\partial\tilde{v}}{\partial\varphi} + \tilde{u}\cot\theta + \tilde{w} = \frac{R_2}{E\delta}(\tilde{T}_2 - \mu\tilde{T}_1), \tag{53.1}$$

$$R_2\tilde{\omega} = \frac{R_2}{R_1}\,\frac{\partial\tilde{v}}{\partial\theta} - \tilde{v}\cot\theta + \frac{1}{\sin\theta}\,\frac{\partial\tilde{u}}{\partial\varphi} = \frac{2(1+\mu)R_2}{E\delta}\,\tilde{S}.$$

$$\tilde{\kappa}_1 = -\frac{1}{R_1}\,\frac{\partial}{\partial\theta}\left[\frac{1}{R_1}\left(\frac{\partial\tilde{w}}{\partial\theta} - \tilde{u}\right)\right] = \frac{i}{cE\delta}(\tilde{T}_2 - T_2^*),$$

$$\tilde{\kappa}_2 = -\frac{1}{R_2^2\sin\theta}\,\frac{\partial}{\partial\varphi}\left(\frac{1}{\sin\theta}\,\frac{\partial\tilde{w}}{\partial\varphi} - \tilde{v}\right) - \frac{\cot\theta}{R_1R_2}\left(\frac{\partial\tilde{w}}{\partial\theta} - \tilde{u}\right) = \frac{i}{cE\delta}(\tilde{T}_1 - T_1^*), \tag{53.2}$$

$$\tilde{\tau} = -\frac{1}{R_1}\frac{\partial}{\partial\theta}\left[\frac{1}{R_2}\left(\frac{1}{\sin\theta}\frac{\partial\tilde{w}}{\partial\varphi} - \tilde{v}\right)\right] + \\ + \frac{1}{R_1R_2\sin\theta}\left(\frac{\partial\tilde{u}}{\partial\varphi} - \tilde{v}\cos\theta\right) = -\frac{i}{cE\delta}(\tilde{S} - S^*), \tag{53.2}$$

where T_1^*, T_2^*, S^* are the general or arbitrary particular integrals of the equations of the membrane theory of shells of revolution, i.e., of the equations (23.4).

If the surface loading is given by the components (52.1), the complex forces and solutions of the membrane theory are obtained in the form

$$\begin{aligned} \tilde{T}_1 &= \tilde{T}_{1,k}\cos k\varphi, \quad \tilde{T}_2 = \tilde{T}_{2,k}\cos k\varphi, \quad \tilde{S} = \tilde{S}_k \sin k\varphi, \\ T_1^* &= T^*_{1,k}\cos k\varphi, \quad T_2^* = T^*_{2,k}\cos k\varphi, \quad S^* = S_k^* \sin k\varphi, \end{aligned} \tag{53.3}$$

where $\tilde{T}_{1,k} \ldots \tilde{T}_{1,k}$ are functions of θ only.

It follows then that also the complex displacements must be taken in a similar form, viz.,

$$\tilde{u} = \tilde{u}_k \cos k\varphi, \quad \tilde{v} = \tilde{v}_k \sin k\varphi, \quad \tilde{w} = \tilde{w}_k \cos k\varphi. \tag{53.4}$$

Substituting (53.3) and (53.4) into the formulae (53.1) and (53.2), one finds

$$\frac{d\tilde{u}_k}{d\theta} + \tilde{w}_k = \frac{R_1}{E\delta}(\tilde{T}_{1,k} - \mu\tilde{T}_{2,k}),$$

$$\frac{k}{\sin\theta}\tilde{v}_k + \tilde{u}_k \operatorname{cotan}\theta + \tilde{w}_k = \frac{R_2}{E\delta}(\tilde{T}_{2,k} - \mu\tilde{T}_{1,k}), \tag{53.5}$$

$$\frac{R_2}{R_1}\frac{d\tilde{v}_k}{d\theta} - \tilde{v}_k \operatorname{cotan}\theta - \frac{k}{\sin\theta}\tilde{u}_k = \frac{2(1+\mu)R_2}{E\delta}\tilde{S}_k.$$

$$-\frac{1}{R_1}\frac{d}{d\theta}\left[\frac{1}{R_1}\left(\frac{d\tilde{w}_k}{d\theta} - \tilde{u}_k\right)\right] = \frac{i}{cE\delta}(\tilde{T}_{2,k} - T^*_{2,k}),$$

$$\frac{k}{R_2^2\sin\theta}\left(\frac{k}{\sin\theta}\tilde{w}_k + \tilde{v}_k\right) - \frac{\operatorname{cotan}\theta}{R_1R_2}\left(\frac{d\tilde{w}_k}{d\theta} - \tilde{u}_k\right) = \frac{i}{cE\delta}(\tilde{T}_{1,k} - T^*_{1,k}),$$

$$\frac{1}{R_1}\frac{d}{d\theta}\left[\frac{1}{R_2}\left(\frac{k}{\sin\theta}\tilde{w}_k + \tilde{v}_k\right)\right] - \frac{1}{R_1R_2\sin\theta}(k\tilde{u}_k + \tilde{v}_k\cos\theta) = \tag{53.6}$$

$$= -\frac{i}{cE\delta}(\tilde{S}_k - S_k^*).$$

Determination of the coefficients in the formulae (53.4) reduces to the simultaneous solution of the systems (53.5) and (53.6).

In this context it should be noted that the formulae (53.1) and (53.2) are only approximately compatible with each other with an error of order δ/R compared with unity. In view of this fact, a similar reasoning holds true with regard to the integration of the equations (53.5), (53.6).

§ 54. Symmetrical deformations of shells of revolution

A particularly important practical problem is the special case when $k = 0$ in the formulae (52.1). Then

$$q_1 = q_{1,0}(\theta), \quad q_2 = 0, \quad q_n = q_{n,0}(\theta), \tag{54.1}$$

i.e., the surface loading is symmetrical with respect to the axis of the shell and the component $q_2(\theta)$ which would twist the shell about its axis is absent.

It will be noted however, that this circumstance does not ensure that the deformations of the shell will be functions of θ only. For example, if a dome loaded by its own weight which is of the form (54.1) is not resting on a continuous foundation, but on a series of columns, then the strains in the dome will be functions of θ as well as of φ. Therefore, in order that the deformations of shells of revolution are axially symmetric, not only the surface loadings but also the edge loadings must exhibit the given symmetry.

It will be assumed that this condition is satisfied and that, in addition, there are no edge forces twisting the shell. Then the loading (54.1) produces in the shell only the forces and moments T_1, T_2, M_1, M_2, while the shear force S and the twisting moment H will be equal to zero. Hence the state of stress will be completely characterized by the two complex forces $\tilde{T}_1$ and $\tilde{T}_2$ (as functions of the angle θ only).

In this case, the equation (51.8) is identically satisfied and the equation (51.11) takes the form

$$\frac{d\tilde{U}}{d\theta} = (q_n \cos\theta - q_1 \sin\theta) R_2 R_1 \sin\theta. \tag{54.2}$$

(Here and in what follows the index $(_0)$ will be omitted in order to avoid confusion in the formulae).

Integrating (54.2) with respect to θ, one finds

$$\tilde{U} = \tilde{C}_1 + \int_{\theta''}^{\theta} (q_n \cos\theta - q_1 \sin\theta)\, R_1 R_2 \sin\theta\, d\theta, \tag{54.3}$$

where the lower limit of integration θ'' can be chosen arbitrarily (for example, at one of the edges of the shell).

Later on it will be shown that the constant $\tilde{C}_1$ in (54.3) is real, so that in the problem under consideration the auxiliary function $\tilde{U}$ may be identified with the auxiliary function U of the membrane theory; this follows from a comparison of the formula (54.3) with (25.3).

Substituting the expression obtained for $\tilde{U}$ into the second of the equations (51.17), one obtains

$$-icG(\tilde{T}) + \tilde{T} = q_n R_2 -$$

$$-\left(\frac{1}{R_1}-\frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\left[\tilde{C}_1+\int_{\theta''}^{\theta}(q_n\cos\theta - q_1\sin\theta)R_1R_2\sin\theta\,d\theta\right], \quad (54.4)$$

where in this case

$$G(\ldots) = \frac{1}{R_1R_2\sin\theta}\frac{d}{d\theta}\left[\frac{R_2^2\sin\theta}{R_1}\frac{d(\ldots)}{d\theta}\right], \quad (54.5)$$

since $\tilde{T}$ does not depend on φ.

Expanding equation (54.4), it may be written in the form

$$\frac{d^2\tilde{T}}{d\theta^2}+\left[\left(2\frac{R_1}{R_2}-1\right)\operatorname{cotan}\theta-\frac{1}{R_1}\frac{dR_1}{d\theta}\right]\frac{d\tilde{T}}{d\theta}+i\frac{R_1^2}{R_2c}\tilde{T}=i\frac{R_1^2}{R_2c}F(\theta), \quad (54.6)$$

where

$$F(\theta)=q_nR_2-\left(\frac{1}{R_1}-\frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\left[\tilde{C}_1+\int_{\theta''}^{\theta}(q_n\cos\theta-q_1\sin\theta)R_1R_2\sin\theta\,d\theta\right]. \quad (54.7)$$

The equation (54.6) is linear and as a result its general solution may be expressed by the formula

$$\tilde{T} = \mathfrak{T} + \tilde{t}, \quad (54.8)$$

where $\mathfrak{T}$ is the general solution of the homogeneous equation

$$\frac{d^2\mathfrak{T}}{d\theta^2}+\left[\left(2\frac{R_1}{R_2}-1\right)\operatorname{cotan}\theta-\frac{1}{R_1}\frac{dR_1}{d\theta}\right]\frac{d\mathfrak{T}}{d\theta}+i\frac{R_1^2}{R_2c}\mathfrak{T}=0, \quad (54.9)$$

and $\tilde{t}$ is any particular integral of the non-homogeneous equation (54.6).

As is known from any textbook on differential equations, the determination of a particular integral does not encounter any principal difficulties, once the solution of the homogeneous equation has been found.

In the present problem, in many cases, an approximation to a particular integral of the non-homogeneous equation (54.6) may be obtained by the following reasoning. It will be noted that the coefficient $i\frac{R_1^2}{R_2 c}$ of the last term on the left hand side of the equation (54.6) has a large absolute value of the order $\frac{R}{\delta}$, whereas the coefficients of the remaining terms are quantities of order unity. Thus a particular integral of the equation (54.6) may be obtained by neglecting all but the last term on the left hand side. In this way one will have

$$\bar{t} \approx F(\theta). \tag{54.10}$$

The error in this formula may be estimated by substituting (54.10) into (54.6) and by comparing the sole remaining term on the left hand side with the omitted terms, i.e., by comparing

$$\left| \frac{cR_2}{R_1^2} \frac{1}{F} \left\{ \frac{d^2F}{d\theta^2} + \left[\left(2\frac{R_1}{R_2} - 1 \right) \operatorname{cotan}\theta - \frac{1}{R_1} \frac{dR_1}{d\theta} \right] \frac{dF}{d\theta} \right\} \right| \tag{54.11}$$

with unity. In the majority of practical problems the error incurred is not great. In those cases where it turns out to be substantial, a particular integral of the equation (54.6) can be obtained by the ordinary method of variation of parameters.

Once the general solution of the equation (54.6) has been found, the complex forces and displacements can be readily determined. It thus follows from (51.6) and (51.7) that

$$\begin{aligned} \bar{T}_1 &= i\frac{c}{R_1} \operatorname{cotan}\theta \frac{d\bar{T}}{d\theta} + \frac{1}{R_2 \sin^2\theta} \bar{U}, \\ \bar{T}_2 &= \bar{T} - \bar{T}_1 = \bar{T} - i\frac{c}{R_1} \operatorname{cotan}\theta \frac{d\bar{T}}{d\theta} - \frac{1}{R_2 \sin^2\theta} \bar{U}. \end{aligned} \tag{54.12}$$

Substituting these expressions into the equations (53.1), (53.2) and taking into consideration the assumed independence of the solution from φ, one obtains the following four equations for the complex displacements

$$R_1\tilde{\varepsilon}_1 = \frac{d\tilde{u}}{d\theta} + \tilde{w} = \frac{R_1}{E\delta}\left\{ (1+\mu) i \frac{c}{R_1} \operatorname{cotan}\theta \frac{d\bar{T}}{d\theta} - \mu\bar{T} + \frac{1+\mu}{R_2 \sin^2\theta} \bar{U} \right\}, \tag{54.13}$$

$$\Delta_x = \tilde{u}\cos\theta + \tilde{w}\sin\theta = \frac{R_2 \sin\theta}{E\delta}\left\{ \bar{T} - (1+\mu) i \frac{c}{R_1} \operatorname{cotan}\theta \frac{d\bar{T}}{d\theta} - \frac{1+\mu}{R_2 \sin^2\theta} \bar{U} \right\},$$

$$\frac{1}{R_1}\frac{d\tilde{\vartheta}}{d\theta} = -\frac{1}{R_1}\frac{d}{d\theta}\frac{1}{R_1}\left(\frac{d\tilde{w}}{d\theta} - \tilde{u}\right) = \tag{54.13}$$

$$= \frac{1}{cE\delta}\left\{i\tilde{T} + \frac{c}{R_1}\operatorname{cotan}\theta\frac{d\tilde{T}}{d\theta} - i\left[\frac{1}{R_2\sin^2\theta}\tilde{U} + T_2^*\right]\right\},$$

$$\tilde{\vartheta} = -\frac{1}{R_1}\left(\frac{d\tilde{w}}{d\theta} - \tilde{u}\right) = \frac{1}{E\delta}\left\{-\frac{R_2}{R_1}\frac{d\tilde{T}}{d\theta} + i\frac{R_2\tan\theta}{c}\left(\frac{1}{R_2\sin^2\theta}\tilde{U} - T_1^*\right)\right\}.$$

In order that the last two equations of this system will be compatible, the operator $\frac{1}{R_1}\frac{d(\ldots)}{d\theta}$ on the right hand side of the fourth equation must be equal to the right hand side of the third equation. Hence it is seen that equation (54.6) will be obtained only if

$$T_1^* = \frac{1}{R_2\sin^2\theta}\tilde{U}. \tag{54.14}$$

Thus this last equality is the condition of compatibility of these two equations. Comparing (54.3) and (54.14) with (25.3), it is seen that

$$\tilde{C}_1 = C_1. \tag{54.15}$$

In other words, as has already been mentioned, the constant $\tilde{C}_1$ in (54.3) is real. It now follows from (54.7), (54.14), (54.15) and the formulae of § 25 that the function $F(\theta)$ on the right hand side of the equation (54.6) may be written in the form

$$F(\theta) = T_1^* + T_2^*, \tag{54.16}$$

whence it is quite clear that in determining the particular integral of the equation (54.6) by the approximate formula (54.10) one is, in effect, invoking the membrane theory.

On the basis of (54.14) and the last of the formulae (54.13) one has for the complex function $\tilde{\vartheta}$ the expression

$$\tilde{\vartheta} = -\frac{1}{R_1}\left(\frac{d\tilde{\omega}}{d\theta} - \tilde{u}\right) = -\frac{1}{E\delta}\frac{R_2}{R_1}\frac{d\tilde{T}}{d\theta}. \tag{54.17}$$

The real part of this function is obviously the angle of rotation of the tangent to the meridian

$$\vartheta = -\frac{1}{R_1}\left(\frac{dw}{d\theta} - u\right).$$

As regards its imaginary part, it will be equal to [cf. (16.6)]

$$I_m(\tilde{\vartheta}) = -\frac{1}{E\delta}\frac{R_2}{R_1}I_m\left(\frac{d\tilde{T}}{d\theta}\right) = \frac{1}{E\delta c}\frac{R_2}{R_1}\frac{1}{1+\mu}\frac{d(M_1+M_2)}{d\theta} = \frac{R_2}{Ec\delta}N_1.$$

Thus, finally,

$$\tilde{\mathfrak{H}} = \vartheta + i\frac{R_2}{Ec\delta}N_1 = -\frac{1}{E\delta}\frac{R_2}{R_1}\frac{d\tilde{T}}{d\theta}. \tag{54.18}$$

It will be noted that the formula (54.18) establishes a connection between the present transformation and that of Meissner [155], since $\tilde{\mathfrak{H}}$ is the basic complex auxiliary function of the above author.

For the determination of the displacements $\tilde{u}$, $\tilde{w}$ the expression

$$\tilde{\Delta}_z = \tilde{w}\cos\theta - \tilde{u}\sin\theta. \tag{54.19}$$

will first be formed. Differentiating it with respect to θ, one finds

$$\frac{d\tilde{\Delta}_z}{d\theta} = \frac{d\tilde{w}}{d\theta}\cos\theta - \tilde{w}\sin\theta - \frac{d\tilde{u}}{d\theta}\sin\theta - \tilde{u}\cos\theta = -R_1(\tilde{\mathfrak{H}}\cos\theta + \tilde{\varepsilon}_1\sin\theta). \tag{54.20}$$

The right hand side of this formula contains quantities which have already been expressed in terms of $\tilde{T}$; this follows from the first of the formulae (54.13) and from (54.18). Thus the right hand side represents a known function of θ.

Integrating (54.20), one finds

$$\tilde{\Delta}_z = \tilde{C}_2 - \int_{\theta^*}^{\theta} R_1(\tilde{\mathfrak{H}}\cos\theta + \tilde{\varepsilon}_1\sin\theta)\,d\theta. \tag{54.21}$$

By adding to this formula the second of the equations (54.13) one may determine separately $\tilde{u}$ and $\tilde{w}$.

It will be noted that the real parts of the functions $\tilde{\Delta}_x$ and $\tilde{\Delta}_z$

$$\begin{aligned} \Delta_x &= u\cos\theta + w\sin\theta, \\ \Delta_z &= w\cos\theta - u\sin\theta, \end{aligned} \tag{54.22}$$

have the following independent geometric interpretations:

Δ_z is the component of the displacement of an arbitrary point on the meridian in the direction of the axis of the shell,

Δ_x is the component of the displacement in the direction perpendicular to this axis (Fig. 73).

In correspondence with this interpretation of Δ_z, the real part of the constant $\tilde{C}_2$ (C) in the formula (54.21) is equal to the value of the axial displacement on the parallel circle θ''. By choice of this constant one may place the origin for Δ_z at any parallel circle. The value of this constant obviously does not influence the stresses and the strains in the shell.

Introduce now the two complex functions

$$\tilde{Q}_x = \tilde{T}_1 \cos\theta + i\frac{c}{R_1}\frac{d\tilde{T}}{d\theta}\sin\theta,$$
$$\tilde{Q}_z = \tilde{T}_1 \sin\theta - i\frac{c}{R_1}\frac{d\tilde{T}}{d\theta}\cos\theta, \tag{54.23}$$

the real parts of which will be

$$Q_x = T_1 \cos\theta + N_1 \sin\theta,$$
$$Q_z = T_1 \sin\theta - N_1 \cos\theta. \tag{54.24}$$

As follows from Fig. 74, Q_z and Q_x are the components of the forces in



Fig. 73.



Fig. 74.

the directions of the axis of the shell and perpendicular to this axis which act through the contemplated point of the meridian.

Substituting in (54.23) for $\tilde{T}_1$ its value from (54.12) and (54.14), one finds

$$\tilde{Q}_x = i\frac{c}{R_1}\frac{1}{\sin\theta}\frac{d\tilde{T}}{d\theta} + \frac{\tilde{U}}{R_2}\frac{\cos\theta}{\sin^2\theta},$$
$$\tilde{Q}_z = Q_z = \frac{1}{R_2 \sin\theta}\tilde{U} = T_1^* \sin\theta. \tag{54.25}$$

It is seen from the last formula that Q_z does not depend on $\tilde{T}$ and that this formula determines this component exactly apart from an arbitrary constant C_1. It will be noted that as a rule the value of Q_z on one of the parallel circles of the shell may be found from a study of the equilibrium of the shell as a whole. Then the constant C_1 will immediately be determined and thereby Q_z will be known at all sections of the shell. In principle, however, it is possible to have the case when at the two parallel sections bounding the shell the displacement Δ_z will be specified. Then the force Q_z will be statically indeterminate.

The above formulae enable the analysis of symmetrically deformed shells of revolution for any boundary conditions.

In conclusion, some observations will be made regarding the physical implications of the approximation of replacing the particular integral of the equations of the moment theory by a solution of the membrane theory.

For this purpose consider first the case

$$q_1 = q_2 = q_n = U = 0,$$

which will be called the homogeneous problem, since its basic equation (54.6) is homogeneous.

As follows from the second of the formulae (54.25), in this case the axial component of the force Q_z is equal to zero, and hence the homogeneous problem corresponds to the loading shown in Fig. 76 (a shell free from surface loading, but subject to forces Q_x and moments M_1 along the edges).

The general case shown in Fig. 75 will now be considered, where, in addition to symmetrical edge loading, the shell carries also symmetric surface loading.



Fig. 75.

For this purpose, impose on its edges the boundary conditions

$$\begin{aligned} &Q_x = Q_x', \quad Q_z = Q_z', \quad M_1 = M_1' \text{ for } \theta = \theta', \\ &Q_x = Q_x'', \quad Q_z = Q_z'', \quad M_1 = M_1'' \text{ for } \theta = \theta''. \end{aligned} \tag{54.26}$$

This system of edge forces must be balanced by all the surface loading, so that the difference

$$2\pi[Q_z' R_2' \sin\theta' - Q_z'' R_2'' \sin\theta'']$$

must be equal to the resultant of all the surface forces. It will be assumed that the solution of this problem has been found by means of the membrane theory. To this solution there will correspond boundary conditions

which are different from (54.26), namely the conditions

$$\begin{aligned} &Q_x = (Q_x^*)',\ Q_z = (Q_z^*)',\ M_1 = 0 \text{ for } \theta = \theta', \\ &Q_x = (Q_x^*)'',\ Q_z = (Q_z^*)'',\ M_1 = 0 \text{ for } \theta = \theta'' \end{aligned} \tag{54.27}$$

where the integration constants entering into the formulae (25.3) must be selected in such a way that

$$(Q_z^*)' = Q_z',\ (Q_z^*)'' = Q_z'', \tag{54.28}$$

i.e., that the boundary conditions (54.26) for the axial components of the force Q_z will be satisfied. This will ensure that the surface and edge loadings will balance.

Subtract now the membrane state of stress from the actual state of stress involving moments; this may be done since all the differential equations are linear and therefore the principle of superposition applies. As a result of this subtraction one arrives at a study of the same shell, but without surface loading, while its edge conditions will be given by

$$\begin{aligned} &Q_z = 0,\ Q_x = Q_x' - (Q_x^*)',\ M_1 = M_1' \text{ for } \theta = \theta', \\ &Q_z = 0,\ Q_x = Q_x'' - (Q_x^*)'',\ M_1 = M_1'' \text{ for } \theta = \theta''. \end{aligned} \tag{54.29}$$

However, this is a loading of the type shown in Fig. 76, i.e., the loading corresponding to the homogeneous problem.

The above reasoning explains essentially the justification of the method of replacing the particular integral of the equation (54.6) by a solution



Fig. 76.



Fig. 77.

of the membrane theory. It should be emphasized that this reasoning applies only if the state of stress corresponding to the given surface loading and edge forces (54.27) will actually be of the membrane type which, as is known from Chapter II, is not always true. This is the limitation imposed on the employment of such an approximate method.

As a result, the following general rule may be formulated by the above reasoning. If a shell of given form and subject to given surface loading, the boundary conditions corresponding to the requirements of the membrane theory, is in a state of stress close to the membrane type, then

one may use for the analysis of the same shell for other boundary conditions, as the particular integral of the non-homogeneous equations of the general theory of shells, the solution of the membrane theory.

§ 55. Asymptotic integration of linear second order differential equations

Consider the linear homogeneous equation of second order

$$\frac{d^2y}{dx^2} + p(x)\frac{dy}{dx} + q(x)y = 0. \tag{55.1}$$

By use of the new unknown

$$z = y \exp\left(\tfrac{1}{2}\int_{x_0}^{x} p\,dx\right), \quad [\exp(x) = e^x] \tag{55.2}$$

(where the lower limit x_0 may be chosen arbitrarily) the above equation may be reduced to the form

$$\frac{d^2z}{dx^2} - F^2 z = 0, \tag{55.3}$$

where

$$F^2 = -q + \frac{1}{2}\frac{dp}{dx} + \frac{1}{4}p^2. \tag{55.4}$$

The equation (55.3) can be transformed to another equation of the same form by means of the following substitutions for the independent and dependent variables:

$$\begin{aligned} dx_1 &= F\,dx, \\ z_1 &= z\sqrt{F}. \end{aligned} \tag{55.5}$$

Introducing these new variables into the equation (55.3), one finds

$$\frac{d^2z_1}{dx_1^2} - F_1^2 z_1 = 0, \tag{55.6}$$

where

$$\begin{aligned} F_1^2 &= 1 + \frac{1}{2}\frac{1}{F}\frac{d^2F}{dx_1^2} - \frac{1}{4}\frac{1}{F^2}\left(\frac{dF}{dx_1}\right)^2 = \\ &= 1 + \frac{1}{2F^2}\left[\frac{1}{F}\frac{d^2F}{dx^2} - \frac{3}{2}\frac{1}{F^2}\left(\frac{dF}{dx}\right)^2\right] = 1 + \Delta_1. \end{aligned} \tag{55.7}$$

In the general case, the transformation of the equation (55.3) into the equation (55.6) does not render any important information, since the coefficient F_1 remains variable and the same difficulties are encountered as with the solution of the equation (55.3).

However, firstly if the function F is given the property that it does not increase on differentiation and, secondly, if it is assumed that its magnitude greatly exceeds unity, then, as is clear from (55.7), the variable terms in this formula which are combined in the term Δ_1 will be small compared with its first term and may be neglected with an error of order $\frac{1}{F^2}$ compared with unity.

Then the equation (55.6) takes the form

$$\frac{d^2z_1}{dx_1^2} - z_1 = 0 \tag{55.8}$$

and its general solution is given by

$$z_1' = C_1 e^{x_1} + C_2 e^{-x_1}. \tag{55.9}$$

Returning now with the help of the formulae (55.5) to the independent variable x and the dependent variable z, one will have

$$z = \frac{1}{\sqrt{F}} \{C_1 e^{\beta} + C_2 e^{-\beta}\}, \tag{55.10}$$

where

$$\beta = \int_{x_0}^{x} F\,dx, \tag{55.11}$$

and the lower integration limit x_0 may be chosen arbitrarily to suit the convenience of the analysis.

The expression (55.10) will be considered as a first approximation to the general solution of the differential equation (55.3), as long as the function F possesses the above characteristics.

By an analogous reasoning one may also construct a second approximation. Namely, introduce another new independent variable

$$dx_2 = F_1 dx_1 \approx \left\{1 + \frac{1}{4F^2}\left[\frac{1}{F}\frac{d^2F}{dx^2} - \frac{3}{2}\frac{1}{F^2}\left(\frac{dF}{dx}\right)^2\right]\right\} F\,dx \tag{55.12}$$

and a new dependent variable

$$z_2 = z_1\sqrt{F_1} \approx z\sqrt{F}\left\{1 + \frac{1}{8F^2}\left[\frac{1}{F}\frac{d^2F}{dx^2} - \frac{3}{2}\frac{1}{F^2}\left(\frac{dF}{dx}\right)^2\right]\right\}. \tag{55.13}$$

Then the equation (55.6) takes the form

$$\frac{d^2z_2}{dx_2^2} - F_2^2 z_2 = 0, \tag{55.14}$$

where

$$F_2^2 = 1 + \frac{1}{2F_1^2}\left[\frac{1}{F_1}\frac{d^2F_1}{dx_1^2} - \frac{3}{2}\frac{1}{F_1^2}\left(\frac{dF_1}{dx_1}\right)^2\right] = 1 + \Delta_2. \tag{55.15}$$

Without writing the expression for Δ_2 out in full, in view of its complexity, it will be noted that if the derivatives of F with respect to x are assumed to be quantities of the same order as F, then Δ_2 will be a quantity of order $\frac{1}{F^4}$, i.e., a quantity which is significantly smaller than Δ_1.

Neglecting Δ_2 compared with unity, one arrives at the differential equation

$$\frac{d^2z_2}{dx_2^2} - z_2 = 0, \tag{55.16}$$

the general solution of which will be

$$z_2 = C_1 e^{x_2} + C_2 e^{-x_2}. \tag{55.17}$$

Reverting now by help of the formulae (55.12) and (55.13) to the variables x and z, one will have

$$z \approx \frac{1 - \frac{1}{8F^2}\left[\frac{1}{F}\frac{d^2F}{dx^2} - \frac{3}{2}\frac{1}{F^2}\left(\frac{dF}{dx}\right)^2\right]}{\sqrt{F}}\{C_1 e^{\beta_1} + C_2 e^{-\beta_1}\}, \tag{55.18}$$

where

$$\beta_1 = \int_{x_0}^{x}\left\{1 + \frac{1}{4F^2}\left[\frac{1}{F}\frac{d^2F}{dx^2} - \frac{3}{2}\frac{1}{F^2}\left(\frac{dF}{dx}\right)^2\right]\right\}F\,dx =$$

$$= \int_{x_0}^{x}\left\{1 + \frac{1}{4F^{3/2}}\frac{d}{dx}\left(\frac{1}{F^{3/2}}\frac{dF}{dx}\right)\right\}F\,dx. \tag{55.19}$$

The expression (55.18) will be regarded as a second approximation to the general solution of the equation (55.3).

It is seen from the above discussion that the first approximation was constructed by neglecting in the coefficients of the differential equation

quantities of order $\frac{1}{F^2}$, and the second by neglecting quantities of order $\frac{1}{F^4}$ compared with unity. In spite of this, it may not be asserted that the formulae (55.10) and (55.18) respectively will have errors of the same order, since errors in the coefficients may occur on a magnified scale (cf. on this subject, for example, "Lectures on numerical approximations" by A. N. Krylov, p. 360).

Considering the expression (55.18), i.e., the second approximation, and rejecting in it terms of order $\frac{1}{F^2}$ compared with unity, one finds

$$z \approx \frac{1}{\sqrt{F}}\{C_1(1+\gamma)e^{x_1} + C_2(1-\gamma)e^{-x_1}\}, \tag{55.20}$$

where

$$\gamma \approx 1 - e^{-\gamma} \approx \frac{1}{4}\int_{x_0}^{x} \frac{1}{\sqrt{F}} \frac{d}{dx}\left(\frac{1}{F^{3/2}} \frac{dF}{dx}\right) dx \tag{55.21}$$

is a quantity of order $\frac{1}{F}$, if the non-dimensional quantity $(x - x_0)$ is of order unity.

Restricting the values of x to satisfy this last condition, one may call the formula (55.20) the general solution of the differential equation (55.3), determined to an accuracy of order $\frac{1}{F}$ inclusively. Hence it is clear that the earlier introduced first approximation has not the above stated degree of accuracy. Therefore, when using the formula for the first approximation (55.10), there is no sense in including terms of order $\frac{1}{F}$. This conclusion permits a certain simplification of the formula (55.10). Namely, on differentiating it with respect to x, one can neglect the variation of the multiplier $\frac{1}{\sqrt{F}}$ compared with the variation of the terms included in the brackets.

Actually, differentiation of the formula (55.10) gives

$$\frac{dz}{dx} = \sqrt{F}\{C_1e^{\beta} - C_2e^{-\beta}\} - \frac{1}{2F^{3/2}} \frac{dF}{dx}\{C_1e^{\beta} + C_2e^{-\beta}\} =$$

$$= \sqrt{F}\left\{C_1e^{\beta} - C_2e^{-\beta} - \frac{1}{2F^2} \frac{dF}{dx}(C_1e^{\beta} + C_2e^{-\beta})\right\}. \tag{55.22}$$

But the factor $\frac{1}{2F^2}\frac{dF}{dx}$ is a quantity of order $\frac{1}{F}$. Therefore the group of terms $\frac{1}{2F^2}\frac{dF}{dx}(C_1e^{\beta} + C_2e^{-\beta})$, compared with the group of terms $C_1e^{\beta} - C_2e^{-\beta}$, will also be a quantity of order $\frac{1}{F}$ and may on this basis be neglected, which is equivalent to neglecting the variation of the coefficient $\frac{1}{\sqrt{F}}$ in the formula (55.10).

Thus, for the degree of accuracy which is inherent in the formula (55.10), the coefficient $\frac{1}{\sqrt{F}}$ must be assumed to be constant. Including it then in the integration constants, one will have

$$z = C_1e^{\beta} + C_2e^{-\beta}. \tag{55.23}$$

As is seen from the preceding reasoning, this form of the first approximation is not only simpler, but also more consistent than the expression (55.10).

§ 56. Approximate integration of the homogeneous differential equation for symmetrical deformations

The theory of the last section will now be applied to the equation (54.9)

$$\frac{d^2\mathfrak{T}}{d\theta^2} + p(\theta)\frac{d\mathfrak{T}}{d\theta} + q(\theta).\mathfrak{T} = 0, \tag{56.1}$$

where

$$\begin{aligned} p(\theta) &= \left(2\frac{R_1}{R_2} - 1\right)\operatorname{cotan}\theta - \frac{1}{R_1}\frac{dR_1}{d\theta}, \\ q(\theta) &= i\frac{{R_1}^2}{R_2c} = i\sqrt{12(1-\mu^2)}\,\frac{{R_1}^2}{R_2\delta}. \end{aligned} \tag{56.2}$$

Introducing the new unknown

$$z = \mathfrak{T}e^{\frac{1}{2}\int\left\{\left(2\frac{R_1}{R_2} - 1\right)\operatorname{cotan}\theta - \frac{1}{R_1}\frac{dR_1}{d\theta}\right\}d\theta} = R_2\sqrt{\frac{\sin\theta}{R_1}}.\mathfrak{T}, \tag{56.3}$$

the equation reduces to the form,

$$\frac{d^2z}{d\theta^2} - F^2z = 0, \tag{56.4}$$

where

$$F^2=\frac{1}{2}\frac{dp}{d\theta}+\frac{1}{4}p^2-q=-i\frac{R_1^2}{R_2c}-\frac{1}{2R_1}\frac{d^2R_1}{d\theta^2}+\frac{3}{4}\frac{1}{R_1^2}\left(\frac{dR_1}{d\theta}\right)^2+$$
$$+\frac{\operatorname{cotan}\theta}{2R_1}\frac{dR_1}{d\theta}-\frac{R_1}{R_2}\frac{1}{\sin^2\theta}+\frac{2+\cos^2\theta}{4\sin^2\theta}. \quad (56.5)$$

It will now be required to find a first approximation to the solution of the equation (56.4) in the same sense as this term has been used in the preceding section. In other words, quantities of order $\frac{1}{F}$ will be neglected on comparison with unity. Further, the approximate solution will not be required to retain its accuracy near the singular points of the equation (56.1), such points being $\theta = 0$ and $\theta = \pi$, and it will be assumed that the radii of curvature R_1 and R_2 are sufficiently smooth functions of θ. With these stipulations all the terms in the formula (56.5), with the exclusion of the first, may be assumed to be quantities of order unity.

As regards the first term

$$-i\frac{R_1^2}{R_2c},$$

it will have an absolute value of order $\frac{R}{\delta}$. Hence, in correspondence with the above stated principle for the construction of an approximate solution, one may put

$$F^2 \approx -i\frac{R_1^2}{R_2c}. \quad (56.6)$$

Further, one finds directly on the basis of the formulae (55.10) and (55.11) that

$$z \approx \frac{\sqrt[4]{R_2c}}{\sqrt{R_1}}\{\tilde{C}_1' e^{-(1-i)\beta}+\tilde{C}_2' e^{(1-i)\beta}\}, \quad (56.7)$$

where

$$\beta=\frac{1}{\sqrt{2}}\int_{\theta_0}^{\theta}\frac{R_1}{\sqrt{R_2c}}\,d\theta=\sqrt[4]{3(1-\mu^2)}\int_{\theta_0}^{\theta}\frac{R_1}{\sqrt{R_2\delta}}\,d\theta, \quad (56.8)$$

and by θ_0 will in future be understood an angle determining one of the edges of the shell.

Reverting now from z to the original dependent variable $\mathfrak{T}$ and introducing instead of C_1', C_2' new integration constants, one obtains

$$\mathfrak{T} = \frac{1}{R_2^{3/4} \sin^{1/2}\theta} [\bar{C}_1'' e^{-(1-i)\beta} + \bar{C}_2'' e^{(1-i)\beta}]. \tag{56.9}$$

As has been shown in the preceding section, the deduced formula is accurate to order $\sqrt{\frac{\delta}{R}}$ compared with unity, since in the present case this is the order of magnitude of $\frac{1}{F}$. In view of this, the factor $\frac{1}{R_2^{3/4} \sin^{1/2}\theta}$ must be assumed to be constant for the differentiation, as has likewise been shown in § 55. Including this factor in the integration constant, one arrives at the following final expression for $\mathfrak{T}$

$$\mathfrak{T} = \bar{C}_1 e^{-(1-i)\beta} + \bar{C}_2 e^{(1-i)\beta}. \tag{56.10}$$

Sometimes it may be required to obtain a second approximation on the basis of the formula (55.20), i.e., an expression for $\mathfrak{T}$ including terms of order $\sqrt{\frac{\delta}{R}}$. This would be equivalent to obtaining everywhere, except near the singular points, a mathematically exact solution of the differential equation (54.9). This is clear from the fact that the equation (54.9), being based on the initial assumptions of the theory of shells, itself involves errors of order $\frac{\delta}{R}$ compared with unity. Hence there is no sense including in its integration terms of higher order than $\sqrt{\frac{\delta}{R}}$, i.e., there is no sense in solving the equation to a greater accuracy than that of the second approximation.

However, since, on the one hand, the formula for the second approximation is very cumbersome and, on the other hand, the first approximation is sufficient for practical calculations, no attention will be given here to the evaluation of the second approximation. Yet it will be emphasized that there will arise no difficulties in its computation.

Certain authors assume that, if in the formula (56.9) one neglects the variation of the factor

$$\frac{1}{R_2^{3/4} \sin^{1/2}\theta},$$

one must also neglect the variation of the quantity

$$\frac{R_1}{\sqrt{R_2 c}}$$

in the formula (56.8), which would lead to the expression

$$\beta = \frac{1}{\sqrt{2}} \frac{R_1^0}{\sqrt{R_2^0 c}} (\theta - \theta_0), \tag{56.11}$$

where by R_1^0, R_2^0 are understood the edge values of the radii of curvature. However, although at a first glance these two simplifications seem to be of the same type, this is actually not quite true.

It is essential that β enters into the formula (56.9) as an exponent, so that its admissible error has a magnified effect on the final result. Practical design calculations show that sometimes corrections such as are given by (56.8) in comparison with (56.11) may be rather significant (for example, in the analysis of elliptical or box-like end sections). Therefore the recommendation to use the formula (56.8) and not (56.11) seems to be better justified.

§ 57. Approximate expressions for the forces, moments and displacements of symmetrically deformed shells of revolution

The work in this section will start off from the approximate formulae (56.10) and (56.8). Substituting (56.10) into the formulae for the complex forces (54.12), one finds

$$\tilde{T}_1 = -\frac{1+i}{\sqrt{2}} \sqrt{\frac{c}{R_2}} \operatorname{cotan} \theta [\tilde{A}_1 e^{-(1-i)\beta} - \tilde{A}_2 e^{(1-i)\beta}] + \tilde{t}_1 =$$

$$= \frac{1+i}{\sqrt{2}} \sqrt{\frac{c}{R_2}} \operatorname{cotan} \theta [\tilde{B}_1 \cosh (1-i)\beta + \tilde{B}_2 \sinh (1-i)\beta] + \tilde{t}_1,$$

$$\tilde{T}_2 = \tilde{A}_1 \left[1 + \frac{1+i}{\sqrt{2}} \sqrt{\frac{c}{R_2}} \operatorname{cotan} \theta \right] e^{-(1-i)\beta} +$$

$$+ \tilde{A}_2 \left[1 - \frac{1+i}{\sqrt{2}} \sqrt{\frac{c}{R_2}} \operatorname{cotan} \theta \right] e^{(1-i)\beta} + \tilde{t}_2 = \tag{57.1}$$

$$= \left[\tilde{B}_1 - \frac{1+i}{\sqrt{2}} \sqrt{\frac{c}{R_2}} \operatorname{cotan} \theta . \tilde{B}_2 \right] \sinh (1-i)\beta +$$

$$+ \left[\tilde{B}_2 - \frac{1+i}{\sqrt{2}} \sqrt{\frac{c}{R_2}} \operatorname{cotan} \theta . \tilde{B}_1 \right] \cosh (1-i)\beta + \tilde{t}_2.$$

Following the principles underlying the approximate solution studied in the preceding section, the underlined terms in the last formula must be neglected as quantities of order $\sqrt{\frac{\delta}{R}}$. In what follows, similar terms will be neglected without stipulation.

The terms in (57.1) which correspond to the particular integral will be

$$\tilde{t}_1 = T_1^* + i\frac{c}{R_1}\operatorname{cotan}\theta\,\frac{d\tilde{t}}{d\theta},$$
$$\tilde{t}_2 = \tilde{t} - T_1^* - i\frac{c}{R_1}\operatorname{cotan}\theta\,\frac{d\tilde{t}}{d\theta}. \tag{57.2}$$

Further, using the formulae (54.17) and (54.13), one finds

$$\tilde{\vartheta} \approx \frac{1-i}{\sqrt{2}}\frac{1}{E\delta}\sqrt{\frac{R_2}{c}}\{\tilde{A}_1 e^{-(1-i)\beta} - \tilde{A}_2 e^{(1-i)\beta}\} - \frac{1}{E\delta}\cdot\frac{R_2}{R_1}\frac{d\tilde{t}}{d\theta} =$$

$$= -\frac{1-i}{\sqrt{2}}\frac{1}{E\delta}\sqrt{\frac{R_2}{c}}\{\tilde{B}_1\cosh(1-i)\beta + \tilde{B}_2\sinh(1-i)\beta\} - \frac{1}{E\delta}\frac{R_2}{R_1}\frac{d\tilde{t}}{d\theta},$$

$$\tilde{\Delta}_x \approx \frac{R_2\sin\theta}{E\delta}\{\tilde{A}_1 e^{-(1-i)\beta} + \tilde{A}_2 e^{(1-i)\beta} + \tilde{t} - (1+\mu)T_1^*\} =$$

$$= \frac{R_2\sin\theta}{E\delta}\{\tilde{B}_2\cosh(1-i)\beta + \tilde{B}_1\sinh(1-i)\beta + \tilde{t} - (1+\mu)T_1^*\}, \tag{57.3}$$

$$R_1\tilde{\varepsilon}_1 = \frac{R_1}{E\delta}\{-\mu[\tilde{A}_1 e^{-(1-i)\beta} + \tilde{A}_2 e^{(1-i)\beta}] - \mu\tilde{t} + (1+\mu)T_1^*\}.$$

Finally, on the basis of the formulae (54.25), one will have

$$\tilde{Q}_x \approx -\frac{1+i}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\frac{1}{\sin\theta}[\tilde{A}_1 e^{-(1-i)\beta} - \tilde{A}_2 e^{(1-i)\beta}] + \tilde{q}_x =$$

$$= \frac{1+i}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\frac{1}{\sin\theta}[\tilde{B}_1\cosh(1-i)\beta + \tilde{B}_2\sinh(1-i)\beta] + \tilde{q}_x, \tag{57.4}$$

$$\tilde{Q}_z = Q_z = T_1^*\sin\theta,$$

where

$$\tilde{q}_x = T_1^*\cos\theta + i\frac{c}{R_1}\frac{1}{\sin\theta}\frac{d\tilde{t}}{d\theta}. \tag{57.5}$$

If the surface loading is sufficiently smooth, one has in these formulae

$$\begin{aligned} &\tilde{t} \approx F(\theta) = T_1^* + T_2^*, \quad \tilde{t}_1 \approx T_1^*, \\ &\tilde{t}_2 \approx T_2^*, \qquad\qquad \tilde{q}_x \approx T_1^* \cos\theta \end{aligned} \tag{57.6}$$

and general expressions for the forces, moments, angles of rotation and displacements may be obtained by separating real and imaginary parts in the formulae (57.1), (57.3), (57.4).

The corresponding computations will only be performed for one of the two forms of solutions deduced above, namely for that which follows from the expression

$$\tilde{T} \approx \tilde{A}_1 e^{-(1-i)\beta} + \tilde{A}_2 e^{(1-i)\beta}. \tag{57.7}$$

For this purpose, the terms corresponding to the particular integral will be omitted, i.e., only the solution of the homogeneous problem will be obtained, since all the aspects of the particular integral have already been sufficiently explained.

Letting

$$\tilde{A}_1 = A_1' + iA_1'', \quad \tilde{A}_2 = A_2' + iA_2'', \tag{57.8}$$

where A_1', A_1'', A_2', A_2'' are arbitrary real constants, one arrives on the basis of (57.1) at the following expressions for the forces and moments:

$$\begin{aligned} T_1 = &-\frac{1}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\operatorname{cotan}\theta\{[(A_1'-A_1'')\cos\beta-(A_1'+A_1'')\sin\beta]e^{-\beta}+ \\ &+[(A_2''-A_2')\cos\beta-(A_2'+A_2'')\sin\beta]e^{\beta}\}, \\ T_2 = &(A_1'\cos\beta - A_1''\sin\beta)e^{-\beta} + (A_2'\cos\beta + A_2''\sin\beta)e^{\beta}, \\ \frac{1}{c}\frac{M_2-\mu M_1}{1-\mu^2} = &\frac{1}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\operatorname{cotan}\theta\{[(A_1'+A_1'')\cos\beta+(A_1'-A_1'')\sin\beta]e^{-\beta}+ \\ &+[-(A_2'+A_2'')\cos\beta+(A_2'-A_2'')\sin\beta]e^{\beta}\}, \\ M_1+M_2 = &-(1+\mu)c[(A_1''\cos\beta+A_1'\sin\beta)e^{-\beta}+(A_2''\cos\beta-A_2'\sin\beta)e^{\beta}]. \end{aligned} \tag{57.9}$$

It follows from the last two formulae that to an accuracy of order $\sqrt{\frac{\delta}{R}}$ compared with unity

$$M_2 \approx \mu M_1 \tag{57.10}$$

and, therefore,

$$M_1 = -c[(A_1''\cos\beta + A_1'\sin\beta)e^{-\beta} + (A_2''\cos\beta - A_2'\sin\beta)e^{\beta}]. \tag{57.11}$$

Further, using the first of the formulae (57.3), one finds

$$N_1 = -\frac{1}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\{[A_1' - A_1'')\cos\beta - (A_1' + A_1'')\sin\beta]e^{-\beta} + \\ + [(A_2'' - A_1')\cos\beta - (A_2' + A_2'')\sin\beta]e^{+\beta}\},$$

$$\vartheta = \frac{1}{\sqrt{2}}\frac{1}{E\delta}\sqrt{\frac{R_2}{c}}\{[(A_1' + A_1'')\cos\beta + (A_1' - A_2'')\sin\beta]e^{-\beta} - \\ - [(A_2' + A_2'')\cos\beta - (A_2' - A_2'')\sin\beta]e^{\beta}\}. \tag{57.12}$$

Now, the formulae (54.25) for $U = 0$ give

$$Q_z = 0, \quad Q_x = \frac{1}{\sin\theta} N_1. \tag{57.13}$$

Finally, it follows from (57.3), (54.18), (54.21) that

$$\Delta_z \approx C + \frac{R_2}{E\delta}\cos\theta(T_1 + T_2) \approx C + \frac{R_2\cos\theta}{E\delta} T_2, \\ \Delta_x \approx \frac{R_2\sin\theta}{E\delta}(T_2 - \mu T_1) \approx \frac{R_2\sin\theta}{E\delta} T_2, \tag{57.14}$$

whence

$$u \approx C\sin\theta, \\ w \approx -C\cos\theta + \frac{R_2}{E\delta} T_2. \tag{57.15}$$

As has already been indicated, the constant C fixes the origin from which the axial displacement Δ_z is measured.

Summarizing all the obtained results, one arrives at the following set of formulae:

$$w \approx \frac{R_2}{E\delta}[(A_1'\cos\beta - A_1''\sin\beta)e^{-\beta} + (A_2'\cos\beta + A_2''\sin\beta)e^{\beta}] \\ \Delta_x \approx \frac{R_2\sin\theta}{E\delta} T_2, \\ \vartheta \approx \frac{1}{E\delta}\frac{1}{\sqrt{2}}\sqrt{\frac{R_2}{c}}\{[(A_1' + A_1'')\cos\beta + (A_1' - A_1'')\sin\beta]e^{-\beta} - \\ - [(A_2' + A_2'')\cos\beta + (A_2'' - A_2')\sin\beta]e^{\beta}\}, \tag{57.16}$$

$$T_1 \approx -\frac{1}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\operatorname{cotan}\theta\{[(A_1'-A_1'')\cos\beta-(A_1'+A_1'')\sin\beta]e^{-\beta}+$$
$$+[(A_2''-A_2')\cos\beta-(A_2'+A_2'')\sin\beta]e^{\beta}\},$$
$$N_1 \approx T_1\tan\theta,\quad Q_x=\frac{N_1}{\sin\theta},\tag{57.16}$$
$$T_2 \approx (A_1'\cos\beta-A_1''\sin\beta)e^{-\beta}+(A_2'\cos\beta+A_2''\sin\beta)e^{\beta},$$
$$M_1 \approx -c[(A_1''\cos\beta+A_1'\sin\beta)e^{-\beta}+(A_2''\cos\beta-A_2'\sin\beta)e^{\beta}],$$
$$M_2 \approx \mu M_1.$$

These formulae are for the general case when the shell of revolution has two edges determined by the angles $\theta=\theta_0$ and $\theta=\theta_1$ (Figs. 76, 77), i.e., when it is a dome or end-panel with a cut-out. If the shell has only one edge $\theta=\theta_0$, being closed at the apex, then the constants A_1', A_1'' in the above solutions must be set equal to zero. Unfortunately, this does not follow directly from the formulae (57.16), since, due to their method of deduction, and as has also been indicated earlier, these formulae are incorrect near the singular points of the differential equation (54.9).

However, if they had been defined on the basis of the second approximation, it would be clear that the functions in the formulae (57.16) with the constants A_1' and A_1'' tend to infinity at $\theta=0$. Hence, if the point $\theta=0$ belongs to the middle surface, then, for the solution to remain finite at this point, it is necessary to assume that

$$A_1'=A_1''=0.\tag{57.17}$$

Thus, the number of arbitrary constants in the formulae (57.16) is halved and this is quite natural, since in the presence of only one edge the number of boundary conditions is likewise halved.

If the middle surface were to contain the point $\theta=\pi$ rather than $\theta=0$, then one would have to put instead $A_2'=A_2''=0$.

The solution given by (57.16) will now be further analyzed. For this purpose, along with $\beta=\beta_1$, introduce the new variable

$$\beta_2=\frac{1}{\sqrt{2}}\int_{\theta_1}^{\theta}\frac{R_1\,d\theta}{\sqrt{R_2c}}=\frac{1}{\sqrt{2}}\int_{\theta_0}^{\theta}\frac{R_1\,d\theta}{\sqrt{R_2c}}+\frac{1}{\sqrt{2}}\int_{\theta_1}^{\theta_0}\frac{R_1\,d\theta}{\sqrt{R_2c}}=\beta_1+\alpha_0,\tag{57.18}$$

where

$$\alpha_0=\frac{1}{\sqrt{2}}\int_{\theta_1}^{\theta_0}\frac{R_1\,d\theta}{\sqrt{R_2c}}\tag{57.19}$$

is a constant.

Replacing the parameter β by β_2, in the formulae (57.16) in those terms which are multiplied by the constants A_1', A_1'' one will have

$$
\begin{aligned}
w &\approx \frac{R_2}{E\delta}\left[(B_1\cos\beta_2 - B_2\sin\beta_2)\,e^{-\beta_2} + (C_1\cos\beta_1 + C_2\sin\beta_1)\,e^{\beta_1}\right],\\
\Delta_x &\approx \frac{R_2\sin\theta}{E\delta}\,T_2,
\end{aligned}
\tag{57.20}
$$

$$
\begin{aligned}
\vartheta &\approx \frac{1}{E\delta}\,\frac{1}{\sqrt{2}}\sqrt{\frac{R_2}{c}}\,\{[(B_1+B_2)\cos\beta_2+(B_1-B_2)\sin\beta_2]\,e^{-\beta_2} -\\
&\qquad - [(C_1 + C_2)\cos\beta_1 + (C_2 - C_1)\sin\beta_1]\,e^{\beta_1}\}.\\
T_1 &\approx -\frac{1}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\cot\theta\{[(B_1-B_2)\cos\beta_2-(B_1+B_2)\sin\beta_2]\,e^{-\beta_2}+\\
&\qquad + [(C_2 - C_1)\cos\beta_1 - (C_1 + C_2)\sin\beta_1]\,e^{\beta_1}\},
\end{aligned}
$$

$$
N_1 = T_1\tan\theta,\quad Q_x = \frac{1}{\sin\theta}\,N_1 = \frac{1}{\cos\theta}\,T_1,
\tag{57.21}
$$

$$
\begin{aligned}
T_2 &\approx (B_1\cos\beta_2 - B_2\sin\beta_2)\,e^{-\beta_2} + (C_1\cos\beta_1 + C_2\sin\beta_1)\,e^{\beta_1},\\
M_1 &\approx -c[(B_2\cos\beta_2 + B_1\sin\beta_2)\,e^{-\beta_2} + (C_2\cos\beta_1 - C_1\sin\beta_1)\,e^{\beta_1}],\\
M_2 &\approx \mu M_1.
\end{aligned}
$$

Here B_1, B_2, C_1, C_2 are new arbitrary constants which are related to the previous ones by the equalities

$$
\begin{aligned}
B_1 &= (A_1'\cos\alpha_0 + A_1''\sin\alpha_0)\,e^{\alpha_0},\\
B_2 &= (A_1''\cos\alpha_0 - A_1'\sin\alpha_0)\,e^{\alpha_0},\\
C_1 &= A_2',\\
C_2 &= A_2''.
\end{aligned}
\tag{57.22}
$$

It will be noted that the parameter

$$
\beta_1 = \frac{1}{\sqrt{2}}\int_{\theta_0}^{\theta}\frac{R_1\,d\theta}{\sqrt{R_2 c}}
\tag{57.23}
$$

vanishes at the edge $\theta = \theta_0$ and that away from this edge it becomes a negative quantity of order $\sqrt{\dfrac{R}{\delta}}$.

Hence it is clear that the functions appearing in the formulae (57.20),

(57.21) with the constants C_1, C_2 decrease rapidly as the point under consideration moves away from the edge $\theta = \theta_0$.

As regards the parameter

$$\beta_2 = \frac{1}{\sqrt{2}} \int_{\theta_1}^{0} \frac{R_1 d\theta}{\sqrt{R_{2c}}}, \tag{57.24}$$

it will vanish at the edge $\theta = \theta_1$ and become, at a short distance from this edge, a positive quantity of order $\sqrt{\frac{R}{\delta}}$. Hence it is clear that the functions occurring in the formulae (57.20), (57.21) with the constants B_1 and B_2 decrease rapidly as the point under consideration leaves the edge $\theta = \theta_1$.

Thus the conclusion is reached that the formulae (57.20), (57.21) or, what is the same thing, the formulae (57.16), because the first set were obtained from the second by replacing one set of integration constants by another, give a state of stress which is localized near the edge of the shell.

If the distance between the edges is sufficiently large, the symmetrical loading Q_x^0, $M_1^{(0)}$, applied to the edge $\theta = \theta_0$, does not, for any practical purpose, cause stresses and displacements near the other edge. The same may be said with regard to the loading Q_x^1, $M_1^{(1)}$ applied to the edge $\theta = \theta_1$.

Thanks to this situation, one may in many problems with edge conditions at two boundaries of a shell of revolution consider these independently from each other, i.e., when considering the boundary condition at the edge $\theta = \theta_0$, one may put $B_1 = B_2 = 0$, and for those at the edge $\theta = \theta_1$, one can put $C_1 = C_2 = 0$. This procedure greatly simplifies the calculations. In fact, only in those cases when the distance between the edges of the shell is small so that it has the form of a comparatively narrow belt is it necessary to consider the boundary conditions simultaneously.

The functions in the solutions (57.20) and (57.21) coincide with those functions in terms of which the bending problem of beams on elastic foundations may be solved. This coincidence is not accidental, because there exists an analogy between the problem under consideration and the problem of bending of a beam on an elastic foundation which enabled I. Shtaerman [143] to give an unusual and very clear study of the theory of symmetrically deformed shells of revolution. If one were to aim only at an acquaintance with this particular problem, it would be impossible to design a better approach to it than that given by the above author.

This problem has been studied in a different manner here only for the reason that interest in this book is directed towards general rather than particular methods which are to apply to the greatest possible range of problems of the theory of thin shells.

§ 58. Influence coefficients

Consider a shell of revolution bounded by a single parallel circle (a dome without an opening or a cap) and loaded along its edge by uniformly distributed forces $Q_x{}^0 = Q_0$ and moments $M_1{}^0 = M_0$.

Then it will depend on whether the external normal to the edge section of the shell is directed towards the side of increasing or decreasing θ, i.e., on whether one has the case shown in Fig. 78(a) or in 78(b); whether in the formulae (57.20), (57.21) one has to put $B_1 = B_2 = 0$, or $C_1 = = C_2 = 0$, as has been discussed above.

For this purpose, one obtains from these formulae the expressions

$$
\begin{aligned}
w &= \frac{R_2}{E\delta}(C_1 \cos\beta - C_2 \sin\beta)e^{-\beta},\\
\Delta_x &= w \sin\theta,\\
\vartheta &= \mp \frac{1}{\sqrt{2}} \sqrt{\frac{R_2}{c}} \frac{1}{E\delta}[(C_1 + C_2)\cos\beta + (C_1 - C_2)\sin\beta]e^{-\beta},\\
T_1 &= \mp \frac{1}{\sqrt{2}} \sqrt{\frac{c}{R_2}} \operatorname{cotan}\theta[(C_2 - C_1)\cos\beta + (C_1 + C_2)\sin\beta]e^{-\beta}, \qquad (58.1)\\
N_1 &= T_1 \tan\theta, \quad Q_x = \frac{N_1}{\sin\theta},\\
T_2 &= (C_1 \cos\beta - C_2 \sin\beta)e^{-\beta},\\
M_1 &= -c(C_2 \cos\beta + C_1 \sin\beta)e^{-\beta},
\end{aligned}
$$

in which the upper signs relate to the case shown in Fig. 78(a) and the lower ones to the case shown in Fig. 78(b).

In the formulae (58.1), the parameter β is given by

$$
\beta = -\beta_1 = -\frac{1}{\sqrt{2}} \int_{\theta_0}^{\theta} \frac{R_1 d\theta}{\sqrt{R_2 c}}, \qquad (58.2)
$$

if the external normal to the edge section of the shell is directed towards

the side of increasing θ, and by

$$\beta = \beta_2 = \frac{1}{\sqrt{2}} \int_{\theta_1}^{\theta} \frac{R_1 d\theta}{\sqrt{R_2 c}}, \tag{58.3}$$

if it points towards the side of decreasing θ.

It will be noted that if one takes as independent variable instead of the angle θ the arc length of the meridian of the shell s, measuring



Fig. 78.

it each time from the edge, then the two formulae (58.2) and (58.3) reduce to the single formula

$$\beta = \frac{1}{\sqrt{2}} \int_0^s \frac{ds}{\sqrt{R_2 c}} = \sqrt[4]{3(1-\mu^2)} \int_0^s \frac{ds}{\sqrt{R_2 \delta}}, \tag{58.4}$$

since in the first case $R_1 d\theta = -ds$ and in the second case $R_1 d\theta = ds$.

Certain authors [147] neglect in the expression (58.4) the variation of R_2 as a result of which it takes the form

$$\beta = \frac{1}{\sqrt{2}} \frac{s}{\sqrt{R_2^0 c}}, \tag{58.5}$$

where R_2^0 is the edge value of the radius R_2. Normally, employment of this simplification does not raise any objections, although it gives rise to more serious errors than the simplification introduced in the preceding section.

In order to obtain from the formulae (58.1) the general solution of the problem under consideration, one has to add to them the solution of the equations of the membrane theory which, as before, will be provided with an asterisk.

Let the edge of the shell be subjected to the uniformly distributed force Q_0 and moment M_0. Then, on the basis of the formulae (58.1) and (54.29), one may write

$$Q_0 = \mp \frac{1}{\sqrt{2}} \sqrt{\frac{c}{R_2}} \frac{1}{\sin\theta_0} (C_2 - C_1) + Q_0^*, \qquad (58.6)$$

$$M_0 = -cC_2 + M_0^* = -cC_2,$$

where Q_0^* and $M_0^* = 0$ are the edge values of the force Q_x and the moment M_1, as given by the membrane theory. Hence

$$C_2 = -\frac{M_0}{c}, \quad C_1 = \pm \sqrt{\frac{2R_2}{c}} \sin\theta_0 (Q_0 - Q_0^*) - \frac{1}{c} M_0. \qquad (58.7)$$

Introducing these values for the constants into the formulae (58.1) and adding there terms corresponding to the particular integral, one finds

$$w = \frac{R_2\sqrt{2}}{E\delta}\left[\pm \sqrt{\frac{R_2}{c}} (Q_0 - Q_0^*) \sin\theta_0 \cos\beta - \frac{M_0}{c} \cos\left(\beta + \frac{\pi}{4}\right)\right] e^{-\beta} + w^*,$$

$$\Delta = \frac{R_2\sqrt{2}}{E\delta} \sin\theta_0 \left[\pm \sqrt{\frac{R_2}{c}} (Q_0 - Q_0^*) \sin\theta_0 \cos\beta - \right.$$

$$\left. - \frac{\sqrt{2}}{c} M_0 \cos\left(\beta + \frac{\pi}{4}\right)\right] e^{-\beta} + \Delta^*,$$

$$\vartheta = -\sqrt{\frac{2R_2}{c}} \frac{1}{E\delta}\left[\sqrt{\frac{R_2}{c}} \sin\theta_0 (Q_0 - Q_0^*) \cos\left(\beta - \frac{\pi}{4}\right) \pm \right. \qquad (58.8)$$

$$\left. \pm \frac{1}{c} M_0 \cos\beta\right] e^{-\beta} + \vartheta^*,$$

$$T_2 = \left[\pm \sqrt{\frac{2R_2}{c}} \sin\theta_0 (Q_0 - Q_0^*) \cos\beta - \frac{M_0}{c} \cos\left(\beta + \frac{\pi}{4}\right)\right] e^{-\beta} + T_2^*,$$

$$M_1 = \left[M_0\sqrt{2} \cos\left(\beta - \frac{\pi}{4}\right) \mp \sqrt{2R_2 c} \sin\theta_0 (Q_0 - Q_0^*) \sin\beta\right] e^{-\beta}.$$

These last formulae determine quantities which characterize the stresses and strains in the shell in terms of the given boundary loading.

By the way, it follows from these formulae that

$$\Delta_0 = \alpha_{11} Q_0 + \alpha_{12} M_0 - \alpha_{11} Q_0^* + \Delta_0^*,$$
$$\vartheta_0 = \alpha_{21} Q_0 + \alpha_{22} M_0 - \alpha_{21} Q_0^* + \vartheta_0^*, \qquad (58.9)$$

where

$$\alpha_{11} = \pm \frac{2\sqrt[4]{3(1-\mu^2)}}{E}\left(\frac{R_2^0}{\delta}\right)^{3/2} \sin^2\theta_0,$$

$$\alpha_{12} = \alpha_{21} = -\frac{\sqrt{12(1-\mu^2)}}{E\delta^2} R_2^0 \sin\theta_0, \qquad (58.10)$$

$$\alpha_{22} = \pm \frac{4[3(1-\mu^2)]^{3/4}}{E\delta^2}\sqrt{\frac{R_2^0}{\delta}},$$

and again the upper sign, as in all the preceding formulae, refers to the case shown in Fig. 78(*a*) and the lower sign to the case shown in Fig. 78(*b*). For the application of the formulae (58.8), it is useful to have the auxiliary functions in Fig. 79.



Fig. 79.

The quantities α_{11}, $\alpha_{12} = \alpha_{21}$, α_{22} may be called influence coefficients for the edge of a symmetrically loaded shell of revolution, since they characterize completely the deformation of the edge under the influence of the force $Q_0 = 1$ and the moment $M_0 = 1$.

Employment of the formulae (58.9), (58.10) simplifies the statical indeterminateness of a roof section between the shell and its supporting contours.

It will be noted that in the problem under consideration the greatest stress is provided by the hoop force T_2 and the bending moment M_1. For these stresses, on the basis of formulae (58.8), one may write down the expressions

$$\sigma_2 = \frac{T_2}{\delta} = \left[\pm 2\sqrt[4]{3(1-\mu^2)}\sqrt{\frac{R_2}{\delta}}\,\frac{\sin\theta_0}{\delta}(Q_0 - Q_0^*)\cos\beta - \right. \qquad (58.11)$$

$$\left. - \sqrt{2}\sqrt{12(1-\mu^2)}\,\frac{M_0}{\delta^2}\cos\left(\beta + \frac{\pi}{4}\right)\right] e^{-\beta} + \sigma_2^*,$$

$$\sigma_M = \frac{6M_1}{\delta^2} = \left[\frac{6\sqrt{2}M_0}{\delta^2}\cos\left(\beta - \frac{\pi}{4}\right) \mp \right.$$
$$\left. \mp \frac{6}{\sqrt{3(1-\mu^2)}}\sqrt{\frac{R_2}{\delta}}\,\frac{\sin\theta_0}{\delta}\,(Q_0 - Q_0^*)\sin\beta\right]e^{-\beta}. \tag{58.11}$$

All the above formulae were obtained on the basis of the assumption that the shell of revolution has only one edge. However, these same formulae may also be used in the case when the shell has not one but two edges, provided the arc length s_0 between these edges is sufficiently large. The errors incurred in this process may be estimated by comparing the quantity

$$\exp\left(-\sqrt{3(1-\mu^2)}\,\frac{s_0}{\sqrt{R_2^0\delta}}\right)$$

with unity, since, in fact, this type of error is introduced by the process of separate determination of the constants in these formulae. Hence it follows that the application of the formulae of this section to shells with two edges is possible, if

$$\frac{s_0}{\sqrt{R_2\delta}} \geqslant 2,$$

when the error involved will not be greater than 10%.

§ 59. The analysis of cylindrical pressure vessels and their end-panels

The theory of the preceding section will now be applied to the analysis of the stresses in a cylindrical pressure-vessel with caps of arbitrary form and subject to uniform normal pressure. In order to simplify the calculations, it will be assumed that the end-panel has the same thickness as the cylindrical part of the vessel and that they are connected by a weld joint. Further, it will be assumed that the length of the vessel is sufficiently large, so that one may consider the stresses in the region of the cylinder near one end cap independently of those near the other end. Fig. 80 shows that part of the vessel which will be studied. It is seen from this drawing that



Fig. 80.

$$R_2^0 \sin\theta_0 = r.$$

where r is the radius of the cylinder and θ_0 is the angle corresponding to the edge of the end-panel.

On the basis of the formulae of the preceding section, one finds:

a) The influence coefficients of the edge of the cylindrical shell

$$\alpha_{11}' = -\frac{2\sqrt[4]{3(1-\mu^2)}}{E}\left(\frac{r}{\delta}\right)^{3/2},$$

$$\alpha_{12}' = \alpha_{21}' = -\frac{2\sqrt{3(1-\mu^2)}}{E\delta}\frac{r}{\delta}, \tag{59.1}$$

$$\alpha_{22}' = -\frac{4[3(1-\mu^2)]^{3/4}}{E\delta^2}\sqrt{\frac{r}{\delta}};$$

b) the influence coefficients of the edge of the end panel

$$\alpha_{11}'' = -\alpha_{11}'\sqrt{\sin\theta_0},$$

$$\alpha_{21}'' = \alpha_{12}'' = \alpha_{12}', \tag{59.2}$$

$$\alpha_{22}'' = -\frac{\alpha_{22}'}{\sqrt{\sin\theta_0}}.$$

When writing down the formulae (59.1) and (59.2), account has been taken of the fact that the external normals to the edge sections of the cylinder and the end-panel are directed towards the sides of decrease and increase of the curvilinear coordinate respectively.

For the cylinder, loaded by uniform normal pressure, the membrane theory gives (§ 25)

$$T_1^* = \tfrac{1}{2}pr,\quad T_2^* = pr,\quad Q_x^* = T_1^*\cos\theta = 0,$$

$$w^* = \varepsilon_2 r = \frac{r}{E\delta}(T_2^* - \mu T_1^*) = \left(1 - \frac{\mu}{2}\right)\frac{pr^2}{E\delta}, \tag{59.3}$$

$$\Delta_x^* = w^*\sin\theta + u^*\cos\theta = w^*,\quad \vartheta^* = -\frac{dw^*}{dx} = 0.$$

Correspondingly, for the end-panel, one finds

$$T_1^* = \frac{pR_2}{2},\quad T_2^* = \frac{pR_2}{2}\left(2 - \frac{R_2}{R_1}\right),\quad Q_x^* = \frac{pR_2}{2}\cos\theta,$$

$$\Delta_x^* = \varepsilon_2 R_2\sin\theta = \frac{R_2\sin\theta}{E\delta}(T_2^* - \mu T_1^*) = \tag{59.4}$$

$$= \frac{pR_2^2\sin\theta}{2E\delta}\left(2 - \mu - \frac{R_2}{R_1}\right),$$

$$\vartheta^* \approx 0.$$

Now, on the basis of the formulae (58.9), one may construct the following expressions for the displacement Δ_0 and the angle of rotation ϑ_0 at the edge of each of the two shells under consideration:

a) For the cylinder

$$\Delta_0' = \alpha_{11}' Q_0' + \alpha_{12}' M_0' + \left(1 - \frac{\mu}{2}\right) \frac{pr^2}{E\delta}, \qquad (59.5)$$

$$\vartheta_0{}^1 = \alpha_{21}' Q_0' + \alpha_{22}' M_0';$$

b) for the end-panel

$$\Delta_0'' = -\alpha_{11}' Q_0'' \sqrt{\sin\theta_0} + \alpha_{12}' M_0'' +$$

$$+ \alpha_{11}' \frac{pr}{2} \sqrt{\sin\theta_0} \operatorname{cotan}\theta_0 + \frac{1}{2} \frac{pr^2}{E\delta} \left[2 - \mu - \left(\frac{R_2}{R_1}\right)_0\right] \frac{1}{\sin\theta_0}, \qquad (59.6)$$

$$\vartheta_0'' = \alpha_{12}' Q_0'' - \alpha_{22}' \frac{M_0''}{\sqrt{\sin\theta_0}} - \alpha_{21}' \frac{pr}{2} \operatorname{cotan}\theta_0.$$

Since the edges of the shells are rigidly connected, they satisfy at the joint the equalities

$$\Delta_0' = \Delta_0'', \quad \vartheta_0' = \vartheta_0'', \quad Q_0' = Q_0'', \quad M_0' = M_0'', \qquad (59.7)$$

the form of which takes into consideration that the positive directions of the corresponding quantities are as shown in Fig. 81.

If the end cap were inverted with respect to the vessel (Fig. 82), then the conditions at the joint of the



Fig. 81.



Fig. 82.

shells would be different, namely:

$$\begin{aligned} \Delta_0' &= \Delta_0'', \quad \vartheta_0 &&= -\vartheta_0'', \\ Q_0' &= Q_0'', \quad M_0' &&= -M_0''. \end{aligned} \tag{59.8}$$

With the help of the equalities (59.7), the formulae (59.5) and (59.6) transform into two equations in the two unknowns

$$Q_0 = Q_0' = Q_0'' \text{ and } M_0 = M_0' = M_0'',$$

and one of these equations will lack terms depending on Q_0, the other terms depending on M_0, so that one obtains directly the formulae

$$Q_0 = \frac{pr}{2} \frac{\sqrt{\sin\theta_0}}{1+\sqrt{\sin\theta_0}} \left\{ \operatorname{cotan}\theta_0 - \frac{1}{2\sqrt[4]{3(1-\mu^2)}} \sqrt{\frac{\delta}{r}} \times \right.$$

$$\left. \times \frac{1}{\sin^{3/2}\theta_0} \left[2 - \mu - \frac{R_2^0}{R_1^0} - (2-\mu)\sin\theta_0 \right] \right\}, \tag{59.9}$$

$$M_0 = -\frac{1}{4} pr \frac{\sqrt{r\delta}}{\sqrt[4]{3(1-\mu^2)}} \frac{\sqrt{\sin\theta_0}}{1+\sqrt{\sin\theta_0}} \operatorname{cotan}\theta_0.$$

Thus, it follows that in the general case when $\theta_0 \neq \frac{\pi}{2}$ the edge force Q_0 is a quantity of order pr and the edge moment a quantity of order $pr\sqrt{r\delta}$.

However, in the particular case $\theta_0 = \frac{\pi}{2}$, the formulae (59.9) give

$$\begin{aligned} Q_0 &= \frac{p\sqrt{r\delta}}{8\sqrt[4]{3(1-\mu^2)}} \left(\frac{R_2}{R_1}\right)_0, \\ M_0 &= 0. \end{aligned} \tag{59.10}$$

Thus, when the meridian of the end-panel goes smoothly over into the generator of the cylinder, the moment M_0 vanishes and the force Q_0 decreases by a factor $\sqrt{\frac{r}{\delta}}$ in comparison with the general case, when the meridian of the end-panel joins the cylinder at some angle. Hence one may conclude that the stresses in the pressure vessel will in the first case be essentially smaller than in the second and that, therefore, it is rational to ensure a smooth junction of the end cap and the cylinder with $\theta_0 = \frac{\pi}{2}$. This deduction which has been obtained under the as-

sumption that the thickness of the end cap and the cylinder are the same, remains true also when the thicknesses are different.



Fig. 83.

In order to gain not only qualitative, but also quantitative impressions of this analysis, two examples will now be considered. In the first of these, the end-panel is to be half an ellipsoid of revolution with a ratio of the semi-axes $\frac{b}{a} = \frac{b}{r} = 0.5$, and in the, second, a spherical segment the height of which is equal to the smaller semi-axis of the ellipsoid of the first example (Fig. 83).

In this case, the trigonometric functions of the edge angle of the spherical shell will be

$$\sin \theta_0 = 0.8, \quad \cos \theta_0 = 0.6,$$

$$\operatorname{cotan} \theta_0 = 0.75,$$

and the radius of the sphere

$$R = 1.25r.$$

Correspondingly, one finds for the radii of curvature of the ellipsoidal end-panel with the given ratio of the semi-axes the expressions

$$R_1 = \frac{2r}{(1 + 3 \sin^2 \theta)^{3/2}}, \quad R_2 = \frac{2r}{(1 + 3 \sin^2 \theta)^{1/2}}, \tag{59.11}$$

and at the edge of the shell

$$\frac{R_2^0}{R_1^0} = 4.$$

Taking these details into consideration and using the formulae (59.10) and (59.11), one finds the following values for the edge loading:

for the first example (ellipsoidal end-panel)

$$Q_0 = 0.389 p \sqrt{r\delta},$$

$$M_0 = 0;$$

for the second example (spherical end-panel)

$$Q_0 = 0.177pr\left(1 + 0.48\sqrt{\frac{\delta}{r}}\right) \approx 0.177pr,$$

$$M_0 = -0.069pr\sqrt{r\delta}.$$

The edge loadings being known, it is not difficult to obtain, on the basis of formulae (58.8), expressions for all the displacements, forces and moments, the most important of which will now be given:

First example

a) Cylindrical shell:

$$w = \frac{pr^2}{E\delta}(1 - \tfrac{1}{2}\mu - e^{-b\xi}\cos b\xi),$$

$$T_2 = pr(1 - e^{-b\xi}\cos b\xi),$$

$$M_1 = \frac{pr\delta}{\sqrt{12(1-\mu^2)}}e^{-b\xi}\sin b\xi,$$

where $\xi = x/r$ (x being the distance from the edge of the cylinder) and

$$b = \sqrt[4]{3(1-\mu^2)}\sqrt{\frac{r}{\delta}}.$$

b) Ellipsoidal end-panel:

$$\Delta x = \frac{pr^2}{E\delta}e^{-\beta}\cos\beta + \Delta^*,$$

$$T_2 = pre^{-\beta}\cos\beta + \frac{pR_2}{2}\left(2 - \frac{R_2}{R_1}\right),$$

$$M_1 = -\frac{pr\delta}{\sqrt{12(1-\mu^2)}}e^{-\beta}\sin\beta,$$

where, in agreement with the formulae (58.2), (59.11),

$$\beta = \sqrt[4]{12(1-\mu^2)}\sqrt{\frac{r}{\delta}}\int_0^{\pi/2}\frac{d\theta}{(1+3\sin^2\theta)^{5/4}} = \sqrt{2}.b\int_0^{\pi/2}\frac{d\theta}{(1+3\sin^2\theta)^{5/4}}.$$

Second example

a) Cylindrical shell:

$$w = \frac{pr^2}{E\delta}\left\{0.85 - 0.322\sqrt{\frac{r}{\delta}}\,e^{-b\xi}\cos\left(b\xi - \frac{\pi}{4}\right)\right\},$$

$$T_2 = pr\left\{1 - 0.322\sqrt{\frac{r}{\delta}}\,e^{-b\xi}\cos\left(b\xi - \frac{\pi}{4}\right)\right\},$$

$$M_1 = -0.0975pr\sqrt{r\delta}\,e^{-b\xi}\cos\left(b\xi + \frac{\pi}{4}\right);$$

b) Spherical end-panel:

$$w = \frac{pr^2}{E\delta}\left\{0.547 - 0.402\sqrt{\frac{r}{\delta}}\,e^{-\beta}\cos\left(\beta - \frac{\pi}{4}\right)\right\},$$

$$T_2 = pr\left\{0.625 - 0.322\sqrt{\frac{r}{\delta}}\,e^{-\beta}\cos\left(\beta - \frac{\pi}{4}\right)\right\},$$

$$M_1 = -0.975pr\sqrt{r\delta}\,e^{-\beta}\cos\left(\beta + \frac{\pi}{4}\right),$$

where $\beta = \sqrt{1.25}b\alpha$ and α is the angle measured from the edge of the spherical shell.

Figs. 84 and 85 show the distributions of the normal deflection w, the hoop stress

$$\delta_2 = \frac{T_2}{\delta},$$

the bending stress

$$\sigma_M = \frac{6M_1}{\delta^2}$$

and of the sum of the meridional normal stress in the extreme fibre of the shell $\sigma = \sigma_M + \frac{T_1}{\delta}$ evaluated on the basis of the above derived results with $r/\delta = 100$.

It will be discovered from a study of these curves that in the first example (the ellipsoidal end-panel) the maximum resultant stress in the pressure vessel exceeds only by 10% the stress

$$\sigma^* = \frac{pr}{\delta}$$

(i.e., the largest stress in the structure in agreement with the membrane theory). Thus, although the pressure vessel with the ellipsoidal end-panels is not in a membrane state of stress, the stresses in it differ only insignificantly from those given by that theory.

In contrast, in the second example (pressure vessel with spherical head), the hoop, bending and resultant meridional stresses significantly exceed the membrane stress $\sigma = \frac{pr}{\delta}$ (being one and a half, four and fives times as large respectively). Hence the advantages which attach to the first mode of construction in comparison with the second, are completely clear and it becomes also quite obvious why end-panels of spherical form usually have to be reinforced in the regions where they are joined to the cylindrical parts of a pressure vessel. In such cases one may use reinforcements (for example, rounded angles) and in those cases where these are not sufficient, ribs may be attached by means of rivets or weld joints to the spherical and cylindrical shells in the neighbourhood of their edges. The theory of the analysis of these reinforcements may be found in the well-known book by P. F. Papkovich [107].



Fig. 84.



Fig. 85.

In conclusion, it will be noted that the above difference between end-panels which are joined smoothly to the cylinder and end-panels which are joined to the cylinder at an angle diminishes with increasing shell thickness. In particular, if in the above examples one were to take

$r/\delta = 25$ instead of $r/\delta = 100$, then the bending stresses in the spherical cap would not be four times, but only twice as large as the membrane stresses in the cylindrical shell.

§ 60. Symmetrical deformation of toroidal shells

The sequence of calculations studied in the last section for symmetrically deformed shells of revolution was based on the assumptions that the particular integral may be taken from the membrane theory and that the solution of the homogeneous problem may be determined in a first approximation by the given asymptotic method. This approach to the analysis applies to a majority of problems of the type which are encountered in practice. However, it is possible to indicate certain problems to which this method does not apply and which require use of specially adapted methods. As an example, the theory of symmetrical deformation of toroidal shells will be considered (since they have a wide range of applications in the manufacture of pressure vessels, turbines and other machinery).



Fig. 86.

For these shells (see Fig. 86)

$$R_1 = r_0, \quad R_2 = R_0 \frac{1 + \alpha \sin\theta}{\sin\theta}, \tag{60.1}$$

where

$$\alpha = r_0/R_0.$$

Substituting these values for the radii of curvature into the equation (54.6), one finds

$$\frac{1}{1 + \alpha \sin\theta} \frac{d}{d\theta}\left[\frac{(1 + \alpha \sin\theta)^2}{\sin\theta} \frac{d\tilde{T}}{d\theta}\right] + i2d^2\tilde{T} = 2id^2(T_1^* + T_2^*), \tag{60.2}$$

where

$$2d^2 = \sqrt{12(1 - \mu^2)} \frac{r_0^2}{R_0\delta}. \tag{60.3}$$

It will now be assumed that the torus is loaded by uniform normal pressure p. Then (cf. § 27)

$$T_1^* = \frac{pr_0}{2}\,\frac{2+\alpha\sin\theta}{1+\alpha\sin\theta} - \frac{\alpha A}{(1+\alpha\sin\theta)\sin\theta},$$
$$T_2^* = \frac{pr_0}{2} + \frac{A}{\sin^2\theta}, \tag{60.4}$$

where A is an integration constant which is determined from static considerations, since on one of the parallel circles of the toroidal shell the axial force Q_z is known (§ 54). Substituting (60.4) in (60.2), one obtains

$$\frac{1}{1+\alpha\sin\theta}\,\frac{d}{d\theta}\left[\frac{(1+\alpha\sin\theta)^2}{\sin\theta}\,\frac{d\tilde{T}}{d\theta}\right] + i2d^2\tilde{T} = i2d^2\left[\frac{pr_0}{2}\,\frac{3+2\alpha\sin\theta}{1+\alpha\sin\theta} + \right.$$
$$\left. + \frac{A}{(1+\alpha\sin\theta)\sin^2\theta}\right]. \tag{60.5}$$

Differentiating this equation with respect to θ and introducing the new variable

$$\tilde{Z} = \frac{(1+\alpha\sin\theta)^2}{\sin\theta}\,\frac{d\tilde{T}}{d\theta}, \tag{60.6}$$

one finds

$$(1+\alpha\sin\theta)^2\,\frac{d}{d\theta}\left[\frac{1}{(1+\alpha\sin\theta)}\,\frac{d\tilde{Z}}{d\theta}\right] + i2d^2\sin\theta\tilde{Z} =$$
$$= -i2d^2\cos\theta\left[\alpha\frac{pr_0}{2} + A\,\frac{2+3\alpha\sin\theta}{\sin^3\theta}\right]. \tag{60.7}$$

Compared with (60.5) this equation has the advantage that its coefficients are finite for all values of the variable θ. However, the right hand side of the equation becomes infinite for $\theta = 0$ and $\theta = \pm\pi$. In order to remove these singularities, introduce into (60.7) the new variable

$$\tilde{Z} = V - i2d^2A\,\operatorname{cotan}\theta, \tag{60.8}$$

after which one arrives at the following differential equation for the auxiliary function V:

$$(1+\alpha\sin\theta)\,\frac{d^2V}{d\theta^2} - \alpha\cos\theta\,\frac{dV}{d\theta} + i2d^2\sin\theta V = 2d^2\tilde{D}\cos\theta, \tag{60.9}$$

where

$$\tilde{D} = -\left(2d^2A + i\alpha\frac{pr_0}{2}\right). \tag{60.10}$$

The analysis of toroidal shells has thus been reduced to the solution of the differential equation (60.9), since after determination of the auxiliary function V one may find by use of the results of § 54 all the quantities characterizing the deformation of the shell. Omitting the intermediate elementary manipulations, the final results will be given here:

$$
\begin{aligned}
T_1 &= -\frac{\alpha\cos\theta}{(1+\alpha\sin\theta)}\,\frac{1}{2d^2}\,I_m(V)+\frac{pr_0}{2}\,\frac{2+\alpha\sin\theta}{1+\alpha\sin\theta}-\alpha A\,\frac{\alpha+\sin\theta}{(1+\alpha\sin\theta)^2},\\
T_2 &= -\frac{1}{2d^2}\,I_m\left[\frac{d}{d\theta}\left(\frac{1}{1+\alpha\sin\theta}\,V\right)\right]+\frac{pr_0}{2}+\alpha A\,\frac{\alpha+\sin\theta}{(1+\alpha\sin\theta)^2},\\
M_1 &= -\frac{c}{2d^2}\left\{\mu\,\frac{\alpha\cos\theta}{(1+\alpha\sin\theta)^2}\,R_e(V)+R_e\left[\frac{d}{d\theta}\left(\frac{1}{1+\alpha\sin\theta}\,V\right)\right]\right\}, \qquad (60.11)\\
N_1 &= -\frac{c}{r_0}\left\{\frac{\sin\theta}{(1+\alpha\sin\theta)^2}\,I_m(V)+\frac{2d^2A\cos\theta}{(1+\alpha\sin\theta)^2}\right\},\\
\vartheta &= -\frac{1}{E\delta}\,\frac{1}{\alpha(1+\alpha\sin\theta)}\,R_e(V);
\end{aligned}
$$

$$
\begin{aligned}
\Delta_x &= \frac{R_0}{E\delta}\,(1+\alpha\sin\theta)(T_2-\mu T_1),\\
\Delta_z &= -r_0\int_0^{\theta}\vartheta\cos\theta\,d\theta+C.
\end{aligned}
\qquad (60.12)
$$

A study of the equation (60.9) readily reveals that the ordinary methods of approximate solution of the equations for symmetrical deformations of shells of revolution do not apply. For example, an attempt to substitute as its particular integral a solution of the membrane theory leads to the formula

$$V_{\text{part.}} \approx -i\tilde{D}\,\operatorname{cotan}\theta, \qquad (60.13)$$

according to which the particular integral tends to infinity at the points $\theta = 0$, $\theta = \pm\pi$. Between these limits, a periodic particular integral of the equation (60.9) must obviously be finite, since (for all values of θ) the coefficients of the equation as well as its right hand side are finite.

Further, it is seen from the equation (60.9) that at the points $\theta = 0$, $\theta = \pm\pi$ the coefficient of the last term on the left hand side of the equation vanishes, whereas the method of asymptotic integration is based on the assumption that this coefficient greatly exceeds unity (§ 55).

It is clear from these observations that, in fact, the ordinary methods of approximate solutions do not apply to toroidal shells (at least not near the points $\theta = 0$ and $\theta = \pm\pi$), so that the integration of the equation (60.9) necessitates a special study which will be presented next.

I. *The homogeneous problem*

Consider the homogeneous equation

$$(1 + \alpha \sin\theta)^2 \frac{d}{d\theta}\left[\frac{1}{1 + \alpha \sin\theta}\frac{dV}{d\theta}\right] + i2d^2 \sin\theta V = 0 \qquad (60.14)$$

and let it be required to determine in a sufficiently convenient manner its integrals in the range $0 \leqslant \theta \leqslant \pi/2$. The equation (60.14) may be written in the form

$$\frac{d^2V}{d\chi^2} + F^2V = 0, \qquad (60.15)$$

where

$$d\chi = (1 + \alpha \sin\theta)\,d\theta, \quad F^2 = 2id^2\frac{\sin\theta}{(1 + \alpha \sin\theta)^3}. \qquad (60.16)$$

Next apply to (60.15) the transformation studied in § 55, i.e., introduce the new dependent variable

$$W = V\sqrt{F} \qquad (60.17)$$

and the new independent variable

$$dx = F\,d\chi = F(1 + \alpha \sin\theta)\,d\theta = \sqrt{2i}\,d\frac{\sqrt{\sin\theta}}{\sqrt{1 + \alpha \sin\theta}}\,d\theta. \qquad (60.18)$$

Then (60.15) takes the form

$$\frac{d^2W}{dx^2} + (1 + \Delta)W = 0, \qquad (60.19)$$

where in the given particular case

$$\Delta = -\frac{1}{2F}\frac{d^2F}{dx^2} + \frac{1}{4F^2}\left(\frac{dF}{dx}\right)^2 = -\frac{1}{2id^2}\left[-\frac{5}{16\sin^3\theta} + \frac{1 + 7\alpha \sin\theta}{16\sin\theta} + \right.$$
$$\left. + \frac{\alpha}{16\sin^2\theta} - \frac{4\alpha\cos^2\theta}{16\sin^2\theta(1 + \alpha \sin\theta)} + \frac{11}{16}\frac{\alpha^2\cos^2\theta}{\sin\theta(1 + \alpha \sin\theta)}\right]. \qquad (60.20)$$

It is seen from the formula (60.20) that $\Delta \to \infty$ as $\theta \to 0$ and therefore

it is impossible to neglect in the equation (60.19) the quantity Δ, as this was done in § 55. However, it may now be concluded that the expression (60.20) may be replaced $\left(\text{in the interval } 0 \leqslant \theta \leqslant \frac{\pi}{2}\right)$ by the simplified expression

$$\Delta \approx \frac{1}{2id^2} \frac{5}{16} \frac{1}{\theta^3}. \tag{60.21}$$

At a first glance, such a simplification seems to be unjustified, since, if the formula (60.21) gives in fact a good approximation to Δ near $\theta = 0$, then it will not even give a rough approximation to Δ near the other end of the interval $\left(\theta = \frac{\pi}{2}\right)$. However, taking into consideration that $\frac{3}{5}d^2 \gg 1$, it becomes clear that only for $\theta \ll 1$ will the quantity Δ be large or have an absolute value comparable with unity $\left(\text{near } \theta = \frac{\pi}{2}, \right.$ however, the quantity $|\Delta|$ will be much smaller than unity$\left.\right)$. Hence it follows that in determining Δ in the equation (60.19) from the formula (60.21), one does not incur a substantial error, since in that region where the value of Δ is large the formula (60.21) is a good approximation, while in the region where this formula deviates greatly, the quantity Δ is generally negligible.

Next the quantity Δ must be expressed in terms of x. On the basis of (60.18), one has for x

$$x = \sqrt{2i}\xi = \sqrt{2i}d \int_0^\theta \frac{\sqrt{\sin\theta}}{\sqrt{1 + \alpha \sin\theta}} d\theta \tag{60.22}$$

or

$$\xi = d \int_0^\theta \frac{\sqrt{\sin\theta}}{\sqrt{1 + \alpha \sin\theta}} d\theta = \frac{2}{3} d\theta^{3/2} \left\{ 1 - \frac{1}{28}\theta^2 + \frac{1}{5280}\theta^4 - \dots \right.$$
$$- \frac{3}{10}\alpha\theta \left[1 - \frac{5}{36}\theta^2 + \frac{11}{1170}\theta^4 - \dots \right] + \tag{60.23}$$
$$\left. + \frac{9}{56}\alpha^2\theta^2 \left[1 - \frac{35}{132}\theta^2 + \frac{91}{2700}\theta^4 - \dots \right] + \dots \right\}.$$

The formulae (60.22) and (60.23) may be used for the practical evalua-

tion of the variable x. It follows from them that for $\theta \to 0$

$$x \approx \sqrt{2i}\,\tfrac{2}{3}d\theta^{3/2}. \tag{60.24}$$

But, as has been stated above, the evaluation of Δ introduces substantial errors into the equation (60.19) only for small θ, i.e., in the region where it is admissible to employ the formula (60.24). Taking this into consideration and substituting (60.24) into (60.21) and (60.21) into (60.19), one finds

$$\frac{d^2W}{dx^2} + \left(1 + \frac{5}{36}\,\frac{1}{x^2}\right) W = 0. \tag{60.25}$$

This last equation belongs to the group of equations which can be integrated by use of Bessel functions. In fact, its general solution may be written in the form

$$W = \tilde{C}_1 h_{1/3}^{(1)}(x) + \tilde{C}_2 h_{1/3}^{(2)}(x), \tag{60.26}$$

where $\tilde{C}_1$, $\tilde{C}_2$ are two complex integration constants and

$$\begin{aligned} h_{1/3}^{(1)}(x) &= i^{5/6}\sqrt{0.5\pi x}\,H_{1/3}^{(1)}(x), \\ h_{1/3}^{(2)}(x) &= i^{-5/6}\sqrt{0.5\pi x}\,H_{1/3}^{(2)}(x), \end{aligned} \tag{60.27}$$

$H_{1/3}^{(1)}(x)$ and $H_{1/3}^{(2)}(x)$ being Hankel-functions of the first and second kinds (of order $\frac{1}{3}$). The constants in the formulae (60.27) have been chosen to suit the convenience of the following manipulations. The reduction of the problem to Bessel functions has in this case a definite advantage, since it permits the use of the well-known series expansions of these functions (for small arguments as well as asymptotic expansions). The employment of Hankel functions here is likewise not accidental, since then one of the two solutions in (60.26) has an absolute value which decreases exponentially, while that of the other increases exponentially as ξ increases. In this way it becomes possible (for different problems of the analysis of tori) to satisfy various boundary conditions (§ 57).

Changing from W to V by use of (60.16), (60.17), one finds

$$V = \left(\frac{\eta}{\sin\theta}\right)^{1/4}(1 + \alpha \sin\theta)^{3/4}[\tilde{C}_1 V_1(\sqrt{2i}\xi) + \tilde{C}_2 V_2(\sqrt{2i}\xi)], \tag{60.28}$$

where the following notation has been introduced:

$$\begin{aligned} V_1(\sqrt{2i}\xi) &= i^{5/6}\sqrt{\frac{\pi}{2}}\,(\sqrt{2i}\xi)^{1/3}H_{1/3}^{(1)(1)}(\sqrt{2i}\xi), \\ V_2(\sqrt{2i}\xi) &= i^{-5/6}\sqrt{\frac{\pi}{2}}\,(\sqrt{2i}\xi)^{1/3}H_{1/3}^{(2)(2)}(\sqrt{2i}\xi), \end{aligned} \tag{60.29}$$

$$\eta^{3/2} = \frac{3}{2d}\xi = \theta^{3/2}\left\{1 - \frac{1}{28}\theta^2 + \ldots\right\}. \tag{60.30}$$

As is seen from (60.30) and (60.23), the ratio $\left(\frac{\eta}{\sin\theta}\right)^{1/4}$ varies little from unity in the interval $-\frac{\pi}{2} \leqslant \theta \leqslant \frac{\pi}{2}$, the variation being not more than a few percent. On this basis, in what follows, will the function V be determined by use of the formula

$$V = (1 + \alpha \sin\theta)^{3/4}[\tilde{C}_1 V_1 + \tilde{C}_2 V_2]. \tag{60.31}$$

For the functions V_1 and V_2, one may give the series

$$\begin{aligned} V_1(\sqrt{2i}\xi) &= i\sqrt{\frac{\pi}{2}}\{1.293e^{\frac{\pi}{4}i}\xi^{2/3}[f_1(\xi) - if_2(\xi)] - \\ &\qquad - 1.079e^{\frac{5\pi}{12}i}[g_1(\xi) - ig_2(\xi)]\}, \\ V_2(\sqrt{2i}\xi) &= -i\sqrt{\frac{\pi}{2}}\{1.293e^{\frac{\pi}{12}i}\xi^{2/3}[f_1(\xi) - if_2(\xi)] - \\ &\qquad - 1.079e^{-\frac{5\pi}{12}i}[g_1(\xi) - ig_2(\xi)]\}, \end{aligned} \tag{60.32}$$

in which

$$\begin{aligned} f_1(\xi) - if_2(\xi) &= (\tfrac{1}{3})!\sum_{k=0}^{\infty}\frac{1}{k!}\frac{1}{(k+\frac{1}{3})!}(-\tfrac{1}{2}i\xi^2)^k = \\ &= 1 - \frac{i\xi^2}{1!2(1+\frac{1}{3})} - \frac{\xi^4}{2!2^2(1+\frac{1}{3})(2+\frac{1}{3})} + \\ &\quad + \frac{i\xi^6}{3!2^3(1+\frac{1}{3})(2+\frac{1}{3})(3+\frac{1}{3})} - \ldots, \\ g_1(\xi) - ig_2(\xi) &= (-\tfrac{1}{3})!\sum_{k=0}^{\infty}\frac{1}{k!}\frac{1}{(k-\frac{1}{3})!}(-\tfrac{1}{2}i\xi^2)^k = \\ &= 1 - \frac{i\xi^2}{1!2(1-\frac{1}{3})} - \frac{\xi^4}{2!2^2(1-\frac{1}{3})(2-\frac{1}{3})} + \\ &\quad + \frac{i\xi^6}{3!2^3(1-\frac{1}{3})(2-\frac{1}{3})(3-\frac{1}{3})} + \ldots. \end{aligned} \tag{60.33}$$

The series (60.33) converge quickly only for relatively small values of ξ ($\xi \ll 1$), while for sufficiently large ξ they are inconvenient. Therefore, for the evaluation of V_1 and V_2 in the region of large ξ ($\xi > 1$),

one has to use the asymptotic expansions for the Bessel functions which (retaining in them only the first terms) lead to the following formulae:

$$V_1(\sqrt{2i}\xi) = \frac{1}{2^{1/12}\xi^{1/6}} e^{-\xi}\left[\cos\left(\xi - \frac{\pi}{24}\right) + i\sin\left(\xi - \frac{\pi}{24}\right)\right],$$
$$V_2(\sqrt{2i}\xi) = \frac{1}{2^{1/12}\xi^{1/6}} e^{\xi}\left[\cos\left(\xi + \frac{\pi}{24}\right) - i\sin\left(\xi + \frac{\pi}{24}\right)\right]. \tag{60.34}$$

Next, the obtained solutions will be extended into the region of negative θ $\left(-\frac{\pi}{2} \leqslant \theta < 0\right)$. For this purpose attention will first be directed to the fact that the equation (60.14) on replacing θ by $-\psi$ takes the form

$$(1 - \alpha\sin\psi)^2 \frac{d}{d\psi}\left[\frac{1}{1 - \alpha\sin\psi}\frac{dV}{d\psi}\right] - i2d^2\sin\psi V = 0. \tag{60.35}$$

Comparing (60.35) with (60.14), it follows immediately that the integrals of the first equation may be taken to be conjugate complex with respect to the integrals of the second equation, provided the independent variable ξ is replaced by

$$\zeta = d\int_0^{\psi} \frac{\sqrt{\sin\psi}}{\sqrt{1 - \alpha\sin\psi}}\, d\psi. \tag{60.36}$$

(The last result is clear from the fact that the equations (60.35)' and (60.14) differ in the signs with the imaginary terms and likewise in the signs with α).

Thus the integrals of the equation (60.14) in the region $-\frac{\pi}{2} \leqslant \theta \leqslant 0$ may be determined from the expressions

$$\overline{V}_1(\sqrt{2i}\zeta) = -i\sqrt{\frac{\pi}{2}}\{1.293^{-\frac{\pi}{4}i}\zeta^{2/3}[f_1(\zeta) + if_2(\zeta)] -$$
$$- 1.079e^{-\frac{5\pi}{12}i}[g_1(\zeta) + ig_2(\zeta)]\}, \tag{60.37}$$
$$\overline{V}_2(\sqrt{2i}\zeta) = i\sqrt{\frac{\pi}{2}}\{1.293e^{-\frac{\pi}{12}i}\zeta^{2/3}[f_1(\zeta) + if_2(\zeta)] -$$
$$- 1.079e^{\frac{5\pi}{12}i}[g_1(\zeta) + ig_2(\zeta)]\},$$

with the asymptotic expansions

$$\bar{V}_1 = \frac{1}{2^{1/12}\zeta^{1/6}} e^{-\zeta}\left[\cos\left(\zeta - \frac{\pi}{24}\right) - i\sin\left(\zeta - \frac{\pi}{24}\right)\right],$$
$$\bar{V}_2 = \frac{1}{2^{1/12}\zeta^{1/6}} e^{\zeta}\left[\cos\left(\zeta + \frac{\pi}{24}\right) + i\sin\left(\zeta + \frac{\pi}{24}\right)\right]. \tag{60.38}$$

However, it is essential to note that the integrals $\bar{V}_1(\sqrt{2i}\zeta)$, $\bar{V}_2(\sqrt{2i}\zeta)$ are not the analytic continuations of the integrals $V_1(\sqrt{2i}\xi)$, $V_2(\sqrt{2i}\xi)$ in the region of negative θ. These are given by other functions, namely:

$$V_1' = -i\sqrt{\frac{\pi}{2}}\{1.293e^{+\frac{\pi}{4}i}\zeta^{2/3}[f_1(\zeta) + if_2(\zeta)] + \\ + 1.079e^{\frac{5}{12}\pi i}[g_1(\zeta) + ig_2(\zeta)]\}, \tag{60.39}$$

$$V_2' = i\sqrt{\frac{\pi}{2}}\{1.293^{\frac{\pi}{12}i}\zeta^{2/3}[f_1(\zeta) + if_2(\zeta)] + 1.079e^{-\frac{5}{12}\pi i}[g_1(\zeta) + ig_2(\zeta)]\},$$

which are linear combinations of $\bar{V}_1$ and $\bar{V}_2$, as a consequence of which one may write down an expression for the auxiliary function V in the entire region $-\frac{\pi}{2} \leqslant \theta \leqslant \frac{\pi}{2}$ in the form

$$V = (1 + \alpha\sin\theta)^{3/4}[\tilde{C}_1 V_1(\theta) + \tilde{C}_2 V_2(\theta)], \tag{60.40}$$

where instead of V_1 and V_2 one has to substitute

$$V_1(\sqrt{2i}\xi),\quad V_2(\sqrt{2i}\xi) \text{ in the region } \theta > 0,$$
$$V_1'(\sqrt{2i}\zeta),\quad V_2'(\sqrt{2i}\zeta) \text{ in the region } \theta < 0.$$

The functions V_1 and V_2 which have been defined in this manner will be continuous (together with all their derivatives) at the point $\theta = 0$.

II. *The particular integral*

Since the right hand side of the equation (60.9) is a periodic function of θ (with period 2π), the particular integral of this equation may be sought in the form of the trigonometric series

$$\mathfrak{B} = a_0 + a_1\cos\theta + a_2\cos 2\theta + \ldots + a_n\cos n\theta + \ldots \\ + b_1\sin\theta + b_2\sin 2\theta + \ldots + b_n\sin n\theta + \ldots, \tag{60.41}$$

Substituting this series into (60.9), one obtains the following set of

recurrence relations between the coefficients:

$$\begin{aligned} &-n^2a_n+\tfrac{1}{2}[2id^2-\alpha(n+1)(n+2)]b_{n+1}- \\ &\qquad -\tfrac{1}{2}[2id^2-\alpha(n-1)(n-2)]b_{n-1}=\beta_n, \\ &-n^2b_n+\tfrac{1}{2}[2id^2-\alpha(n-1)(n-2)]a_{n-1}- \\ &\qquad -\tfrac{1}{2}[2id^2-\alpha(n+1)(n+2)]a_{n+2}=0, \end{aligned} \tag{60.42}$$

where

$$\beta_n = 2d^2\tilde{D} \text{ for } n=1,$$
$$\beta_n = 0 \qquad \text{for } n>1 \text{ and } n=0.$$

These relations may be written in the following expanded form:

$$\begin{aligned} &-a_1+\tfrac{1}{2}(2id^2-2.3\alpha)b_2=2d^2\tilde{D}, \\ &-b_1+id^2a_0-\tfrac{1}{2}(i2d^2-2.3\alpha)a_2=0, \\ &-4a_2+\tfrac{1}{2}(i2d^2-3.4\alpha)b_3-\tfrac{1}{2}i2d^2b_1=0, \\ &-4b_2+\tfrac{1}{2}i2d^2a_1-\tfrac{1}{2}(i2d^2-3.4\alpha)a_3=0, \\ &-9a_3+\tfrac{1}{2}(i2d^2-4.5\alpha)b_4-\tfrac{1}{2}(i2d^2-2.1.\alpha)b_2=0, \\ &-9b_3+\tfrac{1}{2}(i2d^2-2.1\alpha)a_2-\tfrac{1}{2}(i2d^2-4.5\alpha)a_4=0, \\ &\cdots\cdots\cdots\cdots\cdots\cdots\cdots\cdots \\ &\cdots\cdots\cdots\cdots\cdots\cdots\cdots\cdots \end{aligned} \tag{60.43}$$

A study of (60.43) shows that one is essentially dealing with two independent infinite algebraic systems one of which involves the a_i with odd and the b_i with even indices while the other contains the remaining a_i, b_i. In addition, the second system will be homogeneous, and therefore (since only a particular integral is required) all the unknowns in it may be taken equal to zero:

$$a_{2n}=b_{2n+1}=0, \quad n=0,1,2,\ldots$$

The first system, however, may be reduced to the form

$$\begin{aligned} &1^2\frac{ia_1}{d^2}+\left[1+i\frac{2.3}{2d^2}\alpha\right]b_2=-2i\tilde{D}, \\ &2^2\frac{ib_2}{d^2}+a_1-\left(1+i\frac{3.4}{2d^2}\alpha\right)a_3=0, \\ &3^2\frac{ia_3}{d^2}+\left(1+i\frac{4.5}{2d^2}\alpha\right)b_4-\left(1+i\frac{1.2}{2d^2}\alpha\right)b_2=0, \end{aligned} \tag{60.44}$$

$$
\begin{aligned}
&4^2 i\,\frac{b_4}{d^2}+\left(1+i\,\frac{3.2}{2d^2}\,\alpha\right)a_3-\left(1+i\,\frac{5.4}{2d^2}\,\alpha\right)a_5=0,\\
&5^2 i\,\frac{a_5}{d^2}+\left(1+i\,\frac{6.7}{2d^2}\,\alpha\right)b_6-\left(1+i\,\frac{4.3}{2d^2}\,\alpha\right)b_4=0,\\
&\qquad\qquad\qquad

$$-\frac{b_{n+1}}{a_n}i=\cfrac{1+i\dfrac{n(n-1)}{2d^2}\alpha}{\dfrac{(n+1)^2}{d^2}+\cfrac{\left[1+i\dfrac{(n+1)n}{2d^2}\alpha\right]\left[1+i\dfrac{(n+2)(n+3)}{2d^2}\alpha\right]}{\dfrac{(n+2)^2}{d^2}+\cfrac{\left[1+i\dfrac{(n+2)(n+1)}{2d^2}\alpha\right]\left[1+i\dfrac{(n+3)(n+4)}{2d^2}\alpha\right]}{\dfrac{(n+3)^2}{d^2}+\ldots}}},$$

$$n=1,3,5\ldots$$

The expression (60.45) is included in the first of the formulae (60.46) and is obtained from it for $n=1$ and $b_0=-i2\tilde{D}$.

It follows from the above that a periodic particular integral of the equation (60.9) is determined by the series

$$\mathfrak{B}=a_1\cos\theta+b_2\sin 2\theta+a_3\cos 3\theta+b_4\sin 4\theta+\ldots, \quad (60.47)$$

the coefficients of which can be evaluated from the formulae (60.45) (60.46). It may be shown that this periodic solution corresponds to the



Fig. 87.

problem shown in Fig. 87, i.e., to the case of the complete toroidal shell, loaded by uniform normal pressure, cut along its parallel $\theta=\frac{\pi}{2}$ $\left(\text{or } \theta=-\frac{\pi}{2}\right)$ and subjected along this edge to forces $Q_z{}^0$. In addition, it is assumed that on the edges of the shell $\left(\text{i.e., for } \theta=\frac{\pi}{2},\ \theta=-\frac{3}{2}\pi\right)$ the angle of rotation and shearing forces vanish. Actually, substituting (60.47) in the expression (60.11), it may be verified that the above

particular integral satisfies all the formulated boundary conditions.

It must be emphasized that, while the solution under consideration is periodic for the forces, the moments and the angle of rotation, it will not be periodic for the displacements. Namely, the displacement Δ_z will not be single-valued for $\theta = \frac{\pi}{2}$ and $\theta = -3\frac{\pi}{2}$ which is already clear from Fig. 87 and which may be confirmed by computations, after substituting (60.47) into the third of the formulae (60.12).

§ 61. Analysis of stress in arched end-panels

Consider an end-panel formed by joining smoothly a spherical shell to part of a torus bounded by two parallel circles.

Depending on the value of the angle θ_0, this end-panel may be convex ($\theta_0 > 0$) or convex-concave ($\theta_0 < 0$). In the second case, the radius of curvature of the meridian of the cap changes its sign along the joint between the sphere and the torus (Fig. 88).

The stresses in the arched end-panel, which will be considered joined to the cylindrical part of a pressure vessel (by means of a weld), will be analyzed for the case of uniform normal pressure. The cylindrical, toroidal and spherical shells will be assumed to have the same thickness. This permits one to fit the solution to the boundary conditions (in this case the conditions at the joints between the shells) without separating the complex auxiliary functions into their real and imaginary parts.

In the present problem the conditions at these joints reduce to the requirement that at a common edge of two shells the quantities Δ_x, ϑ, Q_x, M_1, evaluated for the one shell must be equal (with appropriate sign) to the corresponding quantities, evaluated for the other shell.

The above four equalities indicated may be replaced by the two

$$|\tilde{T}|_{\mathrm{I}} = |\tilde{T}|_{\mathrm{II}}, \qquad \left|\frac{d\tilde{T}}{ds}\right|_{\mathrm{I}} = \left|\frac{d\tilde{T}}{ds}\right|_{\mathrm{II}}, \tag{61.1}$$

where $ds = R_1 d\theta$ is the differential arc length of the meridian of the shell.

Indeed, on the basis of the formulae (51.5) and (54.18), one finds

$$\begin{aligned} \tilde{T} &= T_2 - \mu T_1 + (1+\mu)T_1 - i\frac{M_1 + M_2}{1(+\mu)c}, \\ \frac{d\tilde{T}}{ds} &= -\frac{E\delta}{R_2}\tilde{\vartheta} = -\frac{E\delta}{R_2}\vartheta - i\frac{N_1}{c}. \end{aligned} \tag{61.2}$$

But in the problem under consideration

1) $M_2 \approx \mu M_1$ (since $\kappa_2 \ll \kappa_1$);

2) from the equality $|N_1|_{\mathrm{I}} = |N_1|_{\mathrm{II}}$ follows inevitably $|T_1|_{\mathrm{I}} = |T_1|_{\mathrm{II}}$ (since statics require that $|Q_z|_{\mathrm{I}} = |Q_z|_{\mathrm{II}}$);

3) $T_2 - \mu T_1 = \dfrac{E\delta}{R_2 \sin\theta} \Delta_x$.

Taking all these results into consideration, one arrives at the conclusion that the equalities (61.1) are equivalent to the equalities

$$|\Delta_x|_{\mathrm{I}} = |\Delta_x|_{\mathrm{II}}, \quad |\vartheta|_{\mathrm{I}} = |\vartheta|_{\mathrm{II}}, \quad |Q_x|_{\mathrm{I}} = |Q_x|_{\mathrm{II}}, \quad |M_1|_{\mathrm{I}} = |M_1|_{\mathrm{II}}, \tag{61.3}$$

i.e., equivalent to conditions of compatibility. Thus the conditions holding at the junction of two shells may actually be fulfilled in complex form, using the equalities (61.1).

It will be noted that the above argument applies only to the case when the tangent to the meridian of the compound shell is continuous (since otherwise R_2 will undergo a discontinuous change at the joint). In addition, the proof assumes that the component shells have the same



Fig. 88.

thickness (which otherwise would undergo a discontinuity c at the joint). By the way, the first of these limitations may be removed by a certain modification of the boundary conditions (61.1); however, this point will not be discussed further here and it will be left to the reader as an exercise.

Example

The end-panel shown in Fig. 88 will now be analyzed.

1) Given data:

$$r_0 = 0.25r, \quad R = 1.026r, \quad \delta/r = 1/25, \quad \theta_0 = -36°.$$

The thicknesses of the cylindrical, toroidal and spherical shells are the same. The loading is the uniform normal pressure p.

2) General solution for the cylinder:

The length of the cylinder will be assumed to be sufficiently large so that the interaction between the states of stress near the two edges of the cylinder may be neglected.

Then

$$\tilde{T}_c = \tilde{A} e^{-b(1-i)\xi} + T_c^*, \tag{61.4}$$

where $\tilde{A}$ is a constant of integration,

$$\begin{aligned} b &= \sqrt[4]{3(1-\mu^2)}\sqrt{\frac{r}{\delta}} = 6.415, \\ T_c^* &= T_1^* + T_2^* = 0.5pr + pr = 1.5pr, \\ \frac{d\tilde{T}_c}{ds} &= \frac{1}{r}\frac{d\tilde{T}_c}{d\xi} = -\tilde{A}\frac{b}{r}(1-i)e^{-b(1-i)\xi}. \end{aligned} \tag{61.5}$$

At the joint of the cylinder and the torus

$$\begin{aligned} \tilde{T}_c &= \tilde{A} + 1.5pr, \\ \frac{d\tilde{T}_c}{ds} &= -\tilde{A}\frac{b}{r}(1-i). \end{aligned} \tag{61.6}$$

3) General solution for the spherical segment:

$$T_s = \tilde{B} e^{a(1+i)(\theta_0-\theta)} + T_s^*, \tag{61.7}$$

where

$$\begin{aligned} a &= \sqrt[4]{3(1-\mu^2)}\sqrt{\frac{R}{\delta}} = b\sqrt{1.026} = 6.50, \\ T_s^* &= T_1^* + T_2^* = -0.5pR - 0.5pR = -1.026pr, \\ \frac{d\tilde{T}_s}{ds} &= -\frac{1}{R}\frac{d\tilde{T}_s}{d\theta} = \frac{a(1+i)}{1.026r}\tilde{B}e^{a(1+i)(\theta_0-\theta)}. \end{aligned} \tag{61.8}$$

At the joint of the torus and the sphere

$$\begin{aligned} \tilde{T}_s &= \tilde{B} - 1.026pr, \\ \frac{d\tilde{T}_s}{ds} &= \frac{6.33}{r}(1+i)\tilde{B}. \end{aligned} \tag{61.9}$$

Note: The minus sign in the formula (61.8) is accounted for by the fact that the radius of the sphere must be assumed negative.

4) General solution for the toroidal segment:

$$r_0 = \tfrac{1}{4}r,\ \alpha = r_0/R_0 = \tfrac{1}{3},\ R_0 = r - r_0 = \tfrac{3}{4}r,$$

$$2d^2 = \sqrt{12(1-\mu^2)}\frac{r_0^2}{R_0\delta} = \sqrt{12(1-0.09)}\frac{25}{4.3} = 6.88.$$

The constant A is determined from the condition

$$Q_z = \left[\frac{pr_0}{2}\frac{2+\alpha\sin\theta}{1+\alpha\sin\theta} - \frac{\alpha A}{(1+\alpha\sin\theta)\sin\theta}\right]\sin\theta = \frac{1}{2}pr \text{ for } \theta = \frac{\pi}{2}. \quad (61.10)$$

Hence

$$A = -1.125pr.$$

On the basis of the formulae (60.6), (60.8) and (60.2), one has

$$\begin{gathered}\tilde{T} = \frac{i}{2d^2}\frac{1}{1+\alpha\sin\theta}\frac{dV}{d\theta} + \frac{3+2\alpha\sin\theta}{1+\alpha\sin\theta}\frac{pr_0}{2},\\ \frac{1}{r_0}\frac{d\tilde{T}}{d\theta} = \frac{d\tilde{T}}{ds} = \frac{1}{r_0}\left[\frac{\sin\theta}{(1+\alpha\sin\theta)^2}V - i\frac{2d^2\cos\theta}{(1+\alpha\sin\theta)^2}A\right],\end{gathered} \quad (61.11)$$

and by (60.31)

$$\begin{gathered}V = (1+\alpha\sin\theta)^{3/4}[\tilde{C}_1V_1 + \tilde{C}_2V_2] + \mathfrak{V},\\ \frac{dV}{d\theta} = (1+\alpha\sin\theta)^{3/4}\left[\tilde{C}_1\frac{dV_1}{d\theta} + \tilde{C}_2\frac{dV_2}{d\theta}\right] -\\ -\frac{\frac{3}{4}\alpha\cos\theta}{(1+\alpha\sin\theta)^{1/4}}(\tilde{C}_1V_1 + \tilde{C}_2V_2) + \frac{d\mathfrak{V}}{d\theta}.\end{gathered} \quad (61.12)$$

a) A particular integral will be

$$\mathfrak{V} = a_1\cos\theta + b_2\sin 2\theta + a_3\cos 3\theta + b_4\sin 4\theta + \ldots \quad (61.13)$$

The coefficients a_j, b_j may be determined by means of the appropriate continued fractions, retaining in each of them up to five steps. As a result one finds

$$\begin{aligned}a_1 &= (-15.91 + 1.67i)pr, & b_2 &= -(2.550 + 10.1i)pr,\\ a_2 &= (-3.63 + 0.89i)pr, & b_4 &= -(0.015 + 0.828i)pr,\\ a_3 &= (-0.119 - 0.16i)pr, & b_6 &= -(0.006 + 0.017i)pr.\end{aligned} \quad (61.14)$$

Hence the values of the particular integral at the edges of the toroid, i.e., for $\theta = 90°$, $\theta = -36°$, are

$$\begin{aligned}\mathfrak{V}(90°) &= 0\\ \mathfrak{V}(-36°) &= (-9.20 + 11.3i)pr.\end{aligned} \quad (61.15)$$

b) Calculation of the functions V_1 and V_2.

From the formulae (60.32), (60.34) one finds the values of the functions V_1 and V_2 in the region $\theta_0 > 0$. Similarly, from the formulae (60.39), one finds their values in the region $\theta_0 < 0$.

At first, the edge values of these functions will be of interest (i.e., the values for $\theta = 90°$ and $\theta = -36°$). Corresponding to these values of θ, one has

$$\xi = d \int_0^{\pi/2} \frac{\sqrt{\sin\theta}}{\sqrt{1 + 0.333 \sin\theta}}\, d\theta \approx 2.43,$$
$$\zeta = d \int_0^{0{,}628} \frac{\sqrt{\sin\psi}}{\sqrt{1 - 0.333 \sin\psi}}\, d\psi \approx 0.616. \tag{61.16}$$

Hence it follows that the edge values of V_1 and V_2 in the region $\theta > 0$ must be evaluated by use of the asymptotic formulae and in the region $\theta < 0$ by use of series.

Using the above stated formulae, one finds

$$V_1\left(\frac{\pi}{2}\right) = -0.048 + 0.053i,$$
$$V_2\left(\frac{\pi}{2}\right) = -7.76 - 5.04i, \tag{61.17}$$
$$V_1(-0.628) = 2.33 - 0.680i,$$
$$V_2(-0.628) = 0.723 + 1.80i.$$

Similarly

$$\left.\begin{aligned} \frac{dV_1}{d\theta} &= -0.0085 - 0.163i \\ \frac{dV_2}{d\theta} &= -20.6 + 4.37i \end{aligned}\right\} \text{for } \theta = \pi/2,$$
$$\left.\begin{aligned} \frac{dV_1'}{d\theta} &= -2.47 - 1.41i \\ \frac{dV_2'}{d\theta} &= 2.33 - 3.42i \end{aligned}\right\} \text{for } \theta = -0.628. \tag{61.18}$$

5) The joints between the cylinder, toroid and sphere.

On the basis of the statements at the beginning of this section, the linking up of the solutions for the cylinder, toroid and sphere may be achieved by use of the equalities (61.1).

In the present particular case, this leads to the following system of four linear algebraic equations:

$$
\begin{aligned}
&(0.022-0.0011i)\bar{C}_1+(-0.591-2.78i)\bar{C}_2+(-1.705+1.17i)pr=\bar{A}+1.5pr,\\
&\frac{1}{r}[(-0.134+0.149i)\bar{C}_1+(-21.7-14.1i)\bar{C}_2]=-6.41\frac{1-i}{r}\bar{A},\\
&(0.216-0.378i)\bar{C}_1+(0.524+0.358i)\bar{C}_2+(0.395-3.83i)pr=\bar{B}-1.026pr,\\
&-\frac{1}{r}[(7.19-2.10i)\bar{C}_1+(2.23+5.55i)\bar{C}_2]+(33.5-2.41i)p=6.33\frac{1+i}{r}\bar{B},
\end{aligned}
\tag{61.19}
$$

from which one finds the following values of the constants:

$$
\begin{aligned}
\bar{C}_1 &= (0.362+1.055i)pr, \quad \bar{C}_2 = (0.084+0.594i)pr,\\
\bar{A} &= (-1.59+0.62i)pr, \quad \bar{B} = (1.72-3.41i)pr;
\end{aligned}
\tag{61.20}
$$

thus the problem is essentially solved, since, once the auxiliary function $\bar{V}$ for the toroid and the auxiliary functions $\bar{T}_c$ and $\bar{T}_s$ are known, all the forces, moments and displacements in the three shells comprising the end-panel under consideration may be evaluated (using the formulae of §§ 57, 60).

Table 23 gives the values of the two stresses in the end-panel which are of greatest practical interest, namely $\sigma_2 = \frac{T_2}{\delta}$, $\sigma_1 = \frac{6M_1}{\delta^2}$, as functions of the angle θ.

Figs. 89 and 90 illustrate the results of this table. Attention should be drawn to the fact that the hoop stress σ_2 reaches a maximum value in the region of the toroid for $\theta = -10°$, where

$$\sigma_{2\max} \approx 3.8pr.$$

As regards the bending stresses, they attain for $\theta = -36°$ their maximum value

$$\sigma_{1\max} \approx 5.6pr.$$

As it has been seen, the investigated end-panel is not a rational design, since the stresses in it are distributed in a very uneven manner and considerable stress concentrations occur in the region of the toroidal shell. In this connection, the greatest danger does not arise from the bending

stresses σ_1, although they are greater, but from the stress σ_2 distributed uniformly through the thickness of the shell. In spite of the above stated unfavourable assessment, end-panels of this type find application in exceptional cases, since their profiles may be found to be convenient.

Table 23

Torus			Sphere			Cylinder		
$\theta°$	$\sigma_1 : \frac{pr}{\delta}$	$\sigma_2 : \frac{pr}{\delta}$	$\theta°$	$\sigma_1 : \frac{pr}{\delta}$	$\sigma_2 : \frac{pr}{\delta}$	ξ	$\sigma_1 : \frac{pr}{\delta}$	$\sigma_2 : \frac{pr}{\delta}$
90	−1.125	−0.594	−36	5.62	1.49	0	−1.110	−0.595
75	−3.19	−1.208	−30	3.34	−0.48	$r/5$	0.690	0.711
60	−4.17	−0.822	−25	1.62	−0.85	$2r/5$	0.195	1.077
45	−4.93	−0.242	−20	0.64	−0.74	$3r/5$	0.015	1.034
30	−4.68	1.278				$4r/5$	0.015	0.99
15	−2.86	2.769				r	0.001	1.00
10	−1.89	3.188						
0	0.42	3.76						
−10	2.88	3.81						
−15	3.90	3.60						
−25	5.38	2.77						
−36	5.62	1.40						

Since there is in the literature a lack of data on concave-convex type arched end-panels and since their analysis is more complex than that of



Fig 89



Fig. 90.

ordinary arched end-panels (in view of the necessity to consider the solution for the toroid in the region $\theta > 0$ as well as in the region $\theta < 0$), this type of end-panel has been chosen as an example.


r/δ = 25
r/δ = 100
pr/δ
R = 2r
r0 = 3/8 r
I
R = 1.5 r
r0 = 1/4 r
II
R = 1.353 r
r0 = 0.1466 r
III
R = 1.25 r
r0 = 0
IV

Fig. 91.

Fig. 91 shows the distributions of the stresses

$$\sigma_1 = \frac{6M_1}{\delta^2} \text{ and } \sigma_2 = \frac{T_2}{\delta}$$

for a number of ordinary arched end-panels, differing from each other by the values of α and r/δ. For the purpose of comparison, the same sketches show the curves for the stresses σ_1 and σ_2 for elliptical ends, the heights of which are equal to those of the arched end-panels (the two upper sketches). The corresponding calculations were performed by the Author in collaboration with B. I. Slepov.

§ 62. Shells of revolution subject to 'wind' loading

As has already been mentioned, the name "wind" loading attaches to that loading system which is obtained from the formulae (52.1) for $k = 1$.

It has been proved in Chapter II that for this loading the equations of the membrane theory may be integrated by quadrature, whatever may be the form of the shell of revolution. It is not difficult to understand that in the case of wind loading the equations of the general theory of shells of revolution, i.e., the differential equations (51.17) may likewise be integrated by quadrature. This follows from the fact that the loading

$$q_1 = q_{1,1} \cos \varphi, \quad q_2 = q_{2,1} \sin \varphi, \quad q_n = q_{n,1} \cos \varphi \tag{62.1}$$

is not self-equilibrating, so that there must exist not only relations between the derivatives of the forces and moments, but likewise certain linear relations between the same forces and moments expressing the equilibrium conditions of a finite part of the shell of revolution severed by cuts perpendicular to its axis.

Further, by the number of the equations of statics, it may be verified that there must be two such linear relations between the forces and moments which may be written down on the basis of a study of the equilibrium of a part of the shell, cut from it in the above manner.

Hence the system (52.3) for $k = 1$, i.e., the system

$$\begin{aligned} &G_1[\tilde{U}^{(1)}] + \left[1 - ic\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\right]\tilde{T}^{(1)} = f_1(\theta), \\ &-icG_1[\tilde{T}^{(1)}] + \tilde{T}^{(1)} + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\,\tilde{U}^{(1)} = R_2 q_{n,1}, \end{aligned} \tag{62.2}$$

where

$$f_{1,1}(\theta) = \frac{1}{R_1 R_2 \sin\theta}\left\{\frac{d}{d\theta}\left[(q_{n,1}\cos\theta - q_{1,1}\sin\theta)R_2^3\sin^2\theta\right] + \right.$$

$$\left. + q_{2,1}R_1R_2^2\sin^2\theta\right\}, \qquad (62.3)$$

$$G_1(\ldots) = \frac{1}{R_1R_2\sin\theta}\frac{d}{d\theta}\left[\frac{R_2^2\sin\theta}{R_1}\frac{d(\ldots)}{d\theta}\right] - \frac{1}{R_2\sin^2\theta}(\ldots), \qquad (62.4)$$

must have at least two quadratures.

In order to find these quadratures the first equation (62.2) will be subtracted from the second. Then one arrives at the second order differential equation

$$G_1(\tilde{W}) - \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\tilde{W} = f_1(\theta) - R_2q_{n,1} \qquad (62.5)$$

with one unknown, the new auxiliary function $\tilde{W}$

$$\tilde{W} = \tilde{U}^{(1)} + ic\tilde{T}^{(1)}. \qquad (62.6)$$

Taking into consideration that the operator $G_1(\ldots)$ is defined by the formula (62.4), the equation (62.5) may be written in the form

$$\frac{1}{R_1R_2\sin\theta}\frac{d}{d\theta}\left[\frac{R_2^2\sin\theta}{R_1}\frac{d\tilde{W}}{d\theta}\right] - \frac{1}{R_1\sin^2\theta}\tilde{W} = f_1(\theta) - R_2q_{n,1}, \qquad (62.7)$$

whence it is clear that it differs from equation (29.2) only in the way that, in the membrane theory, this equation is in terms of the function

$$U = T_1R_2\sin^2\theta, \qquad (62.8)$$

whereas in the theory of shells of revolution, which includes bending, it is in terms of the function

$$\tilde{W} = \tilde{U}^{(1)} + ic\tilde{T}^{(1)} = \tilde{T}_1^{(1)}R_2\sin^2\theta - ic\left[\frac{R_2}{R_1}\sin\theta\cos\theta\frac{d\tilde{T}^{(1)}}{d\theta} - \tilde{T}^{(1)}\right], \qquad (62.9)$$

which for $c \to 0$ tends to the preceding function.

In § 29, the differential equation (62.7) has been integrated by quadrature. The corresponding computations need not be repeated here and it will be sufficient that the final results are given by the expression

$$\tilde{W} = \frac{1}{R_2\sin\theta}\left[C_1 + C_2\int_{\theta^*}^{\theta} R_1\sin\theta d\theta + \int_{\theta^*}^{\theta}\Phi R_1\sin\theta d\theta\right], \qquad (62.10)$$

in which

$$\Phi(\theta) = (q_{n,1}\cos\theta - q_{1,1}\sin\theta)R_2^2\sin\theta - \\ - \int_{\theta''}^{\theta} (q_{n,1}\sin\theta + q_{1,1}\cos\theta - q_{2,1})R_1R_2\sin\theta d\theta, \quad (62.11)$$

and C_1 and C_2 are two real arbitrary constants.

The lower limit of integration θ'' may be chosen arbitrarily to suit computational convenience. In what follows, θ'' will be identified with the angle corresponding to the upper edge of the shell of revolution (Fig. 75).

Having found $\tilde{W}$, by use of the formula (62.6) one may now establish the connection between $\tilde{U}^{(1)}$ and $\tilde{T}^{(1)}$. On the basis of this formula, one finds

$$\tilde{U}^{(1)} = \tilde{W} - ic\tilde{T}^{(1)} = -ic\tilde{T}^{(1)} + \frac{1}{R_2\sin\theta}\left[C_1 + C_2\int_{\theta''}^{\theta} R_1\sin\theta d\theta + \right. \\ \left. + \int_{\theta''}^{\theta} \Phi R_1\sin\theta d\theta\right]. \quad (62.12)$$

Introducing this value of $\tilde{U}^{(1)}$ into the second of the equations of the system (62.2), one arrives at the following differential equation in the single unknown $\tilde{T}^{(1)}$:

$$G_1[\tilde{T}^{(1)}] + \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\tilde{T}^{(1)} + \frac{i}{c}\tilde{T}^{(1)} = \\ = \frac{i}{c}\left[R_2q_{n,1} - \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}\tilde{W}\right], \quad (62.13)$$

which may be rewritten in expanded form

$$\frac{d^2\tilde{T}^{(1)}}{d\theta^2} + \left[\left(2\frac{R_1}{R_2} - 1\right)\operatorname{cotan}\theta - \frac{1}{R_1}\frac{dR_1}{d\theta}\right]\frac{d\tilde{T}^{(1)}}{d\theta} + \frac{R_1}{R_2}\left(1 - 2\frac{R_1}{R_2}\right)\frac{1}{\sin^2\theta}\tilde{T}^{(1)} + \\ + i\frac{R_1^2}{R_2c}\tilde{T}^{(1)} = i\frac{R_1^2}{R_2c}F_1(\theta), \quad (62.14)$$

where

$$F_1(\theta) = R_2 q_{n,1} - \left(\frac{1}{R_1} - \frac{1}{R_2}\right) \frac{1}{R_2 \sin^3\theta} \left[C_1 + C_2 \int_{\theta''}^{\theta} R_1 \sin\theta \, d\theta + \right.$$

$$\left. + \int_{\theta''}^{\theta} \Phi R_1 \sin\theta \, d\theta\right] = T^*_{1,1} + T^*_{2,1}. \quad (62.15)$$

The analysis of shells of revolution of arbitrary shape subject to wind loading has thus been reduced to the integration of the above linear second order differential equation.

Comparing this equation with that deduced earlier for the case of symmetrical deformation, i.e., with (54.6), it is impossible to fail to note the evident similarity of these two equations. As regards their left hand sides, it may be stated that they differ only in one term which has been underlined in equation (62.14). However, as is clear from the analysis of the equation (54.6) which is given in § 55, terms of that type are of secondary importance and are negligibly small (provided the solution is not required near the singular points $\theta = 0$ and $\theta = \pi$). Thus, the equations (54.6) and (62.14) are practically identical from the point of view of methods of solution and all the results in § 53, 54 and 55 referring to the theory of the approximate integration of the equation (54.6) may be carried over to the equation (62.14) almost without modification.

The general solution of the equation (62.14) consists of the sum of any of its particular integrals and the general solution of the homogeneous equation

$$\frac{d^2\mathfrak{T}^{(1)}}{d\theta^2} + \left[\left(2\frac{R_1}{R_2} - 1\right)\operatorname{cotan}\theta - \frac{1}{R_1}\frac{dR_1}{d\theta}\right]\frac{d\mathfrak{T}^{(1)}}{d\theta} +$$

$$+ \frac{R_1}{R_2}\left(1 - 2\frac{R_1}{R_2}\right)\frac{1}{\sin^2\theta}\mathfrak{T}^{(1)} + \frac{iR_1^2}{R_2 c}\mathfrak{T}^{(1)} = 0, \quad (62.16)$$

and, provided the function F_1 defined by the formula (62.15) does not essentially increase on differentiation, one may take as particular integral of the equation (62.14)

$$\tilde{t}^{(1)} = F_1(\theta) = T^*_{1,1} + T^*_{2,1}. \quad (62.17)$$

This method based on the omission on the left hand side of the equation (62.14) of all terms except the last is, in essence, equivalent to an identification of the particular integral of this equation with the solution of

the equation of the membrane theory of shells of revolution for the contemplated type of surface loading. As regards the reasoning, accuracy and limitations of its application, this method is completely analogous to that of the determination of the particular integral of the equation (54.6), which has been discussed in § 54.

Having found in this manner the particular integral, the integration of the equation (62.14) has been reduced to the integration of the homogeneous equation (62.16). Introducing there instead of $\mathfrak{T}_{(1)}$ the new dependent variable

$$Z = R_2 \sqrt{\frac{\sin\theta}{R_1}}\, \mathfrak{T}^{(1)}, \tag{62.18}$$

the equation takes the form

$$\frac{d^2Z}{d\theta^2} - F^2 Z = 0, \tag{62.19}$$

where

$$F^2 = \frac{1}{2}\frac{dp}{d\theta} + \frac{1}{4}p^2 - q = -i\frac{R_1^2}{R_2 c} - \frac{1}{2R_1}\frac{d^2R_1}{d\theta^2} + \frac{3}{4}\frac{1}{R_1^2}\left(\frac{dR_1}{d\theta}\right)^2 + \\ + \frac{\operatorname{cotan}\theta}{2R_1}\frac{dR_1}{d\theta} - \frac{R_1}{R_2}\frac{2}{\sin^2\theta}\left(1 - \frac{R_1}{R_2}\right) + \frac{2+\cos^2\theta}{4\sin^2\theta}. \tag{62.20}$$

As in § 55, the solution will be constructed here only for points lying some distance from the points $\theta = 0$ and $\theta = \pi$ and it will be assumed for this purpose that R_1 and R_2 do not increase on differentiation. Then all terms in the formula (62.20) will be quantities of order unity except for the first term which has an absolute value of order $\frac{R}{\delta}$. Hence, consistent with the accuracy of the first approximation, one may write

$$F^2 \approx -i\frac{R_1^2}{R_2 c}; \tag{62.21}$$

this leads to exactly the same approximate expression for the auxiliary function $\mathfrak{T}^{(1)}$ which was obtained in § 56 for $\mathfrak{T}$,namely

$$\mathfrak{T}^{(1)} = \frac{1}{R_2^{3/4}\sin^{1/2}\theta}\left[\tilde{C}_1 e^{-(1-i)\beta} + \tilde{C}_2 e^{(1-i)\beta}\right], \tag{62.22}$$

where

$$\beta = \frac{1}{\sqrt{2}}\int_{\theta_0}^{\theta}\frac{R_1 d\theta}{\sqrt{R_2 c}} = \sqrt[4]{3(1-\mu^2)}\int_{\theta_0}^{\theta}\frac{R_1 d\theta}{\sqrt{R_2\delta}}. \tag{62.23}$$

Since the accuracy of deduction of the result (62.22) does not ensure that all terms of order $\sqrt{\frac{\delta}{R_2}}$ are retained, the factor $\frac{1}{R_2^{3/4}\sin^{1/2}\theta}$ may be assumed to be constant for the differentiation of the expression (62.22) (§ 54, 55). Including this factor with the constant of integration, one obtains for $\mathfrak{T}^{(1)}$ the following approximate expression which coincides with (56.10):

$$\mathfrak{T}^{(1)} = \tilde{C}_1 e^{-(1-i)\beta} + \tilde{C}_2 e^{(1-i)\beta}, \tag{62.24}$$

which will be accepted as the final result.

With a knowledge of $\mathfrak{T}^{(1)}$, all the complex forces are readily found and this will be demonstrated in the following section.

§ 63. Design formulae for 'wind' loading

First, the general expressions for the displacements, forces and moments in shells of revolution subject to wind loading will be deduced and a beginning will be made with the homogeneous problem which corresponds to the differential equation (62.16) with

$$q_1 = q_2 = q_n = \tilde{W} = 0. \tag{63.1}$$

It follows from this and the formulae (62.12) that

$$\tilde{U}^{(1)} = -ic\mathfrak{T}^{(1)}, \tag{63.2}$$

whence, taking into consideration (51.6) and (52.2), one obtains for the complex force $\tilde{T}_1$ the expression

$$\tilde{T}_1 = \tilde{T}_1^{(1)}\cos\varphi = ic\left[\frac{\operatorname{cotan}\theta}{R_1}\frac{d\mathfrak{T}^{(1)}}{d\theta} - \frac{1}{R_2\sin^2\theta}\mathfrak{T}^{(1)}\right]\cos\varphi. \tag{63.3}$$

However, since $\frac{d\mathfrak{T}^{(1)}}{d\theta}$ in comparison with $\mathfrak{T}^{(1)}$ will be a quantity of order $\sqrt{\frac{R}{\delta}}$, this being a property of the integrals of the equation (62.16), one must neglect in the formula (63.3) the second term, after which (63.3) takes the form

$$\tilde{T}_1 = \tilde{T}_1^{(1)}\cos\varphi = ic\frac{\operatorname{cotan}\theta}{R_1}\frac{d\mathfrak{T}^{(1)}}{d\theta}\cos\varphi. \tag{63.4}$$

Further, by (51.7),

$$\tilde{T}_2 = \tilde{T} - \tilde{T}_1 = \left(\mathfrak{T}^{(1)} - ic\frac{\operatorname{cotan}\theta}{R_1}\frac{d\mathfrak{T}^{(1)}}{d\theta}\right)\cos\varphi \approx \mathfrak{T}^{(1)}\cos\varphi, \quad (63.5)$$

and, finally, on the basis of the equation (51.11), one finds by taking account of the fact that the problem is homogeneous

$$R_1 \sin\theta \frac{d\tilde{S}}{d\varphi} = -\left[\frac{d\tilde{U}^{(1)}}{d\theta} + ic\operatorname{cotan}\theta\frac{R_1}{R_2}\mathfrak{T}^{(1)}\right]\cos\varphi =$$

$$= ic\left[\frac{d\mathfrak{T}^{(1)}}{d\theta} - \operatorname{cotan}\theta\frac{R_1}{R_2}\mathfrak{T}^{(1)}\right]\cos\varphi \approx ic\frac{d\mathfrak{T}^{(1)}}{d\theta}\cos\varphi. \quad (63.6)$$

Hence

$$\tilde{S} = \frac{ic}{R_1\sin\theta}\frac{d\mathfrak{T}^{(1)}}{d\theta}\sin\varphi = \tilde{S}^{(1)}\sin\varphi. \quad (63.7)$$

By the way, it follows from these formulae that, when the problem is homogeneous, there exist between the complex forces the relations

$$\tilde{T}_1\sin\varphi - \tilde{S}\cos\varphi\cos\theta = 0,$$

$$\tilde{T}_1\cos\theta\sin\varphi - \tilde{S}\cos\varphi + \frac{ic}{R_1}\frac{d\mathfrak{T}^{(1)}}{d\theta}\sin\theta\sin\varphi = 0, \quad (63.8)$$

which hold, of course, only for 'wind' loading.

Substituting in (63.3), (63.4) and (63.7) for $\mathfrak{T}^{(1)}$ its value (62.24) and separating real and imaginary parts (as was done similarly in § 57), one arrives at the following general expressions for the forces and moments:

$$\begin{aligned}
T_1 &= -\frac{1}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\operatorname{cotan}\theta\{[(C_1'-C_1'')\cos\beta-(C_1'+C_1'')\sin\beta]e^{-\beta}+\\
&\quad+[(C_2''-C_2')\cos\beta-(C_2'+C_2'')\sin\beta]e^{\beta}\}\cos\varphi,\\
T_2 &= \{(C_1'\cos\beta-C_1''\sin\beta)e^{-\beta}+(C_2'\cos\beta+C_2''\sin\beta)e^{\beta}\}\cos\varphi, \quad (63.9)\\
S &= -\frac{1}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\cdot\frac{1}{\sin\theta}\{([C_1'-C_1'')\cos\beta-(C_1'+C_1'')\sin\beta]e^{-\beta}+\\
&\quad+[(C_2''-C_2')\cos\beta-(C_2'+C_2'')\sin\beta]e^{\beta}\}\sin\varphi,\\
&\qquad M_2 \approx \mu M_1,\\
M_1 &= -c[(C_1''\cos\beta+C_1'\sin\beta)e^{-\beta}+(C_2''\cos\beta-C_2'\sin\beta)e^{\beta}]\cos\varphi.
\end{aligned}$$

The normal shear force N_1 may now be determined as the real part

of the function

$$\frac{ic}{R_1}\frac{d\mathfrak{T}}{d\theta}$$

(§ 56), whence, as in the case of symmetrical loading,

$$N_1 = T_1 \tan\theta. \tag{63.10}$$

There remains to evaluate the displacements and the angle of rotation of the meridian of the shell

$$\vartheta = -\frac{1}{R_1}\left(\frac{\partial w}{\partial\theta} - u\right).$$

Putting in the formulae (53.5) $k = 1$, one obtains for the complex displacements the system of differential equations

$$\frac{d\tilde{u}_1}{d\theta} + \tilde{w}_1 = \frac{R_1}{E\delta}(\tilde{T}_1^{(1)} - \mu\tilde{T}_2^{(1)}),$$

$$\tilde{v}_1 + \tilde{u}_1\cos\theta + \tilde{w}_1\sin\theta = \frac{R_2\sin\theta}{E\delta}[\tilde{T}_2^{(1)} - \mu\tilde{T}_1^{(1)}], \tag{63.11}$$

$$\frac{d\tilde{v}_1}{d\theta} - \left(\tilde{v}_1\operatorname{cotan}\theta + \frac{1}{\sin\theta}\tilde{u}_1\right)\frac{R_1}{R_2} = \frac{2(1+\mu)R_1}{E\delta}\tilde{S}^{(1)},$$

with regard to which it may be stated that it can be integrated by quadrature (on the basis of the results, obtained in §§ 21, 27).

Differentiating the second of the equations (63.11) and combining it with the two other equations of the same system, one finds

$$\tilde{\vartheta}_1 + \frac{\tilde{\Delta}_z}{R_2\sin\theta} = -\frac{R_2}{E\delta}\left\{\left(1 - \frac{ic}{R_1}\right)\frac{1}{R_1}\frac{d\mathfrak{T}^{(1)}}{d\theta} - \frac{2(1+\mu)\tilde{S}^{(1)}}{R_2\sin\theta} + \right.$$

$$\left. + \frac{\tilde{T}_2^{(1)} - \mu\tilde{T}_1^{(1)}}{R_2}\operatorname{cotan}\theta\right\}, \tag{63.12}$$

where

$$\tilde{\Delta}_z = \tilde{w}_1\cos\theta - \tilde{u}_1\sin\theta. \tag{63.13}$$

On the other hand, direct differentiation of Δ_z gives

$$\frac{d\Delta_z}{d\theta} = \frac{d\tilde{w}_1}{d\theta}\cos\theta - \tilde{w}_1\sin\theta - \frac{d\tilde{u}_1}{d\theta}\sin\theta - \tilde{u}_1\cos\theta =$$

$$= -\tilde{\vartheta}_1 R_1\cos\theta - \left(\frac{d\tilde{u}_1}{d\theta} + \tilde{w}_1\right)\sin\theta =$$

$$= -\tilde{\vartheta}_1 R_1\cos\theta - \frac{R_1\sin\theta}{E\delta}(\tilde{T}_1^{(1)} - \mu\tilde{T}_2^{(1)}). \tag{63.14}$$

Hence, if one takes into consideration that $\tilde{T}_1^{(1)}$, $\tilde{S}^{(1)}$ and $\tilde{T}_2^{(1)}$ can be expressed in terms of $\tilde{T}^{(1)}$ by use of the formulae (63.4), (63.5), (63.7), one obtains for Δ_z the first order differential equation

$$\frac{d\Delta_z}{d\theta} - \tilde{\Delta}_z \frac{R_1}{R_2} \operatorname{cotan}\theta = \frac{R_2 \cos\theta}{E\delta} \times$$

$$\times \left\{ \left[1 - \frac{ic}{R_1} \left(1 + 2(1+\mu) \frac{R_1}{R_2} \frac{1+\cos^2\theta}{\sin^2\theta} \right) \right] \frac{d\mathfrak{T}^{(1)}}{d\theta} + \right.$$

$$\left. + (1+\mu) \frac{R_1}{R_2} \operatorname{cotan}\theta \left(1 + \frac{2ic}{R_2 \sin^2\theta} \right) \mathfrak{T}^{(1)} \right\}, \tag{63.15}$$

which, after introduction of the customary simplifications, takes the form

$$\frac{d\tilde{\Delta}_z}{d\theta} - \tilde{\Delta}_z \frac{R_1}{R_2} \operatorname{cotan}\theta = \frac{R_2 \cos\theta}{E\delta} \frac{d\mathfrak{T}^{(1)}}{d\theta}. \tag{63.16}$$

Since it is only necessary to find a particular integral of this equation which for every differentiation will increase in a ratio $\sqrt{\frac{R}{\delta}}$, one may neglect on the left hand side of (63.16) the second term. Further, one may assume for the purpose of the integration that the factor $R_2 \cos\theta$ is constant, neglecting its rate of change in comparison with that of $\mathfrak{T}^{(1)}$.

These considerations lead to the relation

$$\tilde{\Delta}_z \approx \frac{R_2 \cos\theta}{E\delta} \mathfrak{T}^{(1)}, \tag{63.17}$$

which applies in the same region as the remaining approximate formulae of this section. Now, the equation (63.12) permits the writing down of the following expression for $\tilde{\mathfrak{S}}_1$:

$$\tilde{\mathfrak{S}}_1 = -\frac{1}{E\delta} \left\{ \frac{R_2}{R_1} \left[1 - \frac{ic}{R_1} - (1+\mu) \frac{ic}{R_2} \cdot \frac{2+\cos^2\theta}{\sin^2\theta} \right] \frac{d\mathfrak{T}^{(1)}}{d\theta} + \right.$$

$$\left. + 2\mathfrak{T}^{(1)} \operatorname{cotan}\theta \left[1 + (1+\mu) \frac{ic}{R_2 \sin^2\theta} \right] \right\} \approx -\frac{1}{E\delta} \frac{R_2}{R_1} \frac{d\mathfrak{T}^{(1)}}{d\theta}, \tag{63.18}$$

after which $\tilde{u}_1$, $\tilde{v}_1$ and $\tilde{w}_1$ are readily obtained from the system (63.11).

Without dwelling on these computations which would be similar to the preceding ones, the final results will be given in the form of the

following approximate formulae:

$$\tilde{w}_1 = \frac{R_2}{E\delta}\mathfrak{T}^{(1)},$$

$$\tilde{u}_1 = -i\frac{cR_2}{R_1^2 E\delta}(R_2+\mu R_1)\frac{d\mathfrak{T}^{(1)}}{d\theta} = -i\frac{cR_2}{R_1}\cdot\frac{1}{E\delta}\left(\frac{R_2}{R_1}+\mu\right)\frac{d\mathfrak{T}^{(1)}}{d\theta}, \quad (63.19)$$

$$\tilde{v}_1 = \frac{ic}{E\delta\sin\theta}\left(2-\mu-\frac{R_2}{R_1}\right)\mathfrak{T}^{(1)}.$$

The real parts of the functions (63.18), (63.19) will be the coefficients of the expressions

$$u = u_1\cos\varphi,\ v = v_1\sin\varphi,\ w = w_1\cos\varphi,\ \vartheta = \vartheta_1\cos\varphi \quad (63.20)$$

and, therefore, the formulae (63.18) and (63.19) completely determine the displacements and the angle of rotation of shells of revolution, corresponding to the differential equation (62.16).

In what follows, consideration will be limited to the case when a shell of revolution has only one edge, i.e., when it is a dome without opening. Then one must put in the formulae (63.9)

$$C_1' = C_1'' = 0,$$

since the functions multiplying these constants in the case of a more exact solution of the problem under consideration (for example, in the second approximation) tend to infinity for $\theta = 0$.

Taking this circumstance into consideration, one obtains the following approximate expressions for the displacements, the angle of rotation, the forces and moments in a dome without aperture subject to wind loading:

$$u = \frac{\sqrt{R_2 c}}{\sqrt{2}E\delta}\left(\frac{R_2}{R_1}+\mu\right)[(C_2-C_1)\cos\beta+(C_1+C_2)\sin\beta]e^{-\beta}\cos\varphi+u^*,$$

$$v = -\frac{c}{E\delta}\cdot\frac{1}{\sin\theta}\left(2-\mu-\frac{R_2}{R_1}\right)[C_2\cos\beta+C_1\sin\beta]e^{-\beta}\sin\varphi+v^*,$$

$$w = \frac{R_2}{E\delta}(C_1\cos\beta - C_2\sin\beta)e^{-\beta}\cos\varphi + w^*, \quad (63.21)$$

$$\vartheta = -\frac{1}{E\delta}\sqrt{\frac{R_2}{2c}}[(C_1+C_2)\cos\beta+(C_1-C_2)\sin\beta]e^{-\beta}\cos\varphi+\vartheta^*,$$

$$T_1 = \frac{\operatorname{cotan}\theta}{\sqrt{2}}\sqrt{\frac{c}{R_2}}[(C_1-C_2)\cos\beta-(C_1+C_2)\sin\beta]e^{-\beta}\cos\varphi+T_1^*,$$

$$S = \frac{1}{\sqrt{2}\sin\theta}\sqrt{\frac{c}{R_2}}\,[(C_1-C_2)\cos\beta-(C_1+C_2)\sin\beta]e^{-\beta}\sin\varphi+S^*,$$

$$N_1 = \frac{1}{\sqrt{2}}\sqrt{\frac{c}{R_2}}\,[(C_1-C_2)\cos\beta-(C_1+C_2)\sin\beta]e^{-\beta}\cos\varphi,$$

$$T_2 = (C_1\cos\beta - C_2\sin\beta)e^{-\beta}\cos\varphi + T_2^*, \tag{63.22}$$

$$M_2 = \mu M_1,$$

$$M_1 = -c(C_2\cos\beta + C_1\sin\beta)e^{-\beta}\cos\beta.$$

In the formulae (63.21) and (63.22)

$$\beta = \frac{1}{\sqrt{2}}\int_0^s \frac{ds}{\sqrt{R_2 c}}, \tag{63.23}$$

where s is the arc length of the meridian of the dome measured from its edge and $u^* \ldots, T_1^* \ldots$ are understood to be the solutions of the membrane theory. A method for their determination has been given in § 27.

Some attention will now be given to the case where

$$u^* = v^* = \ldots T_2^* = 0, \tag{63.24}$$

i.e., where there is no surface loading on the shell, but only edge loading which varies like $\cos\varphi$ or $\sin\varphi$. Obviously the components of such an edge loading $(T_1^0, N_1^0, S^0, M_1^0)$ may not be given in an arbitrary manner, since this would violate the equilibrium conditions of the shell as a whole. Therefore one need only consider systems of edge loading which are self-equilibrating.

It is readily understood that the conditions for the self-equilibration of the edge loadings

$$T_1^0 = t_1^0\cos\varphi,\ N_1^0 = n_0\cos\varphi,\ S^0 = s_0\sin\varphi,\ M_1^0 = m_0\cos\varphi \tag{63.25}$$

reduce to two equations, whence it follows that in the present case of four components of the edge loading only two may be assigned arbitrarily, the moment M_1^0 and one of the forces. The relation which must hold between the edge forces, in order not to disturb the static equilibrium, will be deduced from the formulae (63.4), (63.7) and (63.10), (63.8). After separating in them real and imaginary parts, one finds

$$\begin{aligned} T_1\sin\varphi - S\cos\varphi\cos\theta &= 0,\\ T_1\cos\theta\sin\varphi - S\cos\varphi + N_1\sin\theta\sin\varphi &= 0. \end{aligned} \tag{63.26}$$

Since the problem is homogeneous, these equalities must be fulfilled at all sections of the shell, including the edge regions. They are essentially the equations of static equilibrium for the shell as a whole. Because the equations (63.4) $\sim$ (63.10) were deduced by omitting certain small terms, the formulae (63.26) express the static conditions only in an approximate manner.

In fact, the moment M_1 has been neglected there in comparison with products of forces and moments of order of magnitude of the radius of curvature of the shell, corresponding to an error of order $\sqrt{\frac{\delta}{R}}$.

The question will now be asked what kind of edge loadings will satisfy these formulae. Excluding from them the force S, one finds that

$$Q_z^0 = T_1^0 \sin\theta - N_1^0 \cos\theta = 0, \tag{63.27}$$

whence it follows that the first requirement, imposed on edge loadings of the type (63.25) by the conditions of statics, is that the edge force cannot have a component in the direction of the axis of the shell.

Let Q_0 denote the component of the edge loading, acting normal to the edge and in its plane, so that

$$Q_0 = T_1^0 \cos\theta_0 + N_1^0 \sin\theta_0 = (t_0 \cos\theta_0 + n_0 \sin\theta_0)\cos\varphi = q_0 \cos\varphi. \tag{63.28}$$

A simultaneous study of the relations (63.27) and (63.28) shows that

$$\begin{aligned} N_1^0 &= Q_0 \sin\theta_0, \\ T_1^0 &= Q_0 \cos\theta_0. \end{aligned} \tag{63.29}$$

Substituting the second of these formulae into the first of the formulae (63.26), one obtains the following relation between Q_0 and S_0:

$$Q_0 \sin\varphi = S_0 \cos\varphi, \tag{63.30}$$

whence

$$q_0 = s_0. \tag{63.31}$$

Thus, the homogeneous problem, i.e., the solution of the equation (62.16), corresponds to having on the edge of the shell two loadings acting in the plane of the edge (Fig. 92):



Fig. 92.

a) Normal forces Q_0

$$Q_0 = q_0 \cos \varphi;$$

b) tangential forces S_0

$$S_0 = q_0 \sin \varphi.$$

In addition, there may be given an arbitrary edge moment

$$M_0 = m_0 \cos \varphi.$$

However, its introduction disturbs the static equilibrium; in order to correct this effect, it is sufficient to adjust the edge forces Q_0, S_0 by amounts of the order $\sqrt{\frac{\delta}{R}}$ (compared with unity). Since terms of such magnitude lie outside the range of accuracy of the underlying theory, no contradictions will result. Consequently, one will reach the conclusion that in the case of the homogeneous problem only two quantities may be fixed arbitrarily at the edge of the shell, the parameters q_0 and m_0, which may be given directly or indirectly (in terms of the displacements and the angle of rotation). This conclusion also does not change in the general case, when the problem is not homogeneous, since the solutions of the membrane theory $u_1^* \ldots T_1^* \ldots$ do not involve arbitrary constants which might have to be disposed of. Therefore problems of stresses in domes under the action of wind loads are, in general, determined by two arbitrary boundary conditions (instead of the customary four of the theory of shells). This reduction of the number of arbitrary boundary conditions is explained by the fact that in the given case two of the four boundary conditions are compulsory and are dictated by the requirements of the equilibrium of the shell as a whole. In fact, this circumstance relates the problem of wind loading to the earlier studied problem of symmetrical deformation of shells of revolution. Thanks to this circumstance, in certain problems, the differential equations of the theory of shells admit quadrature, and correspondingly their order may be reduced. It is impossible to do so for any other loading included in the formulae (52.1), since for $k \geqslant 2$ these formulae give surface loadings which are self-equilibrating, as a consequence of which all components of the edge loading can be fixed arbitrarily.

Thus, the two particular cases $k = 0$ and $k = 1$ are fortunate exceptions and the physical reasons for this situation should now be completely understood.

§ 64. On the integration of the system (52.3) for shells whose radii of curvature satisfy the relation

$$\left(\frac{1}{R_1}-\frac{1}{R_2}\right)\frac{1}{\sin^2\theta}=\text{const}$$

The two types of surface loading which have been considered above and which correspond to $k=0$ and $k=1$ in the formulae (52.1) permit reduction of the solution of the system (52.3) to the integration of differential equations which are only of second order. As has been noted in the previous section, this result cannot be extended to loadings of any other type, so that, as a rule, it is not possible to lower the order of the system (52.3) for $k \geqslant 2$ without introduction of some additional simplifications.

However, there is one family of shells for which the solution of the system (52.3) for any values of k may be reduced to the integration of two independent second order differential equations without any omissions in this system. This property belongs to shells of revolution the radii of curvature of which satisfy the relation

$$\left(\frac{1}{R_1}-\frac{1}{R_2}\right)\frac{1}{\sin^2\theta}=A, \tag{64.1}$$

where A — is a constant parameter.

First of all, the radii of curvature of this family of shells will be determined by supplementing (64.1) by the condition of Codazzi

$$\frac{d(R_2\sin\theta)}{d\theta}=R_1\cos\theta. \tag{64.2}$$

Solving (64.1) for R_1 and substituting the value so obtained into the expression (64.2), one arrives at the following differential equation for R_2:

$$\frac{d(R_2\sin\theta)}{d\theta}=\frac{R_2\cos\theta}{1+AR_2\sin^2\theta}, \tag{64.3}$$

which with

$$x=AR_2\sin^2\theta \tag{64.4}$$

reduces to the form

$$\frac{1+x}{2+x}\,\frac{1}{x}\,\frac{dx}{d\theta}=\operatorname{cotan}\theta. \tag{64.5}$$

A general integral of this last equation is

$$x=-1\pm\sqrt{1+C\sin^2\theta}, \tag{64.6}$$

where C — is a constant of integration. Hence the family of shells under discussion falls into two sub-families the radii of curvature of which are expressed by the formulae:

a)
$$R_1 = \frac{\sqrt{1 + C\sin^2\theta} - 1}{A\sqrt{1 + C\sin^2\theta}\sin^2\theta},$$
$$R_2 = \frac{\sqrt{1 + C\sin^2\theta} - 1}{A\sin^2\theta}; \tag{64.7}$$

b)
$$R_1 = \frac{1 + \sqrt{1 + C\sin^2\theta}}{A\sqrt{1 + C\sin^2\theta}\sin^2\theta},$$
$$R_2 = -\frac{1 + \sqrt{1 + C\sin^2\theta}}{A\sin^2\theta}. \tag{64.8}$$

For the further development it is expedient to introduce instead of A and C two other constants which have clearer geometrical interpretations; in fact,

$$\left.\begin{aligned} \nu &= \left(\frac{R_2}{R_1}\right) \\ r_0 &= R_2 \end{aligned}\right\} \text{ for } \theta = \frac{\pi}{2}. \tag{64.9}$$

The new constant ν is equal to the ratio of the radii of curvature of the middle surface at the equator and the new constant r_0 is equal to the radius of the equatorial section of the shell. Consequently, the first constant characterizes the form of the shell, the second its dimensions.

It follows from the formulae (64.7), (64.8) and (64.9) that

$$C = \nu^2 - 1, \quad A = \frac{\nu - 1}{r_0}, \tag{64.10}$$

whence the formulae (64.7) and (64.8) become

a)
$$R_1 = \frac{r_0}{\nu - 1}\,\frac{\sqrt{1 + (\nu^2 - 1)\sin^2\theta} - 1}{\sqrt{1 + (\nu^2 - 1)\sin^2\theta}\sin^2\theta},$$
$$\nu > 0, \tag{64.11}$$
$$R_2 = \frac{r_0}{\nu - 1}\,\frac{\sqrt{1 + (\nu^2 - 1)\sin^2\theta} - 1}{\sin^2\theta};$$

b) $$R_1 = -\frac{r_0}{1-\nu}\,\frac{\sqrt{1+(\nu^2-1)\sin^2\theta}+1}{\sqrt{1+(\nu^2-1)\sin^2\theta}\,\sin^2\theta},$$

$$\nu < 0, \qquad (64.12)$$

$$R_2 = \frac{r_0}{1-\nu}\,\frac{\sqrt{1+(\nu^2-1)\sin^2\theta}+1}{\sin^2\theta}.$$

Having obtained both radii of curvature as functions of the angle θ, one may now also evaluate the cartesian coordinates of the curves which are the meridians of the shells 'a' and 'b'. Let the origin of the system lie in the equatorial plane, the axis Y coincide with the axis of revolution and the X direction be perpendicular to Y.

The coordinates of the meridian of the middle surface in the above type of cartesian system will be determined by the formulae (Fig. 93)

$$x = R_2 \sin\theta,$$

$$y = -\int_{\frac{\pi}{2}}^{\theta} R_1 \sin\theta\, d\theta. \qquad (64.13)$$

Substituting here the above values for R_1 and R_2, one will have

$$x = \frac{r_0}{\nu-1}\,\frac{-1 \pm \sqrt{1+(\nu^2-1)\sin^2\theta}}{\sin\theta}, \qquad (64.14)$$

$$y = -\frac{r_0}{\nu-1}\int_{\frac{\pi}{2}}^{\theta} \frac{\mp 1+\sqrt{1+(\nu^2-1)\sin^2\theta}}{\sin\theta\sqrt{1+(\nu^2-1)\sin^2\theta}}\, d\theta,$$

where the upper and lower signs refer to the sub-families of shells 'a' and 'b' respectively.

The integral in the expression for y may be evaluated to give the expression

$$y = -\frac{r_0}{\nu-1}\left\{\ln\tan\frac{\theta}{2} \mp \frac{1}{2}\ln\left[\frac{\sqrt{1+\nu^2\tan^2\theta}-1}{1+\sqrt{1+\nu^2\tan^2\theta}}\right]\right\}. \qquad (64.15)$$

Hence one arrives at the following final formulae for the meridians

of the shells 'a' and 'b'

a)
$$x = \frac{r_0}{\nu - 1} \frac{\sqrt{1 + (\nu^2 - 1)\sin^2\theta} - 1}{\sin\theta},$$
$$\nu > 0, \qquad (64.16)$$
$$y = \frac{r_0}{\nu - 1} \ln \frac{1}{\nu} \frac{\sqrt{1 + \nu^2 \tan^2\theta} - 1}{\sec\theta - 1};$$

b)
$$x = -\frac{r_0}{\nu - 1} \frac{\sqrt{1 + (\nu^2 - 1)\sin^2\theta} + 1}{\sin\theta},$$
$$\nu < 0, \qquad (64.17)$$
$$y = -\frac{r_0}{\nu - 1} \ln \frac{1}{\nu} \frac{1 - \sqrt{1 + \nu^2 \tan^2\theta}}{\sec\theta + 1}.$$

In these formulae, θ is assumed to vary between the limits

$$0 \leqslant \theta \leqslant \frac{\pi}{2}.$$

Fig. 94 shows the meridian curves of the families of surfaces under consideration for different values of ν. All these surfaces have the same equatorial width $2r_0$.



Fig. 93.

It is seen from Fig. 94 and likewise directly from the formulae (64.11) and (64.12) that the sub-family 'a' comprises shells of positive, and the sub-family 'b' shells of negative Gaussian curvature. The shape characteristic for the first group recalls ellipsoids of revolution, the second single-sheeted hyperboloids. As a particular case, the sub-family 'a' contains for $\nu = 1$ the sphere, and the sub-family 'b' for $\nu = -1$ the catenoid, i.e., the surface, formed by revolution of a catenary the radii of curvature of which are given by the formulae

$$R_1 = -R_2 = -\frac{r_0}{\sin^2\theta}. \qquad (64.18)$$

The limiting surface, belonging to both sub-families, is the surface of zero Gaussian curvature, the circular cylinder which corresponds to $\nu = 0$. Thus, the formula (64.1) covers a wide range of shells of various forms, the study of which is undoubtedly of interest.

The basic system of differential equations (52.3) for all these shells takes the form

$$\begin{aligned} G_k(\tilde{U}_k) + k^2\left[1 - i\frac{c(\nu-1)}{r_0}\right]\tilde{T}^{(k)} &= f_k(\theta), \\ G_k(\tilde{T}^{(k)}) + \frac{i}{c}\tilde{T}^{(k)} + i\frac{(\nu-1)}{r_0 c}\tilde{U}^{(k)} &= \frac{i}{c}R_2 q_{n,k}, \end{aligned} \tag{64.19}$$

where the operator $G_k(\ldots)$ and the functions of the surface loading $f_k(\theta)$ are defined by the formulae (52.4) and (52.5). It is an essential feature that the terms on the left hand sides of the system (64.19) which do not enter into the operator $G_k(\ldots)$ are in this case constant coefficients. Therefore the system (64.19) may be split up into two independent differential equations of second order, as may be shown by the following reasoning.



Fig. 94.

Introduce the new auxiliary function

$$\tilde{W} = \tilde{U}_k + \alpha\tilde{T}^{(k)}, \tag{64.20}$$

in which α is a constant but so far undetermined coefficient.

Further, expressing $\tilde{U}^{(k)}$ in terms of $\tilde{W}$ and $\tilde{T}^{(k)}$, using (64.20) and substituting in (65.19), one finds

$$\begin{aligned} G_k(\tilde{W}) - \alpha G_k(\tilde{T}^{(k)}) + k^2\left[1 - i\frac{c(\nu-1)}{r_0}\right]\tilde{T}^{(k)} &= f_k(\theta), \\ G_k(\tilde{T}^{(k)}) + \frac{i}{c}\tilde{T}^{(k)} + \frac{i(\nu-1)}{r_0 c}\tilde{W} - \alpha\frac{i(\nu-1)}{r_0 c}\tilde{T}^{(k)} &= \frac{i}{c}R_2 q_{n,k}. \end{aligned} \tag{64.21}$$

Hence, multiplying the second equation by α and adding it to the first equation, one obtains

$$G_k(\tilde{W}) + i\frac{\alpha(\nu-1)}{r_0 c}\tilde{W} + \left\{k^2\left[1 - i\frac{c(\nu-1)}{r_0}\right] + i\frac{\alpha}{c} - \alpha^2\frac{i(\nu-1)}{r_0 c}\right\}\tilde{T}^{(k)} = f_k(\theta) + i\frac{\alpha}{c}R_2 q_{n,k}. \tag{64.22}$$

If now α is chosen in such a manner that the expression in the braces

vanishes, the second unknown $\tilde{T}$ disappears from the equation (64.22). In this way, one obtains for $\tilde{W}$ the second order differential equation

$$G_k(\tilde{W}) + i\,\frac{\alpha(\nu-1)}{r_0 c}\,\tilde{W} = f_k(\theta) + i\,\frac{\alpha}{c}\,R_2 q_{n,k}, \tag{64.23}$$

or, more correctly speaking, two such equations for the two auxiliary functions

$$\begin{aligned} \tilde{W}_1 &= \tilde{U}^{(k)} + \alpha_1 \tilde{T}^{(k)}, \\ \tilde{W}_2 &= \tilde{U}^{(k)} + \alpha_2 \tilde{T}^{(k)}, \end{aligned} \tag{64.24}$$

since the quadratic equation

$$i\,\frac{(\nu-1)}{r_0 c}\,\alpha^2 - \frac{i}{c}\,\alpha - k^2\left[1 - i\,\frac{c(\nu-1)}{r_0}\right] = 0 \tag{64.25}$$

gives two different values α_1 and α_2 for the constant α, each of which may be employed for the above transformation.

Solving the equation (64.25), one finds

$$\begin{aligned} \alpha_1 &= \frac{r_0}{2(\nu-1)}\left\{1 + \sqrt{1 - i4k^2(\nu-1)\,\frac{c}{r_0} - 4k^2(\nu-1)^2\,\frac{c^2}{r_0^2}}\right\}, \\ \alpha_2 &= \frac{r_0}{2(\nu-1)}\left\{1 - \sqrt{1 - i4k^2(\nu-1)\,\frac{c}{r_0} - 4k^2(\nu-1)^2\,\frac{c^2}{r_0^2}}\right\}. \end{aligned} \tag{64.26}$$

Substituting these values for α into the equations (64.23), one arrives at two independent differential equations for the auxiliary functions $\tilde{W}_1$, $\tilde{W}_2$.

It will now be assumed that one has succeeded in integrating these equations. Then one may determine directly the auxiliary functions $\tilde{U}^{(k)}$ and $\tilde{T}^{(k)}$ by solving the linear algebraic system (64.24). However, as has been pointed out already, the determination of these auxiliary functions is equivalent to the complete solution of the problem, since, if they are known, all the complex forces may be evaluated by means of operations involving at the most differentiations (using the formulae of §§ 51, 52). Thus, the analysis for an arbitrary loading of any shell of revolution, the radii of curvature of which satisfy the relation (64.1), has been reduced to the integration of two, independent, linear differential equations of second order of the form (64.23).

It will be noted that the ratio

$$\frac{c}{r_0} = \frac{1}{\sqrt{12(1-\mu^2)}}\,\frac{\delta}{r_0}$$

is a quantity of order $\frac{\delta}{r_0}$. Expanding the roots in the formulae (64.26) in power series of this small parameter and neglecting quantities of order $\frac{c^2}{r_0^2}$ (and higher) in comparison with unity, one finds

$$\alpha_1 \approx \frac{r_0}{\nu - 1}\left[1 - ik^2(\nu - 1)\frac{c}{r_0}\right],$$
$$\alpha_2 \approx ick^2\left[1 + i(k^2 - 1)(\nu - 1)\frac{c}{r_0}\right]. \tag{64.27}$$

These simpler formulae completely replace the formulae (64.26), provided k and ν are not so large that the parameter

$$k^2(\nu - 1)\frac{c}{r_0} \tag{64.28}$$

is of the same order as unity.

It has already repeatedly been mentioned in this book that in the simplification of the formulae of the theory of shells one has to deal with three factors: the relative thickness $\frac{\delta}{R}$, the degree of smoothness of the loading and the degree of smoothness of the form of the shell. The thinner the shell, the smoother its radii of curvature and the components of the surface loading (as functions of the coordinates of its middle surface), the better are the chances with regard to simplifications. The formulae (64.27) clearly demonstrate the roles of these three factors. Side by side with the relative thickness $\frac{c}{r_0}$, they involve the parameters k and ν, characterizing respectively the loading and the shape of the shell. Thus, the larger the value of k, the less smooth will be the loading, and the larger ν, the less smooth will be the shape of the shell (where the last point is shown by Fig. 94).

A study of the formulae (64.27) will confirm that an increase of k or ν could be equivalent to a thickening of the shell. Hence it follows that for shells of insufficiently smooth shapes which are loaded in an insufficiently smooth manner the errors arising out of the initial assumptions underlying the theory of shells must increase. In this connection, terms which, as a rule, may be neglected $\left(\text{terms of order } \frac{\delta}{r}\right)$ begin to play an essential role.

Let the shape of the shell and the character of its loading be sufficiently smooth, i.e., let the parameter (64.28) be small compared with unity. Then the formulae (64.27) may be further simplified; in fact, the second terms in these formulae may be neglected in comparison with the first terms. Hence one finds

$$\alpha_1 \approx \frac{r_0}{\nu - 1}, \qquad \alpha_2 \approx ick^2. \tag{64.29}$$

These expressions are the first approximations to the parameters α_1 and α_2.

Introducing (64.29) into (64.23), one obtains the two differential equations

$$\begin{aligned} G_k(\tilde{W}_1) + \frac{i}{c}\tilde{W}_1 &= f_k(\theta) + i\frac{r_0}{(\nu-1)c} R_2 q_{n,k}, \\ G_k(\tilde{W}_2) - \frac{k^2(\nu-1)}{r_0}\tilde{W}_2 &= f_k(\theta) - k^2 q_{n,k} R_2 \end{aligned} \tag{64.30}$$

for the auxiliary functions

$$\begin{aligned} \tilde{W}_1 &= \tilde{U}^{(k)} + \frac{r_0}{\nu - 1}\tilde{T}^{(k)}, \\ \tilde{W}_2 &= \tilde{U}^{(k)} + ick^2\tilde{T}^{(k)}. \end{aligned} \tag{64.31}$$

The first of these equations may be written out in full in the following manner:

$$\begin{aligned} \frac{d^2\tilde{W}_1}{d\theta^2} + \left[\left(2\frac{R_1}{R_2} - 1\right)\operatorname{cotan}\theta - \frac{1}{R_1}\frac{dR_1}{d\theta}\right]\frac{d\tilde{W}_1}{d\theta} - \frac{R_1^2}{R_2^2}\frac{k^2}{\sin^2\theta}\tilde{W}_1 + \\ + i\frac{R_1^2}{R_2 c}\tilde{W}_1 = \frac{R_1^2}{R_2}\left[f_k(\theta) + i\frac{r_0}{c(\nu-1)}R_2 q_{n,k}\right], \end{aligned} \tag{64.32}$$

whence it becomes clear that it is of the same type as the equations (54.5) and (62.16), i.e., as the equations which had to be integrated for the analysis of arbitrary shells of revolution, subject to symmetrical or wind loading. Consequently, all the methods of approximate solution studied in the preceding sections will also be applicable to the above equation.

As regards the second equation, it takes, on the basis of the equality

$$\frac{\nu - 1}{r_0} = \left(\frac{1}{R_1} - \frac{1}{R_2}\right)\frac{1}{\sin^2\theta}, \tag{64.33}$$

the form

$$\frac{1}{R_1R_2\sin\theta}\frac{d}{d\theta}\left[\frac{R_2\sin^2\theta}{R_1}\frac{d\tilde{W}_2}{d\theta}\right]-\frac{k^2}{R_1\sin^2\theta}\tilde{W}_2=f_k(\theta)-k^2R_2q_{n,k}. \quad (64.34)$$

However, this equation differs in no way from the equation (24.4), i.e., from the basic differential equation of the membrane theory of shells of revolution. Thus, if the parameters α_1 and α_2 in their first approximations are determined from the formulae (64.29), then the analysis of shells of revolution belonging to the family under consideration reduces to the solution of two second order differential equations one of which is analogous to the equation for symmetrical deformation of shells of revolution while the other coincides with the equation of the membrane theory.

When proceeding to the second approximation given by the formulae (64.27), the equations (64.32) and (64.34) undergo a certain change (which increases with the values of ν and k). In that case, the equation (64.34) is found to differ somewhat from the differential equation of the membrane theory, whereas the equation (64.32) preserves its character as an equation of the type for symmetrical deformations of shells of revolution.

Hence it follows that the construction of the general solution of the problem under consideration by superposition of a membrane solution on a solution of the edge effect type is an approximate method which is justified only in those cases when α_1 and α_2 may be determined from the formulae for their first approximations, i.e., from the formulae (64.29). If the radii of curvature of a shell and the components of its loading are sufficiently smooth functions of the curvilinear coordinates of the middle surface, the errors incurred by employment of this method will be insignificant and they will not exceed the limits of accuracy which are customary for the theory of thin shells.

However, this statement requires one reservation. As has been noted by A. L. Gol'denweizer [8], the circular cylindrical shell belonging to the family of shells under consideration exhibits the special feature that the formulae of the first approximations must be used with greater care in this case than in the case of other shells. The fact is that for this shell the radius $R_1 = \infty$ so that the second term on the left hand side of the equation (64.34) vanishes. However, if one determines the formulae from the second, and not from the first approximation, this term will not vanish, although it has a small coefficient. This circumstance is of no importance for short cylindrical shells, while for very long shells it may change the character of the solution significantly.

§ 65. The analysis of spherical shells for arbitrary loading

In the present account of the analysis of spherical shells, it will be assumed that one is dealing with a spherical segment, and no consideration will be given to the study of shells with two edges, i.e., to frusta. As a consequence, one has to exclude from the solution terms which become infinite for $\theta = 0$. In addition, only the homogeneous problem will be considered, i.e., the case when there is no surface loading and the deformations of the shell depend only on the edge loading. For reasons to be explained later this case is of the greatest practical interest.

If the shell has the shape of a spherical segment and its deformations are arbitrary, the complex forces and complex displacements may be represented in the form of trigonometric series in the angle φ, so that it will be sufficient to consider a solution of the form

$$\tilde{T}_1 = \tilde{T}_{1,k} \cos k\varphi, \quad \tilde{T}_2 = \tilde{T}_{2,k} \cos k\varphi, \quad \tilde{S} = \tilde{S}_k \sin k\varphi, \tag{65.1}$$

$$\tilde{u} = \tilde{u}_k \cos k\varphi, \quad \tilde{v} = \tilde{v}_k \sin k\varphi, \quad \tilde{w} = \tilde{w}_k \cos k\varphi, \tag{65.2}$$

in order to make possible a study of the problem in its general form.

Assuming the system (64.19) to be homogeneous and letting $R_1 = R_2 = R$ and $\nu = 1$, one obtains

$$\begin{aligned} \Delta_k[\tilde{U}_k] + k^2 \tilde{T}^{(k)} &= 0, \\ \Delta_k[\tilde{T}^{(k)}] + i2a^2 \tilde{T}^{(k)} &= 0, \end{aligned} \tag{65.3}$$

where

$$\Delta_k(\ldots) = \frac{d^2(\ldots)}{d\theta^2} + \operatorname{cotan}\theta \frac{d(\ldots)}{d\theta} - \frac{k^2}{\sin^2\theta}(\ldots), \tag{65.4}$$

$$\tilde{U}_k = \tilde{T}_{1,k} \sin^2\theta - \frac{i}{2a^2} \sin\theta \cos\theta \frac{d\tilde{T}^{(k)}}{d\theta}, \tag{65.5}$$

$$\tilde{T}^{(k)} = \tilde{T}_{1,k} + \tilde{T}_{2,k}, \tag{65.6}$$

$$4a^4 = 12(1 - \mu^2)\frac{R^2}{\delta^2}. \tag{65.7}$$

Thus, for spherical shells, the second of the equations of the system (64.19) is found immediately, without any transformations, to contain only one unknown, namely the auxiliary function $\tilde{T}^{(k)}$.

Written out in full, this equation becomes

$$\frac{d^2\tilde{T}^{(k)}}{d\theta^2} + \operatorname{cotan}\theta \frac{d\tilde{T}^{(k)}}{d\theta} - \frac{k^2}{\sin^2\theta} \tilde{T}^{(k)} + i2a^2 \tilde{T}^{(k)} = 0. \tag{65.8}$$

It represents a particular case of the differential equation for spherical

harmonics and its general solution is

$$\tilde{T}^{(k)} = \tilde{C}_1 P_n{}^k(\cos\theta) + \tilde{C}_2 Q_n{}^k(\cos\theta), \tag{65.9}$$

where $P_n{}^k$ and $Q_n{}^k$ are spherical harmonics of the first and second kinds and in the present case the lower index is the complex number

$$n(n+1) = i2a^2. \tag{65.10}$$

However, since the spherical harmonics have not been tabulated in the region of interest for the problem under consideration, the above solution is not readily used. Therefore the equation (65.8) will be integrated by another method, namely the asymptotic method studied in §§ 54, 55.

Using the substitution

$$z = \tilde{T}^{(k)}\sqrt{\sin\theta}, \tag{65.11}$$

the equation (65.8) will first be reduced to the form

$$\frac{d^2z}{d\theta^2} - \left(\frac{4k^2-1}{4\sin^2\theta} - \frac{1}{4} - i2a^2\right)z = 0. \tag{65.12}$$

The second term in the bracket may be omitted, since it is clearly small compared with the third term. Introducing this simplification and retaining the accuracy of the first approximation, one obtains

$$z = \tilde{C}_1 e^{\beta} + \tilde{C}_2 e^{-\beta}, \tag{65.13}$$

where

$$\beta = -(1-i)a\int_{\theta_0}^{\theta}\sqrt{1 + i\frac{4k^2-1}{8a^2\sin^2\theta}}\,d\theta, \tag{65.14}$$

and the lower limit in the last integral will be identified with the angle determining the edge of the spherical segment.

In the solution (65.13), the constant C_1 must be put equal to zero, since the function e^{β} becomes infinite for $\theta = 0$. Hence, for the spherical segment,

$$\tilde{T}^{(k)} = \frac{1}{\sqrt{\sin\theta}}z = \frac{1}{\sqrt{\sin\theta}}\tilde{C}_2 e^{-\beta}. \tag{65.15}$$

The deduced solution coincides with that recommended by A. Havers [151] who evaluated the integral in the formula (65.14) and constructed the graph of the function β. However, as was pointed out later on by A. Aas Jakobson [144], for practical purposes sufficient accuracy may

be achieved more simply by taking into consideration that the function $e^{-\beta}$ will decay rapidly with the distance from the edge of the shell. On this basis, one may, firstly, neglect in the formulae (65.15) the rate of change of the factor $\frac{1}{\sqrt{\sin\theta}}$ in comparison with that of $e^{-\beta}$, i.e., one may assume that this multiplier is constant and include it in the constant of integration. Secondly, one may neglect in the integrand of (65.14) the variation of $\sin\theta$ and regard it as a constant ($\sin\theta = \sin\theta_0$) within the limits of the narrow strip in which the stresses, corresponding to the solution (65.15), will be essential.

Then one obtains for β the expression

$$\beta = (b_1 - ib_2)a\alpha, \tag{65.16}$$

where

$$\begin{aligned} b_1 &= \frac{1}{\sqrt{2}}\left\{\sqrt{\sqrt{1+\frac{(4k^2-1)^2}{64a^4\sin^4\theta_0}}+1}+\sqrt{\sqrt{1+\frac{(4k^2-1)^2}{64a^4\sin^4\theta_0}}-1}\right\}, \\ b_2 &= \frac{1}{\sqrt{2}}\left\{\sqrt{\sqrt{1+\frac{(4k^2-1)^2}{64a^4\sin^4\theta_0}}+1}-\sqrt{\sqrt{1+\frac{(4k^2-1)^2}{64a^4\sin^4\theta_0}}-1}\right\}, \end{aligned} \tag{65.17}$$

and

$$\alpha = \theta_0 - \theta \tag{65.18}$$

is the angle, measured from the edge of the segment (Fig. 95).



Fig. 95.

Differentiation with respect to this angle α is equivalent to differentiation with respect to $-\theta$.

Thus, one obtains for the auxiliary function $\tilde{T}^{(k)}$ the following final approximate expression

$$\tilde{T}^{(k)} \approx \tilde{C}e^{-(b_1-ib_2)a\alpha} = \tilde{C}e^{-\beta}, \tag{65.19}$$

which behaves similarly to those solutions which decay rapidly with the distance from the edge of the shell and which were considered in the sections devoted to symmetrical and wind loadings.

Introducing this result into the first of equations (65.3), one obtains the differential equation for the auxiliary function $\tilde{U}_k$

$$\frac{d^2\tilde{U}_k}{d\theta^2} + \operatorname{cotan}\theta\frac{d\tilde{U}_k}{d\theta} - \frac{k^2}{\sin^2\theta}\tilde{U}_k = -k^2\tilde{T}^{(k)} = -k^2\tilde{C}e^{-\beta}. \tag{65.20}$$

Since the function $\tilde{T}^{(k)}$ satisfies the equation (65.8), the particular integral of the equation (65.20) will obviously be

$$\tilde{U}_k = -\frac{i}{2a^2} k^2 \tilde{T}^{(k)} \approx -i \frac{k^2}{2a^2} \tilde{C} e^{-\beta}. \tag{65.21}$$

In order to obtain the general solution of the linear equation (65.20), one has to add to this particular integral the solutions of the homogeneous equation

$$\frac{d^2\tilde{U}_k}{d\theta^2} + \operatorname{cotan}\theta \frac{d\tilde{U}_k}{d\theta} - \frac{k^2}{\sin^2\theta} \tilde{U}_k = 0. \tag{65.22}$$

It may be verified by substitution that this equation is satisfied by

$$\tilde{U}_k = \tilde{B}_1 \tan^k \frac{\theta}{2} + \tilde{B}_2 \operatorname{cotan}^k \frac{\theta}{2}, \tag{65.23}$$

where the constant $\tilde{B}_2$ must be put equal to zero, since in the particular problem under consideration the solution must remain finite for $\theta = 0$.

Adding (65.21) and (65.23) and taking the last observation into consideration, one arrives at the following general expression for the auxiliary function $\tilde{U}_k$:

$$\tilde{U}_k = \tilde{B} \tan^k \frac{\theta}{2} - i \frac{k^2}{2a^2} \tilde{C} e^{-\beta}. \tag{65.24}$$

Thus, both auxiliary functions $\tilde{U}_k$ and $\tilde{T}_k$ have now been determined and this is equivalent to the determination of all complex forces.

Attention will now be given to the fact that the equation (65.22) coincides with the equation which was obtained from the basic differential equation of the membrane theory for spherical shells, i.e., from an equation of Chapter II, if the last equation is assumed to be homogeneous. Hence it may be said that the general solution for a spherical shell subject to edge loading of the type $\begin{pmatrix}\cos k\varphi \\ \sin k\varphi\end{pmatrix}$ may be obtained by superposition of one or the other of the two solutions:

a)
$$\tilde{T}^{(k)} = 0, \tag{65.25}$$
$$\tilde{U}^{(k)} = \tilde{B} \tan^k \frac{\theta}{2};$$

b)
$$\tilde{T}^{(k)} = \tilde{C} e^{-\beta},$$
$$\tilde{U}^{(k)} = -i \frac{k^2}{2a^2} \tilde{C} e^{-\beta} = -i \frac{k^2}{2a^2} \tilde{T}^{(k)}. \tag{65.26}$$

The first of these coincide exactly with the solutions given for the same problem by the membrane theory, while the second, expressed in terms of a rapidly decaying function, are solutions of the edge effect type.

This result has an important fundamental meaning: it shows that the solution of the homogeneous problem for spherical shells may be obtained by adding the solution of the membrane theory to a solution of the edge effect type. It has been shown in the preceding section that such a subdivision of the general solution is possible for many shells, however, only as an approximation. For spherical shells, it is obtained without any omission and it may be considered a result of the same order of accuracy as that of the initial equations of the theory of thin shells. Thus, having divided the present problem into two parts, these will now be solved separately.

a) *The solution of the form* (65.25)

Substituting the solution (65.25) into the formula (65.5), one finds

$$\tilde{T}_{1,k} = \tilde{B} \frac{\tan^k \frac{\theta}{2}}{\sin^2 \theta}. \tag{65.27}$$

After this, the condition

$$\tilde{T}^{(k)} = \tilde{T}_{1,k} + \tilde{T}_{2,k} = 0 \tag{65.28}$$

gives

$$\tilde{T}_{2,k} = -\tilde{B} \frac{1}{\sin^2 \theta} \tan^k \frac{\theta}{2}. \tag{65.29}$$

In order to obtain the last complex force $\tilde{S}$, use will be made of the formulae (51.6) and (51.11). The second of these takes for the homogeneous problem of the theory of spherical shells the form

$$k \sin \theta \tilde{S}_k = -\frac{d\tilde{U}_k}{d\theta} - i \frac{k^2}{2a^2} \tilde{T}^{(k)} \operatorname{cotan} \theta. \tag{65.30}$$

Introducing here the values of $\tilde{U}_k$ and $\tilde{T}^{(k)}$ from (65.25), one finds

$$\tilde{S}_k = -\tilde{B} \frac{1}{\sin^2 \theta} \tan^k \frac{\theta}{2}. \tag{65.31}$$

Thus, the following values of the coefficients in the formulae for the complex forces correspond to the solution of the form (65.25):

$$\tilde{T}_{1,k} = -\tilde{T}_{2,k} = -\tilde{S}_k = \tilde{B} \frac{1}{\sin^2 \theta} \tan^k \frac{\theta}{2}. \tag{65.32}$$

On the basis of this result, the equations for the complex displacements (53.5) and (53.6) for the particular case of spherical shells take the form

$$\frac{d\tilde{u}_k}{d\theta} + \tilde{w}_k = \frac{R(1+\mu)}{E\delta}\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2},$$

$$\frac{k}{\sin\theta}\tilde{v}_k + \tilde{u}_k\operatorname{cotan}\theta + \tilde{w}_k = -\frac{R(1+\mu)}{E\delta}\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2}; \quad (65.33)$$

$$\frac{d\tilde{v}_k}{d\theta} - \tilde{v}_k\operatorname{cotan}\theta - \frac{k}{\sin\theta}\tilde{u}_k = -\frac{2(1+\mu)R}{E\delta}\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2},$$

$$-\frac{d^2\tilde{w}_k}{d\theta^2} + \frac{d\tilde{u}_k}{d\theta} = -\frac{R}{E\delta}i2a^2\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2},$$

(65.34)

$$\frac{k^2}{\sin^2\theta}\tilde{w}_k - \operatorname{cotan}\theta\frac{d\tilde{w}_k}{d\theta} + \frac{k}{\sin\theta}\tilde{v}_k + \tilde{u}_k\operatorname{cotan}\theta = \frac{R}{E\delta}i2a^2\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2},$$

$$\frac{d}{d\theta}\left(\frac{k}{\sin\theta}\tilde{w}_k\right) + \frac{d\tilde{v}_k}{d\theta} - \tilde{v}_k\operatorname{cotan}\theta - \frac{k}{\sin\theta}\tilde{u}_k = \frac{R}{E\delta}i2a^2\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2}.$$

On the basis of (65.33), the relations (65.34) may be somewhat simplified, after which they become

$$\frac{d^2\tilde{w}_k}{d\theta^2} + \tilde{w}_k = i2a^2\frac{R}{E\delta}\left(1 - \frac{i(1+\mu)}{2a^2}\right)\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2},$$

$$\frac{k^2}{\sin^2\theta}\tilde{w}_k - \operatorname{cotan}\theta\frac{d\tilde{w}_k}{d\theta} - \tilde{w}_k = i2a^2\frac{R}{E\delta}\left(1 - i\frac{1+\mu}{2a^2}\right)\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2}, \quad (65.35)$$

$$k\frac{d}{d\theta}\left(\frac{1}{\sin\theta}\tilde{w}_k\right) = i2a^2\frac{R}{E\delta}\left(1 - i\frac{1+\mu}{a^2}\right)\tilde{B}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2}.$$

Subtracting the second equation from the first, one finds

$$\frac{d^2\tilde{w}_k}{d\theta^2} + \operatorname{cotan}\theta\frac{d\tilde{w}_k}{d\theta} - \frac{k^2}{\sin^2\theta}\tilde{w}_k + 2\tilde{w}_k = 0. \quad (65.36)$$

Hence, as may be verified by substitution,

$$\tilde{w}_k = \tilde{D}_1(k + \cos\theta)\tan^k\frac{\theta}{2} + \tilde{D}_2(k - \cos\theta)\operatorname{cotan}^k\frac{\theta}{2}, \quad (65.37)$$

where $\tilde{D}_1$ and $\tilde{D}_2$ are constants of integration. In order to exclude terms which become infinite for $\theta = 0$, one must put here $\tilde{D}_2 = 0$.

The second constant $\tilde{D}_1$ must be determined in such a manner that the formula (65.37) will conform with all the three equations (65.35). Substituting (65.37) into these equations, one arrives at the following three equalities

$$\begin{aligned} k(k^2-1)\tilde{D}_1 &= i2a^2\frac{R}{E\delta}\left(1-i\frac{1+\mu}{2a^2}\right)\tilde{B}, \\ k(k^2-1)\tilde{D}_1 &= i2a^2\frac{R}{E\delta}\left(1-i\frac{1+\mu}{2a^2}\right)\tilde{B}, \\ k(k^2-1)\tilde{D}_1 &= i2a^2\frac{R}{E\delta}\left(1-i\frac{1+\mu}{a^2}\right)\tilde{B}. \end{aligned} \tag{65.38}$$

The first two equalities are seen to be completely consistent, while the third contradicts them to the extent of a term of order $\frac{1}{2a^2}$ in comparison with unity, i.e., a term of order $\frac{\delta}{R}$. This inconsistency does not occur suddenly, since the reader has already been warned (§ 16, § 40) that contradictions of the order $\frac{\delta}{R}$ in comparison with unity would be quite possible in the formulae for the complex displacements as a result of the approximate nature of the reasoning, on the basis of which these formulae were generalized in Chapter I to the case $\mu \neq 0$. Therefore it is impossible to guarantee terms of order $\frac{\delta}{R}$ in (65.38). Hence the second terms on the right hand sides of the formulae (65.38) must be neglected which gives

$$\frac{R}{E\delta}\tilde{B} = -i\frac{k(k^2-1)}{2a^2}\tilde{D}_1 = -i\frac{k(k^2-1)}{2a^2}\tilde{D}. \tag{65.39}$$

In what follows, the constant $\tilde{D}$ will be used instead of the constant $\tilde{B}$. Substituting the expression for $\tilde{w}_k$ into the formulae (65.33), one finds

$$\begin{aligned} \frac{d\tilde{u}_k}{d\theta} &= -\tilde{D}\left\{i\frac{(1+\mu)k(k^2-1)}{2a^2}\cdot\frac{1}{\sin^2\theta}+k+\cos\theta\right\}\tan^k\frac{\theta}{2}, \\ \frac{k}{\sin\theta}\tilde{v}_k+\tilde{u}_k\operatorname{cotan}\theta &= -\tilde{D}\left\{-i\frac{(1+\mu)k(k^2-1)}{2a^2}\frac{1}{\sin^2\theta}+k+\cos\theta\right\}\tan^k\frac{\theta}{2}, \\ \frac{d\tilde{v}_k}{d\theta}-\tilde{v}_k\operatorname{cotan}\theta-\frac{k}{\sin\theta}\tilde{u}_k &= i(1+\mu)\frac{k(k^2-1)}{a^2}\tilde{D}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2}. \end{aligned} \tag{65.40}$$

The first of these formulae gives

$$\tilde{u}_k = -\tilde{D}\left[i\frac{(1+\mu)k(k+\cos\theta)}{2a^2\sin\theta} + \sin\theta\right]\tan^k\frac{\theta}{2} + \tilde{C}, \qquad (65.41)$$

after which one finds from the second formula

$$\tilde{v}_k = \tilde{D}\left\{i\frac{1+\mu}{2a^2}\left[\frac{k(k+\cos\theta)}{\sin\theta} - \sin\theta\right] - \sin\theta\right\}\tan^k\frac{\theta}{2} - \tilde{C}\frac{\sin\theta}{k}. \qquad (65.42)$$

Substituting these expressions for $\tilde{u}_k$ and $\tilde{v}_k$ into the third of the relations (65.40), one arrives at the relation

$$\tilde{C}\frac{k}{\sin\theta} = 0, \qquad (65.43)$$

whence it follows that the constant $\tilde{C}$ must be put equal to zero in order that the deduced formulae will be consistent with all the three relations (65.40).

Thus, for the complex forces and complex displacements corresponding to the solution of the form (65.25) one may write

$$\begin{aligned}
\tilde{u}_k &= -\tilde{D}\left[\sin\theta + i\frac{1+\mu}{2a^2}\,\frac{k(k+\cos\theta)}{\sin\theta}\right]\tan^k\frac{\theta}{2},\\
\tilde{v}_k &= -\tilde{D}\left\{\sin\theta - i\frac{1+\mu}{2a^2}\left[\frac{k(k+\cos\theta)}{\sin\theta} - \sin\theta\right]\right\}\tan^k\frac{\theta}{2},\\
\tilde{w}_k &= \tilde{D}(k+\cos\theta)\tan^k\frac{\theta}{2},\\
\tilde{T}_{1,k} &= -i\frac{E\delta}{R}\,\frac{k(k^2-1)}{2a^2}\,\tilde{D}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2},\\
\tilde{T}_{2,k} = \tilde{S}_k &= i\frac{E\delta}{R}\,\frac{k(k^2-1)}{2a^2}\,\tilde{D}\frac{1}{\sin^2\theta}\tan^k\frac{\theta}{2}.
\end{aligned} \qquad (65.44)$$

Instead of the complex constant $\tilde{D}$ now introduce two real constants B_1 and B_2, defined by

$$\tilde{D} = B_1 - \frac{i2a^2}{1+\mu}B_2.$$

Separating real and imaginary parts, in the formulae (65.44) one obtains the following expressions for the coefficients of $\begin{pmatrix}\sin k\varphi\\ \cos k\varphi\end{pmatrix}$ in the

formulae for the displacements, forces and moments:

$$
\begin{aligned}
u_k &= \operatorname{Re}(\tilde{u}_k) = -\left\{B_1 \sin\theta + B_2 \frac{k(k+\cos\theta)}{\sin\theta}\right\} \tan^k \frac{\theta}{2}, \\
v_k &= \operatorname{Re}(\tilde{v}_k) = -\left\{B_1 \sin\theta - B_2 \left[\frac{k(k+\cos\theta)}{\sin\theta} - \sin\theta\right]\right\} \tan^k \frac{\theta}{2}, \\
w_k &= \operatorname{Re}(\tilde{w}_k) = B_1(k+\cos\theta) \tan^k \frac{\theta}{2}, \qquad (65.45) \\
T_{1,k} &= \operatorname{Re}(\tilde{T}_{1,k}) = -\frac{E\delta}{R(1+\mu)} B_2 \frac{k(k^2-1)}{\sin^2\theta} \tan^k \frac{\theta}{2}, \\
S_{1,k} &= T_{2,k} = -T_{1,k}, \\
M_{1,k} &= -\frac{E\delta^3}{12(1+\mu)R^2} B_1 \frac{k(k^2-1)}{\sin^2\theta} \tan^k \frac{\theta}{2}, \\
M_{1,k} &= -H_k = -M_{2,k}.
\end{aligned}
$$

It follows from these expressions that for $B_1 = 0$

$$M_1 = M_2 = H = 0,$$

and, vice versa, for $B_2 = 0$,

$$T_1 = T_2 = S = 0.$$

Hence it is clear that in (65.45) the terms, multiplied by B_2, represent a pure membrane solution and the terms, multiplied by B_1, a pure moment solution, i.e., solutions which are not accompanied respectively by bending or stretching of the middle surface. As has been stated in Chapter II, the equations of the membrane theory involve side by side with the first also those of the second type, so that the above result is not unexpected.

The above reasoning may be insufficiently logical for the attentive reader, since, in order to satisfy the relations (65.35), terms of order $\frac{1}{2a^2}$ have been neglected in comparison with unity, while terms of the same order have been included in the formulae (65.44) for the purpose of satisfying the relations (65.33). Nevertheless, there is no inconsistency in this procedure, because the relations (65.34) may be handled more freely than the relations (65.33), the left hand sides of which, as a rule, contain small differences of almost equal numbers.

If, instead of the formula (65.39), the constant $\tilde{D}_1$ had been determined

by use of any of the formulae (16.38) which differ from the former by a term of order $\frac{1}{2a^2}$, then, after substitution of the thus defined expression for $\tilde{w}_k$ into the relations (65.33), one could establish that the formulae for $\tilde{u}_k$ and $\tilde{v}_k$ would only change by terms of order $\frac{1}{4a^4}$, i.e., by terms of order $\frac{\delta^2}{R^2}$.

Thus, small errors admitted into the relations (65.34) enter into the relations (65.33) at an essentially reduced scale. This statement is of fundamental value and may be regarded as a general rule for handling the formulae connecting the complex forces and complex displacements.

In fact, inconsistencies which may occur between the formulae (53.5) and (53.6) must be removed at the expense of modifications to the second group of formulae, and not to the first.

b) *Solution of the form* (65.26)

Substituting (65.26) into the formula (65.5), one finds

$$\tilde{T}_{1,k} = \frac{i}{2a^2}\left[\operatorname{cotan}\theta\,\frac{d\tilde{T}^{(k)}}{d\theta} - \frac{k^2}{\sin^2\theta}\,\tilde{T}^{(k)}\right], \tag{65.46}$$

whence

$$\tilde{T}_{2,k} = \tilde{T}^{(k)} - \tilde{T}_1{}^{(k)} = \tilde{T}^{(k)} - \frac{i}{2a^2}\left[\operatorname{cotan}\theta\,\frac{d\tilde{T}^{(k)}}{d\theta} - \frac{k^2}{\sin^2\theta}\,\tilde{T}^{(k)}\right]. \tag{65.47}$$

Further, the formulae (65.30) and (65.26) give

$$S^{(k)} = \frac{i}{2a^2}\,\frac{k}{\sin\theta}\left[\frac{d\tilde{T}^{(k)}}{d\theta} - \tilde{T}^{(k)}\operatorname{cotan}\theta\right]. \tag{65.48}$$

After this, one finds for the determination of the complex displacements corresponding to the solution of the form (65.26) the six relations

$$\frac{d\tilde{u}_k}{d\theta} + \tilde{w}_k = \frac{R}{E\delta}\left[-\mu\tilde{T}^{(k)} + (1+\mu)\,\frac{i}{2a^2}\left(\operatorname{cotan}\theta\,\frac{d\tilde{T}^{(k)}}{d\theta} - \frac{k^2}{\sin^2\theta}\,\tilde{T}^{(k)}\right)\right],$$

$$\frac{k}{\sin\theta}\,\tilde{v}_k + \tilde{u}_k\operatorname{cotan}\theta + \tilde{w}_k = \tag{65.49}$$

$$= \frac{R}{E\delta}\left[\tilde{T}^{(k)} - (1+\mu)\,\frac{i}{2a^2}\left(\operatorname{cotan}\theta\,\frac{d\tilde{T}^{(k)}}{d\theta} - \frac{k^2}{\sin^2\theta}\,\tilde{T}^{(k)}\right)\right].$$

$$\frac{d\tilde{v}_k}{d\theta}-\tilde{v}_k\operatorname{cotan}\theta-\frac{k}{\sin\theta}\tilde{u}_k=\frac{2(1+\mu)R}{E\delta}\frac{i}{2a^2}\frac{k}{\sin\theta}\left[\frac{d\tilde{T}^{(k)}}{d\theta}-\tilde{T}^{(k)}\operatorname{cotan}\theta\right],$$

$$-\frac{d^2\tilde{w}_k}{d\theta^2}+\frac{d\tilde{u}_k}{d\theta}=i2a^2\frac{R}{E\delta}\left[\tilde{T}^{(k)}-\frac{i}{2a^2}\left(\operatorname{cotan}\theta\frac{d\tilde{T}^{(k)}}{d\theta}-\frac{k^2}{\sin^2\theta}\tilde{T}^{(k)}\right)\right],$$

$$\frac{k^2}{\sin^2\theta}\tilde{w}_k-\operatorname{cotan}\theta\frac{d\tilde{w}_k}{d\theta}+\frac{k}{\sin\theta}\tilde{v}_k+\tilde{u}_k\operatorname{cotan}\theta= \tag{65.50}$$

$$=-\frac{R}{E\delta}\left(\operatorname{cotan}\theta\frac{d\tilde{T}^{(k)}}{d\theta}-\frac{k^2}{\sin^2\theta}\tilde{T}^{(k)}\right),$$

$$k\frac{d}{d\theta}\left(\frac{\tilde{w}_k}{\sin\theta}\right)+\frac{d\tilde{v}_k}{d\theta}-\tilde{v}_k\operatorname{cotan}\theta-\frac{k}{\sin\theta}\tilde{u}_k=$$

$$=\frac{k}{\sin\theta}\frac{R}{E\delta}\left(\frac{d\tilde{T}^{(k)}}{d\theta}-\tilde{T}^{(k)}\operatorname{cotan}\theta\right).$$

It will be shown that the first three of these equations are satisfied exactly and the remaining three approximately by letting

$$\tilde{u}_k=-\frac{i(1+\mu)}{2a^2}\frac{R}{E\delta}\frac{d\tilde{T}^{(k)}}{d\theta},\qquad \tilde{v}_k=\frac{i(1+\mu)}{2a^2}\frac{R}{E\delta}\frac{k}{\sin\theta}\tilde{T}^{(k)}, \tag{65.51}$$

$$\tilde{w}_k=\frac{R}{E\delta}\tilde{T}^{(k)}.$$

Actually, substituting (65.51) into the formulae (65.49), it is found that the second and third of these equations become identities, while the first is converted into an equation for $\tilde{T}^{(k)}$ which coincides with the earlier equation (65.8) for the same function.

The relations (65.50), on substitution from (65.51), take the form

$$-\left(1+i\frac{1+\mu}{2a^2}\right)\frac{d^2\tilde{T}^{(k)}}{d\theta^2}=i2a^2\tilde{T}^{(k)}+\operatorname{cotan}\theta\frac{d\tilde{T}^{(k)}}{d\theta}-\frac{k^2}{\sin^2\theta}\tilde{T}^{(k)},$$

$$\left(1+i\frac{1+\mu}{2a^2}\right)\left(\operatorname{cotan}\theta\frac{d\tilde{T}^{(k)}}{d\theta}-\frac{k^2}{\sin^2\theta}\tilde{T}^{(k)}\right)= \tag{65.52}$$

$$=\operatorname{cotan}\theta\frac{d\tilde{T}^{(k)}}{d\theta}-\frac{k^2}{\sin^2\theta}\tilde{T}^{(k)},$$

$$\left(1+i\frac{1+\mu}{a^2}\right)\frac{k}{\sin\theta}\left(\frac{d\tilde{T}^{(k)}}{d\theta}-\tilde{T}^{(k)}\operatorname{cotan}\theta\right)=\frac{k}{\sin\theta}\left[\frac{d\tilde{T}^{(k)}}{d\theta}-\tilde{T}^{(k)}\operatorname{cotan}\theta\right],$$

whence it follows that for the above substitution the first relation

coincides with the equation (65.8) exactly to an accuracy of terms of order $\frac{1}{2a^2}$ in comparison with unity, while the other two relations are satisfied identically to the same degree of accuracy. However, as has already been noted, a similar error must be considered to be admissible and even unavoidable in the second group of formulae for the complex displacements.

Now, having expressed all the complex forces and complex displacements in terms of

$$\tilde{T}^{(k)} = \tilde{C}e^{-\beta} = (C_1 - iC_2)\,e^{-(b_1-ib_2)a\alpha}, \tag{65.53}$$

where C_1 and C_2 are two real constants, the following formulae may be obtained for the coefficients $u_k, \ldots, H_k$:

$$u_k = \frac{R}{E\delta}\frac{(1+\mu)}{2a}[-(C_1b_2+C_2b_1)\cos b_2a\alpha+(C_1b_1-C_2b_2)\sin b_2a\alpha]\,e^{-b_1a\alpha},$$

$$v_k = -\frac{R}{E\delta}\frac{1+\mu}{2a^2}\frac{k}{\sin\theta}[-C_2\cos b_2a\alpha + C_1\sin b_2a\alpha]\,e^{-b_1a\alpha},$$

$$w_k = \frac{R}{E\delta}(C_1\cos b_2a\alpha + C_2\sin b_2a\alpha)\,e^{-b_1a\alpha},$$

$$T_{1,k} = \frac{1}{2a}\Big\{[(C_1b_2+C_2b_1)\cos b_2a\alpha-(C_1b_1-C_2b_2)\sin b_2a\alpha]\operatorname{cotan}\theta+$$

$$+\frac{k^2}{a\sin^2\theta}[-C_2\cos b_2a\alpha+C_1\sin b_2a\alpha]\Big\}e^{-b_1a\alpha},$$

$$T_{2,k} = \Big\{C_1\cos b_2a\alpha+C_2\sin b_2a\alpha+\frac{k^2}{2a^2\sin^2\theta}[C_2\cos b_2a\alpha-$$

$$-C_1\sin b_2a\alpha]\Big\}e^{-b_1a\alpha}, \tag{65.54}$$

$$S_k = \frac{1}{2a}\frac{k}{\sin\theta}[(C_1b_2+C_2b_1)\cos b_2a\alpha-(C_1b_1-C_2b_2)\sin b_2a\alpha]\,e^{-b_1a\alpha},$$

$$M_{1,k} = \frac{R}{2a^2}\Big\{C_2\cos b_2a\alpha-C_1\sin b_2a\alpha-\frac{1-\mu}{2a^2}\frac{k^2}{\sin^2\theta}(C_1\cos b_2a\alpha+$$

$$+C_2\sin b_2a\alpha]\Big\}e^{-b_1a\alpha},$$

$$M_{2,k} = \frac{R}{2a^2}\left\{\mu(C_2\cos b_2 a\alpha - C_1\sin b_2 a\alpha) + \right.$$
$$\left. + \frac{1-\mu}{2a^2}\,\frac{k^2}{\sin^2\theta}\,(C_1\cos b_2 a\alpha + C_2\sin b_2 a\alpha)\right\} e^{-b_1 a\alpha},$$
$$H_k = \frac{1-\mu}{4a^3}\,R\,\frac{k}{\sin\theta}\,[(C_1 b_1 - C_2 b_2)\cos b_2 a\alpha + \tag{65.54}$$
$$+ (C_1 b_2 + C_2 b_1)\sin b_2 a\alpha]\, e^{-b_1 a\alpha}.$$

In these formulae, α denotes the angle measured from the edge of the shell and the variations in $\sin\theta$ and $\operatorname{cotan}\theta$ must be disregarded by putting $\sin\theta = \sin\theta_0$, $\operatorname{cotan}\theta = \operatorname{cotan}\theta_0$, since this simplification was employed during the deduction of the formula (65.16). Adding the expressions (65.54) to the expressions (65.45), one obtains the general solution of the homogeneous problem for shells, having the shape of spherical segments and subject to edge loads obeying the law

$$\begin{pmatrix}\cos k\varphi \\ \sin k\varphi\end{pmatrix}.$$

These results are readily generalized to the case of a spherical shell bounded by two parallel circles, i.e., having the form of a spherical frustum. For this purpose, one only has to retain in the formulae (65.13) and also in (65.23) the terms which become infinite for $\theta = 0$ and to repeat the above manipulations.

Similarly, the obtained solution may be extended to the case when, in addition to edge loads, the shell is subject to surface loading. For this purpose one has to add to the sum of the formulae (65.45) and (65.54) terms corresponding to the particular integral. These are readily determined if the components of the surface loading are expanded in series of spherical harmonics. However, this question will not be discussed here further; in practice, surface loadings are either of the symmetrical or of the wind type, and these two particular cases have been studied above in sufficient detail.

As far as edge loads are regarded, they may exhibit a much greater variety. The group of practical problems the solution of which necessitates the study of values "k" > 2 includes, for example, the analysis of spherical domes supported by columns.

§ 66. The design of catenoid shells

As far as it is known, catenoid shells have no definite technical applications. However, they will be discussed here, although only briefly,

as an example of shells of revolution of negative Gaussian curvature which, as has already been shown in Chapter II, by this very property differ essentially from shells of positive Gaussian curvature. In view of this circumstance, it will be expedient to carry out the solution even though it is for one of the shells of this class. The reason for selecting the catenoid as such an example is that for this shell the equations for shells of revolution may be integrated in terms of elementary functions.

The catenoid shell belongs to the family considered in § 64, and it is obtained from it for $\nu = -1$. Its radii of curvature, as has already been indicated, can be expressed in terms of θ by means of the formulae

$$R_2 = -R_1 = \frac{r_0}{\sin^2\theta}, \tag{66.1}$$

where r_0 is the radius of curvature at the equator and at the same time its smallest radius of curvature.

For this shell, the differential equations (64.23), after putting in them the components of the surface loading equal to zero, take the form

$$\begin{aligned} G_k(W_1) + i2b^2\alpha_1 W_1 &= 0, \\ G_k(W_2) + i2b^2\alpha_2 W_2 &= 0, \end{aligned} \tag{66.2}$$

where in this case

$$G_k(\ldots) = \sin^3\theta \frac{d}{d\theta}\left[\frac{1}{\sin\theta}\frac{d(\ldots)}{d\theta}\right] - k^2(\ldots), \tag{66.3}$$

$$4b^4 = 12(1-\mu)^2\frac{r_0^2}{\delta^2}, \tag{66.4}$$

$$W_1 = \tilde{U}_k + \frac{\alpha_1}{2}\tilde{T}^{(k)}, \quad W_2 = \tilde{U}_k + \frac{\alpha^2}{2}\tilde{T}^{(k)}, \tag{66.5}$$

$$\tilde{U}_k = \tilde{T}_{1,k} + \frac{i}{2b^2}\cos\theta\sin\theta\frac{d\tilde{T}^{(k)}}{d\theta}, \tag{66.6}$$

$$\begin{aligned} \alpha_1 &= \frac{1}{2}\left(1 + \sqrt{1 + i\frac{4k^2}{b^2} - \frac{4k^2}{b^4}}\right), \\ \alpha_2 &= \frac{1}{2}\left(1 - \sqrt{1 + i\frac{4k^2}{b^2} - \frac{4k^2}{b^4}}\right). \end{aligned} \tag{66.7}$$

Since both the equations (66.2) are of the same type, it is sufficient to integrate one of them, in order to be able to write down immediately the solution for the other equation. Therefore, attention will be focussed here on the first of these equations.

Introducing the substitution

$$Y = \frac{W_1}{\sin\theta}, \tag{66.8}$$

one finds after certain manipulations

$$\sin\theta \frac{d}{d\theta}\left(\sin\theta \frac{dY}{d\theta}\right) + (i2b^2\alpha_1 - k^2 - 1)Y = 0. \tag{66.9}$$

Now using the new independent variable

$$x = \ln\left(\tan\frac{\theta}{2}\right), \tag{66.10}$$

this equation will be reduced to the form

$$\frac{d^2Y}{dx^2} + (i2b^2\alpha_1 - k^2 - 1)Y = 0, \tag{66.11}$$

whence it is obvious that

$$Y = \tilde{C}_1\left(\tan\frac{\theta}{2}\right)^{m_1} + \tilde{C}_2\left(\operatorname{cotan}\frac{\theta}{2}\right)^{m_1}, \tag{66.12}$$

where

$$m_1 = \sqrt{k^2 + 1 - i2b^2\alpha_1}. \tag{66.13}$$

Now reverting to the dependent variable W_1, one finds

$$W_1 = \left[\tilde{C}_1\left(\tan\frac{\theta}{2}\right)^{m_1} + \tilde{C}_2\left(\operatorname{cotan}\frac{\theta}{2}\right)^{m_1}\right]\sin\theta. \tag{66.14}$$

By a quite similar reasoning, one may find for W_2

$$W_2 = \left[\tilde{C}_1\left(\tan\frac{\theta}{2}\right)^{m_2} + \tilde{C}_2\left(\operatorname{cotan}\frac{\theta}{2}\right)^{m_2}\right]\sin\theta, \tag{66.15}$$

where

$$m_2 = \sqrt{k^2 + 1 - i2b^2\alpha_2}.$$

The quantities α_1 and α_2 will now be determined from the formulae for the second approximation (§ 64)

$$\begin{aligned} \alpha_1 &= 1 + i\frac{k^2}{b^2}, \\ \alpha_2 &= -i\frac{k^2}{b^2}\left[1 - i\frac{k^2 - 1}{b^2}\right], \end{aligned} \tag{66.16}$$

whence

$$m_1 \approx \sqrt{-i2b^2 + 1 + 3k^2},$$

$$m_2 \approx \sqrt{1 - k^2 + i2\frac{k^2(k^2-1)}{b^2}} \approx \sqrt{1-k^2}\sqrt{1 - i\frac{2k^2}{b^2}}. \tag{66.17}$$

If the ratio $\frac{k^2}{b^2}$ is small compared with unity, a further simplification becomes possible after which the formulae (66.17) take the form

$$m_1 \approx -(1-i)b,$$
$$m_2 \approx i\sqrt{k^2-1}. \tag{66.18}$$

For this smallest degree of accuracy, the integrals corresponding to the exponent m_1 will be the rapidly varying part of the solution (edge effect) and the integrals corresponding to the exponent m_2 will coincide with the solution of the homogeneous problem of the membrane theory for the catenoid. This discussion effectively exhausts the question of the integration of the equations for the catenoid shell, apart from purely technical details.

§ 67. Approximate theory of integration for any shells of revolution subject to arbitrary loading

Reverting to § 64 and considering the formulae for the first approximations to the parameters α_1 and α_2, it is seen that for this degree of accuracy the parameter α_2 is obtained independently of ν, i.e., of the shape of the shell. This fact justifies the statement that not only for shells of the family (64.1) one may arrive at a division of the system into two independent second order equations, but also for shells of revolution of arbitrary shape. However, there will be one difference, namely, that for shells of the family (64.1) this division may be achieved without omitting any terms in the initial system of equations, whereas for arbitrary shells it can only be realized as a first approximation. In § 64, the conditions have been explained under which the first approximation gives good results. These conditions are sufficient smoothness of the shell contour and sufficient smoothness of the loading. In mathematical terms, the last condition reduces to the requirement that the parameter $\frac{ck^2}{R}$ must be small compared with unity. Fulfillment of the two stated conditions guarantees the possibility for the use of the formulae of the first approximation with relatively small errors, except

in the special case of the circular cylindrical shell for which a third factor, the length of the cylinder, may play an essential role.

It will now be assumed that these conditions are fulfilled. Then, for shells of revolution of arbitrary shape, one may write down the approximate differential equation

$$B_k(\tilde{W}_2) = f_k(\theta) + ik^2 R_2 q_n, \tag{67.1}$$

where

$$\tilde{W}_2 = \tilde{U}_k + ick^2 \tilde{T}^{(k)}, \tag{67.2}$$

$$B_k(\ldots) = \frac{1}{R_1 R_2 \sin\theta} \frac{d}{d\theta}\left[\frac{R_2^2 \sin\theta}{R_1} \frac{d(\ldots)}{d\theta}\right] - \frac{k^2}{R_1 \sin^2\theta}(\ldots). \tag{67.3}$$

The left hand side of this equation agrees exactly with the left hand side of the equation (24.4), i.e., with the left hand side of the basic differential equation of the membrane theory of shells of revolution, in view of which the auxiliary function will be

$$\tilde{W}_2 = \tilde{C}_1 \Phi_1 + \tilde{C}_2 \Phi_2 + \tilde{W}_2', \tag{67.4}$$

where Φ_1 and Φ_2 are two linearly independent integrals of the homogeneous membrane equation

$$B_k(\Phi) = 0, \tag{67.5}$$

and $\tilde{W}_2'$ is a particular solution of the equation.

The last may always be determined as soon as one knows Φ_1 and Φ_2.

The problem of the solution of the equation (67.5) has been considered in detail in Chapter II, in view of which there will be no need to repeat it here. It will only be recalled that for shells formed by rotation of second order curves the equation may be integrated by quadratures.

It will now be assumed that the general solution of the equation (67.1) has been obtained and that $\tilde{W}_2$ is a known function of θ. Expressing $\tilde{U}_k$ in terms of $\tilde{W}_2$ and the as yet unknown function $\tilde{T}^{(k)}$ and substituting this expression into the second of the equations (52.3), one obtains for $\tilde{T}^{(k)}$ the following linear second order differential equation:

$$G_k[\tilde{T}^{(k)}] + \frac{i}{c}\left[1 - i\frac{ck^2}{\sin^2\theta}\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\right]\tilde{T}^{(k)} = \\ = \frac{i}{c}\left[R_2 q_{n,k} - \frac{1}{\sin^2\theta}\left(\frac{1}{R_1} - \frac{1}{R_2}\right)\tilde{W}_2\right], \tag{67.6}$$

or, in expanded form,

$$\frac{d^2\tilde{T}^{(k)}}{d\theta^2}+\left[\left(2\frac{R_1}{R_2}-1\right)\operatorname{cotan}\theta-\frac{1}{R_1}\frac{dR_1}{d\theta}\right]\frac{d\tilde{T}^{(k)}}{d\theta}+$$
$$+\frac{k^2}{\sin^2\theta}\frac{R_1}{R_2}\left(1-2\frac{R_1}{R_2}\right)\tilde{T}^{(k)}+i\frac{R_1^2}{R_{2c}}\tilde{T}^{(k)}=$$
$$=i\frac{R_1^2}{R_{2c}}\left[R_2q_{n,k}-\frac{1}{\sin^2\theta}\left(\frac{1}{R_1}-\frac{1}{R_2}\right)\tilde{W}_2\right]. \quad (67.7)$$

For $k=0$, this equation becomes the equation (54.5), and for $k=1$ the equation (62.14). In other words, the equation includes as special cases the differential equations of shells of revolution subject to symmetrical or wind loadings. Hence, clearly, the same convenient approximate methods of integration will be completely applicable to this equation, which have been developed above for the equations (54.5) and (62.16).

In particular, if the right hand side of the equation (67.7) is a function which does not increase significantly on differentiation, one may take as its particular integral the expression

$$\tilde{T}_k'=R_2q_{n,k}-\frac{1}{\sin^2\theta}\left(\frac{1}{R_1}-\frac{1}{R_2}\right)\tilde{W}_2. \quad (67.8)$$

In order to obtain its general solution, one has to add to the result (67.8) all linearly independent integrals of the homogeneous equation

$$\frac{d^2\tilde{T}^{(k)}}{d\theta^2}+\left[\left(2\frac{R_1}{R_2}-1\right)\operatorname{cotan}\theta-\frac{1}{R_1}\frac{dR_1}{d\theta}\right]\frac{d\tilde{T}^{(k)}}{d\theta}+$$
$$+\frac{k^2}{\sin^2\theta}\frac{R_1}{R_2}\left(1-2\frac{R_1}{R_2}\right)\tilde{T}^{(k)}+i\frac{R_1^2}{R_{2c}}\tilde{T}^{(k)}=0. \quad (67.9)$$

These integrals will be rapidly changing functions of the angle θ so that it will not be out of place to determine them by use of asymptotic methods.

Taking this into consideration, let

$$z=\frac{R_2\sqrt{\sin\theta}}{\sqrt{R_1}}\tilde{T}^{(k)}, \quad (67.10)$$

after which the equation (65.9) takes the form

$$\frac{d^2z}{d\theta^2}+\left\{i\frac{R_1^2}{R_{2c}}+\frac{1}{2R_1}\frac{d^2R_1}{d\theta^2}+\frac{3}{4}\frac{1}{R_1^2}\left(\frac{dR_1}{d\theta}\right)^2-\frac{\operatorname{cotan}\theta}{2R_1}\frac{dR_1}{d\theta}+\right.$$
$$\left.+\frac{R_1}{R_2}\frac{1}{\sin^2\theta}-\frac{2+\cos^2\theta}{4\sin^2\theta}+\frac{k^2}{\sin^2\theta}\frac{R_1}{R_2}\left(1-2\frac{R_1}{R_2}\right)\right\}z=0. \quad (67.11)$$

Agreeing to neglect terms of order $\sqrt{\frac{\delta}{R}}$ compared with unity and not to consider points in the neighbourhood of the points $\theta = 0$ and $\theta = \pi$, one obtains the approximate solution

$$z = \tilde{C}_1 e^{\beta} + \tilde{C}_2 e^{-\beta}, \tag{67.12}$$

where

$$\beta = \int_{\theta_0}^{\theta} \sqrt{-i\frac{R_1^2}{R_2 c} - \frac{k^2}{\sin^2\theta}\frac{R_1}{R_2}\left(1 - 2\frac{R_1}{R^2}\right)}\, d\theta =$$

$$= -\frac{1}{\sqrt{2}}(1-i)\int_{\theta_0}^{\theta} \frac{R_1}{\sqrt{R_2 c}} \sqrt{1 - i\frac{k^2}{\sin^2\theta}\frac{c}{R_1}\left(1 - 2\frac{R_1}{R_2}\right)}\, d\theta. \tag{67.13}$$

Attention will now be given to the reasons for retaining in the formula (67.13) the underlined term which by virtue of the first of the above two conditions for the applicability of the stated approximate solutions must be small in comparison with unity.

The fact is that, if it is desired to obtain a solution with an error of order not exceeding $\sqrt{\frac{\delta}{R}}$ in comparison with unity, one is justified in neglecting only terms of order $\frac{\delta}{R}$ in the square bracket of equation (67.1). Meanwhile, the last but one term being small, may all the same (for $k > 2$) be more significant than all the preceding terms in the same bracket. In fact, this is the reason why it must be retained. At the same time, one may neglect in the underlined term of (67.13), on the basis of its true character, the variations of R_1, R_2 and $\sin\theta$, putting these functions equal to their edge values, if the shell has a single edge $\theta = \theta_0$, or equal to the average edge value, if the shell has two edges $\theta = \theta_0$ and $\theta = \theta_1$.

As a result, one obtains for β the following approximate expression:

$$\beta = -\frac{(b_1 - ib_2)}{\sqrt{2}}\int_{\theta_0}^{\theta} \frac{R_1 d\theta}{\sqrt{R_2 c}} = \frac{(b_1 - ib_2)}{\sqrt{2}}\int_0^s \frac{ds}{\sqrt{R_2 c}}, \tag{67.14}$$

where

$$b_1 \approx 1 - \frac{k^2}{2\sin^2\theta_0}\cdot\frac{c}{R_1^0}\left(1 - 2\frac{R_1^0}{R_2^0}\right),$$

$$b_2 \approx 1 + \frac{k^2}{2\sin^2\theta_0}\cdot\frac{c}{R_1^0}\left(1 - 2\frac{R_1^0}{R_2^0}\right), \tag{67.15}$$

and s is the arc length of the meridian of the shell, measured from one of its edges.

For practical purposes, the formula (67.14) may be written with sufficient accuracy in the form

$$\beta = \frac{b_1 - ib_2}{\sqrt{2R_2 c}}\, s. \tag{67.16}$$

If the shell has only one edge and the point $\theta = 0$ belongs to its middle surface, one must put $\tilde{C}_1 = 0$ in the solution (67.12), since the corresponding integral for a more rigorous study of the problem would become infinite for $\theta = 0$.

Now, when the auxiliary functions $\tilde{T}^{(k)}$ and $\tilde{U}^{(k)}$ are known and determined by the formulae

$$\begin{aligned} \tilde{T}^{(k)} &= \tilde{C}_1 e^{\beta} + \tilde{C}_2 e^{-\beta} + \tilde{T}^{(k)\prime} = \tilde{T}^{(k)\prime\prime} + \tilde{T}^{(k)\prime}, \\ \tilde{U}^{(k)} &= W_0 - ick^2 \tilde{T}^{(k)}, \end{aligned} \tag{67.17}$$

the problem is essentially solved, since one may immediately determine from the formulae

$$\begin{aligned} \tilde{T}_{1,k} &= \frac{\tilde{U}^{(k)}}{R_2 \sin^2\theta} + i\,\frac{c}{R_1}\operatorname{cotan}\theta\,\frac{d\tilde{T}^{(k)}}{d\theta}, \\ \tilde{T}_{2,k} &= \tilde{T}^{(k)} - \tilde{T}_{1,k}, \\ \tilde{S}_k &= -\frac{1}{k}\,\frac{1}{R_1 \sin\theta}\cdot\frac{d\tilde{U}^{(k)}}{d\theta} - \frac{ikc}{R_2}\,\frac{\cos\theta}{\sin^2\theta}\,\tilde{T}^{(k)} + \\ &\qquad + (q_{n,k}\cos\theta - q_{1,k}\sin\theta)\,\frac{R_2}{k} \end{aligned} \tag{67.18}$$

all the complex forces after which the evaluation of the forces and moments reduces to a separation of the real and imaginary parts in the expressions (67.18).

When carrying out the operations in the formulae (67.18), it should be remembered that the formula

$$\tilde{T}^{(k)\prime\prime} = \frac{\sqrt{R_1}}{R_2\sqrt{\sin\theta}}\,(\tilde{C}_1 e^{\beta} + \tilde{C}_2 e^{-\beta}) \tag{67.19}$$

contained an error of order $\sqrt{\frac{\delta}{R}}$ in comparison with unity, in correspondence with which, for the differentiation of the expression (67.19), one must assume that the coefficient $\sqrt{R_1} : R_2\sqrt{\sin\theta}$ is constant. This

makes it possible to include this coefficient in the integration constant as the result of which one obtains

$$\tilde{T}^{(k)\prime\prime} = \tilde{C}_1 e^{\beta} + \tilde{C}_2 e^{-\beta}. \tag{67.20}$$

Concluding this study of an approximate method of analysis of shells of revolution of arbitrary shape subject to any loading obeying the law $\begin{pmatrix}\cos k\varphi\\ \sin k\varphi\end{pmatrix}$, it must be noted that in essence this method was known to A. E. H. Love and it has been systematically applied in his book [49]. In fact, the above author considered it to be admissible for the study of shells of revolution bounded by parallel circles, to solve by subdividing the solution into three parts — the membrane, the pure moment and the 'edge effect'. Obviously the above results coincide with this recommendation.

At the same time, the present treatment of the problem differs essentially in two respects from that due to Love. In the first place, Love did not consider the question of the errors involved in the method recommended by him; in the method above, this was obtained as the result of neglecting certain terms, the errors of which may be estimated by comparing the formula

$$\alpha_1 = ick^2 \tag{67.21}$$

with the formula

$$\alpha_1 = ick^2\left[1 - i\frac{c}{\sin^2\theta}\left(\frac{1}{R_1} - \frac{1}{R_2}\right)(k^2 - 1)\right]. \tag{67.22}$$

Secondly, when considering equations of the form (67.9), Love as a rule tended to integrate them mathematically exactly, which was an unnecessary complication, since, from the point of view of interest in practical calculations, the first approximation obtained from the asymptotic method gives already sufficient accuracy.

REFERENCES

The numbers in square brackets refer to the following list of journals:

1. Prikl. Mat. Mekh., Akademiya Nauk. S.S.S.R.
2. D.A.N., S.S.S.R.
3. Zbirnik prats' Inst. mat. A.N.U.S.S.R.
4. Trudy L.P.I.
5. Trudy Kaz. aviats. in-ta.
6. Izv. fiz. mat. ob-va pri Kaz. Un-te.
7. Izv. A.N. S.S.R. O.T.N.
8. Journ. für reine und ang. Math.
9. Phil. Trans. Roy. Soc.
10. Exercise de mathématique
11. Math. Annalen
12. Mém. de l'Acad. Sci, Paris.
13. Z.A.M.M.
14. Proekt i standart
15. Perebod s nem. izdan. Len. in-ta grazhd. vozd. f-ta.
16. Stroitel'naia promyshlennocm'
17. Bauingenieur
18. Zeit. für techn. Phys.
19. Uchenye zapuski Gor'kovck. Un-ta.
20. Izv. Elektr.-tekhn. in-ta
21. Beton und Eisen
22. Ingenieur Archiv
23. Werft und Reederei
24. Proc. of Amer. Soc. Civil. Eng.
25. Inzhenernyi sbornik
26. Izv. Kievck. politekhn. i c.-kh. in-tov.
27. Zeitschr. für Math. und Phys.
28. Trans. A.S.M.E.

CHAP. I. *General theory of Shells*

1. VEKUA, I. N., On the theory of thin shallow elastic shells, [1], Vol. XII, 1, 1948.
2. —, On the theory of elastic shells, [2], 68, 3, 1949.
3. VLASOV, V. Z., The fundamental differential equations of the general theory of elastic shells, [1], VIII, 2, 1944. [Also NACA T. M. 1241].
4. —, The general theory of shells and its industrial applications, Gostekhizdat, 1949.
5. GOL'DENWEIZER, A. L., Additions and corrections to the theory of thin shells, "Plates and Shells", Gosstroiizdat, 1939.
6. —, The equations of the theory of shells, [1], IV, 2, 1940.
7. —, On the applicability of the general theorems of the theory of elasticity to thin shells, [1], VIII, 1, 1944.
8. —, A qualitative study of the state of stress in thin shells, [1], IX, 6, 1945.
9. —, Certain examples of the integration of the equations of the theory of thin shells, [1], X, 3, 1946.

10. GOL'DENWEIZER, A. L., LUR'E, A. I., On the mathematical theory of equilibrium of elastic shells, [1], XI, 5, 1947.
11. GOL'DENWEIZER, A. L., Review of V. V. Novozhilov's book "Theory of Thin Shells", [1], XIII, 1, 1949, p. 117.
12. KIL'CHEVSKII, N. A., A generalization of contemporary shell theory, [1], II, 4, 1939.
13. —, Certain methods of integration of the equations of equilibrium of elastic shells, [1], IV, 2, 1940.
14. —, The basic equations of equilibrium of elastic shells and some methods for their integration, [3], 4, 5, 6, 1940; 6, 1941.
15. LUR'E, A. I., A study in the theory of thin shells, [4], 6, 1937.
16. —, On the equations of the general theory of elastic shells, [1], XIV, 5, 1950.
17. —, The general theory of thin elastic shells, [1], IV, 2, 1940.
18. —, The static theory of thin-walled elastic shells, Gostekhizdat, 1947.
19. RABOTNOV, IU. N., The fundamental equations of the theory of shells, [2], New Series, XLVII, 2, 1945.
20. MUSHTARI, KH. M., On the stability of cylindrical shells subject to torsion, [5], 2, 1938.
21. —, Certain generalizations of the theory of thin shells, [6], XI, 8, 1938.
22. —, On the region of applicability of the linear theory of elastic shells, [2], 58, 6, 1947.
23. —, On the region of applicability of the approximate theory of shells due to Kirchhoff-Love, [1], XI, 5, 1947.
24. —, The invariant equations of equilibrium of the boundaries of elastic shells in complex form, [1], XII, 2, 1948.
25. —, A qualitative study of the state of stress of an elastic shell subject to small deformations and arbitrary displacements, [1], XIII, 2, 1949.
26. NOVODVORSKII, V., Shells, Baku, 1932.
27. NOVOZHILOV, V. V., Theory of thin shells, Oborongiz, 1941.
28. —, Certain remarks regarding the theory of shells, [1], V, 3, 1941.
29. —, On the errors involved in one of the assumptions of the theory of shells, [2], 38, 5–6, 1943.
30. NOVOZHILOV, V. V., FINKEL'SHTEIN, R. M., Regarding the errors connected with the Kirchhoff hypotheses in the theory of shells, [1], VII, 1943.
31. NOVOZHILOV, V. V., On the question of the solutions of problems of the theory of thin shells subject to forces and moments, [2], 38, 9, 1943.
32. —, A new method for the analysis of thin shells, [7], 1, 1946.
33. —, A generalization of the method of complex displacements to the non-homogeneous problem of the theory of shells, [2], 53, 6, 1946.
34. RABOTNOV, IU. N., The boundary conditions in the theory of thin shells, [2], XLVII, 5, 1945.
35. TIMOSHENKO, S. P., Theory of elasticity, Part II, 1916.
36. FEINBERG, S., On the problem of the construction of an approximate theory of thin shells of arbitrary shape, "Studies in the Theory of Structures", Gosstroiizdat, 1939.
37. ARON, H., Das Gleichgewicht und die Bewegung einer unendlich dünnen, beliebig gekrümmten, elastischen Schale, [8], 78, 1874.
38. BASSET, A., On the extension and flexure of thin elastic shells, [9], 179, (A), 1890.
39. CAUCHY, A., Sur l'équilibre et le mouvement d'une plaque solide, [10], 3, 1828.
40. CLEBSCH, A., Théorie de l'élasticité des corps solides, Paris, 1883. (Translated from the German, with notes added by B. de St. Venant).
41. DONNELL, L., Stability of thin-walled tubes under Torsion, NACA Rep. No. 479, 1933.
42. —, A discussion of thin shell theory, Proc. Fifth Congress for Appl. Mech., 1939.
43. FLÜGGE, W., Statik und Dynamik der Schalen, Verlag J. Springer, Berlin, 1934.
44. FÖPPL. A., FÖPPL, L., Drang und Zwang, Vol. II.
45. GECKELER, J., Statics of elastic bodies, OGIZ, 1932.
46. KIRCHHOFF, G., Vorlesungen über Mathematische Physik, Vol. 1, Mechanik, 1876.

47. KRAUSS, F., Über die Grundgleichungen der Elastizitätstheorie schwachdeformierter Schalen, [11], 101, 1, 1929.
48. LOVE, A. E. H., On the small free vibrations and deformations of thin elastic shells, [9], 179 (A), 1888.
49. —, Mathematical theory of elasticity, 4th ed., 1927.
50. POISSON, S. D., Mémoire sur l'équilibre et le mouvement des corps solides, [12], 8, 1829.
51. TREFFTZ, E., Ableitung der Schalenbiegungsgleichungen mit dem Castiglianoschen Prinzip, [13], 2, 1935.
52. TIMOSHENKO, S. P., Plates and shells.

CHAP. II. *The Membrane Theory*

53. VLASOV, V. Z., Analysis of shells of revolution for unsymmetrical loading, [14], 3–4, 1937.
54. —, Analysis of shells, formed by second order surfaces, "Plates and Shells", Gosstroiizdat, 1939.
55. —, Membrane theory of thin shells, formed by second order surfaces, [1], XI, 4, 1947.
56. HAAS, R., DITTSIUS, A., The stretching and deformation of the shells of a flexible Air-ship, [15], 1931.
57. GVOZDEV, A. A., Contribution to membrane theory, [16], 1, 1933.
58. GOL'DENWEIZER, A. L., MROSHCHINSKII, A. K., REPMAN, IU. V., Methods of Analysis of spherical domes using membrane theory, "Plates and Shells", 1939.
59. GOL'DENWEIZER, A. L., The membrane theory of shells, bounded by second order surfaces, [1], XI, 2, 1947.
60. NOVODVORSKII, V., On the so-called membrane theory of shells, [16], 1, 1938.
61. RABOTNOV, IU. N., Certain solutions of the membrane theory of shells, [1], X, 5, 6, 1946.
62. RAPOPORT, I. IA., ZARKHI, L. I., MALIEV, A. S., The floor systems of Zeiss -Dywidag, Soviet Inst. of Structures, Gosstroiizdat, Leningrad, 1932.
63. SOKOLOVSKII, V. V., On membrane shells of revolution, [1], I, 3, 1938.
64. —, The equations of equilibrium of membrane shells, [1], VII, 1, 1943.
65. BELTRAMI, E., Sull equilibrio delle supperficie flessibili ed inestendibili, Mem. R. Acad. Sci di Bologna, 1881.
66. DISCHINGER, F., Shells, Gosstroiizdat, 1932.
67. DISCHINGER, F., Die Rotationsschalen mit unsymmetrischer Form und Belastung, [17], 1935.
68. —, Der Spannungszustand in affinen Schalen und Raumfachwerken, [17], 17, 23–27, 1936.
69. FEDERHOFER, K., Über Schalen gleicher Festigkeit, [17], 27–28, 1939.
70. LAMÉ, G. and CLAPEYRON, B. P. E., Mémoire sur l'équilibre interieur des corps solides, Mém. prés. par div. savants, 4, 1833.
71. LAGALLY, M., Über Spannung und elastische Deformation von unebenen Membranen, [13], 4, 1924.
72. LECORNU, Z., Sur l'équilibre des surfaces flexibles et inextendibles., Journ. de l'école Polytechnique, c. XLVIII.
73. MEGAREUS, G., Die Kuppel gleicher Festigkeit, [17], 20, 1939.
74. MILANCOVIČ, M., O membranoma jednakog otpora, Rad. Iugoslavenske Akademije, kn, 175, 1908.
75. PÖSCHL. TH., Die Verwendung der Spannungsfunktion beim statischen Schalenprobleme, [18], Bd. 8, 1921.
76. —, Technische Daten über tropfenförmige Mineralölbehälter, [17], 8, 1927.
77. PÜCHER, A., Die Berechnung von doppeltgekrümmten Schalen mittels Differenzengleichungen, [17], 18, 9/10, 1937.
78. Ueber die Spannungsfunctionen beliebig gekrümmter dünner Schalen, Proc. of the fifth Int. Congr. for Applied Mech., 1939.

CHAP. III. *Analysis of cylindrical shells*

79. ADADUROV, R. A., Stresses and strains in a cylindrical shell with rigid transverse sections, [2], 62, 2, 1948.
80. AMBARTSUMIAN, S. A., On the analysis of shallow shells, [1], XI, 5, 1947.
81. —, On the theory of anisotropic elastic shells, [1], XII, 1, 1948.
82. BYCHKOV, D., MROSHCHINSKII, A. K., The torsion of metal beams, Stroiizdat, 1944.
83. VLASOV, V. Z., A new practical method for the analysis of folded covers and shells, [16], 11–12, 1932.
84. —, The moment theory of cylindrical shells, [14], 10, 1938.
85. VLASOV, V. Z., GOL'DENWEIZER, A. L., KAGAN, M., Graphs for the analysis of thin-walled wooden shells for the determination of bending and twisting moments, [14], 6, 1938.
86. VLASOV, V. Z., A new method for the analysis of thin-walled prismatic covers and shells, Gosstroiizdat, 1933.
87. —, The structural mechanics of shells, O.N.T.I., Stroiizdat, 1936.
88. —, Analysis of rib-stiffened shells and beams of thin-wall construction subject to bending and torsion, [14], 10, 1936.
89. —, Certain problems of the theories of strength of materials, structural mechanics and elasticity, [7], 9, 1950.
90. —, Thin-walled elastic rods (buckling, stability and vibrations), Gosstroiizdat, 1940.
91. —, Certain new problems of the structural mechanics of shells and thin-walled structures, [7], 1, 1947.
92. —, Contact problems in the theory of shells and thin-walled structures, [7], 6, 1949.
93. GALERKIN, B. G., On the theory of elastic cylindrical shells, [2], IV, 5–6, 1934.
94. —, The equilibrium of elastic cylindrical shells, Trudy-Leningrad Institute of Structures, 1935.
95. GVOZDEV, A. A., On the analysis of thin-walled cylindrical shells, [16], 1, 1932.
96. VLASOV, V. Z., Structural mechanics of thin-walled three-dimensional systems, Gosstroiizdat, 1949.
97. GALERKIN, B. G., PEREL'MAN, IA. I., Stresses and displacements in circular cylindrical pipe-line, Izv. Naychono-issledov, Inst., Gidro-techniki, 27, 1940.
98. GOL'DENWEIZER, A. L., Analysis of thin-walled shells and structures, based on rigid diaphragms, taking into account bending and twisting moments, "Plates and Shells", Gosstroiizdat, 1939.
99. —, On approximate methods for the analysis of thin shells of zero Gaussian curvature, [1], XI, 4, 1947.
100. —, On the theory of thin-walled rods, [1], XIII, 6, 1949.
101. DZHANELIDZE, G. IU., On the theory of slender and thin-walled rods, [1], XIII, 6, 1949.
102. LUR'E, A. I., Concentration of stress in the region of an opening in the surface of a circular cylinder, [1], X, 3, 1946.
103. MARKOV, A. N., On a method of integration of the equations for bending of cylindrical shells, [19], 6, 1938.
104. —, On the theory of bending of cylindrical shells, [19], 6, 1938.
105. MROSHCHINSKII, A. K., Analysis of cylindrical shells subject to concentrated forces, "Plates and Shells", 1939.
106. NOVOZHILOV, V. V., Analysis of cylindrical shells, [7], 6, 1946.
107. PAPKOVICH, P. F., Structural mechanics of ships, "Sea Transport", II, 1, 1947.
108. PASTERNAK, P. L., Practical analysis of structures and cylindrical shells allowing for bending moments. Inf. bull. NKTP, 1932.
109. —, Practical analysis of structures and cylindrical shells allowing for bending moments, [14], 2, 1933.
110. RABOTNOV, IU. N., Bending of cylindrical shells under concentrated loads. [2], 52, 4, 1946.
111. TIMOSHENKO, S. P., On the problem of deformation and stability of cylindrical shells, [20], II, 1914.

112. UMANSKII, A. A., Torsion and bending of air-frames, Oborongiz, 1939.
113. FEINBERG, S., On the problem of the construction of a moment theory of cylindrical shells, [14], 12, 1936.
114. KHACHATURIAN, T. T., Shallow cylindrical shells, A. N. Arm., S.S.R., Erevan, 1949.
115. AAS JAKOBSEN, A., Zylinderschalen mit veränderlichem Krümmungshalbmesser und veränderlicher Wandstärke, [17], 1937.
116. —, Über das Randstörungsproblem an Kreiszylinderschalen, [17], 20, 1939.
117. DISCHINGER, F., Die strenge Theorie der Kreiszylinderschale mit ihrer Anwendung auf Zeiss-Dywidag-Schalen, [21], 1935.
118. FINSTERWALDER, U., Die querversteiften, zylindrischen Schalengewölbe mit kreissegmentförmigem Querschnitt, [22], 1933.
119. MIESEL, K., Über die Festigkeit von Kreiszylinderschalen bei nicht achsensymmetrischer Belastung, [22], I, 1929.
120. REISSNER, H., Formänderung und Spannungen einer dünnwandigen, an den Randen frei aufliegenden Zylinderschale, [13], 1933.
121. VON SANDEN, K., GÜNTER, K., Über das Festigkeitproblem querversteifter Hohlzylinder unter allseitig gleichmässigem Aussendruck, [23], 8, 9, 10, 1920; 17, 1921.
122. SHORRER, H., Line load action on thin cylindrical shells, [24], March, 1935.
123. SCHWERIN, E., Über die Spannungen in freitragenden gefüllten Rohren, [13], 2, 1922.

CHAP. IV. *Analysis of shells of revolution*

124. BURMISTROV, E. F., Symmetrical deformation of a nearly cylindrical shell, [1], XIII, 4, 1949.
125. VEKUA, I. N., Integration of the equations for spherical shells, [1], X, 5, 1945.
126. —, Some fundamental problems of the theory of thin spherical shells, [1], XI, 5, 1947.
127. VLASOV, V. Z., On two representations of the equations for spherical shells, [1], XI, 5, 1947.
128. GALERKIN, B. G., Equilibrium of an elastic spherical shell, [1], VI, 6, 1942.
129. GOL'DENWEIZER, A. L., A study of the state of stress of spherical shells, [1], VIII, 6, 1944.
130. KANTOROVICH, Z. B., Approximate solution of the edge problem for conical shells, [25], I, 2, 1941.
131. LUR'E, A. I., Equilibrium of an elastic symmetrically loaded spherical shell, [1], VII, 6, 1943.
132. FEODOS'EV, V. I., The elastic elements of precision instrument construction, Oborongiz, 1949.
133. NOVOZHILOV, V. V., Analysis of stresses in thin spherical shells for arbitrary loading, [2], XXVII, 6, 1940.
134. —, Analysis of shells of revolution, [7], 7, 1946.
135. REPMAN, IU. V., Analysis of spherical shells by use of the moment theory for arbitrary loading, "Plates and Shells", 1939.
136. SOKOLOVSKII, V. V., Analysis of spherical shells, [2], XVI, 1, 1937.
137. —, On a certain problem of the theory of shells, [2], XVI, 8, 1937.
138. FEODOS'EV, V. I., On the analysis of stiffened box-sections (stressed skins), [25], IV, 1, 1947.
139. SHAPIRO, G. S., On the equilibrium of a cone and conical shells, [1], VIII, 1944.
140. SHTAERMAN, I. IA., On the theory of symmetrical deformation of anisotropic elastic shells, [26], 1924.
141. —, On the integration of the differential equations of equilibrium of elastic shells, [26], 2, 1927.
142. —, Fundamental ideas of the contemporary theory of domes and vaults, Trudy Soviet Conference on Concrete and Reinforced Concrete, 1932.
143. —, Analysis of a dome as an arch on an elastic foundation, [14], 9, 1933.
144. AAS JAKOBSEN, A., Beitrag zur Theorie der Kugelschale auf Einzelstützen, [22], 1937.

145. BLUMENTHAL, O., Über asymptotische Integration von Differentialgleichungen mit Anwendung auf die Berechnung von Spannungen in Kugelschalen, [27], 62, 1914.
146. BOLLE, Z., Festigkeitsberechnung von Kugelschalen, Dissertationsarbeit, Zürich, 1916.
147. COATES, W., The state of stress in full heads of pressure vessels, [28], 52, 1930.
148. DUBOIS, F., Über die Festigkeit der Kugelschale, Promotionsarbeit, Zürich, 1917.
149. GECKELER, J., Über die Festigkeit achsensymmetrischer Schalen, Forsch, Arb. a.d. Geb. Ing. Wes., 276, 1926.
150. —, Die Festigkeit achsensymmetrischer Schalen, [22], I, 1930.
151. HAVERS, A., Asymptotische Biegetheorie der unbelasteten Kugelschalen, [22], 4, 1935.
152. HÖHN, E., Über die Festigkeit der gewölbten Böden und der Zylinderschale, Berlin, Verlag, J. Springer, 1927.
153. MAULBETSCH, J., HETENYI, M., Stresses in pressure vessels, [28], 58, 1936.
154. MEISSNER, E., Über Elastizität und Festigkeit dünner Schalen, Viertelschr. d. natur. Ges., Bd. 60, Zürich, 1915.
155. —, Das Elastizitätsgesetz für dünne Schalen von Ringflächen, Kugel- und Kegelform, Phys. Zeitschr., Bd. 14, 1913.
156. VAN DER NEUT, H., De elastische stabiliteit van den dunwandigen bol., Diss., Delft, 1932.
157. PASTERNAK, P., Die Praktische Berechnung biegefester Kugelschalen kreisrunder Fundamentsplatten auf elastischer Bettung und kreiszylinderscher Wandungen in gegenseitiger monolither Verbindung, [13], 1926.
158. PASTERNAK, P., Verhandl d. 2. Int. Kongr. für techn. Mech., Zürich, 1927.
159. REISSNER, H., Spannungen in Kugelschalen (Kuppeln.), Müller-Breslau,-Festschr., 1912.
160. SCHWERIN, E., Über Spannungen in symmetrisch und unsymmetrisch belasteten Kugelschalen (Kuppeln) insbesondere bei Belastung durch Winddruck, Diss., Berlin, 1918.
161. STANGE, K., Der Spannungszustand einer Kreisringschale, [22], 1931.
162. WISSLER, H., Festigkeitberechnung von Ringflächen, Promotionsarbeit, Zürich, 1916.
163. PONOMAREV, S. D., BIDERMAN, V. L., LIKHAREV, K. K., FEODOS'EV, V. I., Fundamentals of contemporary methods of analysis of the strength of machine designs, Mashgiz, 1950.

AUTHOR INDEX

The numbers in brackets refer to the references listed on p. 367–372.

A

ADADUROV, R. A., [79].
AMBARTSUMIAN, S. A., [80, 81], 5.
ARON, H., [37], 4, 84.

B

BALABUKH, L. I., 54.
BASSET, A., [38].
BELTRAMI, E., [65], 61, 62, 95.
BESSEL, F. W., 309, 311.
BIDERMAN, V. L., [163].
BLUMENTHAL, O., [145], 260.
BOLLE, Z., [146], 260.
BURMISTROV, E. F., [124].
BYCHKOV, D., [82].

C

CAUCHY, A., [39], 3, 4.
CLAPEYRON, B. P. E., [70], 95.
CLEBSCH, A., [40].
COATES, W., [147], 293.
CODAZZI, A., 13, 14.

D

DISCHINGER, F., [66–68, 117], 117, 145.
DITTSIUS, A., [56].
DONNELL, L., [41, 42].
DUBOIS, F., [148], 260.
DZHANELIDZE, G. IU., [101], 183.

F

FEDERHOFER, K., [69].
FEINBERG, S., [36, 113], 5, 86, 90, 183, 184.
FEODOS'EV, V. I., [132, 138, 163].
FINKEL'SHTEIN, R. M., [30].
FINSTERWALDER, U., [118].
FLÜGGE, W., [43], 26.
FÖPPL, A., [44].
FÖPPL, L., [44].
FOURIER, J. B. J., 244.

G

GALERKIN, B. G., [93, 94, 97, 128], 4, 241, 245, 263.
GAUSS, K. F., 14.
GECKELER, J., [45, 149, 150], 261.
GERMAIN, MLLE. SOPHIE, 3.
GOL'DENWEIZER, A. L., [5–11, 58, 59, 85, 98–100, 129], 5, 28, 38, 74, 83, 84, 88, 183, 204, 227, 228, 229, 230, 233, 262, 345.
GÜNTER, K., [121].
GVOZDEV, A. A., [57, 95].

H

HAAS, R., [56].
HANKEL, W. G., 309.
HAVERS, A., [151], 262, 347.
HETENYI, M., [153].
HÖHN, E., [152].
HOOKE, R., 2, 41.

J

JAKOBSON, AAS, A., [115, 116, 144], 347.

K

KAGAN, M., [85].
KANTOROVICH, Z. B., [130].
KELVIN, LORD, 127.
KHACHATURIAN, T. T., [114].
KIL'CHEVSKII, N. A., [12–14].
KIRCHHOFF, G., [46], 3, 4, 5, 33, 43, 49.
KRAUSS, F., [47].
KRYLOV, A. N., 281.

L

LAGALLY, M., [71].
LAMÉ, G., [70], 8, 14, 19, 21, 27, 62, 95, 168, 264.
LAPLACE, P. S., 61, 85, 127.
LECORNU, Z., [72], 95.
LEVY, M., 203.
LIKHAREV, K. K., [163].
LOVE, A. E. H., [48, 49], 4, 52, 55, 84, 262, 366.
LUR'E, A. I., [10, 15–18, 102, 131], 5, 38, 53, 74, 184, 261, 263.

M

MALIEV, A. S., [62].
MARKOV, A. N., [103, 104].
MAULBETSCH, J., [153].
MEGAREUS, G., [73], 132.

MEISSNER, E., [154, 155], 5, 260, 274.
MICHELL, J. H., 61, 62.
MIEŠEL, K., [119].
MILANCOVIČ, M., [74].
MROSHCHINSKII, A. K., [58, 82, 105].
MUSHTARI, KH. M., [20–25], 5, 84, 86, 184, 262.

N

NEUT, A. VAN DER, [156], 262.
NOVODVORSKII, V., [26, 60].
NOVOZHILOV, V. V., [27–33, 106, 133, 134], 5, 53, 54, 74, 77, 81, 83, 90, 183, 184, 185, 261, 262, 324.

P

PAPKOVICH, P. F., [107], 303.
PASTERNAK, P. L., [108, 109, 157, 158], 261.
PEREL'MAN, IA. I., [97].
POISSON, S. D., [50], 3, 4, 63, 69, 75, 79, 116, 250, 257.
PONOMAREV, S. D., [163].
PÖSCHL, TH., [75, 76].
PUCHER, A., [77, 78].

R

RABOTNOV, IU. N., [19, 34, 61, 110], 5, 95, 262.
RAPOPORT, I. IA., [62].
REISSNER, H., [120, 159], 83, 260, 261.
REPMAN, IU. V., [58, 135], 262.
RODRIGUES, O., 10.

S

SAINT-VENANT, A. J. C. BARRÉ DE, [40], 3, 28, 58, 62.
SANDEN, K. VON, [121].
SCHWERIN, E., [123, 160], 261.
SHAPIRO, G. S., [139], 81, 263.
SHORRER, H., [122].
SHPILREIN, Y. N., 141.
SHTAERMAN, I. IA., [140–143], 261, 291.
SLEPOV, B. I., 324.
SOKOLOVSKII, V. V., [63, 64, 136, 137], 95, 138, 262.
STANGE, K., [161].

T

TIMOSHENKO, S. P., [35, 52, 111].
TREFFTZ, E., [51].

U

UMANSKII, A. A., [112], 183.

V

VEKUA, I. N., [1, 2, 125, 126], 262.
VLASOV, V. Z., [3, 4, 53–55, 83–92, 96, 127], 5, 26, 53, 84, 86, 87, 90, 95, 166, 182, 183, 184, 254, 256, 257.

W

WISSLER, H., [162], 260.

Z

ZARKHI, L. I., [62].
ZÜRICH SCHOOL, 260, 261.

SUBJECT INDEX

A

Affine transformation, 145.
Anisotropic shell, 190.
Approximate integration, 282, 361.
Approximate expressions; forces, moments & displacements, 285.
Assumptions, 1, 3, 4.
Asymptotic integration, 278.

B

Beam, 6, 25.
Boundary conditions, 49, 54, 58, 97, 171.

C

Catenoid shells, design of, 358.
——, pure bending of, 164.
Compatibility conditions, 27, 40, 59, 66, 81.
Complex forces, 68, 75.
Complex moments, 68, 75.
Complex transformation, 63, 69.
Components of displacement, 19.
Concepts, 1–6.
Conditions, for membrane stresses, 100.
—— of Codazzi, 13, 23, 28, 41, 103.
—— of Gauss, 14, 28, 41, 103.
Contradictions, 52.
Curvature, abruptly changing, 246.
——, Gaussian, 89, 162, 167, 340.
——, lines of principal, 7, 55.
Cylindrical plates, analysis of, 196.
——, long, simplified theory, 219.
——, reinforced, 234.
Cylindrical pressure vessel, analysis of, 296.
Cylindrical shell, analysis of, 246.
——, equations in complex form, 185.
——, equations of membrane theory, 167.
——, reinforced, 189.
——, semi-membrane theory, 254.
Cylindrical vaults, 175.

D

Deformation, 19.
——, shells of revolution, 157, 270.
——, symmetrical, 108, 155.
——, toroidal shells, 304.
Differential equations, cylindrical shell, 185.
——, membrane shell, 95, 102.
——, shell of revolution, 263.
Differentiation of vectors, 9.
Displacements, 19.
——, approximate expressions for, 285.
——, determination of, 268.
——, shell of revolution, 155.
——, variation, 14.
Domes, membrane theory of, 111.
——, on columns, 141.
Drop shape reservoir, 130.

E

Edge effect, 91, 262, 361, 366.
Elasticity theory, 42, 61.
Equilibrium, shell element, 33, 66.

F

Forces, 29.
——, approximate expressions for, 285.
——, complex, 75.

H

Historical introduction, 182.
—— resumé, 93.
—— remarks, 260.
Homogeneous statical equations, functions satisfying, 38.
Hooke's Law, 2, 42.
Hoop stresses, 115.

I

Influence coefficients, 292.

L

Lamé parameters, 8, 14, 19, 21.
—— equations, 62.
Lines of principal curvature, 7, 55.
Load distribution, 82.
——, hydrostatic pressure, 125.
——, self weight, 130.
——, surface, 104.
Loading, wind type, 134.
——, wind, shells of revolution, 324.
——, wind, design formulae for, 329.

M

Membrane stresses, existence of, 100.
Mambrane theory, 93.
——, cylindrical vault, 175.
——, dome, 111.
——, equations of, 95.
——, pressure vessels, 117.
——, shell of revolution, 102, 106, 138.
——, shell of uniform strength, 124.
——, spherical shell, 140.
——, symmetrical deformation, 108.
Methods of solution, general, 62.
Middle surface, 1, 6, 14, 33, 55, 191.
Moments, 29.
——, approximate expressions for, 285.
——, complex, 75.
Mushtari-Vlasov method, simplification of shell theory, 84.

N

Neutral axis, 6.

O

Orthotropic shell, 190.

P

Plates, 1, 94, 196, 208, 234.
Poisson's ratio, 63.
Pressure vessels, cylindrical, 296.
——, membrane theory of, 117.
Principal curvature, 7, 14, 55.
Principle of St. Venant, 58.

S

Scalar product, 8.
Semi-membrane theory, 254.
Shells, 1.
——, anisotropic, 190.
——, catenoid, 164, 340, 358.
——, complete, 1, 55.
——, cylindrical, 55, 167, 182, 185, 246, 254.
——, incomplete, 1.
——, long cylindrical, 182, 219.
——, medium length cilindrical, 182.
—— of revolution, 102, 106, 108, 138, 260, 263, 267, 270, 285, 324, 337.
—— of uniform strength, 124.
——, oval-cap, 208.
——, reinforced, 185, 189, 234.
——, semi-membrane, 254.
——, short cylindrical, 182.
——, spherical, 54, 140, 159, 346.
——, thick, 2.
——, thin, 2, 3, 47.
——, toroidal, 304.
Spherical shells, analysis of, 346.
——, pure bending of, 159.
State of stress, types of, 90.
Strain, 47.
—— energy, 42, 47.
—— -force relations, 47.
—— -moment relations, 47.
Stress, 29, 42.
——, bending, 90.
——, boundary conditions for, 54, 97.
—— function, 5.
—— in arched end-panels, analysis of, 316.
—— in oval-cap shells, evaluation of, 208.
—— in tubes, 169.
——, membrane, 90, 93.
——, mixed type, 91.
—— resultant, 30, 47.
Surface theory, 6.
——, parallel, 20.

T

Theorem of Rodrigues, 10.
Thickness of shell, 1, 2.
Thrust ring, 114.
Toroidal shell, symmetrical deformation 304.
Transformation, affine, 145.
——, complex, 63, 69.
Tubes, arbitrary cross-section, analysis of, 239.
——, arbitrary end conditions, 252.
——, cylindrical, 55, 182.
——, stress in, 169.

V

Vaults, cylindrical, 175.
Vector product, 9.